

---

# **rocThrust Documentation**

***Release 0.8***

**Advanced Mirco Devices**

**Jul 22, 2019**



## **CONTENTS:**

<b>1</b>	<b>Library API</b>	<b>1</b>
1.1	Class Hierarchy . . . . .	1
1.2	File Hierarchy . . . . .	1
1.3	Full API . . . . .	1
1.3.1	Namespaces . . . . .	1
1.3.2	Classes and Structs . . . . .	20
1.3.3	Functions . . . . .	72
1.3.4	Variables . . . . .	365
1.3.5	Defines . . . . .	369
1.3.6	Typedefs . . . . .	371
<b>2</b>	<b>Indices and tables</b>	<b>373</b>
<b>Index</b>		<b>375</b>



## 1.1 Class Hierarchy

## 1.2 File Hierarchy

## 1.3 Full API

### 1.3.1 Namespaces

#### Namespace placeholders

Facilities for constructing simple functions inline.

##### Contents

- *Detailed Description*

#### Detailed Description

Objects in the `thrust::placeholders` namespace may be used to create simple arithmetic functions inline in an algorithm invocation. Combining placeholders such as `_1` and `_2` with arithmetic operations such as `+` creates an unnamed function object which applies the operation to their arguments. The type of placeholder objects is implementation-defined. The following code snippet demonstrates how to use the placeholders `_1` and `_2` with `thrust::transform` to implement the SAXPY computation:

```
#include<thrust/device_vector.h>
#include<thrust/transform.h>
#include<thrust/functional.h>
```

```
intmain() { thrust::device_vector<float>x(4),y(4); x[0]=1; x[1]=2; x[2]=3; x[3]=4;
y[0]=1; y[1]=1; y[2]=1; y[3]=1;
floata=2.0f;
usingnamespacethrust::placeholders;
thrust::transform(x.begin(),x.end(),y.begin(),y.begin(), a*_1+_2 );
//yisnow{3,5,7,9} }
```

## Namespace thrust

thrust is the top-level namespace which contains all Thrust functions and types.

### Contents

- [Namespaces](#)
- [Classes](#)
- [Functions](#)
- [Variables](#)

## Namespaces

- [Namespace thrust::placeholders](#)
- [Namespace thrust::random](#)
- [Namespace thrust::system](#)

## Classes

- [Template Struct binary\\_function](#)
- [Template Struct binary\\_negate](#)
- [Template Struct binary\\_traits](#)
- [Template Struct bit\\_and](#)
- [Template Struct bit\\_or](#)
- [Template Struct bit\\_xor](#)
- [Template Struct complex](#)
- [Template Struct device\\_allocator::rebind](#)
- [Template Struct device\\_allocator< void >::device\\_allocator< void >](#)
- [Template Struct device\\_execution\\_policy](#)
- [Template Struct device\\_malloc\\_allocator::rebind](#)
- [Template Struct device\\_new\\_allocator::rebind](#)
- [Template Struct divides](#)
- [Template Struct equal\\_to](#)
- [Template Struct greater](#)
- [Template Struct greater\\_equal](#)
- [Template Struct host\\_execution\\_policy](#)
- [Template Struct identity](#)
- [Template Struct less](#)
- [Template Struct less\\_equal](#)

- *Template Struct logical\_and*
- *Template Struct logical\_not*
- *Template Struct logical\_or*
- *Template Struct maximum*
- *Template Struct minimum*
- *Template Struct minus*
- *Template Struct modulus*
- *Template Struct multiplies*
- *Template Struct negate*
- *Template Struct not\_equal\_to*
- *Template Struct pair*
- *Template Struct plus*
- *Template Struct project1st*
- *Template Struct project2nd*
- *Template Struct tuple\_element*
- *Template Struct tuple\_size*
- *Template Struct unary\_function*
- *Template Struct unary\_negate*
- *Template Struct unary\_traits*
- *Template Class device\_allocator*
- *Template Class device\_allocator< void >*
- *Template Class device\_malloc\_allocator*
- *Template Class device\_new\_allocator*
- *Template Class device\_ptr*
- *Template Class device\_reference*
- *Template Class device\_vector*
- *Template Class host\_vector*
- *Template Class tuple*

## Functions

- *Template Function thrust::abs*
- *Template Function thrust::acos*
- *Template Function thrust::acosh*
- *Template Function thrust::adjacent\_difference(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, InputIterator, InputIterator, OutputIterator)*

- *Template Function thrust::adjacent\_difference(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, InputIterator, InputIterator, OutputIterator, BinaryFunction)*
- *Template Function thrust::adjacent\_difference(InputIterator, InputIterator, OutputIterator)*
- *Template Function thrust::adjacent\_difference(InputIterator, InputIterator, OutputIterator, BinaryFunction)*
- *Template Function thrust::advance*
- *Template Function thrust::all\_of(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, InputIterator, InputIterator, Predicate)*
- *Template Function thrust::all\_of(InputIterator, InputIterator, Predicate)*
- *Template Function thrust::any\_of(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, InputIterator, InputIterator, Predicate)*
- *Template Function thrust::any\_of(InputIterator, InputIterator, Predicate)*
- *Template Function thrust::arg*
- *Template Function thrust::asin*
- *Template Function thrust::asinh*
- *Template Function thrust::atan*
- *Template Function thrust::atanh*
- *Template Function thrust::binary\_search(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, ForwardIterator, ForwardIterator, const LessThanComparable&)*
- *Template Function thrust::binary\_search(ForwardIterator, ForwardIterator, const LessThanComparable&)*
- *Template Function thrust::binary\_search(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, ForwardIterator, ForwardIterator, const T&, StrictWeakOrdering)*
- *Template Function thrust::binary\_search(ForwardIterator, ForwardIterator, const T&, StrictWeakOrdering)*
- *Template Function thrust::binary\_search(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, ForwardIterator, ForwardIterator, InputIterator, InputIterator, OutputIterator)*
- *Template Function thrust::binary\_search(ForwardIterator, ForwardIterator, InputIterator, InputIterator, OutputIterator)*
- *Template Function thrust::binary\_search(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, ForwardIterator, ForwardIterator, InputIterator, InputIterator, OutputIterator, StrictWeakOrdering)*
- *Template Function thrust::binary\_search(ForwardIterator, ForwardIterator, InputIterator, InputIterator, OutputIterator, StrictWeakOrdering)*
- *Template Function thrust::conj*
- *Template Function thrust::copy(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, InputIterator, InputIterator, OutputIterator)*
- *Template Function thrust::copy(InputIterator, InputIterator, OutputIterator)*
- *Template Function thrust::copy\_if(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, InputIterator, InputIterator, OutputIterator, Predicate)*
- *Template Function thrust::copy\_if(InputIterator, InputIterator, OutputIterator, Predicate)*
- *Template Function thrust::copy\_if(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, InputIterator1, InputIterator1, InputIterator2, OutputIterator, Predicate)*
- *Template Function thrust::copy\_if(InputIterator1, InputIterator1, InputIterator2, OutputIterator, Predicate)*

- *Template Function thrust::copy\_n(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, InputIterator, Size, OutputIterator)*
- *Template Function thrust::copy\_n(InputIterator, Size, OutputIterator)*
- *Template Function thrust::cos*
- *Template Function thrust::cosh*
- *Template Function thrust::count(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, InputIterator, InputIterator, const EqualityComparable&)*
- *Template Function thrust::count(InputIterator, InputIterator, const EqualityComparable&)*
- *Template Function thrust::count\_if(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, InputIterator, InputIterator, Predicate)*
- *Template Function thrust::count\_if(InputIterator, InputIterator, Predicate)*
- *Template Function thrust::device\_delete*
- *Function thrust::device\_free*
- *Function thrust::device\_malloc*
- *Template Function thrust::device\_new(device\_ptr<void>, const size\_t)*
- *Template Function thrust::device\_new(device\_ptr<void>, const T&, const size\_t)*
- *Template Function thrust::device\_new(const size\_t)*
- *Template Function thrust::device\_pointer\_cast(T \*)*
- *Template Function thrust::device\_pointer\_cast(const device\_ptr<T>&)*
- *Template Function thrust::distance*
- *Template Function thrust::equal(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, InputIterator1, InputIterator1, InputIterator2)*
- *Template Function thrust::equal(InputIterator1, InputIterator1, InputIterator2)*
- *Template Function thrust::equal(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, InputIterator1, InputIterator1, InputIterator2, BinaryPredicate)*
- *Template Function thrust::equal(InputIterator1, InputIterator1, InputIterator2, BinaryPredicate)*
- *Template Function thrust::equal\_range(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, ForwardIterator, ForwardIterator, const LessThanComparable&)*
- *Template Function thrust::equal\_range(ForwardIterator, ForwardIterator, const LessThanComparable&)*
- *Template Function thrust::equal\_range(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, ForwardIterator, ForwardIterator, const T&, StrictWeakOrdering)*
- *Template Function thrust::equal\_range(ForwardIterator, ForwardIterator, const T&, StrictWeakOrdering)*
- *Template Function thrust::exclusive\_scan(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, InputIterator, InputIterator, OutputIterator)*
- *Template Function thrust::exclusive\_scan(InputIterator, InputIterator, OutputIterator)*
- *Template Function thrust::exclusive\_scan(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, InputIterator, InputIterator, OutputIterator, T)*
- *Template Function thrust::exclusive\_scan(InputIterator, InputIterator, OutputIterator, T)*

- *Template Function thrust::exclusive\_scan(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, InputIterator, InputIterator, OutputIterator, T, AssociativeOperator)*
- *Template Function thrust::exclusive\_scan(InputIterator, InputIterator, OutputIterator, T, AssociativeOperator)*
- *Template Function thrust::exclusive\_scan\_by\_key(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, InputIterator1, InputIterator1, InputIterator2, OutputIterator)*
- *Template Function thrust::exclusive\_scan\_by\_key(InputIterator1, InputIterator1, InputIterator2, OutputIterator)*
- *Template Function thrust::exclusive\_scan\_by\_key(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, InputIterator1, InputIterator1, InputIterator2, OutputIterator, T)*
- *Template Function thrust::exclusive\_scan\_by\_key(InputIterator1, InputIterator1, InputIterator2, OutputIterator, T)*
- *Template Function thrust::exclusive\_scan\_by\_key(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, InputIterator1, InputIterator1, InputIterator2, OutputIterator, T, BinaryPredicate)*
- *Template Function thrust::exclusive\_scan\_by\_key(InputIterator1, InputIterator1, InputIterator2, OutputIterator, T, BinaryPredicate)*
- *Template Function thrust::exclusive\_scan\_by\_key(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, InputIterator1, InputIterator1, InputIterator2, OutputIterator, T, BinaryPredicate, AssociativeOperator)*
- *Template Function thrust::exclusive\_scan\_by\_key(InputIterator1, InputIterator1, InputIterator2, OutputIterator, T, BinaryPredicate, AssociativeOperator)*
- *Template Function thrust::exp*
- *Template Function thrust::fill(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, ForwardIterator, ForwardIterator, const T&)*
- *Template Function thrust::fill(ForwardIterator, ForwardIterator, const T&)*
- *Template Function thrust::fill\_n(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, OutputIterator, Size, const T&)*
- *Template Function thrust::fill\_n(OutputIterator, Size, const T&)*
- *Template Function thrust::find(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, InputIterator, InputIterator, const T&)*
- *Template Function thrust::find(InputIterator, InputIterator, const T&)*
- *Template Function thrust::find\_if(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, InputIterator, InputIterator, Predicate)*
- *Template Function thrust::find\_if(InputIterator, InputIterator, Predicate)*
- *Template Function thrust::find\_if\_not(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, InputIterator, InputIterator, Predicate)*
- *Template Function thrust::find\_if\_not(InputIterator, InputIterator, Predicate)*
- *Template Function thrust::for\_each(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, InputIterator, InputIterator, UnaryFunction)*
- *Template Function thrust::for\_each(InputIterator, InputIterator, UnaryFunction)*
- *Template Function thrust::for\_each\_n(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, InputIterator, Size, UnaryFunction)*
- *Template Function thrust::for\_each\_n(InputIterator, Size, UnaryFunction)*

- *Template Function thrust::free*
- *Template Function thrust::gather(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, InputIterator, InputIterator, RandomAccessIterator, OutputIterator)*
- *Template Function thrust::gather(InputIterator, InputIterator, RandomAccessIterator, OutputIterator)*
- *Template Function thrust::gather\_if(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, InputIterator1, InputIterator1, InputIterator2, RandomAccessIterator, OutputIterator)*
- *Template Function thrust::gather\_if(InputIterator1, InputIterator1, InputIterator2, RandomAccessIterator, OutputIterator)*
- *Template Function thrust::gather\_if(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, InputIterator1, InputIterator1, InputIterator2, RandomAccessIterator, OutputIterator, Predicate)*
- *Template Function thrust::gather\_if(InputIterator1, InputIterator1, InputIterator2, RandomAccessIterator, OutputIterator, Predicate)*
- *Template Function thrust::generate(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, ForwardIterator, ForwardIterator, Generator)*
- *Template Function thrust::generate(ForwardIterator, ForwardIterator, Generator)*
- *Template Function thrust::generate\_n(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, OutputIterator, Size, Generator)*
- *Template Function thrust::generate\_n(OutputIterator, Size, Generator)*
- *Template Function thrust::get(detail::cons<HT, TT>&)*
- *Template Function thrust::get(const detail::cons<HT, TT>&)*
- *Template Function thrust::get\_temporary\_buffer*
- *Template Function thrust::inclusive\_scan(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, InputIterator, InputIterator, OutputIterator)*
- *Template Function thrust::inclusive\_scan(InputIterator, InputIterator, OutputIterator)*
- *Template Function thrust::inclusive\_scan(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, InputIterator, InputIterator, OutputIterator, AssociativeOperator)*
- *Template Function thrust::inclusive\_scan(InputIterator, InputIterator, OutputIterator, AssociativeOperator)*
- *Template Function thrust::inclusive\_scan\_by\_key(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, InputIterator1, InputIterator1, InputIterator2, OutputIterator)*
- *Template Function thrust::inclusive\_scan\_by\_key(InputIterator1, InputIterator1, InputIterator2, OutputIterator)*
- *Template Function thrust::inclusive\_scan\_by\_key(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, InputIterator1, InputIterator1, InputIterator2, OutputIterator, BinaryPredicate)*
- *Template Function thrust::inclusive\_scan\_by\_key(InputIterator1, InputIterator1, InputIterator2, OutputIterator, BinaryPredicate)*
- *Template Function thrust::inclusive\_scan\_by\_key(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, InputIterator1, InputIterator1, InputIterator2, OutputIterator, BinaryPredicate, AssociativeOperator)*
- *Template Function thrust::inclusive\_scan\_by\_key(InputIterator1, InputIterator1, InputIterator2, OutputIterator, BinaryPredicate, AssociativeOperator)*
- *Template Function thrust::inner\_product(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, InputIterator1, InputIterator1, InputIterator2, OutputType)*

- *Template Function thrust::inner\_product(InputIterator1, InputIterator1, InputIterator2, OutputType)*
- *Template Function thrust::inner\_product(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, InputIterator1, InputIterator1, InputIterator2, OutputType, BinaryFunction1, BinaryFunction2)*
- *Template Function thrust::inner\_product(InputIterator1, InputIterator1, InputIterator2, OutputType, BinaryFunction1, BinaryFunction2)*
- *Template Function thrust::is\_partitioned(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, InputIterator, InputIterator, Predicate)*
- *Template Function thrust::is\_partitioned(InputIterator, InputIterator, Predicate)*
- *Template Function thrust::is\_sorted(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, ForwardIterator, ForwardIterator)*
- *Template Function thrust::is\_sorted(ForwardIterator, ForwardIterator)*
- *Template Function thrust::is\_sorted(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, ForwardIterator, ForwardIterator, Compare)*
- *Template Function thrust::is\_sorted(ForwardIterator, ForwardIterator, Compare)*
- *Template Function thrust::is\_sorted\_until(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, ForwardIterator, ForwardIterator)*
- *Template Function thrust::is\_sorted\_until(ForwardIterator, ForwardIterator)*
- *Template Function thrust::is\_sorted\_until(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, ForwardIterator, ForwardIterator, Compare)*
- *Template Function thrust::is\_sorted\_until(ForwardIterator, ForwardIterator, Compare)*
- *Template Function thrust::log*
- *Template Function thrust::log10*
- *Template Function thrust::lower\_bound(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, ForwardIterator, ForwardIterator, const LessThanComparable&)*
- *Template Function thrust::lower\_bound(ForwardIterator, ForwardIterator, const LessThanComparable&)*
- *Template Function thrust::lower\_bound(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, ForwardIterator, ForwardIterator, const T&, StrictWeakOrdering)*
- *Template Function thrust::lower\_bound(ForwardIterator, ForwardIterator, const T&, StrictWeakOrdering)*
- *Template Function thrust::lower\_bound(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, ForwardIterator, ForwardIterator, InputIterator, InputIterator, OutputIterator)*
- *Template Function thrust::lower\_bound(ForwardIterator, ForwardIterator, InputIterator, InputIterator, InputIterator, OutputIterator)*
- *Template Function thrust::lower\_bound(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, ForwardIterator, ForwardIterator, InputIterator, InputIterator, OutputIterator, StrictWeakOrdering)*
- *Template Function thrust::lower\_bound(ForwardIterator, ForwardIterator, InputIterator, InputIterator, InputIterator, OutputIterator, StrictWeakOrdering)*
- *Template Function thrust::make\_pair*
- *Template Function thrust::make\_tuple(const T0&)*
- *Template Function thrust::make\_tuple(const T0&, const T1&)*
- *Template Function thrust::malloc(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, std::size\_t)*

- *Template Function thrust::malloc(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, std::size\_t)*
- *Template Function thrust::max\_element(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, ForwardIterator, ForwardIterator)*
- *Template Function thrust::max\_element(ForwardIterator, ForwardIterator)*
- *Template Function thrust::max\_element(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, ForwardIterator, ForwardIterator, BinaryPredicate)*
- *Template Function thrust::max\_element(ForwardIterator, ForwardIterator, BinaryPredicate)*
- *Template Function thrust::merge(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, InputIterator1, InputIterator1, InputIterator2, InputIterator2, OutputIterator)*
- *Template Function thrust::merge(InputIterator1, InputIterator1, InputIterator2, InputIterator2, OutputIterator)*
- *Template Function thrust::merge(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, InputIterator1, InputIterator1, InputIterator2, InputIterator2, OutputIterator, StrictWeakCompare)*
- *Template Function thrust::merge(InputIterator1, InputIterator1, InputIterator2, InputIterator2, OutputIterator, StrictWeakCompare)*
- *Template Function thrust::merge\_by\_key(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, InputIterator1, InputIterator1, InputIterator2, InputIterator2, InputIterator3, InputIterator4, OutputIterator1, OutputIterator2)*
- *Template Function thrust::merge\_by\_key(InputIterator1, InputIterator1, InputIterator2, InputIterator2, InputIterator3, InputIterator4, OutputIterator1, OutputIterator2)*
- *Template Function thrust::merge\_by\_key(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, InputIterator1, InputIterator1, InputIterator2, InputIterator2, InputIterator3, InputIterator4, OutputIterator1, OutputIterator2, Compare)*
- *Template Function thrust::merge\_by\_key(InputIterator1, InputIterator1, InputIterator2, InputIterator2, InputIterator3, InputIterator4, OutputIterator1, OutputIterator2, StrictWeakCompare)*
- *Template Function thrust::min\_element(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, ForwardIterator, ForwardIterator)*
- *Template Function thrust::min\_element(ForwardIterator, ForwardIterator)*
- *Template Function thrust::min\_element(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, ForwardIterator, ForwardIterator, BinaryPredicate)*
- *Template Function thrust::min\_element(ForwardIterator, ForwardIterator, BinaryPredicate)*
- *Template Function thrust::minmax\_element(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, ForwardIterator, ForwardIterator)*
- *Template Function thrust::minmax\_element(ForwardIterator, ForwardIterator)*
- *Template Function thrust::minmax\_element(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, ForwardIterator, ForwardIterator, BinaryPredicate)*
- *Template Function thrust::minmax\_element(ForwardIterator, ForwardIterator, BinaryPredicate)*
- *Template Function thrust::mismatch(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, InputIterator1, InputIterator1, InputIterator2)*
- *Template Function thrust::mismatch(InputIterator1, InputIterator1, InputIterator2)*
- *Template Function thrust::mismatch(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, InputIterator1, InputIterator1, InputIterator2, BinaryPredicate)*
- *Template Function thrust::mismatch(InputIterator1, InputIterator1, InputIterator2, BinaryPredicate)*

- *Template Function thrust::none\_of(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, InputIterator, InputIterator, Predicate)*
- *Template Function thrust::none\_of(InputIterator, InputIterator, Predicate)*
- *Template Function thrust::norm*
- *Template Function thrust::not1*
- *Template Function thrust::not2*
- *Template Function thrust::operator!=(const complex<T0>&, const complex<T1>&)*
- *Template Function thrust::operator!=(const complex<T0>&, const std::complex<T1>&)*
- *Template Function thrust::operator!=(const std::complex<T0>&, const complex<T1>&)*
- *Template Function thrust::operator!=(const T0&, const complex<T1>&)*
- *Template Function thrust::operator!=(const complex<T0>&, const T1 &)*
- *Template Function thrust::operator!=(const pair<T1, T2>&, const pair<T1, T2>&)*
- *Template Function thrust::operator\*(const complex<T0>&, const complex<T1>&)*
- *Template Function thrust::operator\*(const complex<T0>&, const T1 &)*
- *Template Function thrust::operator\*(const T0&, const complex<T1>&)*
- *Template Function thrust::operator+(const complex<T0>&, const complex<T1>&)*
- *Template Function thrust::operator+(const complex<T0>&, const complex<T1>&)*
- *Template Function thrust::operator+(const complex<T0>&, const T1 &)*
- *Template Function thrust::operator+(const T0&, const complex<T1>&)*
- *Template Function thrust::operator-(const complex<T0>&, const complex<T1>&)*
- *Template Function thrust::operator-(const complex<T0>&, const T1 &)*
- *Template Function thrust::operator-(const T0&, const complex<T1>&)*
- *Template Function thrust::operator-(const complex<T0>&, const complex<T1>&)*
- *Template Function thrust::operator/(const complex<T0>&, const complex<T1>&)*
- *Template Function thrust::operator/(const complex<T0>&, const T1 &)*
- *Template Function thrust::operator/(const T0&, const complex<T1>&)*
- *Template Function thrust::operator<*
- *Template Function thrust::operator<<*
- *Template Function thrust::operator<=*
- *Template Function thrust::operator==(const complex<T0>&, const complex<T1>&)*
- *Template Function thrust::operator==(const complex<T0>&, const std::complex<T1>&)*
- *Template Function thrust::operator==(const std::complex<T0>&, const complex<T1>&)*
- *Template Function thrust::operator==(const T0&, const complex<T1>&)*
- *Template Function thrust::operator==(const complex<T0>&, const T1 &)*
- *Template Function thrust::operator==(const pair<T1, T2>&, const pair<T1, T2>&)*
- *Template Function thrust::operator>*

- *Template Function thrust::operator>=*
- *Template Function thrust::operator>>*
- *Template Function thrust::partition(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, ForwardIterator, ForwardIterator, Predicate)*
- *Template Function thrust::partition(ForwardIterator, ForwardIterator, Predicate)*
- *Template Function thrust::partition(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, ForwardIterator, ForwardIterator, InputIterator, Predicate)*
- *Template Function thrust::partition(ForwardIterator, ForwardIterator, InputIterator, Predicate)*
- *Template Function thrust::partition\_copy(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, InputIterator, InputIterator, OutputIterator1, OutputIterator2, Predicate)*
- *Template Function thrust::partition\_copy(InputIterator, InputIterator, OutputIterator1, OutputIterator2, Predicate)*
- *Template Function thrust::partition\_copy(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, InputIterator1, InputIterator1, InputIterator2, OutputIterator1, OutputIterator2, Predicate)*
- *Template Function thrust::partition\_copy(InputIterator1, InputIterator1, InputIterator2, OutputIterator1, OutputIterator2, Predicate)*
- *Template Function thrust::partition\_point(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, ForwardIterator, ForwardIterator, Predicate)*
- *Template Function thrust::partition\_point(ForwardIterator, ForwardIterator, Predicate)*
- *Template Function thrust::polar*
- *Template Function thrust::pow(const complex<T0>&, const complex<T1>&)*
- *Template Function thrust::pow(const complex<T0>&, const T1&)*
- *Template Function thrust::pow(const T0&, const complex<T1>&)*
- *Template Function thrust::proj*
- *Template Function thrust::raw\_pointer\_cast*
- *Template Function thrust::raw\_reference\_cast(T&)*
- *Template Function thrust::raw\_reference\_cast(const T&)*
- *Template Function thrust::reduce(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, InputIterator, InputIterator)*
- *Template Function thrust::reduce(InputIterator, InputIterator)*
- *Template Function thrust::reduce(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, InputIterator, InputIterator, T)*
- *Template Function thrust::reduce(InputIterator, InputIterator, T)*
- *Template Function thrust::reduce(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, InputIterator, InputIterator, T, BinaryFunction)*
- *Template Function thrust::reduce(InputIterator, InputIterator, T, BinaryFunction)*
- *Template Function thrust::reduce\_by\_key(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, InputIterator1, InputIterator1, InputIterator2, OutputIterator1, OutputIterator2)*
- *Template Function thrust::reduce\_by\_key(InputIterator1, InputIterator1, InputIterator2, OutputIterator1, OutputIterator2)*

- *Template Function thrust::reduce\_by\_key(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, InputIterator1, InputIterator1, InputIterator2, OutputIterator1, OutputIterator2, BinaryPredicate)*
- *Template Function thrust::reduce\_by\_key(InputIterator1, InputIterator1, InputIterator2, OutputIterator1, OutputIterator2, BinaryPredicate)*
- *Template Function thrust::reduce\_by\_key(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, InputIterator1, InputIterator1, InputIterator2, OutputIterator1, OutputIterator2, BinaryPredicate, BinaryFunction)*
- *Template Function thrust::reduce\_by\_key(InputIterator1, InputIterator1, InputIterator2, OutputIterator1, OutputIterator2, BinaryPredicate, BinaryFunction)*
- *Template Function thrust::remove(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, ForwardIterator, ForwardIterator, const T&)*
- *Template Function thrust::remove(ForwardIterator, ForwardIterator, const T&)*
- *Template Function thrust::remove\_copy(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, InputIterator, InputIterator, OutputIterator, const T&)*
- *Template Function thrust::remove\_copy(InputIterator, InputIterator, OutputIterator, const T&)*
- *Template Function thrust::remove\_copy\_if(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, InputIterator, InputIterator, OutputIterator, Predicate)*
- *Template Function thrust::remove\_copy\_if(InputIterator, InputIterator, OutputIterator, Predicate)*
- *Template Function thrust::remove\_copy\_if(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, InputIterator1, InputIterator1, InputIterator2, OutputIterator, Predicate)*
- *Template Function thrust::remove\_copy\_if(InputIterator1, InputIterator1, InputIterator2, OutputIterator, Predicate)*
- *Template Function thrust::remove\_if(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, ForwardIterator, ForwardIterator, Predicate)*
- *Template Function thrust::remove\_if(ForwardIterator, ForwardIterator, Predicate)*
- *Template Function thrust::remove\_if(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, ForwardIterator, ForwardIterator, InputIterator, Predicate)*
- *Template Function thrust::remove\_if(ForwardIterator, ForwardIterator, InputIterator, Predicate)*
- *Template Function thrust::replace(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, ForwardIterator, ForwardIterator, const T&, const T&)*
- *Template Function thrust::replace(ForwardIterator, ForwardIterator, const T&, const T&)*
- *Template Function thrust::replace\_copy(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, InputIterator, InputIterator, OutputIterator, const T&, const T&)*
- *Template Function thrust::replace\_copy(InputIterator, InputIterator, OutputIterator, const T&, const T&)*
- *Template Function thrust::replace\_copy\_if(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, InputIterator, InputIterator, OutputIterator, Predicate, const T&)*
- *Template Function thrust::replace\_copy\_if(InputIterator, InputIterator, OutputIterator, Predicate, const T&)*
- *Template Function thrust::replace\_copy\_if(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, InputIterator1, InputIterator1, InputIterator2, OutputIterator, Predicate, const T&)*
- *Template Function thrust::replace\_copy\_if(InputIterator1, InputIterator1, InputIterator2, OutputIterator, Predicate, const T&)*
- *Template Function thrust::replace\_copy\_if(InputIterator1, InputIterator1, InputIterator2, OutputIterator, Predicate, const T&)*

- *Template Function thrust::replace\_if(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, ForwardIterator, ForwardIterator, Predicate, const T&)*
- *Template Function thrust::replace\_if(ForwardIterator, ForwardIterator, Predicate, const T&)*
- *Template Function thrust::replace\_if(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, ForwardIterator, ForwardIterator, InputIterator, Predicate, const T&)*
- *Template Function thrust::replace\_if(ForwardIterator, ForwardIterator, InputIterator, Predicate, const T&)*
- *Template Function thrust::return\_temporary\_buffer*
- *Template Function thrust::reverse(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, BidirectionalIterator, BidirectionalIterator)*
- *Template Function thrust::reverse(BidirectionalIterator, BidirectionalIterator)*
- *Template Function thrust::reverse\_copy(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, BidirectionalIterator, BidirectionalIterator, OutputIterator)*
- *Template Function thrust::reverse\_copy(BidirectionalIterator, BidirectionalIterator, OutputIterator)*
- *Template Function thrust::scatter(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, InputIterator1, InputIterator1, InputIterator2, RandomAccessIterator)*
- *Template Function thrust::scatter(InputIterator1, InputIterator1, InputIterator2, RandomAccessIterator)*
- *Template Function thrust::scatter\_if(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, InputIterator1, InputIterator1, InputIterator2, InputIterator3, RandomAccessIterator)*
- *Template Function thrust::scatter\_if(InputIterator1, InputIterator1, InputIterator2, InputIterator3, RandomAccessIterator)*
- *Template Function thrust::scatter\_if(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, InputIterator1, InputIterator1, InputIterator2, InputIterator3, RandomAccessIterator, Predicate)*
- *Template Function thrust::scatter\_if(InputIterator1, InputIterator1, InputIterator2, InputIterator3, RandomAccessIterator, Predicate)*
- *Template Function thrust::sequence(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, ForwardIterator, ForwardIterator)*
- *Template Function thrust::sequence(ForwardIterator, ForwardIterator)*
- *Template Function thrust::sequence(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, ForwardIterator, ForwardIterator, T)*
- *Template Function thrust::sequence(ForwardIterator, ForwardIterator, T)*
- *Template Function thrust::sequence(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, ForwardIterator, ForwardIterator, T, T)*
- *Template Function thrust::sequence(ForwardIterator, ForwardIterator, T, T)*
- *Template Function thrust::set\_difference(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, InputIterator1, InputIterator1, InputIterator2, InputIterator2, OutputIterator)*
- *Template Function thrust::set\_difference(InputIterator1, InputIterator1, InputIterator2, InputIterator2, OutputIterator)*
- *Template Function thrust::set\_difference(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, InputIterator1, InputIterator1, InputIterator2, InputIterator2, OutputIterator, StrictWeakCompare)*
- *Template Function thrust::set\_difference(InputIterator1, InputIterator1, InputIterator2, InputIterator2, OutputIterator, StrictWeakCompare)*



- *Template Function thrust::set\_symmetric\_difference\_by\_key(InputIterator1, InputIterator1, InputIterator2, InputIterator2, InputIterator3, InputIterator4, OutputIterator1, OutputIterator2, StrictWeakCompare)*
- *Template Function thrust::set\_union(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, InputIterator1, InputIterator1, InputIterator2, InputIterator2, OutputIterator)*
- *Template Function thrust::set\_union(InputIterator1, InputIterator1, InputIterator2, InputIterator2, OutputIterator)*
- *Template Function thrust::set\_union(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, InputIterator1, InputIterator1, InputIterator2, InputIterator2, OutputIterator, StrictWeakCompare)*
- *Template Function thrust::set\_union(InputIterator1, InputIterator1, InputIterator2, InputIterator2, OutputIterator, StrictWeakCompare)*
- *Template Function thrust::set\_union\_by\_key(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, InputIterator1, InputIterator1, InputIterator2, InputIterator2, InputIterator3, InputIterator4, OutputIterator1, OutputIterator2)*
- *Template Function thrust::set\_union\_by\_key(InputIterator1, InputIterator1, InputIterator2, InputIterator2, InputIterator3, InputIterator4, OutputIterator1, OutputIterator2)*
- *Template Function thrust::set\_union\_by\_key(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, InputIterator1, InputIterator1, InputIterator2, InputIterator2, InputIterator3, InputIterator4, OutputIterator1, OutputIterator2, StrictWeakCompare)*
- *Template Function thrust::set\_union\_by\_key(InputIterator1, InputIterator1, InputIterator2, InputIterator2, InputIterator3, InputIterator4, OutputIterator1, OutputIterator2, StrictWeakCompare)*
- *Template Function thrust::sin*
- *Template Function thrust::sinh*
- *Template Function thrust::sort(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, RandomAccessIterator, RandomAccessIterator)*
- *Template Function thrust::sort(RandomAccessIterator, RandomAccessIterator)*
- *Template Function thrust::sort(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, RandomAccessIterator, RandomAccessIterator, StrictWeakOrdering)*
- *Template Function thrust::sort(RandomAccessIterator, RandomAccessIterator, StrictWeakOrdering)*
- *Template Function thrust::sort\_by\_key(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, RandomAccessIterator1, RandomAccessIterator1, RandomAccessIterator2)*
- *Template Function thrust::sort\_by\_key(RandomAccessIterator1, RandomAccessIterator1, RandomAccessIterator2)*
- *Template Function thrust::sort\_by\_key(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, RandomAccessIterator1, RandomAccessIterator1, RandomAccessIterator2, StrictWeakOrdering)*
- *Template Function thrust::sort\_by\_key(RandomAccessIterator1, RandomAccessIterator1, RandomAccessIterator2, StrictWeakOrdering)*
- *Template Function thrust::sqrt*
- *Template Function thrust::stable\_partition(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, ForwardIterator, ForwardIterator, Predicate)*
- *Template Function thrust::stable\_partition(ForwardIterator, ForwardIterator, Predicate)*
- *Template Function thrust::stable\_partition(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, ForwardIterator, ForwardIterator, InputIterator, Predicate)*

- *Template Function thrust::stable\_partition(ForwardIterator, ForwardIterator, InputIterator, Predicate)*
- *Template Function thrust::stable\_partition\_copy(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, InputIterator, InputIterator, OutputIterator1, OutputIterator2, Predicate)*
- *Template Function thrust::stable\_partition\_copy(InputIterator, InputIterator, OutputIterator1, OutputIterator2, Predicate)*
- *Template Function thrust::stable\_partition\_copy(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, InputIterator1, InputIterator1, InputIterator2, OutputIterator1, OutputIterator2, Predicate)*
- *Template Function thrust::stable\_partition\_copy(InputIterator1, InputIterator1, InputIterator2, OutputIterator1, OutputIterator2, Predicate)*
- *Template Function thrust::stable\_sort(RandomAccessIterator, RandomAccessIterator, StrictWeakOrdering)*
- *Template Function thrust::stable\_sort(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, RandomAccessIterator, RandomAccessIterator)*
- *Template Function thrust::stable\_sort(RandomAccessIterator, RandomAccessIterator)*
- *Template Function thrust::stable\_sort(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, RandomAccessIterator, RandomAccessIterator, StrictWeakOrdering)*
- *Template Function thrust::stable\_sort\_by\_key(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, RandomAccessIterator1, RandomAccessIterator1, RandomAccessIterator2)*
- *Template Function thrust::stable\_sort\_by\_key(RandomAccessIterator1, RandomAccessIterator1, RandomAccessIterator2)*
- *Template Function thrust::stable\_sort\_by\_key(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, RandomAccessIterator1, RandomAccessIterator1, RandomAccessIterator2, StrictWeakOrdering)*
- *Template Function thrust::stable\_sort\_by\_key(RandomAccessIterator1, RandomAccessIterator1, RandomAccessIterator2, StrictWeakOrdering)*
- *Template Function thrust::swap(device\_reference<T>&, device\_reference<T>&)*
- *Template Function thrust::swap(pair<T1, T2>&, pair<T1, T2>&)*
- *Template Function thrust::swapAssignable1&, Assignable2&)*
- *Template Function thrust::swap(tuple<T0, T1, T2, T3, T4, T5, T6, T7, T8, T9>&, tuple<U0, U1, U2, U3, U4, U5, U6, U7, U8, U9>&)*
- *Template Function thrust::swap\_ranges(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, ForwardIterator1, ForwardIterator1, ForwardIterator2)*
- *Template Function thrust::swap\_ranges(ForwardIterator1, ForwardIterator1, ForwardIterator2)*
- *Template Function thrust::tabulate(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, ForwardIterator, ForwardIterator, UnaryOperation)*
- *Template Function thrust::tabulate(ForwardIterator, ForwardIterator, UnaryOperation)*
- *Template Function thrust::tan*
- *Template Function thrust::tanh*
- *Template Function thrust::THRUST\_PREVENT\_MACRO\_SUBSTITUTION(const T&, const T&, BinaryPredicate)*
- *Template Function thrust::THRUST\_PREVENT\_MACRO\_SUBSTITUTION(const T&, const T&)*
- *Template Function thrust::THRUST\_PREVENT\_MACRO\_SUBSTITUTION(const T&, const T&, BinaryPredicate)*

- *Template Function thrust::THRUST\_PREVENT\_MACRO\_SUBSTITUTION(const T&, const T&)*
- *Template Function thrust::tie(T0&)*
- *Template Function thrust::tie(T0&, T1&)*
- *Template Function thrust::transform(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, InputIterator, InputIterator, OutputIterator, UnaryFunction)*
- *Template Function thrust::transform(InputIterator, InputIterator, OutputIterator, UnaryFunction)*
- *Template Function thrust::transform(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, InputIterator1, InputIterator1, InputIterator2, OutputIterator, BinaryFunction)*
- *Template Function thrust::transform(InputIterator1, InputIterator1, InputIterator2, OutputIterator, BinaryFunction)*
- *Template Function thrust::transform\_exclusive\_scan(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, InputIterator, InputIterator, OutputIterator, UnaryFunction, T, AssociativeOperator)*
- *Template Function thrust::transform\_exclusive\_scan(InputIterator, InputIterator, OutputIterator, UnaryFunction, T, AssociativeOperator)*
- *Template Function thrust::transform\_if(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, InputIterator, InputIterator, ForwardIterator, UnaryFunction, Predicate)*
- *Template Function thrust::transform\_if(InputIterator, InputIterator, ForwardIterator, UnaryFunction, Predicate)*
- *Template Function thrust::transform\_if(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, InputIterator1, InputIterator1, InputIterator2, ForwardIterator, UnaryFunction, Predicate)*
- *Template Function thrust::transform\_if(InputIterator1, InputIterator1, InputIterator2, ForwardIterator, UnaryFunction, Predicate)*
- *Template Function thrust::transform\_if(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, InputIterator1, InputIterator1, InputIterator2, InputIterator3, ForwardIterator, BinaryFunction, Predicate)*
- *Template Function thrust::transform\_if(InputIterator1, InputIterator1, InputIterator2, InputIterator3, ForwardIterator, BinaryFunction, Predicate)*
- *Template Function thrust::transform\_inclusive\_scan(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, InputIterator, InputIterator, OutputIterator, UnaryFunction, AssociativeOperator)*
- *Template Function thrust::transform\_inclusive\_scan(InputIterator, InputIterator, OutputIterator, UnaryFunction, AssociativeOperator)*
- *Template Function thrust::transform\_reduce(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, InputIterator, InputIterator, UnaryFunction, OutputType, BinaryFunction)*
- *Template Function thrust::transform\_reduce(InputIterator, InputIterator, UnaryFunction, OutputType, BinaryFunction)*
- *Template Function thrust::uninitialized\_copy(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, InputIterator, InputIterator, ForwardIterator)*
- *Template Function thrust::uninitialized\_copy(InputIterator, InputIterator, ForwardIterator)*
- *Template Function thrust::uninitialized\_copy\_n(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, InputIterator, Size, ForwardIterator)*
- *Template Function thrust::uninitialized\_copy\_n(InputIterator, Size, ForwardIterator)*
- *Template Function thrust::uninitialized\_fill(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, ForwardIterator, ForwardIterator, const T&)*

- *Template Function thrust::uninitialized\_fill(ForwardIterator, ForwardIterator, const T&)*
- *Template Function thrust::uninitialized\_fill\_n(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, ForwardIterator, Size, const T&)*
- *Template Function thrust::uninitialized\_fill\_n(ForwardIterator, Size, const T&)*
- *Template Function thrust::unique(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, ForwardIterator, ForwardIterator)*
- *Template Function thrust::unique(ForwardIterator, ForwardIterator)*
- *Template Function thrust::unique(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, ForwardIterator, ForwardIterator, BinaryPredicate)*
- *Template Function thrust::unique(ForwardIterator, ForwardIterator, BinaryPredicate)*
- *Template Function thrust::unique\_by\_key(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, ForwardIterator1, ForwardIterator1, ForwardIterator2)*
- *Template Function thrust::unique\_by\_key(ForwardIterator1, ForwardIterator1, ForwardIterator2)*
- *Template Function thrust::unique\_by\_key(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, ForwardIterator1, ForwardIterator1, ForwardIterator2, BinaryPredicate)*
- *Template Function thrust::unique\_by\_key(ForwardIterator1, ForwardIterator1, ForwardIterator2, BinaryPredicate)*
- *Template Function thrust::unique\_by\_key\_copy(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, InputIterator1, InputIterator1, InputIterator2, OutputIterator1, OutputIterator2)*
- *Template Function thrust::unique\_by\_key\_copy(InputIterator1, InputIterator1, InputIterator2, OutputIterator1, OutputIterator2)*
- *Template Function thrust::unique\_by\_key\_copy(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, InputIterator1, InputIterator1, InputIterator2, OutputIterator1, OutputIterator2, BinaryPredicate)*
- *Template Function thrust::unique\_by\_key\_copy(InputIterator1, InputIterator1, InputIterator2, OutputIterator1, OutputIterator2, BinaryPredicate)*
- *Template Function thrust::unique\_copy(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, InputIterator, InputIterator, OutputIterator)*
- *Template Function thrust::unique\_copy(InputIterator, InputIterator, OutputIterator)*
- *Template Function thrust::unique\_copy(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, InputIterator, InputIterator, OutputIterator, BinaryPredicate)*
- *Template Function thrust::unique\_copy(InputIterator, InputIterator, OutputIterator, BinaryPredicate)*
- *Template Function thrust::upper\_bound(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, ForwardIterator, ForwardIterator, const LessThanComparable&)*
- *Template Function thrust::upper\_bound(ForwardIterator, ForwardIterator, const LessThanComparable&)*
- *Template Function thrust::upper\_bound(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, ForwardIterator, ForwardIterator, const T&, StrictWeakOrdering)*
- *Template Function thrust::upper\_bound(ForwardIterator, ForwardIterator, const T&, StrictWeakOrdering)*
- *Template Function thrust::upper\_bound(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, ForwardIterator, ForwardIterator, InputIterator, InputIterator, OutputIterator)*
- *Template Function thrust::upper\_bound(ForwardIterator, ForwardIterator, InputIterator, InputIterator, OutputIterator)*

- *Template Function thrust::upper\_bound(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, ForwardIterator, ForwardIterator, InputIterator, InputIterator, OutputIterator, StrictWeakOrdering)*
- *Template Function thrust::upper\_bound(ForwardIterator, ForwardIterator, InputIterator, InputIterator, InputIterator, OutputIterator, StrictWeakOrdering)*

## Variables

- *Variable thrust::device*
- *Variable thrust::host*

## Namespace thrust::placeholders

### Contents

- *Variables*

## Variables

- *Variable thrust::placeholders::\_1*
- *Variable thrust::placeholders::\_10*
- *Variable thrust::placeholders::\_2*
- *Variable thrust::placeholders::\_3*
- *Variable thrust::placeholders::\_4*
- *Variable thrust::placeholders::\_5*
- *Variable thrust::placeholders::\_6*
- *Variable thrust::placeholders::\_7*
- *Variable thrust::placeholders::\_8*
- *Variable thrust::placeholders::\_9*

## Namespace thrust::random

thrust::random is the namespace which contains random number engine class templates, random number engine adaptor class templates, engines with predefined parameters, and random number distribution class templates. They are provided in a separate namespace for import convenience but are also aliased in the top-level `thrust` namespace for easy access.

### Contents

- *Typedefs*

## Typedefs

- *Typedef thrust::random::default\_random\_engine*
- *Typedef thrust::random::ranlux24*
- *Typedef thrust::random::ranlux48*
- *Typedef thrust::random::taus88*

## Namespace thrust::system

thrust::system is the namespace which contains functionality for manipulating memory specific to one of Thrust's backend systems. It also contains functionality for reporting error conditions originating from the operating system or other low-level application program interfaces such as the HIP runtime. They are provided in a separate namespace for import convenience but are also aliased in the top-level `thrust` namespace for easy access.

### 1.3.2 Classes and Structs

#### Template Struct `binary_function`

- Defined in `file_thrust_functional.h`

#### Struct Documentation

```
template<typename Argument1, typename Argument2, typename Result>
struct binary_function
```

`binary_function` is an empty base class: it contains no member functions or member variables, but only type information. The only reason it exists is to make it more convenient to define types that are models of the concept Adaptable Binary Function. Specifically, any model of Adaptable Binary Function must define nested `typedefs`. Those `typedefs` are provided by the base class `binary_function`.

The following code snippet demonstrates how to construct an Adaptable Binary Function using `binary_function`.

```
struct exponentiate : public thrust::binary_function<float, float, float>
{
    __host__ __device__
    float operator()(float x, float y) { return powf(x,y); }
};
```

**Note** Because C++11 language support makes the functionality of `binary_function` obsolete, its use is optional if C++11 language features are enabled.

**See** [http://www.sgi.com/tech/stl/binary\\_function.html](http://www.sgi.com/tech/stl/binary_function.html)

**See** `unary_function`

#### Public Types

```
typedef first_argument_type
```

The type of the function object's first argument.

---

**typedef second\_argument\_type**  
The type of the function object's second argument.

**typedef result\_type**  
The type of the function object's result;.

### Template Struct binary\_negate

- Defined in file\_thrust\_functional.h

### Inheritance Relationships

#### Base Type

- public thrust::binary\_function< Predicate::first\_argument\_type, Predicate::second\_argument\_type, bool > (*Template Struct binary\_function*)

### Struct Documentation

```
template<typename Predicate>
struct binary_negate : public thrust::binary_function<Predicate::first_argument_type, Predicate::second_argument_type, bool>
```

*binary\_negate* is a function object adaptor: it is an Adaptable Binary Predicate that represents the logical negation of some other Adaptable Binary Predicate. That is: if *f* is an object of class *binary\_negate*<AdaptablePredicate>, then there exists an object *pred* of class AdaptableBinaryPredicate such that *f*(*x*, *y*) always returns the same value as !*pred*(*x*, *y*). There is rarely any reason to construct a *binary\_negate* directly; it is almost always easier to use the helper function *not2*.

See [http://www.sgi.com/tech/stl/binary\\_negate.html](http://www.sgi.com/tech/stl/binary_negate.html)

#### Public Functions

---

**\_\_host\_\_ \_\_device\_\_ thrust::binary\_negate::binary\_negate(Predicate p)**  
Constructor takes a Predicate object to negate.

##### Parameters

- p*: The Predicate object to negate.

---

**\_\_host\_\_ \_\_device\_\_ bool thrust::binary\_negate::operator()(const typename Predicate::first\_argument\_type x, const typename Predicate::second\_argument\_type y)**  
Function call operator. The return value is !*pred*(*x*, *y*).

### Template Struct binary\_traits

- Defined in file\_thrust\_functional.h

### Struct Documentation

---

```
template<typename Operation>
struct binary_traits
```

## Template Struct `bit_and`

- Defined in `file_thrust_functional.h`

### Struct Documentation

```
template<typename T>
struct bit_and
```

`bit_and` is a function object. Specifically, it is an Adaptable Binary Function. If `f` is an object of class `bit_and<T>`, and `x` and `y` are objects of class `T`, then `f(x, y)` returns `x&y`.

The following code snippet demonstrates how to use `bit_and` to take the bitwise AND of one `device_vector` of `ints` by another.

#### Template Parameters

- `T`: is a model of `Assignable`, and if `x` and `y` are objects of type `T`, then `x&y` must be defined and must have a return type that is convertible to `T`.

```
#include <thrust/device_vector.h>
#include <thrust/functional.h>
#include <thrust/sequence.h>
#include <thrust/fill.h>
#include <thrust/transform.h>
...
const int N = 1000;
thrust::device_vector<int> V1(N);
thrust::device_vector<int> V2(N);
thrust::device_vector<int> V3(N);

thrust::sequence(V1.begin(), V1.end(), 1);
thrust::fill(V2.begin(), V2.end(), 13);

thrust::transform(V1.begin(), V1.end(), V2.begin(), V3.begin(),
                 thrust::bit_and<int>());
// V3 is now {1&13, 2&13, 3&13, ..., 1000%13}
```

See `binary_function`

### Public Types

**typedef first\_argument\_type**

The type of the function object's first argument.

**typedef second\_argument\_type**

The type of the function object's second argument.

**typedef result\_type**

The type of the function object's result;

### Public Functions

```
__host__ __device__ T thrust::bit_and::operator() (const T & lhs, const T & rhs) const
```

Function call operator. The return value is `lhs & rhs`.

## Template Struct `bit_or`

- Defined in file `thrust/functional.h`

## Struct Documentation

```
template<typename T>
```

```
struct bit_or
```

`bit_or` is a function object. Specifically, it is an Adaptable Binary Function. If `f` is an object of class `bit_and<T>`, and `x` and `y` are objects of class `T`, then `f(x, y)` returns `x | y`.

The following code snippet demonstrates how to use `bit_or` to take the bitwise OR of one `device_vector` of ints by another.

### Template Parameters

- `T`: is a model of `Assignable`, and if `x` and `y` are objects of type `T`, then `x | y` must be defined and must have a return type that is convertible to `T`.

```
#include <thrust/device_vector.h>
#include <thrust/functional.h>
#include <thrust/sequence.h>
#include <thrust/fill.h>
#include <thrust/transform.h>

...
const int N = 1000;
thrust::device_vector<int> V1(N);
thrust::device_vector<int> V2(N);
thrust::device_vector<int> V3(N);

thrust::sequence(V1.begin(), V1.end(), 1);
thrust::fill(V2.begin(), V2.end(), 13);

thrust::transform(V1.begin(), V1.end(), V2.begin(), V3.begin(),
                 thrust::bit_or<int>());
// V3 is now {1/13, 2/13, 3/13, ..., 1000/13}
```

See `binary_function`

## Public Types

**typedef first\_argument\_type**

The type of the function object's first argument.

**typedef second\_argument\_type**

The type of the function object's second argument.

**typedef result\_type**

The type of the function object's result;

## Public Functions

```
__host__ __device__ T thrust::bit_or::operator()(const T & lhs, const T & rhs) const
```

Function call operator. The return value is `lhs | rhs`.

## Template Struct `bit_xor`

- Defined in file `thrust_functional.h`

## Struct Documentation

```
template<typename T>
```

```
struct bit_xor
```

`bit_xor` is a function object. Specifically, it is an Adaptable Binary Function. If `f` is an object of class `bit_and<T>`, and `x` and `y` are objects of class `T`, then `f(x, y)` returns `x^y`.

The following code snippet demonstrates how to use `bit_xor` to take the bitwise XOR of one `device_vector` of `ints` by another.

### Template Parameters

- `T`: is a model of `Assignable`, and if `x` and `y` are objects of type `T`, then `x^y` must be defined and must have a return type that is convertible to `T`.

```
#include <thrust/device_vector.h>
#include <thrust/functional.h>
#include <thrust/sequence.h>
#include <thrust/fill.h>
#include <thrust/transform.h>
...
const int N = 1000;
thrust::device_vector<int> V1(N);
thrust::device_vector<int> V2(N);
thrust::device_vector<int> V3(N);

thrust::sequence(V1.begin(), V1.end(), 1);
thrust::fill(V2.begin(), V2.end(), 13);

thrust::transform(V1.begin(), V1.end(), V2.begin(), V3.begin(),
                 thrust::bit_xor<int>());
// V3 is now {1^13, 2^13, 3^13, ..., 1000^13}
```

See `binary_function`

## Public Types

```
typedef first_argument_type
```

The type of the function object's first argument.

```
typedef second_argument_type
```

The type of the function object's second argument.

```
typedef result_type
```

The type of the function object's result;

## Public Functions

```
__host__ __device__ T thrust::bit_xor::operator()(const T & lhs, const T & rhs) const
```

Function call operator. The return value is `lhs ^ rhs`.

## Template Struct complex

- Defined in file\_thrust\_complex.h

### Struct Documentation

```
template<typename T>
struct complex
```

`complex` is the Thrust equivalent to `std::complex`. It is functionally identical to it, but can also be used in device code which `std::complex` currently cannot.

#### Template Parameters

- `T`: The type used to hold the real and imaginary parts. Should be `float` or `double`. Others types are not supported.

#### Public Types

```
typedef T value_type
```

`value_type` is the type of `complex`'s real and imaginary parts.

#### Public Functions

```
__host__ __device__ thrust::complex::complex(const T & re)
```

Construct a complex number with an imaginary part of 0.

##### Parameters

- `re`: The real part of the number.

```
__host__ __device__ thrust::complex::complex(const T & re, const T & im)
```

Construct a complex number from its real and imaginary parts.

##### Parameters

- `re`: The real part of the number.
- `im`: The imaginary part of the number.

```
__host__ __device__ thrust::complex::complex()
```

Default construct a complex number.

```
__host__ __device__ thrust::complex::complex(const complex < T > & z)
```

This copy constructor copies from a `complex` with a type that is convertible to this `complex`'s `value_type`.

##### Parameters

- `z`: The `complex` to copy from.

```
template<typename U> __host__ __device__ thrust::complex::complex(const complex < U >
```

This converting copy constructor copies from a `complex` with a type that is convertible to this `complex`'s `value_type`.

##### Parameters

- z: The complex to copy from.

#### Template Parameters

- U: is convertible to value\_type.

```
host_ THRUST_STD_COMPLEX_DEVICE thrust::complex(const std::complex< T > &
```

This converting copy constructor copies from a std::complex with a type that is convertible to this complex's value\_type.

#### Parameters

- z: The complex to copy from.

```
template<typename U> host_ THRUST_STD_COMPLEX_DEVICE thrust::complex(const
```

This converting copy constructor copies from a std::complex with a type that is convertible to this complex's value\_type.

#### Parameters

- z: The complex to copy from.

#### Template Parameters

- U: is convertible to value\_type.

```
host_ __device_ complex& thrust::complex::operator=(const T & re)
```

Assign re to the real part of this complex and set the imaginary part to 0.

#### Parameters

- re: The real part of the number.

```
host_ __device_ complex& thrust::complex::operator=(const complex < T > & z)
```

Assign z.real() and z.imag() to the real and imaginary parts of this complex respectively.

#### Parameters

- z: The complex to copy from.

```
template<typename U> host_ __device_ complex& thrust::complex::operator=(const complex & comp)
```

Assign z.real() and z.imag() to the real and imaginary parts of this complex respectively.

#### Parameters

- z: The complex to copy from.

#### Template Parameters

- U: is convertible to value\_type.

```
host_ THRUST_STD_COMPLEX_DEVICE complex& thrust::complex::operator=(const std::comp)
```

Assign z.real() and z.imag() to the real and imaginary parts of this complex respectively.

#### Parameters

- z: The complex to copy from.

```
template<typename U> host_ THRUST_STD_COMPLEX_DEVICE complex& thrust::complex::operator=
```

Assign z.real() and z.imag() to the real and imaginary parts of this complex respectively.

#### Parameters

- z: The complex to copy from.

**Template Parameters**

- U: is convertible to value\_type.

```
template<typename U> __host__ __device__ complex<T>& thrust::complex::operator+=(const
    Adds a complex to this complex and assigns the result to this complex.
```

**Parameters**

- z: The complex to be added.

**Template Parameters**

- U: is convertible to value\_type.

```
template<typename U> __host__ __device__ complex<T>& thrust::complex::operator-=(const
    Subtracts a complex from this complex and assigns the result to this complex.
```

**Parameters**

- z: The complex to be subtracted.

**Template Parameters**

- U: is convertible to value\_type.

```
template<typename U> __host__ __device__ complex<T>& thrust::complex::operator*=(const
    Multiplies this complex by another complex and assigns the result to this complex.
```

**Parameters**

- z: The complex to be multiplied.

**Template Parameters**

- U: is convertible to value\_type.

```
template<typename U> __host__ __device__ complex<T>& thrust::complex::operator/=(const
    Divides this complex by another complex and assigns the result to this complex.
```

**Parameters**

- z: The complex to be divided.

**Template Parameters**

- U: is convertible to value\_type.

```
template<typename U> __host__ __device__ complex<T>& thrust::complex::operator+=(const
    Adds a scalar to this complex and assigns the result to this complex.
```

**Parameters**

- z: The complex to be added.

**Template Parameters**

- U: is convertible to value\_type.

```
template<typename U> __host__ __device__ complex<T>& thrust::complex::operator-=(const
    Subtracts a scalar from this complex and assigns the result to this complex.
```

**Parameters**

- z: The scalar to be subtracted.

### Template Parameters

- U: is convertible to value\_type.

```
template<typename U> __host__ __device__ complex<T>& thrust::complex::operator*=(const U& z);
```

Multiples this complex by a scalar and assigns the result to this complex.

### Parameters

- z: The scalar to be multiplied.

### Template Parameters

- U: is convertible to value\_type.

```
template<typename U> __host__ __device__ complex<T>& thrust::complex::operator/=(const U& z);
```

Divides this complex by a scalar and assigns the result to this complex.

### Parameters

- z: The scalar to be divided.

### Template Parameters

- U: is convertible to value\_type.

```
__host__ __device__ T thrust::complex::real() const volatile;
```

Returns the real part of this complex.

```
__host__ __device__ T thrust::complex::imag() const volatile;
```

Returns the imaginary part of this complex.

```
__host__ __device__ T thrust::complex::real() const;
```

Returns the real part of this complex.

```
__host__ __device__ T thrust::complex::imag() const;
```

Returns the imaginary part of this complex.

```
__host__ __device__ void thrust::complex::real(T re) volatile;
```

Sets the real part of this complex.

### Parameters

- re: The new real part of this complex.

```
__host__ __device__ void thrust::complex::imag(T im) volatile;
```

Sets the imaginary part of this complex.

### Parameters

- im: The new imaginary part of this complex.

```
__host__ __device__ void thrust::complex::real(T re) volatile;
```

Sets the real part of this complex.

### Parameters

- re: The new real part of this complex.

```
__host__ __device__ void thrust::complex::imag(T im) volatile;
```

Sets the imaginary part of this complex.

### Parameters

- `im`: The new imaginary part of this `complex`.
- `__host__ __device__ thrust::complex< T >() const`**  
Casts this `complex` to a `std::complex` of the same type.

## Template Struct `device_allocator::rebind`

- Defined in file `thrust/device_allocator.h`

### Nested Relationships

This struct is a nested type of [Template Class `device\_allocator`](#).

### Struct Documentation

```
template<typename U>
struct rebind
The rebind metafunction provides the type of a device_allocator instantiated with another type.
```

#### Template Parameters

- `U`: The other type to use for instantiation.

### Public Types

```
template<>
typedef device_allocator<U> other
The typedef other gives the type of the rebound device_allocator.
```

## Template Struct `device_allocator< void >::device_allocator< void >`

- Defined in file `thrust/device_allocator.h`

### Nested Relationships

This struct is a nested type of [Template Class `device\_allocator< void >`](#).

### Struct Documentation

```
template<typename U>
struct rebind
The rebind metafunction provides the type of a device_allocator instantiated with another type.
```

#### Template Parameters

- `U`: The other type to use for instantiation.

## Public Types

```
template<>
```

```
typedef device_allocator<U> other
```

The typedef `other` gives the type of the rebound `device_allocator`.

## Template Struct `device_execution_policy`

- Defined in file `thrust_execution_policy.h`

## Inheritance Relationships

### Base Type

- `public thrust::system::__THRUST_DEVICE_SYSTEM_NAMESPACE::execution_policy<DerivedPolicy >`

## Struct Documentation

```
template<typename DerivedPolicy>
```

```
struct device_execution_policy : public thrust::system::__THRUST_DEVICE_SYSTEM_NAMESPACE::execution_policy<  
device_execution_policy>
```

`device_execution_policy` is the base class for all Thrust parallel execution policies which are derived from Thrust's default device backend system configured with the `THRUST_DEVICE_SYSTEM` macro.

Custom user-defined backends which wish to inherit the functionality of Thrust's device backend system should derive a policy from this type in order to interoperate with Thrust algorithm dispatch.

The following code snippet demonstrates how to derive a standalone custom execution policy from `thrust::device_execution_policy` to implement a backend which specializes `for_each` while inheriting the behavior of every other algorithm from the device system:

```
#include <thrust/execution_policy.h>
#include <iostream>

// define a type derived from thrust::device_execution_policy to distinguish our
// custom execution policy:
struct my_policy : thrust::device_execution_policy<my_policy> {}

// overload for_each on my_policy
template<typename Iterator, typename Function>
Iterator for_each(my_policy, Iterator first, Iterator last, Function f)
{
    std::cout << "Hello, world from for_each(my_policy)!" << std::endl;

    for(; first < last; ++first)
    {
        f(*first);
    }

    return first;
}

struct ignore_argument
```

(continues on next page)

(continued from previous page)

```

{
    void operator() (int) { }
};

int main()
{
    int data[4];

    // dispatch thrust::for_each using our custom policy:
    my_policy exec;
    thrust::for_each(exec, data, data + 4, ignore_argument());

    // dispatch thrust::transform whose behavior our policy inherits
    thrust::transform(exec, data, data + 4, data, thrust::identity<int>());

    return 0;
}

```

**See** `execution_policy`**See** `host_execution_policy`

## Template Struct `device_malloc_allocator::rebind`

- Defined in file `thrust/device_malloc_allocator.h`

### Nested Relationships

This struct is a nested type of [Template Class `device\_malloc\_allocator`](#).

### Struct Documentation

```
template<typename U>
struct rebind
```

The `rebind` metafunction provides the type of a `device_malloc_allocator` instantiated with another type.

#### Template Parameters

- `U`: The other type to use for instantiation.

### Public Types

```
template<>
typedef device_malloc_allocator<U> other
```

The `typedef other` gives the type of the rebound `device_malloc_allocator`.

## Template Struct `device_new_allocator::rebind`

- Defined in file `thrust/device_new_allocator.h`

## Nested Relationships

This struct is a nested type of [Template Class device\\_new\\_allocator](#).

### Struct Documentation

```
template<typename U>
struct rebind
```

The `rebind` metafunction provides the type of a `device_new_allocator` instantiated with another type.

#### Template Parameters

- `U`: The other type to use for instantiation.

#### Public Types

```
template<>
typedef device_new_allocator<U> other
```

The `typedef other` gives the type of the rebound `device_new_allocator`.

### Template Struct divides

- Defined in `file_thrust_functional.h`

### Struct Documentation

```
template<typename T>
struct divides
```

`divides` is a function object. Specifically, it is an Adaptable Binary Function. If `f` is an object of class `divides<T>`, and `x` and `y` are objects of class `T`, then `f(x, y)` returns `x/y`.

The following code snippet demonstrates how to use `divides` to divide one `device_vectors` of `floats` by another.

#### Template Parameters

- `T`: is a model of [Assignable](#), and if `x` and `y` are objects of type `T`, then `x/y` must be defined and must have a return type that is convertible to `T`.

```
#include <thrust/device_vector.h>
#include <thrust/functional.h>
#include <thrust/sequence.h>
#include <thrust/fill.h>
#include <thrust/transform.h>

...
const int N = 1000;
thrust::device_vector<float> V1(N);
thrust::device_vector<float> V2(N);
thrust::device_vector<float> V3(N);

thrust::sequence(V1.begin(), V1.end(), 1);
thrust::fill(V2.begin(), V2.end(), 75);
```

(continues on next page)

(continued from previous page)

```
thrust::transform(V1.begin(), V1.end(), V2.begin(), V3.begin(),
                  thrust::divides<float>());
// V3 is now {1/75, 2/75, 3/75, ..., 1000/75}
```

See <http://www.sgi.com/tech/stl/divides.html>

See *binary\_function*

## Public Types

### **typedef first\_argument\_type**

The type of the function object's first argument.

### **typedef second\_argument\_type**

The type of the function object's second argument.

### **typedef result\_type**

The type of the function object's result;

## Public Functions

```
__host__ __device__ T thrust::divides::operator() (const T & lhs, const T & rhs) const
```

Function call operator. The return value is lhs / rhs.

## Template Struct equal\_to

- Defined in file\_thrust\_functional.h

## Struct Documentation

`template<typename T>`

### **struct equal\_to**

`equal_to` is a function object. Specifically, it is an Adaptable Binary Predicate, which means it is a function object that tests the truth or falsehood of some condition. If f is an object of class `equal_to<T>` and x and y are objects of class T, then f(x, y) returns `true` if x == y and `false` otherwise.

See [http://www.sgi.com/tech/stl/equal\\_to.html](http://www.sgi.com/tech/stl/equal_to.html)

See *binary\_function*

## Template Parameters

- T: is a model of Equality Comparable.

## Public Types

### **typedef first\_argument\_type**

The type of the function object's first argument.

### **typedef second\_argument\_type**

The type of the function object's second argument.

**typedef result\_type**

The type of the function object's result;

### Public Functions

**\_\_host\_\_ \_\_device\_\_ bool thrust::equal\_to::operator()(const T & lhs, const T & rhs) const**

Function call operator. The return value is  $lhs == rhs$ .

### Template Struct greater

- Defined in file\_thrust\_functional.h

### Struct Documentation

template<typename T>

**struct greater**

greater is a function object. Specifically, it is an Adaptable Binary Predicate, which means it is a function object that tests the truth or falsehood of some condition. If  $f$  is an object of class `greater<T>` and  $x$  and  $y$  are objects of class  $T$ , then  $f(x, y)$  returns `true` if  $x > y$  and `false` otherwise.

See <http://www.sgi.com/tech/stl/greater.html>

See [binary\\_function](#)

#### Template Parameters

- $T$ : is a model of `LessThan Comparable`.

### Public Types

**typedef first\_argument\_type**

The type of the function object's first argument.

**typedef second\_argument\_type**

The type of the function object's second argument.

**typedef result\_type**

The type of the function object's result;

### Public Functions

**\_\_host\_\_ \_\_device\_\_ bool thrust::greater::operator()(const T & lhs, const T & rhs) const**

Function call operator. The return value is  $lhs > rhs$ .

### Template Struct greater\_equal

- Defined in file\_thrust\_functional.h

## Struct Documentation

```
template<typename T>
struct greater_equal
```

`greater_equal` is a function object. Specifically, it is an Adaptable Binary Predicate, which means it is a function object that tests the truth or falsehood of some condition. If `f` is an object of class `greater_equal<T>` and `x` and `y` are objects of class `T`, then `f(x, y)` returns `true` if `x >= y` and `false` otherwise.

See [http://www.sgi.com/tech/stl/greater\\_equal.html](http://www.sgi.com/tech/stl/greater_equal.html)

See [binary\\_function](#)

### Template Parameters

- `T`: is a model of [LessThan Comparable](#).

### Public Types

```
typedef first_argument_type
```

The type of the function object's first argument.

```
typedef second_argument_type
```

The type of the function object's second argument.

```
typedef result_type
```

The type of the function object's result;;

### Public Functions

```
__host__ __device__ bool thrust::greater_equal::operator()(const T & lhs, const T & rhs)
```

Function call operator. The return value is `lhs >= rhs`.

## Template Struct host\_execution\_policy

- Defined in `file_thrust_execution_policy.h`

### Inheritance Relationships

#### Base Type

- `public thrust::system::__THRUST_HOST_SYSTEM_NAMESPACE::execution_policy< DerivedPolicy >`

## Struct Documentation

```
template<typename DerivedPolicy>
```

```
struct host_execution_policy : public thrust::system::__THRUST_HOST_SYSTEM_NAMESPACE::execution_policy<
```

`host_execution_policy` is the base class for all Thrust parallel execution policies which are derived from Thrust's default host backend system configured with the `THRUST_HOST_SYSTEM` macro.

Custom user-defined backends which wish to inherit the functionality of Thrust's host backend system should derive a policy from this type in order to interoperate with Thrust algorithm dispatch.

The following code snippet demonstrates how to derive a standalone custom execution policy from `thrust::host_execution_policy` to implement a backend which specializes `for_each` while inheriting the behavior of every other algorithm from the host system:

```
#include <thrust/execution_policy.h>
#include <iostream>

// define a type derived from thrust::host_execution_policy to distinguish our
// custom execution policy:
struct my_policy : thrust::host_execution_policy<my_policy> {};

// overload for_each on my_policy
template<typename Iterator, typename Function>
Iterator for_each(my_policy, Iterator first, Iterator last, Function f)
{
    std::cout << "Hello, world from for_each(my_policy)!" << std::endl;

    for(; first < last; ++first)
    {
        f(*first);
    }

    return first;
}

struct ignore_argument
{
    void operator()(int) {}
};

int main()
{
    int data[4];

    // dispatch thrust::for_each using our custom policy:
    my_policy exec;
    thrust::for_each(exec, data, data + 4, ignore_argument());

    // dispatch thrust::transform whose behavior our policy inherits
    thrust::transform(exec, data, data + 4, data, thrust::identity<int>());

    return 0;
}
```

**See** `execution_policy`

**See** `device_execution_policy`

## Template Struct `identity`

- Defined in `file_thrust_functional.h`

## Struct Documentation

```
template<typename T>
struct identity
```

`identity` is a Unary Function that represents the identity function: it takes a single argument `x`, and returns `x`.

The following code snippet demonstrates that `identity` returns its argument.

### Template Parameters

- `T`: No requirements on `T`.

```
#include <thrust/functional.h>
#include <assert.h>
...
int x = 137;
thrust::identity<int> id;
assert(x == id(x));
```

See <http://www.sgi.com/tech/stl/identity.html>

See [unary\\_function](#)

## Public Types

**typedef argument\_type**

The type of the function object's first argument.

**typedef result\_type**

The type of the function object's result;

## Public Functions

**\_\_host\_\_ \_\_device\_\_ const T& thrust::identity::operator()(const T & x) const**

Function call operator. The return value is `x`.

## Template Struct less

- Defined in `file_thrust_functional.h`

## Struct Documentation

```
template<typename T>
struct less
```

`less` is a function object. Specifically, it is an Adaptable Binary Predicate, which means it is a function object that tests the truth or falsehood of some condition. If `f` is an object of class `less<T>` and `x` and `y` are objects of class `T`, then `f(x, y)` returns `true` if `x < y` and `false` otherwise.

See <http://www.sgi.com/tech/stl/less.html>

See [binary\\_function](#)

### Template Parameters

- T: is a model of [LessThan Comparable](#).

## Public Types

### **typedef first\_argument\_type**

The type of the function object's first argument.

### **typedef second\_argument\_type**

The type of the function object's second argument.

### **typedef result\_type**

The type of the function object's result;

## Public Functions

### **\_\_host\_\_ \_\_device\_\_ bool thrust::less::operator()(const T & lhs, const T & rhs) const**

Function call operator. The return value is  $lhs < rhs$ .

## Template Struct less\_equal

- Defined in [file\\_thrust\\_functional.h](#)

## Struct Documentation

template<typename T>

### **struct less\_equal**

[less\\_equal](#) is a function object. Specifically, it is an Adaptable Binary Predicate, which means it is a function object that tests the truth or falsehood of some condition. If f is an object of class `less_equal<T>` and x and y are objects of class T, then `f(x, y)` returns true if  $x \leq y$  and false otherwise.

See [http://www.sgi.com/tech/stl/less\\_equal.html](http://www.sgi.com/tech/stl/less_equal.html)

See [binary\\_function](#)

## Template Parameters

- T: is a model of [LessThan Comparable](#).

## Public Types

### **typedef first\_argument\_type**

The type of the function object's first argument.

### **typedef second\_argument\_type**

The type of the function object's second argument.

### **typedef result\_type**

The type of the function object's result;

## Public Functions

### **\_\_host\_\_ \_\_device\_\_ bool thrust::less\_equal::operator()(const T & lhs, const T & rhs) const**

Function call operator. The return value is  $lhs \leq rhs$ .

## Template Struct logical\_and

- Defined in file\_thrust\_functional.h

### Struct Documentation

```
template<typename T>
```

```
struct logical_and
```

*logical\_and* is a function object. Specifically, it is an Adaptable Binary Predicate, which means it is a function object that tests the truth or falsehood of some condition. If *f* is an object of class *logical\_and*<*T*> and *x* and *y* are objects of class *T* (where *T* is convertible to *bool*) then *f*(*x*, *y*) returns *true* if and only if both *x* and *y* are *true*.

See [http://www.sgi.com/tech/stl/logical\\_and.html](http://www.sgi.com/tech/stl/logical_and.html)

See [binary\\_function](#)

#### Template Parameters

- T*: must be convertible to *bool*.

#### Public Types

```
typedef first_argument_type
```

The type of the function object's first argument.

```
typedef second_argument_type
```

The type of the function object's second argument.

```
typedef result_type
```

The type of the function object's result;

#### Public Functions

```
__host__ __device__ bool thrust::logical_and::operator()(const T & lhs, const T & rhs)
```

Function call operator. The return value is *lhs* && *rhs*.

## Template Struct logical\_not

- Defined in file\_thrust\_functional.h

### Struct Documentation

```
template<typename T>
```

```
struct logical_not
```

*logical\_not* is a function object. Specifically, it is an Adaptable Predicate, which means it is a function object that tests the truth or falsehood of some condition. If *f* is an object of class *logical\_not*<*T*> and *x* is an object of class *T* (where *T* is convertible to *bool*) then *f*(*x*) returns *true* if and only if *x* is *false*.

The following code snippet demonstrates how to use *logical\_not* to transform a *device\_vector* of *bools* into its logical complement.

#### Template Parameters

- T: must be convertible to bool.

```
#include <thrust/device_vector.h>
#include <thrust/transform.h>
#include <thrust/functional.h>
...
thrust::device_vector<bool> V;
...
thrust::transform(V.begin(), V.end(), V.begin(), thrust::logical_not<bool>());
// The elements of V are now the logical complement of what they were prior
```

See [http://www.sgi.com/tech/stl/logical\\_not.html](http://www.sgi.com/tech/stl/logical_not.html)

See [unary\\_function](#)

## Public Types

**typedef first\_argument\_type**

The type of the function object's first argument.

**typedef second\_argument\_type**

The type of the function object's second argument.

**typedef result\_type**

The type of the function object's result;

## Public Functions

**\_\_host\_\_ \_\_device\_\_ bool thrust::logical\_not::operator()(const T & x) const**  
Function call operator. The return value is !x.

## Template Struct logical\_or

- Defined in file\_thrust\_functional.h

## Struct Documentation

template<typename T>

**struct logical\_or**

*logical\_or* is a function object. Specifically, it is an Adaptable Binary Predicate, which means it is a function object that tests the truth or falsehood of some condition. If f is an object of class `logical_or<T>` and x and y are objects of class T (where T is convertible to `bool`) then `f(x, y)` returns true if and only if either x or y are true.

See [http://www.sgi.com/tech/stl/logical\\_or.html](http://www.sgi.com/tech/stl/logical_or.html)

See [binary\\_function](#)

## Template Parameters

- T: must be convertible to `bool`.

## Public Types

### `typedef first_argument_type`

The type of the function object's first argument.

### `typedef second_argument_type`

The type of the function object's second argument.

### `typedef result_type`

The type of the function object's result;

## Public Functions

### `__host__ __device__ bool thrust::logical_or::operator()(const T & lhs, const T & rhs)`

Function call operator. The return value is `lhs || rhs`.

## Template Struct maximum

- Defined in `file_thrust_functional.h`

## Struct Documentation

`template<typename T>`

### `struct maximum`

`maximum` is a function object that takes two arguments and returns the greater of the two. Specifically, it is an Adaptable Binary Function. If `f` is an object of class `maximum<T>` and `x` and `y` are objects of class `T` `f(x, y)` returns `x` if `x > y` and `y`, otherwise.

The following code snippet demonstrates that `maximum` returns its greater argument.

### Template Parameters

- `T`: is a model of `LessThan Comparable`.

```
#include <thrust/functional.h>
#include <assert.h>
...
int x = 137;
int y = -137;
thrust::maximum<int> mx;
assert(x == mx(x, y));
```

See `minimum`

See `min`

See `binary_function`

## Public Types

### `typedef first_argument_type`

The type of the function object's first argument.

### `typedef second_argument_type`

The type of the function object's second argument.

**typedef result\_type**

The type of the function object's result;.

**Public Functions**

**\_\_host\_\_ \_\_device\_\_ T thrust::maximum::operator() (const T & lhs, const T & rhs) const**  
Function call operator. The return value is rhs < lhs ? lhs : rhs.

**Template Struct minimum**

- Defined in file\_thrust\_functional.h

**Struct Documentation**

template<typename T>

**struct minimum**

minimum is a function object that takes two arguments and returns the lesser of the two. Specifically, it is an Adaptable Binary Function. If f is an object of class minimum<T> and x and y are objects of class T f(x, y) returns x if x < y and y, otherwise.

The following code snippet demonstrates that minimum returns its lesser argument.

**Template Parameters**

- T: is a model of LessThan Comparable.

```
#include <thrust/functional.h>
#include <assert.h>
...
int x = 137;
int y = -137;
thrust::minimum<int> mn;
assert(y == mn(x, y));
```

See [maximum](#)

See [max](#)

See [binary\\_function](#)

**Public Types****typedef first\_argument\_type**

The type of the function object's first argument.

**typedef second\_argument\_type**

The type of the function object's second argument.

**typedef result\_type**

The type of the function object's result;.

## Public Functions

```
__host__ __device__ T thrust::minimum::operator() (const T & lhs, const T & rhs) const
```

Function call operator. The return value is  $\text{lhs} < \text{rhs} ? \text{lhs} : \text{rhs}$ .

## Template Struct minus

- Defined in file\_thrust\_functional.h

## Struct Documentation

```
template<typename T>
struct minus
```

minus is a function object. Specifically, it is an Adaptable Binary Function. If  $f$  is an object of class  $\text{minus}<\text{T}>$ , and  $x$  and  $y$  are objects of class  $T$ , then  $f(x, y)$  returns  $x - y$ .

The following code snippet demonstrates how to use minus to subtract a *device\_vector* of floats from another.

### Template Parameters

- $T$ : is a model of *Assignable*, and if  $x$  and  $y$  are objects of type  $T$ , then  $x - y$  must be defined and must have a return type that is convertible to  $T$ .

```
#include <thrust/device_vector.h>
#include <thrust/functional.h>
#include <thrust/sequence.h>
#include <thrust/fill.h>
#include <thrust/transform.h>
...
const int N = 1000;
thrust::device_vector<float> V1(N);
thrust::device_vector<float> V2(N);
thrust::device_vector<float> V3(N);

thrust::sequence(V1.begin(), V1.end(), 1);
thrust::fill(V2.begin(), V2.end(), 75);

thrust::transform(V1.begin(), V1.end(), V2.begin(), V3.begin(),
                 thrust::minus<float>());
// V3 is now {-74, -75, -76, ..., -925}
```

See <http://www.sgi.com/tech/stl/minus.html>

See *binary\_function*

## Public Types

**typedef first\_argument\_type**

The type of the function object's first argument.

**typedef second\_argument\_type**

The type of the function object's second argument.

**typedef result\_type**

The type of the function object's result;

## Public Functions

```
__host__ __device__ T thrust::minus::operator()(const T & lhs, const T & rhs) const
```

Function call operator. The return value is  $\text{lhs} - \text{rhs}$ .

## Template Struct modulus

- Defined in file\_thrust\_functional.h

## Struct Documentation

```
template<typename T>
struct modulus
```

`modulus` is a function object. Specifically, it is an Adaptable Binary Function. If `f` is an object of class `modulus<T>`, and `x` and `y` are objects of class `T`, then `f(x, y)` returns  $x \% y$ .

The following code snippet demonstrates how to use `modulus` to take the modulus of one device\_vectors of floats by another.

### Template Parameters

- `T`: is a model of `Assignable`, and if `x` and `y` are objects of type `T`, then `x \% y` must be defined and must have a return type that is convertible to `T`.

```
#include <thrust/device_vector.h>
#include <thrust/functional.h>
#include <thrust/sequence.h>
#include <thrust/fill.h>
#include <thrust/transform.h>
...
const int N = 1000;
thrust::device_vector<float> V1(N);
thrust::device_vector<float> V2(N);
thrust::device_vector<float> V3(N);

thrust::sequence(V1.begin(), V1.end(), 1);
thrust::fill(V2.begin(), V2.end(), 75);

thrust::transform(V1.begin(), V1.end(), V2.begin(), V3.begin(),
                 thrust::modulus<int>());
// V3 is now {1%75, 2%75, 3%75, ..., 1000%75}
```

See <http://www.sgi.com/tech/stl/modulus.html>

See `binary_function`

## Public Types

```
typedef first_argument_type
```

The type of the function object's first argument.

```
typedef second_argument_type
```

The type of the function object's second argument.

```
typedef result_type
```

The type of the function object's result;

## Public Functions

```
__host__ __device__ T thrust::modulus::operator() (const T & lhs, const T & rhs) const
```

Function call operator. The return value is  $\text{lhs} \% \text{rhs}$ .

## Template Struct multiplies

- Defined in file\_thrust\_functional.h

## Struct Documentation

template<typename T>

### **struct multiplies**

`multiplies` is a function object. Specifically, it is an Adaptable Binary Function. If  $f$  is an object of class `minus<T>`, and  $x$  and  $y$  are objects of class  $T$ , then  $f(x, y)$  returns  $x * y$ .

The following code snippet demonstrates how to use `multiplies` to multiply two device\_vectors of floats.

### Template Parameters

- $T$ : is a model of `Assignable`, and if  $x$  and  $y$  are objects of type  $T$ , then  $x * y$  must be defined and must have a return type that is convertible to  $T$ .

```
#include <thrust/device_vector.h>
#include <thrust/functional.h>
#include <thrust/sequence.h>
#include <thrust/fill.h>
#include <thrust/transform.h>

...
const int N = 1000;
thrust::device_vector<float> V1(N);
thrust::device_vector<float> V2(N);
thrust::device_vector<float> V3(N);

thrust::sequence(V1.begin(), V1.end(), 1);
thrust::fill(V2.begin(), V2.end(), 75);

thrust::transform(V1.begin(), V1.end(), V2.begin(), V3.begin(),
                 thrust::multiplies<float>());
// V3 is now {75, 150, 225, ..., 75000}
```

See <http://www.sgi.com/tech/stl/multiplies.html>

See [binary\\_function](#)

## Public Types

### **typedef first\_argument\_type**

The type of the function object's first argument.

### **typedef second\_argument\_type**

The type of the function object's second argument.

### **typedef result\_type**

The type of the function object's result;.

## Public Functions

```
__host__ __device__ T thrust::multiplies::operator()(const T & lhs, const T & rhs) const;
```

Function call operator. The return value is  $\text{lhs} * \text{rhs}$ .

## Template Struct negate

- Defined in file\_thrust\_functional.h

## Struct Documentation

```
template<typename T>
struct negate
```

`negate` is a function object. Specifically, it is an Adaptable Unary Function. If  $f$  is an object of class `negate<T>`, and  $x$  is an object of class  $T$ , then  $f(x)$  returns  $-x$ .

The following code snippet demonstrates how to use `negate` to negate the element of a *device\_vector* of floats.

### Template Parameters

- $T$ : is a model of `Assignable`, and if  $x$  is an object of type  $T$ , then  $-x$  must be defined and must have a return type that is convertible to  $T$ .

```
#include <thrust/device_vector.h>
#include <thrust/functional.h>
#include <thrust/sequence.h>
#include <thrust/transform.h>
...
const int N = 1000;
thrust::device_vector<float> V1(N);
thrust::device_vector<float> V2(N);

thrust::sequence(V1.begin(), V1.end(), 1);
thrust::transform(V1.begin(), V1.end(), V2.begin(),
                 thrust::negate<float>());
// V2 is now {-1, -2, -3, ..., -1000}
```

See <http://www.sgi.com/tech/stl/negate.html>

See [unary\\_function](#)

## Public Types

```
typedef argument_type
```

The type of the function object's argument.

```
typedef result_type
```

The type of the function object's result;

## Public Functions

```
__host__ __device__ T thrust::negate::operator() (const T & x) const
```

Function call operator. The return value is  $-x$ .

## Template Struct not\_equal\_to

- Defined in file\_thrust\_functional.h

## Struct Documentation

template<typename T>

**struct not\_equal\_to**

*not\_equal\_to* is a function object. Specifically, it is an Adaptable Binary Predicate, which means it is a function object that tests the truth or falsehood of some condition. If  $f$  is an object of class *not\_equal\_to*< $T$ > and  $x$  and  $y$  are objects of class  $T$ , then  $f(x, y)$  returns `true` if  $x \neq y$  and `false` otherwise.

See [http://www.sgi.com/tech/stl/not\\_equal\\_to.html](http://www.sgi.com/tech/stl/not_equal_to.html)

See [binary\\_function](#)

### Template Parameters

- $T$ : is a model of Equality Comparable.

## Public Types

**typedef first\_argument\_type**

The type of the function object's first argument.

**typedef second\_argument\_type**

The type of the function object's second argument.

**typedef result\_type**

The type of the function object's result;

## Public Functions

```
__host__ __device__ bool thrust::not_equal_to::operator() (const T & lhs, const T & rhs)
```

Function call operator. The return value is  $lhs \neq rhs$ .

## Template Struct pair

- Defined in file\_thrust\_pair.h

## Struct Documentation

template<typename T1, typename T2>

**struct pair**

*pair* is a generic data structure encapsulating a heterogeneous pair of values.

### Template Parameters

- T1: The type of pair's first object type. There are no requirements on the type of T1. T1's type is provided by `pair::first_type`.
- T2: The type of pair's second object type. There are no requirements on the type of T2. T2's type is provided by `pair::second_type`.

## Public Types

**typedef T1 first\_type**

first\_type is the type of pair's first object type.

**typedef T2 second\_type**

second\_type is the type of pair's second object type.

## Public Functions

**\_\_host\_\_ \_\_device\_\_ thrust::pair(void)**

pair's default constructor constructs first and second using first\_type & second\_type's default constructors, respectively.

**\_\_host\_\_ \_\_device\_\_ thrust::pair(const T1 & x, const T2 & y)**

This constructor accepts two objects to copy into this pair.

### Parameters

- x: The object to copy into first.
- y: The object to copy into second.

**template<typename U1, typename U2> \_\_host\_\_ \_\_device\_\_ thrust::pair::pair(const pair <**

This copy constructor copies from a pair whose types are convertible to this pair's first\_type and second\_type, respectively.

### Parameters

- p: The pair to copy from.

### Template Parameters

- U1: is convertible to first\_type.
- U2: is convertible to second\_type.

**template<typename U1, typename U2> \_\_host\_\_ \_\_device\_\_ thrust::pair::pair(const std::pair <**

This copy constructor copies from a std::pair whose types are convertible to this pair's first\_type and second\_type, respectively.

### Parameters

- p: The std::pair to copy from.

### Template Parameters

- U1: is convertible to first\_type.
- U2: is convertible to second\_type.

**\_\_host\_\_ \_\_device\_\_ void thrust::pair::swap(pair & p)**

swap swaps the elements of two pairs.

### Parameters

- p: The other pair with which to swap.

## Public Members

### *first\_type* **first**

The pair's first object.

### *second\_type* **second**

The pair's second object.

## Template Struct plus

- Defined in file\_thrust\_functional.h

## Struct Documentation

template<typename T>

### **struct plus**

plus is a function object. Specifically, it is an Adaptable Binary Function. If f is an object of class plus<T>, and x and y are objects of class T, then f(x, y) returns x+y.

The following code snippet demonstrates how to use plus to sum two device\_vectors of floats.

### Template Parameters

- T: is a model of [Assignable](#), and if x and y are objects of type T, then x+y must be defined and must have a return type that is convertible to T.

```
#include <thrust/device_vector.h>
#include <thrust/functional.h>
#include <thrust/sequence.h>
#include <thrust/fill.h>
#include <thrust/transform.h>
...
const int N = 1000;
thrust::device_vector<float> V1(N);
thrust::device_vector<float> V2(N);
thrust::device_vector<float> V3(N);

thrust::sequence(V1.begin(), V1.end(), 1);
thrust::fill(V2.begin(), V2.end(), 75);

thrust::transform(V1.begin(), V1.end(), V2.begin(), V3.begin(),
                 thrust::plus<float>());
// V3 is now {76, 77, 78, ..., 1075}
```

See <http://www.sgi.com/tech/stl/plus.html>

See [binary\\_function](#)

## Public Types

### **typedef first\_argument\_type**

The type of the function object's first argument.

**typedef second\_argument\_type**

The type of the function object's second argument.

**typedef result\_type**

The type of the function object's result;.

**Public Functions**

```
__host__ __device__ T thrust::plus::operator() (const T & lhs, const T & rhs) const
```

Function call operator. The return value is `lhs + rhs`.

**Template Struct project1st**

- Defined in `file_thrust_functional.h`

**Struct Documentation**

```
template<typename T1, typename T2>
```

**struct project1st**

`project1st` is a function object that takes two arguments and returns its first argument; the second argument is unused. It is essentially a generalization of identity to the case of a Binary Function.

```
#include <thrust/functional.h>
#include <assert.h>
...
int x = 137;
int y = -137;
thrust::project1st<int> pj1;
assert(x == pj1(x,y));
```

See `identity`

See `project2nd`

See `binary_function`

**Public Types****typedef first\_argument\_type**

The type of the function object's first argument.

**typedef second\_argument\_type**

The type of the function object's second argument.

**typedef result\_type**

The type of the function object's result;.

**Public Functions**

```
__host__ __device__ const T1& thrust::project1st::operator() (const T1 & lhs, const T2 &
```

Function call operator. The return value is `lhs`.

## Template Struct project2nd

- Defined in file\_thrust\_functional.h

### Struct Documentation

template<typename **T1**, typename **T2**>

**struct project2nd**

*project2nd* is a function object that takes two arguments and returns its second argument; the first argument is unused. It is essentially a generalization of identity to the case of a Binary Function.

```
#include <thrust/functional.h>
#include <assert.h>
...
int x = 137;
int y = -137;
thrust::project2nd<int> pj2;
assert(y == pj2(x,y));
```

See *identity*

See *project1st*

See *binary\_function*

### Public Types

**typedef first\_argument\_type**

The type of the function object's first argument.

**typedef second\_argument\_type**

The type of the function object's second argument.

**typedef result\_type**

The type of the function object's result;

### Public Functions

**\_host\_ \_device\_ const **T2&** thrust::project2nd::operator() (const **T1** &, const **T2** & rhs)**

Function call operator. The return value is rhs.

## Template Struct tuple\_element

- Defined in file\_thrust\_pair.h

### Struct Documentation

template<int **N**, class **T**>

**struct tuple\_element**

This convenience metafunction is included for compatibility with *tuple*. It returns either the type of a pair's *first\_type* or *second\_type* in its nested type, *type*.

This metafunction returns the type of a *tuple*'s *N*th element.

**Template Parameters**

- N: This parameter selects the member of interest.
- T: A pair type of interest.

See [pair](#)

See [tuple](#)

**Template Parameters**

- N: This parameter selects the element of interest.
- T: A tuple type of interest.

**Public Types**

**typedef** tuple\_element<N - 1, Next>::type **type**  
The result of this metafunction is returned in type.

**Template Struct tuple\_size**

- Defined in file\_thrust\_pair.h

**Struct Documentation**

template<class T>  
**struct tuple\_size**

This convenience metafunction is included for compatibility with tuple. It returns 2, the number of elements of a pair, in its nested data member, value.

This metafunction returns the number of elements of a tuple type of interest.

**Template Parameters**

- Pair: A pair type of interest.

See [pair](#)

See [tuple](#)

**Template Parameters**

- T: A tuple type of interest.

**Public Static Attributes**

**const int value = 1 + tuple\_size<typename T::tail\_type>::value**  
The result of this metafunction is returned in value.

**Template Struct unary\_function**

- Defined in file\_thrust\_functional.h

## Struct Documentation

```
template<typename Argument, typename Result>
struct unary_function
```

*unary\_function* is an empty base class: it contains no member functions or member variables, but only type information. The only reason it exists is to make it more convenient to define types that are models of the concept Adaptable Unary Function. Specifically, any model of Adaptable Unary Function must define nested `typedefs`. Those `typedefs` are provided by the base class *unary\_function*.

The following code snippet demonstrates how to construct an Adaptable Unary Function using *unary\_function*.

```
struct sine : public thrust::unary_function<float, float>
{
    __host__ __device__
    float operator()(float x) { return sinf(x); }
};
```

**Note** Because C++11 language support makes the functionality of *unary\_function* obsolete, its use is optional if C++11 language features are enabled.

See [http://www.sgi.com/tech/stl/unary\\_function.html](http://www.sgi.com/tech/stl/unary_function.html)

See *binary\_function*

## Public Types

**typedef argument\_type**

The type of the function object's argument.

**typedef result\_type**

The type of the function object's result.

## Template Struct unary\_negate

- Defined in file\_thrust\_functional.h

## Inheritance Relationships

### Base Type

- public `thrust::unary_function< Predicate::argument_type, bool >` (*Template Struct unary\_function*)

## Struct Documentation

```
template<typename Predicate>
```

```
struct unary_negate : public thrust::unary_function<Predicate::argument_type, bool>
```

*unary\_negate* is a function object adaptor: it is an Adaptable Predicate that represents the logical negation of some other Adaptable Predicate. That is: if *f* is an object of class `unary_negate<AdaptablePredicate>`, then there exists an object *pred* of class

AdaptablePredicate such that  $f(x)$  always returns the same value as  $\neg pred(x)$ . There is rarely any reason to construct a `unary_negate` directly; it is almost always easier to use the helper function `not1`.

See [http://www.sgi.com/tech/stl/unary\\_negate.html](http://www.sgi.com/tech/stl/unary_negate.html)

See `not1`

## Public Functions

`__host__ __device__ thrust::unary_negate::unary_negate(Predicate p)`  
Constructor takes a Predicate object to negate.

### Parameters

- `p`: The Predicate object to negate.

`__host__ __device__ bool thrust::unary_negate::operator()(const typename Predicate::arg_type& x)`  
Function call operator. The return value is  $\neg pred(x)$ .

## Template Struct `unary_traits`

- Defined in `file_thrust_functional.h`

## Struct Documentation

```
template<typename Operation>
struct unary_traits
```

## Template Class `device_allocator`

- Defined in `file_thrust_device_allocator.h`

## Nested Relationships

### Nested Types

- *Template Struct `device_allocator::rebind`*

## Inheritance Relationships

### Base Type

- `public thrust::device_new_allocator< T >` (*Template Class `device_new_allocator`*)

## Class Documentation

```
template<typename T>
class device_allocator: public thrust::device_new_allocator<T>
    device_allocator is a device memory allocator. This implementation inherits from
    device_new_allocator.
```

See [device\\_ptr](#)

See [device\\_new\\_allocator](#)

See <http://www.sgi.com/tech/stl/Allocators.html>

### Public Functions

```
__host__ __device__ thrust::device_allocator::device_allocator()
    No-argument constructor has no effect.
```

```
__host__ __device__ thrust::device_allocator::device_allocator(device_allocator const&)
    Copy constructor has no effect.
```

```
template<typename U> __host__ __device__ thrust::device_allocator::device_allocator(device_allocator<U> const&)
    Constructor from other allocator has no effect.
```

```
template<typename U>
struct rebind
```

The rebind metafunction provides the type of a [device\\_allocator](#) instantiated with another type.

### Template Parameters

- U: The other type to use for instantiation.

### Public Types

```
template<>
typedef device_allocator<U> other
The typedef other gives the type of the rebound device\_allocator.
```

## Template Class device\_allocator< void >

- Defined in file\_thrust\_device\_allocator.h

### Nested Relationships

#### Nested Types

- *Template Struct device\_allocator< void >::device\_allocator< void >*

## Class Documentation

```
template<>
class device_allocator<void>
```

*device\_allocator<void>* is a device memory allocator. This class is a specialization for `void`.

See [device\\_ptr](#)

See <http://www.sgi.com/tech/stl/Allocators.html>

### Public Types

```
typedef void value_type
```

Type of element allocated, `void`.

```
typedef device_ptr<void> pointer
```

Pointer to allocation, `device_ptr<void>`.

```
typedef device_ptr<const void> const_pointer
```

const pointer to allocation, `device_ptr<const void>`.

```
typedef std::size_t size_type
```

Type of allocation size, `std::size_t`.

```
typedef pointer::difference_type difference_type
```

Type of allocation difference, `pointer::difference_type`.

```
template<typename U>
```

```
struct rebind
```

The `rebind` metafunction provides the type of a `device_allocator` instantiated with another type.

### Template Parameters

- `U`: The other type to use for instantiation.

### Public Types

```
template<>
```

```
typedef device_allocator<U> other
```

The `typedef other` gives the type of the rebound `device_allocator`.

## Template Class `device_malloc_allocator`

- Defined in file `thrust/device_malloc_allocator.h`

### Nested Relationships

#### Nested Types

- *Template Struct `device_malloc_allocator::rebind`*

## Class Documentation

template<typename T>

**class device\_malloc\_allocator**

*device\_malloc\_allocator* is a device memory allocator that employs the *device\_malloc* function for allocation.

**See** *device\_malloc*

**See** *device\_ptr*

**See** <http://www.sgi.com/tech/stl/Allocators.html>

### Public Types

**typedef T value\_type**

Type of element allocated, T.

**typedef device\_ptr<T> pointer**

Pointer to allocation, *device\_ptr*<T>.

**typedef device\_ptr<const T> const\_pointer**

const pointer to allocation, *device\_ptr*<const T>.

**typedef device\_reference<T> reference**

Reference to allocated element, *device\_reference*<T>.

**typedef device\_reference<const T> const\_reference**

const reference to allocated element, *device\_reference*<const T>.

**typedef std::size\_t size\_type**

Type of allocation size, *std::size\_t*.

**typedef pointer::difference\_type difference\_type**

Type of allocation difference, *pointer::difference\_type*.

### Public Functions

**\_\_host\_\_ \_\_device\_\_ thrust::device\_malloc\_allocator::device\_malloc\_allocator()**  
No-argument constructor has no effect.

**\_\_host\_\_ \_\_device\_\_ thrust::device\_malloc\_allocator::~device\_malloc\_allocator()**  
No-argument destructor has no effect.

**\_\_host\_\_ \_\_device\_\_ thrust::device\_malloc\_allocator::device\_malloc\_allocator(device\_malloc\_allocator const&)**  
Copy constructor has no effect.

**template<typename U> \_\_host\_\_ \_\_device\_\_ thrust::device\_malloc\_allocator::device\_malloc\_allocator(device\_malloc\_allocator<U> const&)**  
Constructor from other *device\_malloc\_allocator* has no effect.

**\_\_host\_\_ \_\_device\_\_ pointer thrust::device\_malloc\_allocator::address(reference r)**  
Returns the address of an allocated object.

**Return** &r.

**\_\_host\_\_ \_\_device\_\_ const\_pointer thrust::device\_malloc\_allocator::address(const\_reference r)**  
Returns the address of an allocated object.

**Return** &r.

```
__host__ pointer thrust::device_malloc_allocator::allocate(size_type cnt, const pointer
```

Allocates storage for `cnt` objects.

**Return** A pointer to uninitialized storage for `cnt` objects.

**Note** Memory allocated by this function must be deallocated with `deallocate`.

#### Parameters

- `cnt`: The number of objects to allocate.

```
__host__ void thrust::device_malloc_allocator::deallocate(pointer p, size_type cnt)
```

Deallocates storage for objects allocated with `allocate`.

**Note** Memory deallocated by this function must previously have been allocated with `allocate`.

#### Parameters

- `p`: A pointer to the storage to deallocate.
- `cnt`: The size of the previous allocation.

```
size_type max_size() const
```

Returns the largest value `n` for which `allocate(n)` might succeed.

**Return** The largest value `n` for which `allocate(n)` might succeed.

```
__host__ __device__ bool thrust::device_malloc_allocator::operator==(device_malloc_allocator
```

Compares against another `device_malloc_allocator` for equality.

**Return** `true`

```
__host__ __device__ bool thrust::device_malloc_allocator::operator!=(device_malloc_allocator
```

Compares against another `device_malloc_allocator` for inequality.

**Return** `false`

```
template<typename U>
```

```
struct rebind
```

The `rebind` metafunction provides the type of a `device_malloc_allocator` instantiated with another type.

#### Template Parameters

- `U`: The other type to use for instantiation.

### Public Types

```
template<>
typedef device_malloc_allocator<U> other
```

The `typedef other` gives the type of the rebound `device_malloc_allocator`.

### Template Class `device_new_allocator`

- Defined in file `thrust/device_new_allocator.h`

## Nested Relationships

### Nested Types

- *Template Struct device\_new\_allocator::rebind*

## Inheritance Relationships

### Derived Type

- public thrust::device\_allocator< T > (*Template Class device\_allocator*)

## Class Documentation

```
template<typename T>
class device_new_allocator
    device_new_allocator is a device memory allocator that employs the device_new function for allocation.
```

See *device\_new*

See *device\_ptr*

See <http://www.sgi.com/tech/stl/Allocators.html>

Subclassed by *thrust::device\_allocator< T >*

### Public Types

**typedef T value\_type**

Type of element allocated, T.

**typedef device\_ptr<T> pointer**

Pointer to allocation, device\_ptr<T>.

**typedef device\_ptr<const T> const\_pointer**

const pointer to allocation, device\_ptr<const T>.

**typedef device\_reference<T> reference**

Reference to allocated element, device\_reference<T>.

**typedef device\_reference<const T> const\_reference**

const reference to allocated element, device\_reference<const T>.

**typedef std::size\_t size\_type**

Type of allocation size, std::size\_t.

**typedef pointer::difference\_type difference\_type**

Type of allocation difference, pointer::difference\_type.

## Public Functions

```
__host__ __device__ thrust::device_new_allocator::device_new_allocator()
```

No-argument constructor has no effect.

```
__host__ __device__ thrust::device_new_allocator::~device_new_allocator()
```

No-argument destructor has no effect.

```
__host__ __device__ thrust::device_new_allocator::device_new_allocator(device_new_allocator&)
```

Copy constructor has no effect.

```
template<typename U> __host__ __device__ thrust::device_new_allocator::device_new_allocator(U)
```

Constructor from other `device_malloc_allocator` has no effect.

```
__host__ __device__ pointer thrust::device_new_allocator::address(reference r)
```

Returns the address of an allocated object.

**Return** &r.

```
__host__ __device__ const_pointer thrust::device_new_allocator::address(const_reference r)
```

Returns the address an allocated object.

**Return** &r.

```
__host__ pointer thrust::device_new_allocator::allocate(size_type cnt, const_pointer = 0)
```

Allocates storage for cnt objects.

**Return** A pointer to uninitialized storage for cnt objects.

**Note** Memory allocated by this function must be deallocated with `deallocate`.

### Parameters

- cnt: The number of objects to allocate.

```
__host__ void thrust::device_new_allocator::deallocate(pointer p, size_type)
```

Deallocates storage for objects allocated with `allocate`.

**Note** Memory deallocated by this function must previously have been allocated with `allocate`.

### Parameters

- p: A pointer to the storage to deallocate.
- cnt: The size of the previous allocation.

```
__host__ __device__ size_type thrust::device_new_allocator::max_size() const
```

Returns the largest value n for which `allocate(n)` might succeed.

**Return** The largest value n for which `allocate(n)` might succeed.

```
__host__ __device__ bool thrust::device_new_allocator::operator==(device_new_allocator)
```

Compares against another `device_malloc_allocator` for equality.

**Return** true

```
__host__ __device__ bool thrust::device_new_allocator::operator!=(device_new_allocator)
```

Compares against another `device_malloc_allocator` for inequality.

**Return** false

```
template<typename U>
struct rebind
```

The `rebind` metaprogram provides the type of a `device_new_allocator` instantiated with another type.

## Template Parameters

- U: The other type to use for instantiation.

## Public Types

```
template<>
```

```
typedef device_new_allocator<U> other
```

The `typedef other` gives the type of the rebound `device_new_allocator`.

## Template Class `device_ptr`

- Defined in `file_thrust_device_malloc_allocator.h`

## Inheritance Relationships

### Base Type

- `public thrust::pointer< T, thrust::device_system_tag,`  
`thrust::device_reference< T >, thrust::device_ptr< T > >`

## Class Documentation

```
template<typename T>
```

```
class device_ptr : public thrust::pointer<T, thrust::device_system_tag, thrust::device_reference<T>, thrust::device_ptr<T>>
```

`device_ptr` stores a pointer to an object allocated in device memory. This type provides type safety when dispatching standard algorithms on ranges resident in device memory.

`device_ptr` has pointer semantics: it may be dereferenced safely from the host and may be manipulated with pointer arithmetic.

`device_ptr` can be created with the functions `device_malloc`, `device_new`, or `device_pointer_cast`, or by explicitly calling its constructor with a raw pointer.

The raw pointer encapsulated by a `device_ptr` may be obtained by either its `get` method or the `raw_pointer_cast` free function.

**Note** `device_ptr` is not a smart pointer; it is the programmer's responsibility to deallocate memory pointed to by `device_ptr`.

**See** `device_malloc`

**See** `device_new`

**See** `device_pointer_cast`

**See** `raw_pointer_cast`

## Public Functions

```
host device thrust::device_ptr::device_ptr()
```

`device_ptr`'s null constructor initializes its raw pointer to 0.

```
template<typename OtherT> __host__ __device__ thrust::device_ptr::device_ptr(OtherT * p)
    device_ptr's copy constructor is templated to allow copying to a device_ptr<const T> from a
    T *.
```

#### Parameters

- `ptr`: A raw pointer to copy from, presumed to point to a location in device memory.

```
__host__ __device__ thrust::device_ptr::device_ptr(T * ptr)
```

```
template<typename OtherT> __host__ __device__ thrust::device_ptr::device_ptr(const device_ptr<OtherT> &other)
    device_ptr's copy constructor allows copying from another device_ptr with related type.
```

#### Parameters

- `other`: The `device_ptr` to copy from.

```
template<typename OtherT> __host__ __device__ device_ptr& thrust::device_ptr::operator=(const device_ptr<OtherT> &other)
    device_ptr's assignment operator allows assigning from another device_ptr with related type.
```

#### Return `*this`

#### Parameters

- `other`: The other `device_ptr` to copy from.

## Template Class `device_reference`

- Defined in file `thrust/device_ptr.h`

## Inheritance Relationships

### Base Type

- public `thrust::reference< T, thrust::device_ptr< T >, thrust::device_reference< T > >`

## Class Documentation

```
template<typename T>
class device_reference : public thrust::reference<T, thrust::device_ptr<T>, thrust::device_reference<T>>
    device_reference acts as a reference-like object to an object stored in device memory.
    device_reference is not intended to be used directly; rather, this type is the result of dereferencing a
    device_ptr. Similarly, taking the address of a device_reference yields a device_ptr.
```

`device_reference` may often be used from host code in place of operations defined on its associated `value_type`. For example, when `device_reference` refers to an arithmetic type, arithmetic operations on it are legal:

```
#include <thrust/device_vector.h>

int main(void)
{
    thrust::device_vector<int> vec(1, 13);

    thrust::device_reference<int> ref_to_thirteen = vec[0];
```

(continues on next page)

(continued from previous page)

```

int x = ref_to_thirteen + 1;

// x is 14

return 0;
}

```

Similarly, we can print the value of `ref_to_thirteen` in the above code by using an `iostream`:

```

#include <thrust/device_vector.h>
#include <iostream>

int main(void)
{
    thrust::device_vector<int> vec(1, 13);

    thrust::device_reference<int> ref_to_thirteen = vec[0];

    std::cout << ref_to_thirteen << std::endl;

    // 13 is printed

    return 0;
}

```

Of course, we needn't explicitly create a `device_reference` in the previous example, because one is returned by `device_vector`'s bracket operator. A more natural way to print the value of a `device_vector` element might be:

```

#include <thrust/device_vector.h>
#include <iostream>

int main(void)
{
    thrust::device_vector<int> vec(1, 13);

    std::cout << vec[0] << std::endl;

    // 13 is printed

    return 0;
}

```

These kinds of operations should be used sparingly in performance-critical code, because they imply a potentially expensive copy between host and device space.

Some operations which are possible with regular objects are impossible with their corresponding `device_reference` objects due to the requirements of the C++ language. For example, because the member access operator cannot be overloaded, member variables and functions of a referent object cannot be directly accessed through its `device_reference`.

The following code, which generates a compiler error, illustrates:

```

#include <thrust/device_vector.h>

struct foo

```

(continues on next page)

(continued from previous page)

```
{
    int x;
};

int main(void)
{
    thrust::device_vector<foo> foo_vec(1);

    thrust::device_reference<foo> foo_ref = foo_vec[0];

    foo_ref.x = 13; // ERROR: x cannot be accessed through foo_ref

    return 0;
}
```

Instead, a host space copy must be created to access `foo`'s `x` member:

```
#include <thrust/device_vector.h>

struct foo
{
    int x;
};

int main(void)
{
    thrust::device_vector<foo> foo_vec(1);

    // create a local host-side foo object
    foo host_foo;
    host_foo.x = 13;

    thrust::device_reference<foo> foo_ref = foo_vec[0];

    foo_ref = host_foo;

    // foo_ref's x member is 13

    return 0;
}
```

Another common case where a `device_reference` cannot directly be used in place of its referent object occurs when passing them as parameters to functions like `printf` which have varargs parameters. Because varargs parameters must be Plain Old Data, a `device_reference` to a POD type requires a cast when passed to `printf`:

```
#include <stdio.h>
#include <thrust/device_vector.h>

int main(void)
{
    thrust::device_vector<int> vec(1,13);

    // vec[0] must be cast to int when passing to printf
    printf("%d\n", (int) vec[0]);
```

(continues on next page)

(continued from previous page)

```

    return 0;
}

```

See [device\\_ptr](#)

See [device\\_vector](#)

## Public Types

### **typedef** super\_t::value\_type **value\_type**

The type of the value referenced by this type of [device\\_reference](#).

### **typedef** super\_t::pointer **pointer**

The type of the expression `&ref`, where `ref` is a [device\\_reference](#).

## Public Functions

### **template<typename OtherT> \_\_host\_\_ \_\_device\_\_ thrust::device\_reference::device\_reference**

This copy constructor accepts a const reference to another [device\\_reference](#). After this [device\\_reference](#) is constructed, it shall refer to the same object as other.

The following code snippet demonstrates the semantics of this copy constructor.

#### Parameters

- other: A [device\\_reference](#) to copy from.

```

#include <thrust/device_vector.h>
#include <assert.h>
...
thrust::device_vector<int> v(1, 0);
thrust::device_reference<int> ref = v[0];

// ref equals the object at v[0]
assert(ref == v[0]);

// the address of ref equals the address of v[0]
assert(&ref == &v[0]);

// modifying v[0] modifies ref
v[0] = 13;
assert(ref == 13);

```

**Note** This constructor is templated primarily to allow initialization of [device\\_reference<const T>](#) from [device\\_reference<T>](#).

### **\_\_host\_\_ \_\_device\_\_ thrust::device\_reference::device\_reference(const pointer & ptr)**

This copy constructor initializes this [device\\_reference](#) to refer to an object pointed to by the given [device\\_ptr](#). After this [device\\_reference](#) is constructed, it shall refer to the object pointed to by `ptr`.

The following code snippet demonstrates the semantic of this copy constructor.

#### Parameters

- ptr: A [device\\_ptr](#) to copy from.

```
#include <thrust/device_vector.h>
#include <assert.h>
...
thrust::device_vector<int> v(1, 0);
thrust::device_ptr<int> ptr = &v[0];
thrust::device_reference<int> ref(ptr);

// ref equals the object pointed to by ptr
assert(ref == *ptr);

// the address of ref equals ptr
assert(&ref == ptr);

// modifying *ptr modifies ref
*ptr = 13;
assert(ref == 13);
```

**template<typename OtherT> \_\_host\_\_ \_\_device\_\_ device\_reference& thrust::device\_reference::operator=(const OtherT& other)**

This assignment operator assigns the value of the object referenced by the given `device_reference` to the object referenced by this `device_reference`.

**Return** `*this`

**Parameters**

- `other`: The `device_reference` to assign from.

**\_\_host\_\_ \_\_device\_\_ device\_reference& thrust::device\_reference::operator=(const value\_type& x)**

Assignment operator assigns the value of the given value to the value referenced by this `device_reference`.

**Return** `*this`

**Parameters**

- `x`: The value to assign from.

## Template Class `device_vector`

- Defined in file `thrust/device_vector.h`

## Inheritance Relationships

### Base Type

- `public detail::vector_base< T, Alloc >`

## Class Documentation

```
template<typename T, typename Alloc = thrust::device_malloc_allocator<T>>
class device_vector : public detail::vector_base<T, Alloc>
```

A `device_vector` is a container that supports random access to elements, constant time removal of elements at the end, and linear time insertion and removal of elements at the beginning or in the middle. The number

of elements in a `device_vector` may vary dynamically; memory management is automatic. The memory associated with a `device_vector` resides in the memory space of a parallel device.

See <http://www.sgi.com/tech/stl/Vector.html>

See `host_vector`

## Public Functions

`_host_device_vector(void)`

This constructor creates an empty `device_vector`.

`_host ~device_vector(void)`

The destructor erases the elements.

`_host_device_vector(size_type n)`

This constructor creates a `device_vector` with the given size.

### Parameters

- n: The number of elements to initially create.

`_host_device_vector(size_type n, const value_type &value)`

This constructor creates a `device_vector` with copies of an exemplar element.

### Parameters

- n: The number of elements to initially create.
- value: An element to copy.

`_host_device_vector(const device_vector &v)`

Copy constructor copies from an exemplar `device_vector`.

### Parameters

- v: The `device_vector` to copy.

`_host_device_vector& thrust::device_vector::operator=(const device_vector & v)`

Copy assign operator copies another `device_vector` with the same type.

### Parameters

- v: The `device_vector` to copy.

`template<typename OtherT, typename OtherAlloc> _host__device__ thrust::device_vector<OtherT, OtherAlloc>`

Copy constructor copies from an exemplar `device_vector` with different type.

### Parameters

- v: The `device_vector` to copy.

`template<typename OtherT, typename OtherAlloc> _host__ device_vector& thrust::device_v`

Assign operator copies from an exemplar `device_vector` with different type.

### Parameters

- v: The `device_vector` to copy.

`template<typename OtherT, typename OtherAlloc>`

`_host_device_vector(const std::vector<OtherT, OtherAlloc> &v)`

Copy constructor copies from an exemplar `std::vector`.

**Parameters**

- v: The `std::vector` to copy.

```
template<typename OtherT, typename OtherAlloc> __host__ device_vector& thrust::device_v
```

Assign operator copies from an exemplar `std::vector`.

**Parameters**

- v: The `std::vector` to copy.

```
template<typename OtherT, typename OtherAlloc>
__host__ device_vector(const host_vector<OtherT, OtherAlloc> &v)
```

Copy constructor copies from an exemplar `host_vector` with possibly different type.

**Parameters**

- v: The `host_vector` to copy.

```
template<typename OtherT, typename OtherAlloc> __host__ device_vector& thrust::device_v
```

Assign operator copies from an exemplar `host_vector`.

**Parameters**

- v: The `host_vector` to copy.

```
template<typename InputIterator>
__host__ device_vector(InputIterator first, InputIterator last)
```

This constructor builds a `device_vector` from a range.

**Parameters**

- first: The beginning of the range.
- last: The end of the range.

## Template Class `host_vector`

- Defined in file `thrust/device_vector.h`

## Inheritance Relationships

### Base Type

- public `detail::vector_base< T, Alloc >`

## Class Documentation

```
template<typename T, typename Alloc = std::allocator<T>>
class host_vector : public detail::vector_base<T, Alloc>
```

A `host_vector` is a container that supports random access to elements, constant time removal of elements at the end, and linear time insertion and removal of elements at the beginning or in the middle. The number of elements in a `host_vector` may vary dynamically; memory management is automatic. The memory associated with a `host_vector` resides in the memory space of the host associated with a parallel device.

See <http://www.sgi.com/tech/stl/Vector.html>

See `device_vector`

## Public Functions

`__host__ host_vector(void)`

This constructor creates an empty `host_vector`.

`__host__ ~host_vector(void)`

The destructor erases the elements.

`__host__ host_vector(size_type n)`

This constructor creates a `host_vector` with the given size.

### Parameters

- n: The number of elements to initially create.

`__host__ host_vector(size_type n, const value_type &value)`

This constructor creates a `host_vector` with copies of an exemplar element.

### Parameters

- n: The number of elements to initially create.
- value: An element to copy.

`__host__ host_vector(const host_vector &v)`

Copy constructor copies from an exemplar `host_vector`.

### Parameters

- v: The `host_vector` to copy.

`__host__ host_vector& thrust::host_vector::operator=(const host_vector &v)`

Assign operator copies from an exemplar `host_vector`.

### Parameters

- v: The `host_vector` to copy.

`template<typename OtherT, typename OtherAlloc>`

`__host__ host_vector(const host_vector<OtherT, OtherAlloc> &v)`

Copy constructor copies from an exemplar `host_vector` with different type.

### Parameters

- v: The `host_vector` to copy.

`template<typename OtherT, typename OtherAlloc> __host__ host_vector& thrust::host_vector::operator=(const host_vector &v)`

Assign operator copies from an exemplar `host_vector` with different type.

### Parameters

- v: The `host_vector` to copy.

`template<typename OtherT, typename OtherAlloc>`

`__host__ host_vector(const std::vector<OtherT, OtherAlloc> &v)`

Copy constructor copies from an exemplar `std::vector`.

### Parameters

- v: The `std::vector` to copy.

`template<typename OtherT, typename OtherAlloc> __host__ host_vector& thrust::host_vector::operator=(const std::vector &v)`

Assign operator copies from an exemplar `std::vector`.

### Parameters

- v: The `std::vector` to copy.

```
template<typename OtherT, typename OtherAlloc>
__host__ host_vector(const device_vector<OtherT, OtherAlloc> &v)
```

Copy constructor copies from an exemplar `device_vector` with possibly different type.

#### Parameters

- v: The `device_vector` to copy.

```
template<typename OtherT, typename OtherAlloc> __host__ host_vector& thrust::host_vector::operator=
```

Assign operator copies from an exemplar `device_vector`.

#### Parameters

- v: The `device_vector` to copy.

```
template<typename InputIterator>
__host__ host_vector(InputIterator first, InputIterator last)
```

This constructor builds a `host_vector` from a range.

#### Parameters

- first: The beginning of the range.
- last: The end of the range.

## Template Class tuple

- Defined in file\_thrust\_tuple.h

## Inheritance Relationships

### Base Type

- public detail::map\_tuple\_to\_cons::type< T0, T1, T2, T3, T4, T5, T6, T7, T8, T9 >

## Class Documentation

```
template<class T0, class T1, class T2, class T3, class T4, class T5, class T6, class T7, class T8, class T9>
class tuple : public detail::map_tuple_to_cons::type<T0, T1, T2, T3, T4, T5, T6, T7, T8, T9>
```

`tuple` is a class template that can be instantiated with up to ten arguments. Each template argument specifies the type of element in the `tuple`. Consequently, tuples are heterogeneous, fixed-size collections of values. An instantiation of `tuple` with two arguments is similar to an instantiation of `pair` with the same two arguments. Individual elements of a `tuple` may be accessed with the `get` function.

The following code snippet demonstrates how to create a new `tuple` object and inspect and modify the value of its elements.

### Template Parameters

- TN: The type of the N tuple element. Thrust's `tuple` type currently supports up to ten elements.

```

#include <thrust/tuple.h>
#include <iostream>

...
// create a tuple containing an int, a float, and a string
thrust::tuple<int, float, const char*> t(13, 0.1f, "thrust");

// individual members are accessed with the free function get
std::cout << "The first element's value is " << thrust::get<0>(t) << std::endl;

// or the member function get
std::cout << "The second element's value is " << t.get<1>() << std::endl;

// we can also modify elements with the same function
thrust::get<0>(t) += 10;

```

See [pair](#)

See [get](#)

See [make\\_tuple](#)

See [tuple\\_element](#)

See [tuple\\_size](#)

See [tie](#)

## Public Functions

**`__host__ __device__ thrust::tuple(void)`**  
`tuple`'s no-argument constructor initializes each element.

**`__host__ __device__ thrust::tuple(typename access_traits< T0 >::parameter_type t0)`**  
`tuple`'s one-argument constructor copy constructs the first element from the given parameter and initializes all other elements.

### Parameters

- `t0`: The value to assign to this `tuple`'s first element.

**`__host__ __device__ thrust::tuple(typename access_traits< T0 >::parameter_type t0, typename access_traits< T1 >::parameter_type t1)`**  
`tuple`'s one-argument constructor copy constructs the first two elements from the given parameters and initializes all other elements.

**Note** `tuple`'s constructor has ten variants of this form, the rest of which are omitted here for brevity.

### Parameters

- `t0`: The value to assign to this `tuple`'s first element.
- `t1`: The value to assign to this `tuple`'s second element.

**`template<class U1, class U2> __host__ __device__ tuple& thrust::tuple::operator=(const pair<U1, U2> & p)`**  
This assignment operator allows assigning the first two elements of this `tuple` from a `pair`.

### Parameters

- `p`: A `pair` to assign from.

**`__host__ __device__ void thrust::tuple::swap(tuple & t)`**  
`swap` swaps the elements of two tuples.

**Parameters**

- `t`: The other tuple with which to swap.

### 1.3.3 Functions

**Template Function thrust::abs**

- Defined in file\_thrust\_complex.h

**Function Documentation**

```
template<typename T> __host__ __device__ T thrust::abs(const complex < T > & z)
```

Returns the magnitude (also known as absolute value) of a complex.

**Parameters**

- `z`: The complex from which to calculate the absolute value.

**Template Function thrust::acos**

- Defined in file\_thrust\_complex.h

**Function Documentation**

```
template<typename T> __host__ __device__ complex<T> thrust::acos(const complex < T > & z)
```

Returns the complex arc cosine of a complex number.

The range of the real part of the result is [0, Pi] and the range of the imaginary part is [-inf, +inf]

**Parameters**

- `z`: The complex argument.

**Template Function thrust::acosh**

- Defined in file\_thrust\_complex.h

**Function Documentation**

```
template<typename T> __host__ __device__ complex<T> thrust::acosh(const complex < T > & z)
```

Returns the complex inverse hyperbolic cosine of a complex number.

The range of the real part of the result is [0, +inf] and the range of the imaginary part is [-Pi, Pi]

**Parameters**

- `z`: The complex argument.

## Template Function `thrust::adjacent_difference(const thrust::detail::execution_policy_base<DerivedPolicy>&, InputIterator, InputIterator, OutputIterator)`

- Defined in file `thrust_adjacent_difference.h`

### Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::adjacent_difference`” with arguments (`const thrust::detail::execution_policy_base<DerivedPolicy>&`, `InputIterator`, `InputIterator`, `OutputIterator`) in doxygen xml output for project “rocThrust” from directory: `./docBin/xml`. Potential matches:

```
- template<typename DerivedPolicy, typename InputIterator, typename OutputIterator,
→typename BinaryFunction> __host__ __device__ OutputIterator thrust::adjacent_
→difference(const thrust::detail::execution_policy_base< DerivedPolicy > &,_
→InputIterator, InputIterator, OutputIterator, BinaryFunction)
- template<typename DerivedPolicy, typename InputIterator, typename OutputIterator>_ 
→_host__ __device__ OutputIterator thrust::adjacent_difference(const_
→thrust::detail::execution_policy_base< DerivedPolicy > &, InputIterator,_
→InputIterator, OutputIterator)
- template<typename InputIterator, typename OutputIterator, typename BinaryFunction>
  OutputIterator thrust::adjacent_difference(InputIterator, InputIterator,_
→OutputIterator, BinaryFunction)
- template<typename InputIterator, typename OutputIterator>
  OutputIterator thrust::adjacent_difference(InputIterator, InputIterator,_
→OutputIterator)
```

## Template Function `thrust::adjacent_difference(const thrust::detail::execution_policy_base<DerivedPolicy>&, InputIterator, InputIterator, OutputIterator, BinaryFunction)`

### Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::adjacent_difference`” with arguments (`const thrust::detail::execution_policy_base<DerivedPolicy>&`, `InputIterator`, `InputIterator`, `OutputIterator`, `BinaryFunction`) in doxygen xml output for project “rocThrust” from directory: `./docBin/xml`. Potential matches:

```
- template<typename DerivedPolicy, typename InputIterator, typename OutputIterator,
→typename BinaryFunction> __host__ __device__ OutputIterator thrust::adjacent_
→difference(const thrust::detail::execution_policy_base< DerivedPolicy > &,_
→InputIterator, InputIterator, OutputIterator, BinaryFunction)
- template<typename DerivedPolicy, typename InputIterator, typename OutputIterator>_ 
→_host__ __device__ OutputIterator thrust::adjacent_difference(const_
→thrust::detail::execution_policy_base< DerivedPolicy > &, InputIterator,_
→InputIterator, OutputIterator)
- template<typename InputIterator, typename OutputIterator, typename BinaryFunction>
  OutputIterator thrust::adjacent_difference(InputIterator, InputIterator,_
→OutputIterator, BinaryFunction)
- template<typename InputIterator, typename OutputIterator>
  OutputIterator thrust::adjacent_difference(InputIterator, InputIterator,_
→OutputIterator)
```

**Template Function `thrust::adjacent_difference`(`InputIterator`, `InputIterator`, `OutputIterator`)****Function Documentation**

```
template<typename InputIterator, typename OutputIterator>
OutputIterator thrust::adjacent_difference(InputIterator first, InputIterator last, OutputIterator
                                         result)
adjacent_difference calculates the differences of adjacent elements in the range [first, last).
That is, *first is assigned to *result, and, for each iterator i in the range [first + 1, last), the
difference of *i and *(i - 1) is assigned to *(result + (i - first)).
```

This version of adjacent\_difference uses operator- to calculate differences.

The following code snippet demonstrates how to use adjacent\_difference to compute the difference between adjacent elements of a range.

**Return** The iterator `result + (last - first)`

**Remark** Note that `result` is permitted to be the same iterator as `first`. This is useful for computing differences “in place”.

**Parameters**

- `first`: The beginning of the input range.
- `last`: The end of the input range.
- `result`: The beginning of the output range.

**Template Parameters**

- `InputIterator`: is a model of `Input Iterator`, and `x` and `y` are objects of `InputIterator`'s `value_type`, then `x - y` is defined, and `InputIterator`'s `value_type` is convertible to a type in `OutputIterator`'s set of `value_types`, and the return type of `x - y` is convertible to a type in `OutputIterator`'s set of `value_types`.
- `OutputIterator`: is a model of `Output Iterator`.

```
#include <thrust/adjacent_difference.h>
#include <thrust/device_vector.h>
...
int h_data[8] = {1, 2, 1, 2, 1, 2, 1, 2};
thrust::device_vector<int> d_data(h_data, h_data + 8);
thrust::device_vector<int> d_result(8);

thrust::adjacent_difference(d_data.begin(), d_data.end(), d_result.begin());

// d_result is now [1, 1, -1, 1, -1, 1, -1, 1]
```

See [http://www.sgi.com/tech/stl/adjacent\\_difference.html](http://www.sgi.com/tech/stl/adjacent_difference.html)

See `inclusive_scan`

**Template Function `thrust::adjacent_difference`(`InputIterator`, `InputIterator`, `OutputIterator`, `BinaryFunction`)****Function Documentation**

```
template<typename InputIterator, typename OutputIterator, typename BinaryFunction>
```

*OutputIterator* `thrust::adjacent_difference` (*InputIterator* `first`, *InputIterator* `last`, *OutputIterator* `result`, *BinaryFunction* `binary_op`)

`adjacent_difference` calculates the differences of adjacent elements in the range [`first`, `last`). That is, `*first` is assigned to `*result`, and, for each iterator `i` in the range [`first + 1`, `last`), `binary_op(*i, *(i - 1))` is assigned to `*(result + (i - first))`.

This version of `adjacent_difference` uses the binary function `binary_op` to calculate differences.

The following code snippet demonstrates how to use `adjacent_difference` to compute the sum between adjacent elements of a range.

**Return** The iterator `result + (last - first)`

**Remark** Note that `result` is permitted to be the same iterator as `first`. This is useful for computing differences “in place”.

### Parameters

- `first`: The beginning of the input range.
- `last`: The end of the input range.
- `result`: The beginning of the output range.
- `binary_op`: The binary function used to compute differences.

### Template Parameters

- `InputIterator`: is a model of `Input Iterator`, and `InputIterator`'s `value_type` is convertible to `BinaryFunction`'s `first_argument_type` and `second_argument_type`, and `InputIterator`'s `value_type` is convertible to a type in `OutputIterator`'s set of `value_types`.
- `OutputIterator`: is a model of `Output Iterator`.
- `BinaryFunction`'s `result_type` is convertible to a type in `OutputIterator`'s set of `value_types`.

```
#include <thrust/adjacent_difference.h>
#include <thrust/functional.h>
#include <thrust/device_vector.h>
...
int h_data[8] = {1, 2, 1, 2, 1, 2, 1, 2};
thrust::device_vector<int> d_data(h_data, h_data + 8);
thrust::device_vector<int> d_result(8);

thrust::adjacent_difference(d_data.begin(), d_data.end(), d_result.begin(), _  
  thrust::plus<int>());

// d_result is now [1, 3, 3, 3, 3, 3, 3]
```

**See** [http://www.sgi.com/tech/stl/adjacent\\_difference.html](http://www.sgi.com/tech/stl/adjacent_difference.html)

**See** `inclusive_scan`

### Template Function `thrust::advance`

- Defined in file `_thrust_advance.h`

## Function Documentation

**template<typename InputIterator, typename Distance> \_\_host\_\_ \_\_device\_\_ void thrust::advance(InputIterator i, Distance n)**

advance(i, n) increments the iterator i by the distance n. If n > 0 it is equivalent to executing ++i n times, and if n < 0 it is equivalent to executing i -n times. If n == 0, the call has no effect.

The following code snippet demonstrates how to use advance to increment an iterator a given number of times.

**Pre** n shall be negative only for bidirectional and random access iterators.

### Parameters

- i: The iterator to be advanced.
- n: The distance by which to advance the iterator.

### Template Parameters

- InputIterator: is a model of [Input Iterator](#).
- Distance: is an integral type that is convertible to InputIterator's distance type.

```
#include <thrust/advance.h>
#include <thrust/device_vector.h>
...
thrust::device_vector<int> vec(13);
thrust::device_vector<int>::iterator iter = vec.begin();

thrust::advance(iter, 7);

// iter - vec.begin() == 7
```

See <http://www.sgi.com/tech/stl/advance.html>

## Template Function thrust::all\_of(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, InputIterator, InputIterator, Predicate)

- Defined in file\_thrust\_logical.h

## Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “thrust::all\_of” with arguments (const thrust::detail::execution\_policy\_base<DerivedPolicy>&, InputIterator, InputIterator, Predicate) in doxygen xml output for project “rocThrust” from directory: ./docBin/xml. Potential matches:

```
- template<typename DerivedPolicy, typename InputIterator, typename Predicate> __
  host__ __device__ bool thrust::all_of(const thrust::detail::execution_policy_base<
  < DerivedPolicy > &, InputIterator, InputIterator, Predicate)
- template<typename InputIterator, typename Predicate> __
  bool thrust::all_of(InputIterator, InputIterator, Predicate)
```

## Template Function thrust::all\_of(InputIterator, InputIterator, Predicate)

## Function Documentation

template<typename **InputIterator**, typename **Predicate**>  
**bool** thrust::**all\_of**(**InputIterator** first, **InputIterator** last, **Predicate** pred)  
 all\_of determines whether all elements in a range satisfy a predicate. Specifically, all\_of returns true if pred(\*i) is true for every iterator i in the range [first, last) and false otherwise.

```
#include <thrust/logical.h>
#include <thrust/functional.h>
...
bool A[3] = {true, true, false};

thrust::all_of(A, A + 2, thrust::identity<bool>()); // returns true
thrust::all_of(A, A + 3, thrust::identity<bool>()); // returns false

// empty range
thrust::all_of(A, A, thrust::identity<bool>()); // returns false
```

**Return** true, if all elements satisfy the predicate; false, otherwise.

### Parameters

- first: The beginning of the sequence.
- last: The end of the sequence.
- pred: A predicate used to test range elements.

### Template Parameters

- InputIterator: is a model of Input Iterator,
- Predicate: must be a model of Predicate.

**See** any\_of

**See** none\_of

**See** transform\_reduce

**Template Function** **thrust::any\_of(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, InputIterator, InputIterator, Predicate)**

- Defined in file\_thrust\_logical.h

## Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “thrust::any\_of” with arguments (const thrust::detail::execution\_policy\_base<DerivedPolicy>&, InputIterator, InputIterator, Predicate) in doxygen xml output for project “rocThrust” from directory: ./docBin/xml. Potential matches:

```
- template<typename DerivedPolicy, typename InputIterator, typename Predicate> __
  host__ __device__ bool thrust::any_of(const thrust::detail::execution_policy_base
  < DerivedPolicy > &, InputIterator, InputIterator, Predicate)
- template<typename InputIterator, typename Predicate>
  bool thrust::any_of(InputIterator, InputIterator, Predicate)
```

## Template Function `thrust::any_of(InputIterator, InputIterator, Predicate)`

### Function Documentation

```
template<typename InputIterator, typename Predicate>
bool thrust::any_of(InputIterator first, InputIterator last, Predicate pred)
    any_of determines whether any element in a range satisfies a predicate. Specifically, any_of returns true if pred(*i) is true for any iterator i in the range [first, last) and false otherwise.
```

```
#include <thrust/logical.h>
#include <thrust/functional.h>
...
bool A[3] = {true, true, false};

thrust::any_of(A, A + 2, thrust::identity<bool>()); // returns true
thrust::any_of(A, A + 3, thrust::identity<bool>()); // returns true

thrust::any_of(A + 2, A + 3, thrust::identity<bool>()); // returns false

// empty range
thrust::any_of(A, A, thrust::identity<bool>()); // returns false
```

**Return** true, if any element satisfies the predicate; false, otherwise.

#### Parameters

- `first`: The beginning of the sequence.
- `last`: The end of the sequence.
- `pred`: A predicate used to test range elements.

#### Template Parameters

- `InputIterator`: is a model of `Input Iterator`,
- `Predicate`: must be a model of `Predicate`.

**See** `all_of`

**See** `none_of`

**See** `transform_reduce`

## Template Function `thrust::arg`

- Defined in file `thrust_complex.h`

### Function Documentation

```
template<typename T> __host__ __device__ T thrust::arg(const complex < T > & z)
    Returns the phase angle (also known as argument) in radians of a complex.
```

#### Parameters

- `z`: The complex from which to calculate the phase angle.

## Template Function `thrust::asin`

- Defined in file\_thrust\_complex.h

### Function Documentation

```
template<typename T> __host__ __device__ complex<T> thrust::asin(const complex < T > & z)
```

Returns the complex arc sine of a complex number.

The range of the real part of the result is [-Pi/2, Pi/2] and the range of the imaginary part is [-inf, +inf]

#### Parameters

- z: The complex argument.

## Template Function `thrust::asinh`

- Defined in file\_thrust\_complex.h

### Function Documentation

```
template<typename T> __host__ __device__ complex<T> thrust::asinh(const complex < T > & z)
```

Returns the complex inverse hyperbolic sine of a complex number.

The range of the real part of the result is [-inf, +inf] and the range of the imaginary part is [-Pi/2, Pi/2]

#### Parameters

- z: The complex argument.

## Template Function `thrust::atan`

- Defined in file\_thrust\_complex.h

### Function Documentation

```
template<typename T> __host__ __device__ complex<T> thrust::atan(const complex < T > & z)
```

Returns the complex arc tangent of a complex number.

The range of the real part of the result is [-Pi/2, Pi/2] and the range of the imaginary part is [-inf, +inf]

#### Parameters

- z: The complex argument.

## Template Function `thrust::atanh`

- Defined in file\_thrust\_complex.h

## Function Documentation

```
template<typename T> __host__ __device__ complex<T> thrust::atanh(const complex < T > & z)
```

Returns the complex inverse hyperbolic tangent of a complex number.

The range of the real part of the result is [-inf, +inf] and the range of the imaginary part is [-Pi/2, Pi/2]

### Parameters

- z: The complex argument.

**Template Function** `thrust::binary_search(const thrust::detail::execution_policy_base<DerivedPolicy>&, ForwardIterator, ForwardIterator, const LessThanComparable&)`

- Defined in file `thrust_binary_search.h`

## Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::binary_search`” with arguments (`const thrust::detail::execution_policy_base<DerivedPolicy>&`, `ForwardIterator`, `ForwardIterator`, `const LessThanComparable&`) in doxygen xml output for project “rocThrust” from directory: `./docBin/xml`. Potential matches:

```
- template<class ForwardIterator, class InputIterator, class OutputIterator, class StrictWeakOrdering>
    OutputIterator thrust::binary_search(ForwardIterator, ForwardIterator,
                                         InputIterator, InputIterator, OutputIterator, StrictWeakOrdering)
- template<class ForwardIterator, class InputIterator, class OutputIterator>
    OutputIterator thrust::binary_search(ForwardIterator, ForwardIterator,
                                         InputIterator, InputIterator, OutputIterator)
- template<class ForwardIterator, class LessThanComparable>
    bool thrust::binary_search(ForwardIterator, ForwardIterator, const LessThanComparable&)
- template<class ForwardIterator, class T, class StrictWeakOrdering>
    bool thrust::binary_search(ForwardIterator, ForwardIterator, const T&,
                               StrictWeakOrdering)
- template<typename DerivedPolicy, typename ForwardIterator, typename InputIterator,
          typename OutputIterator, typename StrictWeakOrdering> __host__ __device__
    OutputIterator thrust::binary_search(const thrust::detail::execution_policy_base<DerivedPolicy> &, ForwardIterator, ForwardIterator, InputIterator, InputIterator, OutputIterator, StrictWeakOrdering)
- template<typename DerivedPolicy, typename ForwardIterator, typename InputIterator,
          typename OutputIterator> __host__ __device__ OutputIterator thrust::binary_
    search(const thrust::detail::execution_policy_base<DerivedPolicy> &, ForwardIterator, InputIterator, InputIterator, OutputIterator)
- template<typename DerivedPolicy, typename ForwardIterator, typename LessThanComparable> __host__ __device__ bool thrust::binary_search(const thrust::detail::execution_policy_base<DerivedPolicy> &, ForwardIterator, ForwardIterator, const LessThanComparable &)
- template<typename DerivedPolicy, typename ForwardIterator, typename T, typename StrictWeakOrdering> __host__ __device__ bool thrust::binary_search(const thrust::detail::execution_policy_base<DerivedPolicy> &, ForwardIterator, ForwardIterator, const T &, StrictWeakOrdering)
```

## Template Function `thrust::binary_search(ForwardIterator, ForwardIterator, const LessThanComparable&)`

### Function Documentation

```
template<class ForwardIterator, class LessThanComparable>
bool thrust::binary_search(ForwardIterator first, ForwardIterator last, const LessThanComparable &value)
```

`binary_search` is a version of binary search: it attempts to find the element value in an ordered range [*first*, *last*). It returns `true` if an element that is equivalent to *value* is present in [*first*, *last*) and `false` if no such element exists. Specifically, this version returns `true` if and only if there exists an iterator *i* in [*first*, *last*) such that  $*i < \text{value}$  and  $\text{value} < *i$  are both `false`.

The following code snippet demonstrates how to use `binary_search` to search for values in a ordered range.

**Return** `true` if an equivalent element exists in [*first*, *last*), otherwise `false`.

#### Parameters

- *first*: The beginning of the ordered sequence.
- *last*: The end of the ordered sequence.
- *value*: The value to be searched.

#### Template Parameters

- `ForwardIterator`: is a model of `Forward Iterator`.
- `LessThanComparable`: is a model of `LessThanComparable`.

```
#include <thrust/binary_search.h>
#include <thrust/device_vector.h>
...
thrust::device_vector<int> input(5);

input[0] = 0;
input[1] = 2;
input[2] = 5;
input[3] = 7;
input[4] = 8;

thrust::binary_search(input.begin(), input.end(), 0); // returns true
thrust::binary_search(input.begin(), input.end(), 1); // returns false
thrust::binary_search(input.begin(), input.end(), 2); // returns true
thrust::binary_search(input.begin(), input.end(), 3); // returns false
thrust::binary_search(input.begin(), input.end(), 8); // returns true
thrust::binary_search(input.begin(), input.end(), 9); // returns false
```

**See** [http://www.sgi.com/tech/stl/binary\\_search.html](http://www.sgi.com/tech/stl/binary_search.html)

**See** `lower_bound`

**See** `upper_bound`

**See** `equal_range`

## Template Function `thrust::binary_search(const thrust::detail::execution_policy_base<DerivedPolicy>&, ForwardIterator, ForwardIterator, const T&, StrictWeakOrdering)`

## Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “thrust::binary\_search” with arguments (const thrust::detail::execution\_policy\_base<DerivedPolicy>&, ForwardIterator, ForwardIterator, const T&, StrictWeakOrdering) in doxygen xml output for project “rocThrust” from directory: ./docBin/xml. Potential matches:

```
- template<class ForwardIterator, class InputIterator, class OutputIterator, class StrictWeakOrdering>
    OutputIterator thrust::binary_search(ForwardIterator, ForwardIterator,
                                         InputIterator, InputIterator, OutputIterator, StrictWeakOrdering)
- template<class ForwardIterator, class InputIterator, class OutputIterator>
    OutputIterator thrust::binary_search(ForwardIterator, ForwardIterator,
                                         InputIterator, InputIterator, OutputIterator)
- template<class ForwardIterator, class LessThanComparable>
    bool thrust::binary_search(ForwardIterator, ForwardIterator, const LessThanComparable&)
- template<class ForwardIterator, class T, class StrictWeakOrdering>
    bool thrust::binary_search(ForwardIterator, ForwardIterator, const T&,
                               StrictWeakOrdering)
- template<typename DerivedPolicy, typename ForwardIterator, typename InputIterator,
          typename OutputIterator, typename StrictWeakOrdering>__host__ __device__
    OutputIterator thrust::binary_search(const thrust::detail::execution_policy_base<DerivedPolicy> &, ForwardIterator, ForwardIterator, InputIterator, InputIterator,
                                         OutputIterator, StrictWeakOrdering)
- template<typename DerivedPolicy, typename ForwardIterator, typename InputIterator,
          typename OutputIterator>__host__ __device__ OutputIterator thrust::binary_
    search(const thrust::detail::execution_policy_base<DerivedPolicy> &, ForwardIterator,
           ForwardIterator, InputIterator, InputIterator, OutputIterator)
- template<typename DerivedPolicy, typename ForwardIterator, typename LessThanComparable>__host__ __device__ bool thrust::binary_search(const thrust::detail::execution_policy_base<DerivedPolicy> &, ForwardIterator,
                                         const LessThanComparable &)
- template<typename DerivedPolicy, typename ForwardIterator, typename T, typename StrictWeakOrdering>__host__ __device__ bool thrust::binary_search(const thrust::detail::execution_policy_base<DerivedPolicy> &, ForwardIterator,
                                         const T &, StrictWeakOrdering)
```

## Template Function thrust::binary\_search(ForwardIterator, ForwardIterator, const T&, StrictWeakOrdering)

### Function Documentation

```
template<class ForwardIterator, class T, class StrictWeakOrdering>
bool thrust::binary_search(ForwardIterator first, ForwardIterator last, const T &value,
                           StrictWeakOrdering comp)
```

binary\_search is a version of binary search: it attempts to find the element value in an ordered range [first, last). It returns true if an element that is equivalent to value is present in [first, last) and false if no such element exists. Specifically, this version returns true if and only if there exists an iterator i in [first, last) such that comp(\*i, value) and comp(value, \*i) are both false.

The following code snippet demonstrates how to use binary\_search to search for values in a ordered range.

**Return** true if an equivalent element exists in [first, last), otherwise false.

## Parameters

- `first`: The beginning of the ordered sequence.
- `last`: The end of the ordered sequence.
- `value`: The value to be searched.
- `comp`: The comparison operator.

## Template Parameters

- `ForwardIterator`: is a model of [Forward Iterator](#).
- `T`: is comparable to `ForwardIterator`'s `value_type`.
- `StrictWeakOrdering`: is a model of [Strict Weak Ordering](#).

```
#include <thrust/binary_search.h>
#include <thrust/device_vector.h>
#include <thrust/functional.h>
...
thrust::device_vector<int> input(5);

input[0] = 0;
input[1] = 2;
input[2] = 5;
input[3] = 7;
input[4] = 8;

thrust::binary_search(input.begin(), input.end(), 0, thrust::less<int>()); // ↵
// returns true
thrust::binary_search(input.begin(), input.end(), 1, thrust::less<int>()); // ↵
// returns false
thrust::binary_search(input.begin(), input.end(), 2, thrust::less<int>()); // ↵
// returns true
thrust::binary_search(input.begin(), input.end(), 3, thrust::less<int>()); // ↵
// returns false
thrust::binary_search(input.begin(), input.end(), 8, thrust::less<int>()); // ↵
// returns true
thrust::binary_search(input.begin(), input.end(), 9, thrust::less<int>()); // ↵
// returns false
```

**See** [http://www.sgi.com/tech/stl/binary\\_search.html](http://www.sgi.com/tech/stl/binary_search.html)

**See** `lower_bound`

**See** `upper_bound`

**See** `equal_range`

**Template Function** `thrust::binary_search(const thrust::detail::execution_policy_base<DerivedPolicy>&, ForwardIterator, ForwardIterator, InputIterator, InputIterator, OutputIterator)`

## Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “thrust::binary\_search” with arguments (const thrust::detail::execution\_policy\_base<DerivedPolicy>&, ForwardIterator, ForwardIterator, InputIterator, InputIterator, OutputIterator) in doxygen xml output for project “rocThrust” from directory: ./docBin/xml. Potential matches:

```
- template<class ForwardIterator, class InputIterator, class OutputIterator, class StrictWeakOrdering>
    OutputIterator thrust::binary_search(ForwardIterator, ForwardIterator, InputIterator, InputIterator, OutputIterator, StrictWeakOrdering)
- template<class ForwardIterator, class InputIterator, class OutputIterator>
    OutputIterator thrust::binary_search(ForwardIterator, ForwardIterator, InputIterator, InputIterator, OutputIterator)
- template<class ForwardIterator, class LessThanComparable>
    bool thrust::binary_search(ForwardIterator, ForwardIterator, const LessThanComparable&)
- template<class ForwardIterator, class T, class StrictWeakOrdering>
    bool thrust::binary_search(ForwardIterator, ForwardIterator, const T&, StrictWeakOrdering)
- template<typename DerivedPolicy, typename ForwardIterator, typename InputIterator,
          typename OutputIterator, typename StrictWeakOrdering>__host__ __device__
    OutputIterator thrust::binary_search(const thrust::detail::execution_policy_base<DerivedPolicy> &, ForwardIterator, ForwardIterator, InputIterator, InputIterator, OutputIterator, StrictWeakOrdering)
- template<typename DerivedPolicy, typename ForwardIterator, typename InputIterator,
          typename OutputIterator>__host__ __device__ OutputIterator thrust::binary_
    search(const thrust::detail::execution_policy_base<DerivedPolicy> &, ForwardIterator, InputIterator, InputIterator, OutputIterator)
- template<typename DerivedPolicy, typename ForwardIterator, typename LessThanComparable>__host__ __device__ bool thrust::binary_search(const thrust::detail::execution_policy_base<DerivedPolicy> &, ForwardIterator, const LessThanComparable &)
- template<typename DerivedPolicy, typename ForwardIterator, typename T, typename StrictWeakOrdering>__host__ __device__ bool thrust::binary_search(const thrust::detail::execution_policy_base<DerivedPolicy> &, ForwardIterator, const T &, StrictWeakOrdering)
```

## Template Function `thrust::binary_search(ForwardIterator, ForwardIterator, InputIterator, InputIterator, OutputIterator)`

### Function Documentation

```
template<class ForwardIterator, class InputIterator, class OutputIterator>
OutputIterator thrust::binary_search(ForwardIterator first, ForwardIterator last, InputIterator values_first, InputIterator values_last, OutputIterator result)
binary_search is a vectorized version of binary search: for each iterator v in [values_first, values_last) it attempts to find the value *v in an ordered range [first, last). It returns true if an element that is equivalent to value is present in [first, last) and false if no such element exists.
```

The following code snippet demonstrates how to use `binary_search` to search for multiple values in a ordered range.

**Pre** The ranges `[first, last)` and `[result, result + (last - first))` shall not overlap.

#### Parameters

- `first`: The beginning of the ordered sequence.

- `last`: The end of the ordered sequence.
- `values_first`: The beginning of the search values sequence.
- `values_last`: The end of the search values sequence.
- `result`: The beginning of the output sequence.

### Template Parameters

- `ForwardIterator`: is a model of [Forward Iterator](#).
- `InputIterator`: is a model of [Input Iterator](#). and `InputIterator`'s `value_type` is [LessThanComparable](#).
- `OutputIterator`: is a model of [Output Iterator](#). and `bool` is convertible to `OutputIterator`'s `value_type`.

```
#include <thrust/binary_search.h>
#include <thrust/device_vector.h>
...
thrust::device_vector<int> input(5);

input[0] = 0;
input[1] = 2;
input[2] = 5;
input[3] = 7;
input[4] = 8;

thrust::device_vector<int> values(6);
values[0] = 0;
values[1] = 1;
values[2] = 2;
values[3] = 3;
values[4] = 8;
values[5] = 9;

thrust::device_vector<bool> output(6);

thrust::binary_search(input.begin(), input.end(),
                     values.begin(), values.end(),
                     output.begin());

// output is now [true, false, true, false, true, false]
```

**See** [http://www.sgi.com/tech/stl/binary\\_search.html](http://www.sgi.com/tech/stl/binary_search.html)

**See** `lower_bound`

**See** `upper_bound`

**See** `equal_range`

**Template Function** `thrust::binary_search(const thrust::detail::execution_policy_base<DerivedPolicy>&, ForwardIterator, ForwardIterator, InputIterator, InputIterator, OutputIterator, StrictWeakOrdering)`

## Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “thrust::binary\_search” with arguments (const thrust::detail::execution\_policy\_base<DerivedPolicy>&, ForwardIterator, ForwardIterator, InputIterator, InputIterator, OutputIterator, StrictWeakOrdering) in doxygen xml output for project “rocThrust” from directory: ./docBin/xml. Potential matches:

```
- template<class ForwardIterator, class InputIterator, class OutputIterator, class StrictWeakOrdering>
    OutputIterator thrust::binary_search(ForwardIterator, ForwardIterator, InputIterator, InputIterator, OutputIterator, StrictWeakOrdering)
- template<class ForwardIterator, class InputIterator, class OutputIterator>
    OutputIterator thrust::binary_search(ForwardIterator, ForwardIterator, InputIterator, InputIterator, OutputIterator)
- template<class ForwardIterator, class LessThanComparable>
    bool thrust::binary_search(ForwardIterator, ForwardIterator, const LessThanComparable&)
- template<class ForwardIterator, class T, class StrictWeakOrdering>
    bool thrust::binary_search(ForwardIterator, ForwardIterator, const T&, StrictWeakOrdering)
- template<typename DerivedPolicy, typename ForwardIterator, typename InputIterator,
          typename OutputIterator, typename StrictWeakOrdering>__host__ __device__
    OutputIterator thrust::binary_search(const thrust::detail::execution_policy_base<DerivedPolicy> &, ForwardIterator, ForwardIterator, InputIterator, InputIterator, OutputIterator, StrictWeakOrdering)
- template<typename DerivedPolicy, typename ForwardIterator, typename InputIterator,
          typename OutputIterator>__host__ __device__ OutputIterator thrust::binary_
    search(const thrust::detail::execution_policy_base<DerivedPolicy> &, ForwardIterator, InputIterator, InputIterator, OutputIterator)
- template<typename DerivedPolicy, typename ForwardIterator, typename LessThanComparable>__host__ __device__ bool thrust::binary_search(const thrust::detail::execution_policy_base<DerivedPolicy> &, ForwardIterator, ForwardIterator, const LessThanComparable &)
- template<typename DerivedPolicy, typename ForwardIterator, typename T, typename StrictWeakOrdering>__host__ __device__ bool thrust::binary_search(const thrust::detail::execution_policy_base<DerivedPolicy> &, ForwardIterator, ForwardIterator, const T &, StrictWeakOrdering)
```

**Template Function thrust::binary\_search(ForwardIterator, ForwardIterator, InputIterator, InputIterator, OutputIterator, StrictWeakOrdering)**

## Function Documentation

```
template<class ForwardIterator, class InputIterator, class OutputIterator, class StrictWeakOrdering>
OutputIterator thrust::binary_search(ForwardIterator first, ForwardIterator last, InputIterator values_first, InputIterator values_last, OutputIterator result, StrictWeakOrdering comp)
```

binary\_search is a vectorized version of binary search: for each iterator v in [values\_first, values\_last) it attempts to find the value \*v in an ordered range [first, last). It returns true if an element that is equivalent to value is present in [first, last) and false if no such element exists. This version of binary\_search uses function object comp for comparison.

The following code snippet demonstrates how to use binary\_search to search for multiple values in a ordered range.

**Pre** The ranges `[first, last)` and `[result, result + (last - first))` shall not overlap.

### Parameters

- `first`: The beginning of the ordered sequence.
- `last`: The end of the ordered sequence.
- `values_first`: The beginning of the search values sequence.
- `values_last`: The end of the search values sequence.
- `result`: The beginning of the output sequence.
- `comp`: The comparison operator.

### Template Parameters

- `ForwardIterator`: is a model of [Forward Iterator](#).
- `InputIterator`: is a model of [Input Iterator](#). and `InputIterator`'s `value_type` is [LessThanComparable](#).
- `OutputIterator`: is a model of [Output Iterator](#). and `bool` is convertible to `OutputIterator`'s `value_type`.
- `StrictWeakOrdering`: is a model of [Strict Weak Ordering](#).

```
#include <thrust/binary_search.h>
#include <thrust/device_vector.h>
#include <thrust/functional.h>
...
thrust::device_vector<int> input(5);

input[0] = 0;
input[1] = 2;
input[2] = 5;
input[3] = 7;
input[4] = 8;

thrust::device_vector<int> values(6);
values[0] = 0;
values[1] = 1;
values[2] = 2;
values[3] = 3;
values[4] = 8;
values[5] = 9;

thrust::device_vector<bool> output(6);

thrust::binary_search(input.begin(), input.end(),
                     values.begin(), values.end(),
                     output.begin(),
                     thrust::less<T>());

// output is now [true, false, true, false, true, false]
```

**See** [http://www.sgi.com/tech/stl/binary\\_search.html](http://www.sgi.com/tech/stl/binary_search.html)

**See** `lower_bound`

**See** `upper_bound`

See [equal\\_range](#)

### Template Function `thrust::conj`

- Defined in file\_thrust\_complex.h

#### Function Documentation

```
template<typename T> __host__ __device__ complex<T> thrust::conj(const complex < T > & z)
```

Returns the complex conjugate of a complex.

##### Parameters

- z: The complex from which to calculate the complex conjugate.

### Template Function `thrust::copy`(`const thrust::detail::execution_policy_base<DerivedPolicy>&`, `InputIterator`, `InputIterator`, `OutputIterator`)

- Defined in file\_thrust\_copy.h

#### Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “thrust::copy” with arguments (`const thrust::detail::execution_policy_base<DerivedPolicy>&`, `InputIterator`, `InputIterator`, `OutputIterator`) in doxygen xml output for project “rocThrust” from directory: ./docBin/xml. Potential matches:

```
- template<typename DerivedPolicy, typename InputIterator, typename OutputIterator>_
  __host__ __device__ OutputIterator thrust::copy(const thrust::detail::execution_
  <policy_base< DerivedPolicy > &, InputIterator, InputIterator, OutputIterator)
- template<typename InputIterator, typename OutputIterator>
  OutputIterator thrust::copy(InputIterator, InputIterator, OutputIterator)
```

### Template Function `thrust::copy`(`InputIterator`, `InputIterator`, `OutputIterator`)

#### Function Documentation

```
template<typename InputIterator, typename OutputIterator>
OutputIterator thrust::copy (InputIterator first, InputIterator last, OutputIterator result)
```

`copy` copies elements from the range  $[first, last]$  to the range  $[result, result + (last - first)]$ . That is, it performs the assignments  $*result = *first$ ,  $*(result + 1) = *(first + 1)$ , and so on. Generally, for every integer  $n$  from 0 to  $last - first$ , `copy` performs the assignment  $*(result + n) = *(first + n)$ . Unlike `std::copy`, `copy` offers no guarantee on order of operation. As a result, calling `copy` with overlapping source and destination ranges has undefined behavior.

The return value is  $result + (last - first)$ .

The following code snippet demonstrates how to use `copy` to copy from one range to another.

**Return** The end of the destination sequence.

See <http://www.sgi.com/tech/stl/copy.html>

**Pre** `result` may be equal to `first`, but `result` shall not be in the range `[first, last)` otherwise.

### Parameters

- `first`: The beginning of the sequence to copy.
- `last`: The end of the sequence to copy.
- `result`: The destination sequence.

### Template Parameters

- `InputIterator`: must be a model of `Input Iterator` and `InputIterator`'s `value_type` must be convertible to `OutputIterator`'s `value_type`.
- `OutputIterator`: must be a model of `Output Iterator`.

```
#include <thrust/copy.h>
#include <thrust/device_vector.h>
...
thrust::device_vector<int> vec0(100);
thrust::device_vector<int> vec1(100);
...
thrust::copy(vec0.begin(), vec0.end(),
            vec1.begin());
// vec1 is now a copy of vec0
```

**Template Function `thrust::copy_if(const thrust::detail::execution_policy_base<DerivedPolicy>&, InputIterator, InputIterator, OutputIterator, Predicate)`**

- Defined in file `thrust_copy.h`

## Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::copy_if`” with arguments `(const thrust::detail::execution_policy_base<DerivedPolicy>&, InputIterator, InputIterator, OutputIterator, Predicate)` in doxygen xml output for project “rocThrust” from directory: `./docBin/xml`. Potential matches:

```
- template<typename DerivedPolicy, typename InputIterator, typename OutputIterator,
          typename Predicate> __host__ __device__ OutputIterator thrust::copy_if(const
          thrust::detail::execution_policy_base< DerivedPolicy > &, InputIterator,
          InputIterator, OutputIterator, Predicate)
- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2,
          typename OutputIterator, typename Predicate> __host__ __device__ OutputIterator
          thrust::copy_if(const thrust::detail::execution_policy_base< DerivedPolicy > &,
          InputIterator1, InputIterator1, InputIterator2, OutputIterator, Predicate)
- template<typename InputIterator, typename OutputIterator, typename Predicate>
          OutputIterator thrust::copy_if(InputIterator, InputIterator, OutputIterator,
          Predicate)
- template<typename InputIterator1, typename InputIterator2, typename
          OutputIterator, typename Predicate>
          OutputIterator thrust::copy_if(InputIterator1, InputIterator1, InputIterator2,
          OutputIterator, Predicate)
```

**Template Function `thrust::copy_if(InputIterator, InputIterator, OutputIterator, Predicate)`****Function Documentation**

```
template<typename InputIterator, typename OutputIterator, typename Predicate>
OutputIterator thrust::copy_if(InputIterator first, InputIterator last, OutputIterator result, Predicate
                           pred)
```

This version of `copy_if` copies elements from the range `[first, last)` to a range beginning at `result`, except that any element which causes `pred` to `false` is not copied. `copy_if` is stable, meaning that the relative order of elements that are copied is unchanged.

More precisely, for every integer `n` such that  $0 \leq n < \text{last} - \text{first}$ , `copy_if` performs the assignment `*result = *(first + n)` and `result` is advanced one position if `pred(*(first + n))`. Otherwise, no assignment occurs and `result` is not advanced.

The following code snippet demonstrates how to use `copy_if` to perform stream compaction to copy even numbers to an output range.

**Return** `result + n`, where `n` is equal to the number of times `pred` evaluated to `true` in the range `[first, last)`.

**Pre** The ranges `[first, last)` and `[result, result + (last - first))` shall not overlap.

**Parameters**

- `first`: The beginning of the sequence from which to copy.
- `last`: The end of the sequence from which to copy.
- `result`: The beginning of the sequence into which to copy.
- `pred`: The predicate to test on every value of the range `[first, last)`.

**Template Parameters**

- `InputIterator`: is a model of `Input Iterator`, and `InputIterator`'s `value_type` is convertible to `Predicate`'s `argument_type`.
- `OutputIterator`: is a model of `Output Iterator`.
- `Predicate`: is a model of `Predicate`.

```
#include <thrust/copy.h>
...
struct is_even
{
    __host__ __device__
    bool operator() (const int x)
    {
        return (x % 2) == 0;
    }
};
...
const int N = 6;
int V[N] = {-2, 0, -1, 0, 1, 2};
int result[4];

thrust::copy_if(V, V + N, result, is_even());

// V remains {-2, 0, -1, 0, 1, 2}
// result is now { -2, 0, 0, 2 }
```

See `remove_copy_if`

**Template Function `thrust::copy_if(const thrust::detail::execution_policy_base<DerivedPolicy>&, InputIterator1, InputIterator1, InputIterator2, OutputIterator, Predicate)`**

## Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::copy_if`” with arguments (`const thrust::detail::execution_policy_base<DerivedPolicy>&`, `InputIterator1`, `InputIterator1`, `InputIterator2`, `OutputIterator`, `Predicate`) in doxygen xml output for project “rocThrust” from directory: `./docBin/xml`. Potential matches:

```
- template<typename DerivedPolicy, typename InputIterator, typename OutputIterator,
         typename Predicate> __host__ __device__ OutputIterator thrust::copy_if(const
         thrust::detail::execution_policy_base< DerivedPolicy > &, InputIterator,
         InputIterator, OutputIterator, Predicate)
- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2,
         typename OutputIterator, typename Predicate> __host__ __device__ OutputIterator
         thrust::copy_if(const thrust::detail::execution_policy_base< DerivedPolicy > &, InputIterator1,
         InputIterator1, InputIterator2, OutputIterator, Predicate)
- template<typename InputIterator, typename OutputIterator, typename Predicate>
         OutputIterator thrust::copy_if(InputIterator, InputIterator, OutputIterator,
         Predicate)
- template<typename InputIterator1, typename InputIterator2, typename
         OutputIterator, typename Predicate>
         OutputIterator thrust::copy_if(InputIterator1, InputIterator1, InputIterator2,
         OutputIterator, Predicate)
```

**Template Function `thrust::copy_if(InputIterator1, InputIterator1, InputIterator2, OutputIterator, Predicate)`**

## Function Documentation

```
template<typename InputIterator1, typename InputIterator2, typename OutputIterator, typename Predicate>
OutputIterator thrust::copy_if(InputIterator1 first, InputIterator1 last, InputIterator2 stencil, OutputIterator result, Predicate pred)
```

This version of `copy_if` copies elements from the range `[first, last)` to a range beginning at `result`, except that any element whose corresponding `stencil` element causes `pred` to be `false` is not copied. `copy_if` is stable, meaning that the relative order of elements that are copied is unchanged.

More precisely, for every integer `n` such that  $0 \leq n < \text{last} - \text{first}$ , `copy_if` performs the assignment `*result = *(first + n)` and `result` is advanced one position if `pred(* (stencil + n))`. Otherwise, no assignment occurs and `result` is not advanced.

The following code snippet demonstrates how to use `copy_if` to perform stream compaction to copy numbers to an output range when corresponding stencil elements are even:

**Return** `result + n`, where `n` is equal to the number of times `pred` evaluated to `true` in the range `[stencil, stencil + (last - first))`.

**Pre** The ranges `[first, last)` and `[result, result + (last - first))` shall not overlap.

**Pre** The ranges `[stencil, stencil + (last - first))` and `[result, result + (last - first))` shall not overlap.

## Parameters

- `first`: The beginning of the sequence from which to copy.
- `last`: The end of the sequence from which to copy.
- `stencil`: The beginning of the stencil sequence.
- `result`: The beginning of the sequence into which to copy.
- `pred`: The predicate to test on every value of the range `[stencil, stencil + (last-first)]`.

## Template Parameters

- `InputIterator1`: is a model of `Input Iterator`.
- `InputIterator2`: is a model of `Input Iterator`, and `InputIterator2`'s `value_type` is convertible to `Predicate`'s `argument_type`.
- `OutputIterator`: is a model of `Output Iterator`.
- `Predicate`: is a model of `Predicate`.

```
#include <thrust/copy.h>
...
struct is_even
{
    __host__ __device__
    bool operator() (const int x)
    {
        return (x % 2) == 0;
    }
};
...
int N = 6;
int data[N] = { 0, 1, 2, 3, 4, 5 };
int stencil[N] = {-2, 0, -1, 0, 1, 2};
int result[4];

thrust::copy_if(data, data + N, stencil, result, is_even());
```

// data remains = { 0, 1, 2, 3, 4, 5 };
// stencil remains = {-2, 0, -1, 0, 1, 2};
// result is now { 0, 1, 3, 5 }

See `remove_copy_if`

**Template Function `thrust::copy_n(const thrust::detail::execution_policy_base<DerivedPolicy>&, InputIterator, Size, OutputIterator)`**

- Defined in `file_thrust_copy.h`

## Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “thrust::copy\_n” with arguments (const thrust::detail::execution\_policy\_base<DerivedPolicy>&, InputIterator, Size, OutputIterator) in doxygen xml output for project “rocThrust” from directory: ./docBin/xml. Potential matches:

```
- template<typename DerivedPolicy, typename InputIterator, typename Size, typename_
  ↵OutputIterator> __host__ __device__ OutputIterator thrust::copy_n(const_
  ↵thrust::detail::execution_policy_base< DerivedPolicy > &, InputIterator, Size,_
  ↵OutputIterator)
- template<typename InputIterator, typename Size, typename OutputIterator>
  OutputIterator thrust::copy_n(InputIterator, Size, OutputIterator)
```

## Template Function `thrust::copy_n(InputIterator, Size, OutputIterator)`

### Function Documentation

```
template<typename InputIterator, typename Size, typename OutputIterator>
OutputIterator thrust::copy_n(InputIterator first, Size n, OutputIterator result)
```

`copy_n` copies elements from the range  $[first, first + n]$  to the range  $[result, result + n]$ . That is, it performs the assignments  $*result = *first$ ,  $*(result + 1) = *(first + 1)$ , and so on. Generally, for every integer  $i$  from 0 to  $n$ , `copy` performs the assignment  $*(result + i) = *(first + i)$ . Unlike `std::copy_n`, `copy_n` offers no guarantee on order of operation. As a result, calling `copy_n` with overlapping source and destination ranges has undefined behavior.

The return value is `result + n`.

The following code snippet demonstrates how to use `copy` to copy from one range to another.

**Return** The end of the destination range.

**Pre** `result` may be equal to `first`, but `result` shall not be in the range  $[first, first + n]$  otherwise.

### Parameters

- `first`: The beginning of the range to copy.
- `n`: The number of elements to copy.
- `result`: The beginning destination range.

### Template Parameters

- `InputIterator`: must be a model of `Input Iterator` and `InputIterator`'s `value_type` must be convertible to `OutputIterator`'s `value_type`.
- `Size`: is an integral type.
- `OutputIterator`: must be a model of `Output Iterator`.

```
#include <thrust/copy.h>
#include <thrust/device_vector.h>
...
size_t n = 100;
thrust::device_vector<int> vec0(n);
thrust::device_vector<int> vec1(n);
...
thrust::copy_n(vec0.begin(), n, vec1.begin());
// vec1 is now a copy of vec0
```

See [http://www.sgi.com/tech/stl/copy\\_n.html](http://www.sgi.com/tech/stl/copy_n.html)

See `thrust::copy`

### Template Function `thrust::cos`

- Defined in file `thrust_complex.h`

#### Function Documentation

```
template<typename T> __host__ __device__ complex<T> thrust::cos(const complex < T > & z)
```

Returns the complex cosine of a complex number.

##### Parameters

- `z`: The complex argument.

### Template Function `thrust::cosh`

- Defined in file `thrust_complex.h`

#### Function Documentation

```
template<typename T> __host__ __device__ complex<T> thrust::cosh(const complex < T > & z)
```

Returns the complex hyperbolic cosine of a complex number.

##### Parameters

- `z`: The complex argument.

### Template Function `thrust::count(const thrust::detail::execution_policy_base<DerivedPolicy>&, InputIterator, InputIterator, const EqualityComparable&)`

- Defined in file `thrust_count.h`

#### Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::count`” with arguments `(const thrust::detail::execution_policy_base<DerivedPolicy>&, InputIterator, InputIterator, const EqualityComparable&)` in doxygen xml output for project “rocThrust” from directory: `./docBin/xml`. Potential matches:

```
- template<typename DerivedPolicy, typename InputIterator, typename EqualityComparable> __host__ __device__ thrust::iterator_traits<InputIterator>::difference_type thrust::count(const thrust::detail::execution_policy_base<DerivedPolicy> &, InputIterator, InputIterator, const EqualityComparable &)
- template<typename InputIterator, typename EqualityComparable> thrust::iterator_traits<InputIterator>::difference_type thrust::count(InputIterator, InputIterator, const EqualityComparable &)
```

**Template Function `thrust::count(InputIterator, InputIterator, const EqualityComparable&)`****Function Documentation**

```
template<typename InputIterator, typename EqualityComparable>
thrust::iterator_traits<InputIterator>::difference_type thrust::count(InputIterator first, InputIterator last, const EqualityComparable &value)
count finds the number of elements in [first, last) that are equal to value. More precisely, count returns the number of iterators i in [first, last) such that *i == value.
```

The following code snippet demonstrates how to use **count** to count the number of instances in a range of a value of interest.

```
#include <thrust/count.h>
#include <thrust/device_vector.h>
...
// put 3 1s in a device_vector
thrust::device_vector<int> vec(5, 0);
vec[1] = 1;
vec[3] = 1;
vec[4] = 1;

// count the 1s
int result = thrust::count(vec.begin(), vec.end(), 1);
// result == 3
```

**Return** The number of elements equal to **value**.

**Parameters**

- **first**: The beginning of the sequence.
- **last**: The end of the sequence.
- **value**: The value to be counted.

**Template Parameters**

- **InputIterator**: must be a model of **Input Iterator** and **InputIterator**'s **value\_type** must be a model of **Equality Comparable**.
- **EqualityComparable**: must be a model of **Equality Comparable** and can be compared for equality with **InputIterator**'s **value\_type**

**See** <http://www.sgi.com/tech/stl/count.html>

**Template Function `thrust::count_if(const thrust::detail::execution_policy_base<DerivedPolicy>&, InputIterator, InputIterator, Predicate)`**

- Defined in file `_thrust_count.h`

## Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “thrust::count\_if” with arguments (const thrust::detail::execution\_policy\_base<DerivedPolicy>&, InputIterator, InputIterator, Predicate) in doxygen xml output for project “rocThrust” from directory: ./docBin/xml. Potential matches:

```
- template<typename DerivedPolicy, typename InputIterator, typename Predicate> __  
→ host __ device __ thrust::iterator_traits<InputIterator>::difference_type __  
→ thrust::count_if(const thrust::detail::execution_policy_base< DerivedPolicy > &, __  
→ InputIterator, InputIterator, Predicate)  
- template<typename InputIterator, typename Predicate>  
  thrust::iterator_traits<InputIterator>::difference_type thrust::count_ __  
→ if(InputIterator, InputIterator, Predicate)
```

## Template Function thrust::count\_if(InputIterator, InputIterator, Predicate)

### Function Documentation

```
template<typename InputIterator, typename Predicate>  
thrust::iterator_traits<InputIterator>::difference_type thrust::count_if (InputIterator first, InputIterator last, Predicate pred)  
  count_if finds the number of elements in [first, last) for which a predicate is true. More precisely,  
  count_if returns the number of iterators i in [first, last) such that pred(*i) == true.
```

The following code snippet demonstrates how to use count to count the number of odd numbers in a range.

```
#include <thrust/count.h>  
#include <thrust/device_vector.h>  
...  
struct is_odd  
{  
  __host__ __device__  
  bool operator() (int &x)  
  {  
    return x & 1;  
  }  
};  
...  
// fill a device_vector with even & odd numbers  
thrust::device_vector<int> vec(5);  
vec[0] = 0;  
vec[1] = 1;  
vec[2] = 2;  
vec[3] = 3;  
vec[4] = 4;  
  
// count the odd elements in vec  
int result = thrust::count_if(vec.begin(), vec.end(), is_odd());  
// result == 2
```

**Return** The number of elements where pred is true.

### Parameters

- first: The beginning of the sequence.

- `last`: The end of the sequence.
- `pred`: The predicate.

### Template Parameters

- `InputIterator`: must be a model of `Input Iterator` and `InputIterator`'s `value_type` must be convertible to `Predicate`'s `argument_type`.
- `Predicate`: must be a model of `Predicate`.

See <http://www.sgi.com/tech/stl/count.html>

## Template Function `thrust::device_delete`

### Function Documentation

```
template<typename T>
void thrust::device_delete(thrust::device_ptr<T> ptr, const size_t n = 1)
    device_delete deletes a device_ptr allocated with device_new.
```

See [device\\_ptr](#)

See [device\\_new](#)

### Parameters

- `ptr`: The `device_ptr` to delete, assumed to have been allocated with `device_new`.
- `n`: The number of objects to destroy at `ptr`. Defaults to 1 similar to `device_new`.

## Function `thrust::device_free`

### Function Documentation

```
void thrust::device_free(thrust::device_ptr<void> ptr)
    device_free deallocates memory allocated by the function device_malloc.
```

The following code snippet demonstrates how to use `device_free` to deallocate memory allocated by `device_malloc`.

### Parameters

- `ptr`: A `device_ptr` pointing to memory to be deallocated.

```
#include <thrust/device_malloc.h>
#include <thrust/device_free.h>
...
// allocate some integers with device_malloc
const int N = 100;
thrust::device_ptr<int> int_array = thrust::device_malloc<int>(N);

// manipulate integers
...

// deallocate with device_free
thrust::device_free(int_array);
```

See [device\\_ptr](#)

See [device\\_malloc](#)

## Function `thrust::device_malloc`

### Function Documentation

`device_ptr<T> thrust::device_malloc(const std::size_t n)`

This version of `device_malloc` allocates sequential device storage for bytes.

The following code snippet demonstrates how to use `device_malloc` to allocate a range of device memory.

**Return** A `device_ptr` to the newly allocated memory.

#### Parameters

- `n`: The number of bytes to allocate sequentially in device memory.

```
#include <thrust/device_malloc.h>
#include <thrust/device_free.h>
...
// allocate some memory with device_malloc
const int N = 100;
thrust::device_ptr<void> void_ptr = thrust::device_malloc(N);

// manipulate memory
...

// deallocate with device_free
thrust::device_free(void_ptr);
```

This version of `device_malloc` allocates sequential device storage for new objects of the given type.

See [device\\_ptr](#)

See [device\\_free](#)

The following code snippet demonstrates how to use `device_malloc` to allocate a range of device memory.

**Return** A `device_ptr` to the newly allocated memory.

#### Parameters

- `n`: The number of objects of type `T` to allocate sequentially in device memory.

```
#include <thrust/device_malloc.h>
#include <thrust/device_free.h>
...
// allocate some integers with device_malloc
const int N = 100;
thrust::device_ptr<int> int_array = thrust::device_malloc<int>(N);

// manipulate integers
...

// deallocate with device_free
thrust::device_free(int_array);
```

See [device\\_ptr](#)

See [device\\_free](#)

### Template Function `thrust::device_new(device_ptr<void>, const size_t)`

- Defined in file `thrust_device_new.h`

#### Function Documentation

```
template<typename T>
device_ptr<T> thrust::device_new(device_ptr<void> p, const size_t n = 1)
    device_new implements the placement new operator for types resident in device memory. device_new
    calls T's null constructor on a array of objects in device memory. No memory is allocated by this function.
```

**Return** p, casted to T's type.

See [device\\_ptr](#)

#### Parameters

- p: A `device_ptr` to a region of device memory into which to construct one or many Ts.
- n: The number of objects to construct at p.

### Template Function `thrust::device_new(device_ptr<void>, const T&, const size_t)`

#### Function Documentation

```
template<typename T>
device_ptr<T> thrust::device_new(device_ptr<void> p, const T &exemplar, const size_t n = 1)
    device_new implements the placement new operator for types resident in device memory. device_new
    calls T's copy constructor on a array of objects in device memory. No memory is allocated by this function.
```

**Return** p, casted to T's type.

See [device\\_ptr](#)

See [fill](#)

#### Parameters

- p: A `device_ptr` to a region of device memory into which to construct one or many Ts.
- exemplar: The value from which to copy.
- n: The number of objects to construct at p.

### Template Function `thrust::device_new(const size_t)`

#### Function Documentation

```
template<typename T>
device_ptr<T> thrust::device_new(const size_t n = 1)
    device_new implements the new operator for types resident in device memory. It allocates device memory
    large enough to hold n new objects of type T.
```

**Return** A `device_ptr` to the newly allocated region of device memory.

#### Parameters

- n: The number of objects to allocate. Defaults to 1.

### Template Function `thrust::device_pointer_cast(T *)`

- Defined in file `thrust_device_ptr.h`

#### Function Documentation

```
template<typename T> __host__ __device__ device_ptr<T> thrust::device_pointer_cast(T * ptr)
```

`device_pointer_cast` creates a `device_ptr` from a raw pointer which is presumed to point to a location in device memory.

**Return** A `device_ptr` wrapping ptr.

#### Parameters

- ptr: A raw pointer, presumed to point to a location in device memory.

### Template Function `thrust::device_pointer_cast(const device_ptr<T>&)`

#### Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::device_pointer_cast`” with arguments (`const device_ptr<T>&`) in doxygen xml output for project “rocThrust” from directory: ./docBin/xml. Potential matches:

```
- template<typename T> __host__ __device__ device_ptr<T> thrust::device_pointer_
  ↪cast(T *)
- template<typename T> __host__ __device__ device_ptr<T> thrust::device_pointer_
  ↪cast(const device_ptr < T > &)
```

### Template Function `thrust::distance`

- Defined in file `thrust_distance.h`

#### Function Documentation

```
template<typename InputIterator> __host__ __device__ thrust::iterator_traits<InputIterator>
distance finds the distance between first and last, i.e. the number of times that first must be incremented until it is equal to last.
```

The following code snippet demonstrates how to use `distance` to compute the distance to one iterator from another.

**Return** The distance between the beginning and end of the input range.

**Pre** If `InputIterator` meets the requirements of random access iterator, `last` shall be reachable from `first` or `first` shall be reachable from `last`; otherwise, `last` shall be reachable from `first`.

## Parameters

- `first`: The beginning of an input range of interest.
- `last`: The end of an input range of interest.

## Template Parameters

- `InputIterator`: is a model of `Input Iterator`.

```
#include <thrust/distance.h>
#include <thrust/device_vector.h>
...
thrust::device_vector<int> vec(13);
thrust::device_vector<int>::iterator iter1 = vec.begin();
thrust::device_vector<int>::iterator iter2 = iter1 + 7;

int d = thrust::distance(iter1, iter2);

// d is 7
```

See <http://www.sgi.com/tech/stl/distance.html>

## Template Function `thrust::equal(const thrust::detail::execution_policy_base<DerivedPolicy>&, InputIterator1, InputIterator1, InputIterator2)`

- Defined in file `thrust_equal.h`

## Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::equal`” with arguments (`const thrust::detail::execution_policy_base<DerivedPolicy>&`, `InputIterator1`, `InputIterator1`, `InputIterator2`) in doxygen xml output for project “rocThrust” from directory: `./docBin/xml`. Potential matches:

```
- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2,
→ typename BinaryPredicate> __host__ __device__ bool thrust::equal(const
→ thrust::detail::execution_policy_base< DerivedPolicy > &, InputIterator1,
→ InputIterator1, InputIterator2, BinaryPredicate)
- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2>
→ __host__ __device__ bool thrust::equal(const thrust::detail::execution_policy_base
→ < DerivedPolicy > &, InputIterator1, InputIterator1, InputIterator2)
- template<typename InputIterator1, typename InputIterator2, typename_
→ BinaryPredicate>
→ bool thrust::equal(InputIterator1, InputIterator1, InputIterator2,
→ BinaryPredicate)
- template<typename InputIterator1, typename InputIterator2>
→ bool thrust::equal(InputIterator1, InputIterator1, InputIterator2)
```

## Template Function `thrust::equal(InputIterator1, InputIterator1, InputIterator2)`

## Function Documentation

`template<typename InputIterator1, typename InputIterator2>`

```
bool thrust::equal(InputIterator1 first1, InputIterator1 last1, InputIterator2 first2)
    equal returns true if the two ranges [first1, last1) and [first2, first2 + (last1 - first1)) are identical when compared element-by-element, and otherwise returns false.
```

This version of `equal` returns true if and only if for every iterator `i` in `[first1, last1)`, `*i == *(first2 + (i - first1))`.

The following code snippet demonstrates how to use `equal` to test two ranges for equality.

**Return** `true`, if the sequences are equal; `false`, otherwise.

#### Parameters

- `first1`: The beginning of the first sequence.
- `last1`: The end of the first sequence.
- `first2`: The beginning of the second sequence.

#### Template Parameters

- `InputIterator1`: is a model of `Input Iterator`, and `InputIterator1`'s `value_type` is a model of `Equality Comparable`, and `InputIterator1`'s `value_type` can be compared for equality with `InputIterator2`'s `value_type`.
- `InputIterator2`: is a model of `Input Iterator`, and `InputIterator2`'s `value_type` is a model of `Equality Comparable`, and `InputIterator2`'s `value_type` can be compared for equality with `InputIterator1`'s `value_type`.

```
#include <thrust/equal.h>
...
int A1[7] = {3, 1, 4, 1, 5, 9, 3};
int A2[7] = {3, 1, 4, 2, 8, 5, 7};
...
bool result = thrust::equal(A1, A1 + 7, A2);
// result == false
```

See <http://www.sgi.com/tech/stl/equal.html>

**Template Function `thrust::equal(const thrust::detail::execution_policy_base<DerivedPolicy>&, InputIterator1, InputIterator1, InputIterator2, BinaryPredicate)`**

#### Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::equal`” with arguments (`const thrust::detail::execution_policy_base<DerivedPolicy>&`, `InputIterator1`, `InputIterator1`, `InputIterator2`, `BinaryPredicate`) in doxygen xml output for project “rocThrust” from directory: `./docBin/xml`. Potential matches:

```
- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2,
          typename BinaryPredicate> __host__ __device__ bool thrust::equal(const
          thrust::detail::execution_policy_base< DerivedPolicy > &, InputIterator1,
          InputIterator1, InputIterator2, BinaryPredicate)
- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2>
          __host__ __device__ bool thrust::equal(const thrust::detail::execution_policy_base
          < DerivedPolicy > &, InputIterator1, InputIterator1, InputIterator2)
- template<typename InputIterator1, typename InputIterator2, typename
          BinaryPredicate>
          bool thrust::equal(InputIterator1, InputIterator1, InputIterator2,
          BinaryPredicate)
- template<typename InputIterator1, typename InputIterator2>
          bool thrust::equal(InputIterator1, InputIterator1, InputIterator2)
```

## Template Function `thrust::equal(InputIterator1, InputIterator1, InputIterator2, BinaryPredicate)`

### Function Documentation

```
template<typename InputIterator1, typename InputIterator2, typename BinaryPredicate>
bool thrust::equal (InputIterator1 first1, InputIterator1 last1, InputIterator2 first2, BinaryPredicate binary_pred)
    equal returns true if the two ranges [first1, last1) and [first2, first2 + (last1 - first1)) are identical when compared element-by-element, and otherwise returns false.
```

This version of `equal` returns true if and only if for every iterator `i` in `[first1, last1)`, `binary_pred(*i, *(first2 + (i - first1)))` is true.

The following code snippet demonstrates how to use `equal` to compare the elements in two ranges modulo 2.

**Return** true, if the sequences are equal; false, otherwise.

#### Parameters

- `first1`: The beginning of the first sequence.
- `last1`: The end of the first sequence.
- `first2`: The beginning of the second sequence.
- `binary_pred`: Binary predicate used to test element equality.

#### Template Parameters

- `InputIterator1`: is a model of `Input Iterator`, and `InputIterator1`'s `value_type` is convertible to `BinaryPredicate`'s `first_argument_type`.
- `InputIterator2`: is a model of `Input Iterator`, and `InputIterator2`'s `value_type` is convertible to `BinaryPredicate`'s `second_argument_type`.
- `BinaryPredicate`: is a model of `Binary Predicate`.

```
#include <thrust/equal.h>

struct compare_modulo_two
{
    __host__ __device__
    bool operator() (int x, int y) const
    {
        return (x % 2) == (y % 2);
    }
};

...
int x[6] = {0, 2, 4, 6, 8, 10};
int y[6] = {1, 3, 5, 7, 9, 11};

bool result = thrust::equal(x, x + 5, y, compare_modulo_two());
// result is true
```

See <http://www.sgi.com/tech/stl/equal.html>

**Template Function `thrust::equal_range(const thrust::detail::execution_policy_base<DerivedPolicy>&, ForwardIterator, ForwardIterator, const LessThanComparable&)`**

- Defined in file `thrust_binary_search.h`

**Function Documentation**

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::equal_range`” with arguments (`const thrust::detail::execution_policy_base<DerivedPolicy>&`, `ForwardIterator`, `ForwardIterator`, `const LessThanComparable&`) in doxygen xml output for project “rocThrust” from directory: `./docBin/xml`. Potential matches:

```
- template<class ForwardIterator, class LessThanComparable>
  thrust::pair<ForwardIterator, ForwardIterator> thrust::equal_
  →range(ForwardIterator, ForwardIterator, const LessThanComparable&)
- template<class ForwardIterator, class T, class StrictWeakOrdering>
  thrust::pair<ForwardIterator, ForwardIterator> thrust::equal_
  →range(ForwardIterator, ForwardIterator, const T&, StrictWeakOrdering)
- template<typename DerivedPolicy, typename ForwardIterator, typename_
  →LessThanComparable>__host__ __device__ thrust::pair<ForwardIterator,_
  →ForwardIterator> thrust::equal_range(const thrust::detail::execution_policy_base<_
  →DerivedPolicy > &, ForwardIterator, ForwardIterator, const LessThanComparable &)
- template<typename DerivedPolicy, typename ForwardIterator, typename T, typename_
  →StrictWeakOrdering>__host__ __device__ thrust::pair<ForwardIterator,_
  →ForwardIterator> thrust::equal_range(const thrust::detail::execution_policy_base<_
  →DerivedPolicy > &, ForwardIterator, ForwardIterator, const T &,_
  →StrictWeakOrdering)
```

**Template Function `thrust::equal_range(ForwardIterator, ForwardIterator, const LessThanComparable&)`****Function Documentation**

```
template<class ForwardIterator, class LessThanComparable>
thrust::pair<ForwardIterator, ForwardIterator> thrust::equal_range(ForwardIterator first, ForwardIterator last, const LessThanComparable &value)
```

`equal_range` is a version of binary search: it attempts to find the element `value` in an ordered range `[first, last]`. The value returned by `equal_range` is essentially a combination of the values returned by `lower_bound` and `upper_bound`: it returns a pair of iterators `i` and `j` such that `i` is the first position where `value` could be inserted without violating the ordering and `j` is the last position where `value` could be inserted without violating the ordering. It follows that every element in the range `[i, j]` is equivalent to `value`, and that `[i, j]` is the largest subrange of `[first, last]` that has this property.

This version of `equal_range` returns a pair of iterators `[i, j]`, where `i` is the furthermost iterator in `[first, last]` such that, for every iterator `k` in `[first, i]`,  $*k < value$ . `j` is the furthermost iterator in `[first, last]` such that, for every iterator `k` in `[first, j]`,  $value < *k$  is false. For every iterator `k` in `[i, j]`, neither  $value < *k$  nor  $*k < value$  is true.

The following code snippet demonstrates how to use `equal_range` to search for values in a ordered range.

**Return** A pair of iterators `[i, j]` that define the range of equivalent elements.

**Parameters**

- `first`: The beginning of the ordered sequence.
- `last`: The end of the ordered sequence.
- `value`: The value to be searched.

### Template Parameters

- `ForwardIterator`: is a model of `Forward Iterator`.
- `LessThanComparable`: is a model of `LessThanComparable`.

```
#include <thrust/binary_search.h>
#include <thrust/device_vector.h>
...
thrust::device_vector<int> input(5);

input[0] = 0;
input[1] = 2;
input[2] = 5;
input[3] = 7;
input[4] = 8;

thrust::equal_range(input.begin(), input.end(), 0); // returns [input.begin(), ↵
↪ input.begin() + 1)
thrust::equal_range(input.begin(), input.end(), 1); // returns [input.begin() + 1,
↪ input.begin() + 1)
thrust::equal_range(input.begin(), input.end(), 2); // returns [input.begin() + 1,
↪ input.begin() + 2)
thrust::equal_range(input.begin(), input.end(), 3); // returns [input.begin() + 2,
↪ input.begin() + 2)
thrust::equal_range(input.begin(), input.end(), 8); // returns [input.begin() + 4,
↪ input.end)
thrust::equal_range(input.begin(), input.end(), 9); // returns [input.end(), ↵
↪ input.end)
```

**See** [http://www.sgi.com/tech/stl/equal\\_range.html](http://www.sgi.com/tech/stl/equal_range.html)

**See** `lower_bound`

**See** `upper_bound`

**See** `binary_search`

**Template Function `thrust::equal_range(const thrust::detail::execution_policy_base<DerivedPolicy>&, ForwardIterator, ForwardIterator, const T&, StrictWeakOrdering)`**

### Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::equal_range`” with arguments (`const thrust::detail::execution_policy_base<DerivedPolicy>&`, `ForwardIterator`, `ForwardIterator`, `const T&`, `StrictWeakOrdering`) in doxygen xml output for project “rocThrust” from directory: `./docBin/xml`. Potential matches:

```
- template<class ForwardIterator, class LessThanComparable>
    thrust::pair<ForwardIterator, ForwardIterator> thrust::equal_
    →range(ForwardIterator, ForwardIterator, const LessThanComparable&)
- template<class ForwardIterator, class T, class StrictWeakOrdering>
    thrust::pair<ForwardIterator, ForwardIterator> thrust::equal_
    →range(ForwardIterator, ForwardIterator, const T&, StrictWeakOrdering)
- template<typename DerivedPolicy, typename ForwardIterator, typename_
    →LessThanComparable>__host__ __device__ thrust::pair<ForwardIterator,_
    →ForwardIterator> thrust::equal_range(const thrust::detail::execution_policy_base<_
    →DerivedPolicy > &, ForwardIterator, ForwardIterator, const LessThanComparable &)
- template<typename DerivedPolicy, typename ForwardIterator, typename T, typename_
    →StrictWeakOrdering>__host__ __device__ thrust::pair<ForwardIterator,_
    →ForwardIterator> thrust::equal_range(const thrust::detail::execution_policy_base<_
    →DerivedPolicy > &, ForwardIterator, ForwardIterator, const T &,_
    →StrictWeakOrdering)
```

## Template Function `thrust::equal_range(ForwardIterator, ForwardIterator, const T&, StrictWeakOrdering)`

### Function Documentation

```
template<class ForwardIterator, class T, class StrictWeakOrdering>
thrust::pair<ForwardIterator, ForwardIterator> thrust::equal_range(ForwardIterator first, ForwardIter-
    →ator last, const T &value,
    →StrictWeakOrdering comp)
```

`equal_range` is a version of binary search: it attempts to find the element value in an ordered range  $[first, last]$ . The value returned by `equal_range` is essentially a combination of the values returned by `lower_bound` and `upper_bound`: it returns a pair of iterators  $i$  and  $j$  such that  $i$  is the first position where `value` could be inserted without violating the ordering and  $j$  is the last position where `value` could be inserted without violating the ordering. It follows that every element in the range  $[i, j]$  is equivalent to `value`, and that  $[i, j]$  is the largest subrange of  $[first, last]$  that has this property.

This version of `equal_range` returns a pair of iterators  $[i, j]$ .  $i$  is the furthermost iterator in  $[first, last]$  such that, for every iterator  $k$  in  $[first, i]$ ,  $\text{comp}(*k, \text{value})$  is true.  $j$  is the furthermost iterator in  $[first, last]$  such that, for every iterator  $k$  in  $[first, last]$ ,  $\text{comp}(\text{value}, *k)$  is false. For every iterator  $k$  in  $[i, j]$ , neither  $\text{comp}(\text{value}, *k)$  nor  $\text{comp}(*k, \text{value})$  is true.

The following code snippet demonstrates how to use `equal_range` to search for values in a ordered range.

**Return** A pair of iterators  $[i, j]$  that define the range of equivalent elements.

### Parameters

- `first`: The beginning of the ordered sequence.
- `last`: The end of the ordered sequence.
- `value`: The value to be searched.
- `comp`: The comparison operator.

### Template Parameters

- `ForwardIterator`: is a model of `Forward Iterator`.
- `T`: is comparable to `ForwardIterator`'s `value_type`.
- `StrictWeakOrdering`: is a model of `Strict Weak Ordering`.

```

#include <thrust/binary_search.h>
#include <thrust/device_vector.h>
#include <thrust/functional.h>
...
thrust::device_vector<int> input(5);

input[0] = 0;
input[1] = 2;
input[2] = 5;
input[3] = 7;
input[4] = 8;

thrust::equal_range(input.begin(), input.end(), 0, thrust::less<int>()); // ↵
// returns [input.begin(), input.begin() + 1)
thrust::equal_range(input.begin(), input.end(), 1, thrust::less<int>()); // ↵
// returns [input.begin() + 1, input.begin() + 1)
thrust::equal_range(input.begin(), input.end(), 2, thrust::less<int>()); // ↵
// returns [input.begin() + 1, input.begin() + 2)
thrust::equal_range(input.begin(), input.end(), 3, thrust::less<int>()); // ↵
// returns [input.begin() + 2, input.begin() + 2)
thrust::equal_range(input.begin(), input.end(), 8, thrust::less<int>()); // ↵
// returns [input.begin() + 4, input.end)
thrust::equal_range(input.begin(), input.end(), 9, thrust::less<int>()); // ↵
// returns [input.end(), input.end)

```

**See** [http://www.sgi.com/tech/stl/equal\\_range.html](http://www.sgi.com/tech/stl/equal_range.html)

**See** `lower_bound`

**See** `upper_bound`

**See** `binary_search`

**Template Function** `thrust::exclusive_scan(const thrust::detail::execution_policy_base<DerivedPolicy>&, InputIterator, InputIterator, OutputIterator)`

- Defined in file `thrust_scan.h`

## Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::exclusive_scan`” with arguments (`const thrust::detail::execution_policy_base<DerivedPolicy>&`, `InputIterator`, `InputIterator`, `OutputIterator`) in doxygen xml output for project “rocThrust” from directory: `./docBin/xml`. Potential matches:

```
- template<typename DerivedPolicy, typename InputIterator, typename OutputIterator,>
→typename T, typename AssociativeOperator>__host__ __device__ OutputIterator
→thrust::exclusive_scan(const thrust::detail::execution_policy_base< DerivedPolicy >
→&, InputIterator, InputIterator, OutputIterator, T, AssociativeOperator)
- template<typename DerivedPolicy, typename InputIterator, typename OutputIterator,>
→typename T>__host__ __device__ OutputIterator thrust::exclusive_scan(const
→thrust::detail::execution_policy_base< DerivedPolicy > &, InputIterator,
→InputIterator, OutputIterator, T)
- template<typename DerivedPolicy, typename InputIterator, typename OutputIterator>_
→_host__ __device__ OutputIterator thrust::exclusive_scan(const
→thrust::detail::execution_policy_base< DerivedPolicy > &, InputIterator,
→InputIterator, OutputIterator)
- template<typename InputIterator, typename OutputIterator, typename T, typename
→AssociativeOperator>
→OutputIterator thrust::exclusive_scan(InputIterator, InputIterator,
→OutputIterator, T, AssociativeOperator)
- template<typename InputIterator, typename OutputIterator, typename T>
→OutputIterator thrust::exclusive_scan(InputIterator, InputIterator,
→OutputIterator, T)
- template<typename InputIterator, typename OutputIterator>
→OutputIterator thrust::exclusive_scan(InputIterator, InputIterator,
→OutputIterator)
```

## Template Function `thrust::exclusive_scan(InputIterator, InputIterator, OutputIterator)`

### Function Documentation

```
template<typename InputIterator, typename OutputIterator>
OutputIterator thrust::exclusive_scan(InputIterator first, InputIterator last, OutputIterator result)
    exclusive_scan computes an exclusive prefix sum operation. The term ‘exclusive’ means that each result does not include the corresponding input operand in the partial sum. More precisely, 0 is assigned to *result and the sum of 0 and *first is assigned to *(result + 1), and so on. This version of exclusive_scan assumes plus as the associative operator and 0 as the initial value. When the input and output sequences are the same, the scan is performed in-place.
```

The following code snippet demonstrates how to use `exclusive_scan`

**Return** The end of the output sequence.

**Pre** `first` may equal `result` but the range `[first, last)` and the range `[result, result + (last - first))` shall not overlap otherwise.

### Parameters

- `first`: The beginning of the input sequence.
- `last`: The end of the input sequence.
- `result`: The beginning of the output sequence.

### Template Parameters

- `InputIterator`: is a model of `Input Iterator` and `InputIterator`'s `value_type` is convertible to `OutputIterator`'s `value_type`.
- `OutputIterator`: is a model of `Output Iterator`, and if `x` and `y` are objects of `OutputIterator`'s `value_type`, then `x + y` is defined. If `T` is `OutputIterator`'s

`value_type`, then `T(0)` is defined.

```
#include <thrust/scan.h>

int data[6] = {1, 0, 2, 2, 1, 3};

thrust::exclusive_scan(data, data + 6, data); // in-place scan

// data is now {0, 1, 1, 3, 5, 6}
```

See [http://www.sgi.com/tech/stl/partial\\_sum.html](http://www.sgi.com/tech/stl/partial_sum.html)

**Template Function `thrust::exclusive_scan(const thrust::detail::execution_policy_base<DerivedPolicy>&, InputIterator, InputIterator, OutputIterator, T)`**

### Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::exclusive_scan`” with arguments (`const thrust::detail::execution_policy_base<DerivedPolicy>&`, `InputIterator`, `InputIterator`, `OutputIterator`, `T`) in doxygen xml output for project “rocThrust” from directory: ./docBin/xml. Potential matches:

```
- template<typename DerivedPolicy, typename InputIterator, typename OutputIterator,
         typename T, typename AssociativeOperator> __host__ __device__ OutputIterator
         thrust::exclusive_scan(const thrust::detail::execution_policy_base< DerivedPolicy > &,
                               InputIterator, InputIterator, OutputIterator, T, AssociativeOperator)
- template<typename DerivedPolicy, typename InputIterator, typename OutputIterator,
         typename T> __host__ __device__ OutputIterator thrust::exclusive_scan(const
         thrust::detail::execution_policy_base< DerivedPolicy > &, InputIterator,
         InputIterator, OutputIterator, T)
- template<typename DerivedPolicy, typename InputIterator, typename OutputIterator> __host__ __device__ OutputIterator thrust::exclusive_scan(const
         thrust::detail::execution_policy_base< DerivedPolicy > &, InputIterator,
         InputIterator, OutputIterator)
- template<typename InputIterator, typename OutputIterator, typename T, typename
         AssociativeOperator>
         OutputIterator thrust::exclusive_scan(InputIterator, InputIterator,
         OutputIterator, T, AssociativeOperator)
- template<typename InputIterator, typename OutputIterator, typename T>
         OutputIterator thrust::exclusive_scan(InputIterator, InputIterator,
         OutputIterator, T)
- template<typename InputIterator, typename OutputIterator>
         OutputIterator thrust::exclusive_scan(InputIterator, InputIterator,
         OutputIterator)
```

**Template Function `thrust::exclusive_scan(InputIterator, InputIterator, OutputIterator, T)`**

### Function Documentation

```
template<typename InputIterator, typename OutputIterator, typename T>
OutputIterator thrust::exclusive_scan(InputIterator first, InputIterator last, OutputIterator result, T
                                     init)
```

`exclusive_scan` computes an exclusive prefix sum operation. The term ‘exclusive’ means that each result

does not include the corresponding input operand in the partial sum. More precisely, `init` is assigned to `*result` and the sum of `init` and `*first` is assigned to `*(result + 1)`, and so on. This version of `exclusive_scan` assumes `plus` as the associative operator but requires an initial value `init`. When the input and output sequences are the same, the scan is performed in-place.

The following code snippet demonstrates how to use `exclusive_scan`

**Return** The end of the output sequence.

**Pre** `first` may equal `result` but the range `[first, last)` and the range `[result, result + (last - first))` shall not overlap otherwise.

### Parameters

- `first`: The beginning of the input sequence.
- `last`: The end of the input sequence.
- `result`: The beginning of the output sequence.
- `init`: The initial value.

### Template Parameters

- `InputIterator`: is a model of `Input Iterator` and `InputIterator`'s `value_type` is convertible to `OutputIterator`'s `value_type`.
- `OutputIterator`: is a model of `Output Iterator`, and if `x` and `y` are objects of `OutputIterator`'s `value_type`, then `x + y` is defined.
- `T`: is convertible to `OutputIterator`'s `value_type`.

```
#include <thrust/scans.h>

int data[6] = {1, 0, 2, 2, 1, 3};

thrust::exclusive_scan(data, data + 6, data, 4); // in-place scan

// data is now {4, 5, 5, 7, 9, 10}
```

See [http://www.sgi.com/tech/stl/partial\\_sum.html](http://www.sgi.com/tech/stl/partial_sum.html)

**Template Function** `thrust::exclusive_scan(const thrust::detail::execution_policy_base<DerivedPolicy>&, InputIterator, InputIterator, OutputIterator, T, AssociativeOperator)`

### Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::exclusive_scan`” with arguments (`const thrust::detail::execution_policy_base<DerivedPolicy>&`, `InputIterator`, `InputIterator`, `OutputIterator`, `T`, `AssociativeOperator`) in doxygen xml output for project “rocThrust” from directory: `./docBin/xml`. Potential matches:

```

- template<typename DerivedPolicy, typename InputIterator, typename OutputIterator,
        typename T, typename AssociativeOperator> __host__ __device__ OutputIterator
        thrust::exclusive_scan(const thrust::detail::execution_policy_base< DerivedPolicy >
        &, InputIterator, InputIterator, OutputIterator, T, AssociativeOperator)
- template<typename DerivedPolicy, typename InputIterator, typename OutputIterator,
        typename T> __host__ __device__ OutputIterator thrust::exclusive_scan(const
        thrust::detail::execution_policy_base< DerivedPolicy > &, InputIterator,
        InputIterator, OutputIterator, T)
- template<typename DerivedPolicy, typename InputIterator, typename OutputIterator> __host__ __device__ OutputIterator thrust::exclusive_scan(const
        thrust::detail::execution_policy_base< DerivedPolicy > &, InputIterator,
        InputIterator, OutputIterator)
- template<typename InputIterator, typename OutputIterator, typename T, typename
        AssociativeOperator> OutputIterator thrust::exclusive_scan(InputIterator, InputIterator,
        OutputIterator, T, AssociativeOperator)
- template<typename InputIterator, typename OutputIterator, typename T> OutputIterator thrust::exclusive_scan(InputIterator, InputIterator,
        OutputIterator, T)
- template<typename InputIterator, typename OutputIterator> OutputIterator thrust::exclusive_scan(InputIterator, InputIterator,
        OutputIterator)

```

## Template Function `thrust::exclusive_scan(InputIterator, InputIterator, OutputIterator, T, AssociativeOperator)`

### Function Documentation

`template<typename InputIterator, typename OutputIterator, typename T, typename AssociativeOperator>`  
`OutputIterator thrust::exclusive_scan(InputIterator first, InputIterator last, OutputIterator result, T`  
 `init, AssociativeOperator binary_op)`

`exclusive_scan` computes an exclusive prefix sum operation. The term ‘exclusive’ means that each result does not include the corresponding input operand in the partial sum. More precisely, `init` is assigned to `*result` and the value `binary_op(init, *first)` is assigned to `*(result + 1)`, and so on. This version of the function requires both an associative operator and an initial value `init`. When the input and output sequences are the same, the scan is performed in-place.

The following code snippet demonstrates how to use `exclusive_scan`

**Return** The end of the output sequence.

**Pre** `first` may equal `result` but the range `[first, last)` and the range `[result, result + (last - first))` shall not overlap otherwise.

### Parameters

- `first`: The beginning of the input sequence.
- `last`: The end of the input sequence.
- `result`: The beginning of the output sequence.
- `init`: The initial value.
- `binary_op`: The associative operator used to ‘sum’ values.

### Template Parameters

- `InputIterator`: is a model of `Input Iterator` and `InputIterator`'s `value_type` is convertible to `OutputIterator`'s `value_type`.
- `OutputIterator`: is a model of `Output Iterator` and `OutputIterator`'s `value_type` is convertible to both `AssociativeOperator`'s `first_argument_type` and `second_argument_type`.
- `T`: is convertible to `OutputIterator`'s `value_type`.
- `AssociativeOperator`: is a model of `Binary Function` and `AssociativeOperator`'s `result_type` is convertible to `OutputIterator`'s `value_type`.

```
#include <thrust/scan.h>
#include <thrust/functional.h>

int data[10] = {-5, 0, 2, -3, 2, 4, 0, -1, 2, 8};

thrust::maximum<int> binary_op;

thrust::exclusive_scan(data, data + 10, data, 1, binary_op); // in-place scan

// data is now {1, 1, 1, 2, 2, 2, 4, 4, 4, 4}
```

See [http://www.sgi.com/tech/stl/partial\\_sum.html](http://www.sgi.com/tech/stl/partial_sum.html)

### Template Function `thrust::exclusive_scan_by_key(const thrust::detail::execution_policy_base<DerivedPolicy>&, InputIterator1, InputIterator1, InputIterator2, OutputIterator)`

- Defined in file `thrust_scan.h`

### Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::exclusive_scan_by_key`” with arguments (`const thrust::detail::execution_policy_base<DerivedPolicy>&`, `InputIterator1`, `InputIterator1`, `InputIterator2`, `OutputIterator`) in doxygen xml output for project “rocThrust” from directory: `./docBin/xml`. Potential matches:

```

- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2,
  ~ typename OutputIterator, typename T, typename BinaryPredicate, typename_
  ~AssociativeOperator> __host__ __device__ OutputIterator thrust::exclusive_scan_by_
  ~key(const thrust::detail::execution_policy_base< DerivedPolicy > &,
  ~InputIterator1, InputIterator1, InputIterator2, OutputIterator, T,
  ~BinaryPredicate, AssociativeOperator)
- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2,
  ~ typename OutputIterator, typename T, typename BinaryPredicate> __host__ __device__
  ~OutputIterator thrust::exclusive_scan_by_key(const thrust::detail::execution_
  ~policy_base< DerivedPolicy > &, InputIterator1, InputIterator1, InputIterator2,
  ~OutputIterator, T, BinaryPredicate)
- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2,
  ~ typename OutputIterator, typename T> __host__ __device__ OutputIterator
  ~thrust::exclusive_scan_by_key(const thrust::detail::execution_policy_base<
  ~DerivedPolicy > &, InputIterator1, InputIterator1, InputIterator2, OutputIterator,
  ~T)
- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2,
  ~ typename OutputIterator> __host__ __device__ OutputIterator thrust::exclusive_
  ~scan_by_key(const thrust::detail::execution_policy_base< DerivedPolicy > &,
  ~InputIterator1, InputIterator1, InputIterator2, OutputIterator)
- template<typename InputIterator1, typename InputIterator2, typename_
  ~OutputIterator, typename T, typename BinaryPredicate, typename_
  ~AssociativeOperator>
  OutputIterator thrust::exclusive_scan_by_key(InputIterator1, InputIterator1,
  ~InputIterator2, OutputIterator, T, BinaryPredicate, AssociativeOperator)
- template<typename InputIterator1, typename InputIterator2, typename_
  ~OutputIterator, typename T, typename BinaryPredicate>
  OutputIterator thrust::exclusive_scan_by_key(InputIterator1, InputIterator1,
  ~InputIterator2, OutputIterator, T, BinaryPredicate)
- template<typename InputIterator1, typename InputIterator2, typename_
  ~OutputIterator, typename T>
  OutputIterator thrust::exclusive_scan_by_key(InputIterator1, InputIterator1,
  ~InputIterator2, OutputIterator, T)
- template<typename InputIterator1, typename InputIterator2, typename_
  ~OutputIterator>
  OutputIterator thrust::exclusive_scan_by_key(InputIterator1, InputIterator1,
  ~InputIterator2, OutputIterator)

```

## Template Function `thrust::exclusive_scan_by_key(InputIterator1, InputIterator1, InputIterator2, OutputIterator)`

### Function Documentation

```
template<typename InputIterator1, typename InputIterator2, typename OutputIterator>
OutputIterator thrust::exclusive_scan_by_key(InputIterator1 first1, InputIterator1 last1, InputIterator2 first2, OutputIterator result)
```

`exclusive_scan_by_key` computes an exclusive segmented prefix

This version of `exclusive_scan_by_key` uses the value 0 to initialize the exclusive scan operation.

This version of `exclusive_scan_by_key` assumes `plus` as the associative operator used to perform the prefix sum. When the input and output sequences are the same, the scan is performed in-place.

This version of `exclusive_scan_by_key` assumes `equal_to` as the binary predicate used to compare adjacent keys. Specifically, consecutive iterators `i` and `i+1` in the range `[first1, last1]` belong to the

same segment if `*i == *(i+1)`, and belong to different segments otherwise.

Refer to the most general form of `exclusive_scan_by_key` for additional details.

The following code snippet demonstrates how to use `exclusive_scan_by_key`.

**Pre** `first1` may equal `result` but the range `[first1, last1)` and the range `[result, result + (last1 - first1))` shall not overlap otherwise.

**Pre** `first2` may equal `result` but the range `[first2, first2 + (last1 - first1))` and range `[result, result + (last1 - first1))` shall not overlap otherwise.

### Parameters

- `first1`: The beginning of the key sequence.
- `last1`: The end of the key sequence.
- `first2`: The beginning of the input value sequence.
- `result`: The beginning of the output value sequence.

```
#include <thrust/scan.h>

int keys[10] = {0, 0, 0, 1, 1, 2, 3, 3, 3, 3};
int vals[10] = {1, 1, 1, 1, 1, 1, 1, 1, 1, 1};

thrust::exclusive_scan_by_key(key, key + 10, vals, vals); // in-place scan

// vals is now {0, 1, 2, 0, 1, 0, 0, 1, 2, 3};
```

See `exclusive_scan`

**Template Function** `thrust::exclusive_scan_by_key(const thrust::detail::execution_policy_base<DerivedPolicy>&, InputIterator1, InputIterator1, InputIterator2, OutputIterator, T)`

### Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::exclusive_scan_by_key`” with arguments (`const thrust::detail::execution_policy_base<DerivedPolicy>&`, `InputIterator1`, `InputIterator1`, `InputIterator2`, `OutputIterator`, `T`) in doxygen xml output for project “rocThrust” from directory: `./docBin/xml`. Potential matches:

```

- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2,
  ~ typename OutputIterator, typename T, typename BinaryPredicate, typename_
  ~AssociativeOperator> __host__ __device__ OutputIterator thrust::exclusive_scan_by_
  ~key(const thrust::detail::execution_policy_base< DerivedPolicy > &,
  ~InputIterator1, InputIterator1, InputIterator2, OutputIterator, T,
  ~BinaryPredicate, AssociativeOperator)
- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2,
  ~ typename OutputIterator, typename T, typename BinaryPredicate> __host__ __device__
  ~OutputIterator thrust::exclusive_scan_by_key(const thrust::detail::execution_
  ~policy_base< DerivedPolicy > &, InputIterator1, InputIterator1, InputIterator2,
  ~OutputIterator, T, BinaryPredicate)
- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2,
  ~ typename OutputIterator, typename T> __host__ __device__ OutputIterator_
  ~thrust::exclusive_scan_by_key(const thrust::detail::execution_policy_base<
  ~DerivedPolicy > &, InputIterator1, InputIterator1, InputIterator2, OutputIterator,
  ~T)
- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2,
  ~ typename OutputIterator> __host__ __device__ OutputIterator thrust::exclusive_
  ~scan_by_key(const thrust::detail::execution_policy_base< DerivedPolicy > &,
  ~InputIterator1, InputIterator1, InputIterator2, OutputIterator)
- template<typename InputIterator1, typename InputIterator2, typename_
  ~OutputIterator, typename T, typename BinaryPredicate, typename_
  ~AssociativeOperator>
  OutputIterator thrust::exclusive_scan_by_key(InputIterator1, InputIterator1,
  ~InputIterator2, OutputIterator, T, BinaryPredicate, AssociativeOperator)
- template<typename InputIterator1, typename InputIterator2, typename_
  ~OutputIterator, typename T, typename BinaryPredicate>
  OutputIterator thrust::exclusive_scan_by_key(InputIterator1, InputIterator1,
  ~InputIterator2, OutputIterator, T, BinaryPredicate)
- template<typename InputIterator1, typename InputIterator2, typename_
  ~OutputIterator, typename T>
  OutputIterator thrust::exclusive_scan_by_key(InputIterator1, InputIterator1,
  ~InputIterator2, OutputIterator, T)
- template<typename InputIterator1, typename InputIterator2, typename_
  ~OutputIterator>
  OutputIterator thrust::exclusive_scan_by_key(InputIterator1, InputIterator1,
  ~InputIterator2, OutputIterator)

```

## Template Function `thrust::exclusive_scan_by_key(InputIterator1, InputIterator1, InputIterator2, OutputIterator, T)`

### Function Documentation

```
template<typename InputIterator1, typename InputIterator2, typename OutputIterator, typename T>
OutputIterator thrust::exclusive_scan_by_key(InputIterator1 first1, InputIterator1 last1, InputIterator2 first2, OutputIterator result, T init)
```

`exclusive_scan_by_key` computes an exclusive key-value or ‘segmented’ prefix sum operation. The term ‘exclusive’ means that each result does not include the corresponding input operand in the partial sum. The term ‘segmented’ means that the partial sums are broken into distinct segments. In other words, within each segment a separate exclusive scan operation is computed. Refer to the code sample below for example usage.

This version of `exclusive_scan_by_key` uses the value `init` to initialize the exclusive scan operation.

The following code snippet demonstrates how to use `exclusive_scan_by_key`

**Return** The end of the output sequence.

**Pre** `first1` may equal `result` but the range `[first1, last1)` and the range `[result, result + (last1 - first1))` shall not overlap otherwise.

**Pre** `first2` may equal `result` but the range `[first2, first2 + (last1 - first1))` and range `[result, result + (last1 - first1))` shall not overlap otherwise.

### Parameters

- `first1`: The beginning of the key sequence.
- `last1`: The end of the key sequence.
- `first2`: The beginning of the input value sequence.
- `result`: The beginning of the output value sequence.
- `init`: The initial of the exclusive sum value.

```
#include <thrust/scan.h>
#include <thrust/functional.h>

int keys[10] = {0, 0, 0, 1, 1, 2, 3, 3, 3, 3};
int vals[10] = {1, 1, 1, 1, 1, 1, 1, 1, 1, 1};

int init = 5;

thrust::exclusive_scan_by_key(key, key + 10, vals, vals, init); // in-place scan

// vals is now {5, 6, 7, 5, 6, 5, 5, 6, 7, 8};
```

**See** `exclusive_scan`

**See** `inclusive_scan_by_key`

**Template Function** `thrust::exclusive_scan_by_key(const thrust::detail::execution_policy_base<DerivedPolicy>&, InputIterator1, InputIterator1, InputIterator2, OutputIterator, T, BinaryPredicate)`

### Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::exclusive_scan_by_key`” with arguments (`const thrust::detail::execution_policy_base<DerivedPolicy>&`, `InputIterator1`, `InputIterator1`, `InputIterator2`, `OutputIterator`, `T`, `BinaryPredicate`) in doxygen xml output for project “rocThrust” from directory: `./docBin/xml`. Potential matches:

```

- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2,
  ~ typename OutputIterator, typename T, typename BinaryPredicate, typename_
  ~AssociativeOperator> __host__ __device__ OutputIterator thrust::exclusive_scan_by_
  ~key(const thrust::detail::execution_policy_base< DerivedPolicy > &,
  ~InputIterator1, InputIterator1, InputIterator2, OutputIterator, T,
  ~BinaryPredicate, AssociativeOperator)
- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2,
  ~ typename OutputIterator, typename T, typename BinaryPredicate> __host__ __device__
  ~OutputIterator thrust::exclusive_scan_by_key(const thrust::detail::execution_
  ~policy_base< DerivedPolicy > &, InputIterator1, InputIterator1, InputIterator2,
  ~OutputIterator, T, BinaryPredicate)
- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2,
  ~ typename OutputIterator, typename T> __host__ __device__ OutputIterator
  ~thrust::exclusive_scan_by_key(const thrust::detail::execution_policy_base<
  ~DerivedPolicy > &, InputIterator1, InputIterator1, InputIterator2, OutputIterator,
  ~T)
- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2,
  ~ typename OutputIterator> __host__ __device__ OutputIterator thrust::exclusive_
  ~scan_by_key(const thrust::detail::execution_policy_base< DerivedPolicy > &,
  ~InputIterator1, InputIterator1, InputIterator2, OutputIterator)
- template<typename InputIterator1, typename InputIterator2, typename_
  ~OutputIterator, typename T, typename BinaryPredicate, typename_
  ~AssociativeOperator>
  OutputIterator thrust::exclusive_scan_by_key(InputIterator1, InputIterator1,
  ~InputIterator2, OutputIterator, T, BinaryPredicate, AssociativeOperator)
- template<typename InputIterator1, typename InputIterator2, typename_
  ~OutputIterator, typename T, typename BinaryPredicate>
  OutputIterator thrust::exclusive_scan_by_key(InputIterator1, InputIterator1,
  ~InputIterator2, OutputIterator, T, BinaryPredicate)
- template<typename InputIterator1, typename InputIterator2, typename_
  ~OutputIterator, typename T>
  OutputIterator thrust::exclusive_scan_by_key(InputIterator1, InputIterator1,
  ~InputIterator2, OutputIterator, T)
- template<typename InputIterator1, typename InputIterator2, typename_
  ~OutputIterator>
  OutputIterator thrust::exclusive_scan_by_key(InputIterator1, InputIterator1,
  ~InputIterator2, OutputIterator)

```

## Template Function `thrust::exclusive_scan_by_key(InputIterator1, InputIterator1, InputIterator2, OutputIterator, T, BinaryPredicate)`

### Function Documentation

```
template<typename InputIterator1, typename InputIterator2, typename OutputIterator, typename T, typename Bin-
  OutputIterator thrust::exclusive_scan_by_key(InputIterator1 first1, InputIterator1 last1, InputIt-
  erator2 first2, OutputIterator result, T init, Binary-
  Predicate binary_pred)
```

`exclusive_scan_by_key` computes an exclusive key-value or ‘segmented’ prefix sum operation. The term ‘exclusive’ means that each result does not include the corresponding input operand in the partial sum. The term ‘segmented’ means that the partial sums are broken into distinct segments. In other words, within each segment a separate exclusive scan operation is computed. Refer to the code sample below for example usage.

This version of `exclusive_scan_by_key` uses the value `init` to initialize the exclusive scan operation.

This version of `exclusive_scan_by_key` uses the binary predicate `binary_pred` to compare adjacent

keys. Specifically, consecutive iterators `i` and `i+1` in the range `[first1, last1)` belong to the same segment if `binary_pred(*i, *(i+1))` is true, and belong to different segments otherwise.

The following code snippet demonstrates how to use `exclusive_scan_by_key`

**Return** The end of the output sequence.

**Pre** `first1` may equal `result` but the range `[first1, last1)` and the range `[result, result + (last1 - first1))` shall not overlap otherwise.

**Pre** `first2` may equal `result` but the range `[first2, first2 + (last1 - first1))` and range `[result, result + (last1 - first1))` shall not overlap otherwise.

### Parameters

- `first1`: The beginning of the key sequence.
- `last1`: The end of the key sequence.
- `first2`: The beginning of the input value sequence.
- `result`: The beginning of the output value sequence.
- `init`: The initial of the exclusive sum value.
- `binary_pred`: The binary predicate used to determine equality of keys.

```
#include <thrust/scan.h>
#include <thrust/functional.h>

int keys[10] = {0, 0, 0, 1, 1, 2, 3, 3, 3, 3};
int vals[10] = {1, 1, 1, 1, 1, 1, 1, 1, 1, 1};

int init = 5;

thrust::equal_to<int> binary_pred;

thrust::exclusive_scan_by_key(key, key + 10, vals, vals, init, binary_pred); // ↵
// in-place scan

// vals is now {5, 6, 7, 5, 6, 5, 5, 6, 7, 8};
```

**See** `exclusive_scan`

**See** `inclusive_scan_by_key`

**Template Function** `thrust::exclusive_scan_by_key(const thrust::detail::execution_policy_base<DerivedPolicy>&, InputIterator1, InputIterator1, InputIterator2, OutputIterator, T, BinaryPredicate, AssociativeOperator)`

### Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::exclusive_scan_by_key`” with arguments (`const thrust::detail::execution_policy_base<DerivedPolicy>&`, `InputIterator1`, `InputIterator1`, `InputIterator2`, `OutputIterator`, `T`, `BinaryPredicate`, `AssociativeOperator`) in doxygen xml output for project “rocThrust” from directory: `./docBin/xml`. Potential matches:

```

- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2,
  ~ typename OutputIterator, typename T, typename BinaryPredicate, typename_
  ~AssociativeOperator> __host__ __device__ OutputIterator thrust::exclusive_scan_by_
  ~key(const thrust::detail::execution_policy_base< DerivedPolicy > &,
  ~InputIterator1, InputIterator1, InputIterator2, OutputIterator, T,
  ~BinaryPredicate, AssociativeOperator)
- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2,
  ~ typename OutputIterator, typename T, typename BinaryPredicate> __host__ __device__
  ~OutputIterator thrust::exclusive_scan_by_key(const thrust::detail::execution_
  ~policy_base< DerivedPolicy > &, InputIterator1, InputIterator1, InputIterator2,
  ~OutputIterator, T, BinaryPredicate)
- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2,
  ~ typename OutputIterator, typename T> __host__ __device__ OutputIterator_
  ~thrust::exclusive_scan_by_key(const thrust::detail::execution_policy_base<
  ~DerivedPolicy > &, InputIterator1, InputIterator1, InputIterator2, OutputIterator,
  ~T)
- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2,
  ~ typename OutputIterator> __host__ __device__ OutputIterator thrust::exclusive_
  ~scan_by_key(const thrust::detail::execution_policy_base< DerivedPolicy > &,
  ~InputIterator1, InputIterator1, InputIterator2, OutputIterator)
- template<typename InputIterator1, typename InputIterator2, typename_
  ~OutputIterator, typename T, typename BinaryPredicate, typename_
  ~AssociativeOperator>
  OutputIterator thrust::exclusive_scan_by_key(InputIterator1, InputIterator1,
  ~InputIterator2, OutputIterator, T, BinaryPredicate, AssociativeOperator)
- template<typename InputIterator1, typename InputIterator2, typename_
  ~OutputIterator, typename T, typename BinaryPredicate>
  OutputIterator thrust::exclusive_scan_by_key(InputIterator1, InputIterator1,
  ~InputIterator2, OutputIterator, T, BinaryPredicate)
- template<typename InputIterator1, typename InputIterator2, typename_
  ~OutputIterator, typename T>
  OutputIterator thrust::exclusive_scan_by_key(InputIterator1, InputIterator1,
  ~InputIterator2, OutputIterator, T)
- template<typename InputIterator1, typename InputIterator2, typename_
  ~OutputIterator>
  OutputIterator thrust::exclusive_scan_by_key(InputIterator1, InputIterator1,
  ~InputIterator2, OutputIterator)

```

## Template Function `thrust::exclusive_scan_by_key(InputIterator1, InputIterator1, InputIterator2, OutputIterator, T, BinaryPredicate, AssociativeOperator)`

### Function Documentation

```
template<typename InputIterator1, typename InputIterator2, typename OutputIterator, typename T, typename Bin-
  aryPredicate AssociativeOperator>
OutputIterator thrust::exclusive_scan_by_key(InputIterator1 first1, InputIterator1 last1, Input-
  Iterator2 first2, OutputIterator result, T init, Bin-
  aryPredicate binary_pred, AssociativeOperator bi-
  nary_op)
```

`exclusive_scan_by_key` computes an exclusive key-value or ‘segmented’ prefix sum operation. The term ‘exclusive’ means that each result does not include the corresponding input operand in the partial sum. The term ‘segmented’ means that the partial sums are broken into distinct segments. In other words, within each segment a separate exclusive scan operation is computed. Refer to the code sample below for example usage.

This version of `exclusive_scan_by_key` uses the value `init` to initialize the exclusive scan operation.

This version of `exclusive_scan_by_key` uses the binary predicate `binary_pred` to compare adjacent keys. Specifically, consecutive iterators `i` and `i+1` in the range `[first1, last1)` belong to the same segment if `binary_pred(*i, *(i+1))` is true, and belong to different segments otherwise.

This version of `exclusive_scan_by_key` uses the associative operator `binary_op` to perform the prefix sum. When the input and output sequences are the same, the scan is performed in-place.

The following code snippet demonstrates how to use `exclusive_scan_by_key`

**Return** The end of the output sequence.

**Pre** `first1` may equal `result` but the range `[first1, last1)` and the range `[result, result + (last1 - first1))` shall not overlap otherwise.

**Pre** `first2` may equal `result` but the range `[first2, first2 + (last1 - first1))` and range `[result, result + (last1 - first1))` shall not overlap otherwise.

### Parameters

- `first1`: The beginning of the key sequence.
- `last1`: The end of the key sequence.
- `first2`: The beginning of the input value sequence.
- `result`: The beginning of the output value sequence.
- `init`: The initial of the exclusive sum value.
- `binary_pred`: The binary predicate used to determine equality of keys.
- `binary_op`: The associative operator used to ‘sum’ values.

### Template Parameters

- `InputIterator1`: is a model of `Input Iterator`
- `InputIterator2`: is a model of `Input Iterator` and `InputIterator2`'s `value_type` is convertible to `OutputIterator`'s `value_type`.
- `OutputIterator`: is a model of `Output Iterator`, and if `x` and `y` are objects of `OutputIterator`'s `value_type`, then `binary_op(x, y)` is defined.
- `T`: is convertible to `OutputIterator`'s `value_type`.
- `BinaryPredicate`: is a model of `Binary Predicate`.
- `AssociativeOperator`: is a model of `Binary Function` and `AssociativeOperator`'s `result_type` is convertible to `OutputIterator`'s `value_type`.

```
#include <thrust/scans.h>
#include <thrust/functional.h>

int keys[10] = {0, 0, 0, 1, 1, 2, 3, 3, 3, 3};
int vals[10] = {1, 1, 1, 1, 1, 1, 1, 1, 1, 1};

int init = 5;

thrust::equal_to<int> binary_pred;
thrust::plus<int> binary_op;

thrust::exclusive_scan_by_key(key, key + 10, vals, vals, init, binary_pred,
    ↵binary_op); // in-place scan

// vals is now {5, 6, 7, 5, 6, 5, 5, 6, 7, 8};
```

See `exclusive_scan`

See `inclusive_scan_by_key`

### Template Function `thrust::exp`

- Defined in file `thrust_complex.h`

#### Function Documentation

```
template<typename T> __host__ __device__ complex<T> thrust::exp(const complex < T > & z)
```

Returns the complex exponential of a complex number.

#### Parameters

- `z`: The complex argument.

### Template Function `thrust::fill`(`const thrust::detail::execution_policy_base<DerivedPolicy>&`, `ForwardIterator`, `ForwardIterator`, `const T&`)

- Defined in file `thrust_fill.h`

#### Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::fill`” with arguments (`const thrust::detail::execution_policy_base<DerivedPolicy>&`, `ForwardIterator`, `ForwardIterator`, `const T&`) in doxygen xml output for project “rocThrust” from directory: `./docBin/xml`. Potential matches:

```
- template<typename DerivedPolicy, typename ForwardIterator, typename T> __host__ __device__ void thrust::fill(const thrust::detail::execution_policy_base<DerivedPolicy> &, ForwardIterator, ForwardIterator, const T &)
- template<typename ForwardIterator, typename T> __host__ __device__ void thrust::fill(ForwardIterator, ForwardIterator, const T &)
```

### Template Function `thrust::fill`(`ForwardIterator`, `ForwardIterator`, `const T&`)

#### Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::fill`” with arguments (`ForwardIterator`, `ForwardIterator`, `const T&`) in doxygen xml output for project “rocThrust” from directory: `./docBin/xml`. Potential matches:

```
- template<typename DerivedPolicy, typename ForwardIterator, typename T> __host__ __device__ void thrust::fill(const thrust::detail::execution_policy_base<DerivedPolicy> &, ForwardIterator, ForwardIterator, const T &)
- template<typename ForwardIterator, typename T> __host__ __device__ void thrust::fill(ForwardIterator, ForwardIterator, const T &)
```

**Template Function `thrust::fill_n(const thrust::detail::execution_policy_base<DerivedPolicy>&, OutputIterator, Size, const T&)`**

- Defined in file\_thrust\_fill.h

**Function Documentation**

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::fill_n`” with arguments (`const thrust::detail::execution_policy_base<DerivedPolicy>&`, `OutputIterator`, `Size`, `const T&`) in doxygen xml output for project “rocThrust” from directory: ./docBin/xml. Potential matches:

```
- template<typename DerivedPolicy, typename OutputIterator, typename Size, typename _  
→T> __host__ __device__ OutputIterator thrust::fill_n(const _  
→thrust::detail::execution_policy_base< DerivedPolicy > &, OutputIterator, Size, _  
→const T &)  
- template<typename OutputIterator, typename Size, typename T> __host__ __device__ _  
→OutputIterator thrust::fill_n(OutputIterator, Size, const T &)
```

**Template Function `thrust::fill_n(OutputIterator, Size, const T&)`****Function Documentation**

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::fill_n`” with arguments (`OutputIterator`, `Size`, `const T&`) in doxygen xml output for project “rocThrust” from directory: ./docBin/xml. Potential matches:

```
- template<typename DerivedPolicy, typename OutputIterator, typename Size, typename _  
→T> __host__ __device__ OutputIterator thrust::fill_n(const _  
→thrust::detail::execution_policy_base< DerivedPolicy > &, OutputIterator, Size, _  
→const T &)  
- template<typename OutputIterator, typename Size, typename T> __host__ __device__ _  
→OutputIterator thrust::fill_n(OutputIterator, Size, const T &)
```

**Template Function `thrust::find(const thrust::detail::execution_policy_base<DerivedPolicy>&, InputIterator, InputIterator, const T&)`**

- Defined in file\_thrust\_find.h

**Function Documentation**

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::find`” with arguments (`const thrust::detail::execution_policy_base<DerivedPolicy>&`, `InputIterator`, `InputIterator`, `const T&`) in doxygen xml output for project “rocThrust” from directory: ./docBin/xml. Potential matches:

```
- template<typename DerivedPolicy, typename InputIterator, typename T> __host__ __  
→device__ InputIterator thrust::find(const thrust::detail::execution_policy_base<  
→DerivedPolicy > &, InputIterator, InputIterator, const T &)  
- template<typename InputIterator, typename T> _  
→InputIterator thrust::find(InputIterator, InputIterator, const T &)
```

## Template Function `thrust::find(InputIterator, InputIterator, const T&)`

### Function Documentation

```
template<typename InputIterator, typename T>
InputIterator thrust::find(InputIterator first, InputIterator last, const T &value)
    find returns the first iterator i in the range [first, last) such that *i == value or last if no such iterator exists.
```

```
#include <thrust/find.h>
#include <thrust/device_vector.h>
...
thrust::device_vector<int> input(4);

input[0] = 0;
input[1] = 5;
input[2] = 3;
input[3] = 7;

thrust::device_vector<int>::iterator iter;

iter = thrust::find(input.begin(), input.end(), 3); // returns input.first() + 2
iter = thrust::find(input.begin(), input.end(), 5); // returns input.first() + 1
iter = thrust::find(input.begin(), input.end(), 9); // returns input.end()
```

**Return** The first iterator *i* such that \**i* == value or last.

#### Parameters

- **first**: Beginning of the sequence to search.
- **last**: End of the sequence to search.
- **value**: The value to find.

#### Template Parameters

- **InputIterator**: is a model of `Input Iterator` and `InputIterator`'s `value_type` is equality comparable to type `T`.
- **T**: is a model of `EqualityComparable`.

**See** `find_if`

**See** `mismatch`

## Template Function `thrust::find_if(const thrust::detail::execution_policy_base<DerivedPolicy>&, InputIterator, InputIterator, Predicate)`

- Defined in file `thrust/find.h`

## Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “thrust::find\_if” with arguments (const thrust::detail::execution\_policy\_base<DerivedPolicy>&, InputIterator, InputIterator, Predicate) in doxygen xml output for project “rocThrust” from directory: ./docBin/xml. Potential matches:

```
- template<typename DerivedPolicy, typename InputIterator, typename Predicate> __  
  ↳ host __ device __ InputIterator thrust::find_if(const thrust::detail::execution_  
  ↳ policy_base< DerivedPolicy > &, InputIterator, InputIterator, Predicate)  
- template<typename InputIterator, typename Predicate>  
  InputIterator thrust::find_if(InputIterator, InputIterator, Predicate)
```

### Template Function thrust::find\_if(InputIterator, InputIterator, Predicate)

#### Function Documentation

template<typename **InputIterator**, typename **Predicate**>

*InputIterator* **thrust::find\_if**(*InputIterator first*, *InputIterator last*, *Predicate pred*)

*find\_if* returns the first iterator *i* in the range [*first*, *last*] such that *pred(\*i)* is true or *last* if no such iterator exists.

```
#include <thrust/find.h>  
#include <thrust/device_vector.h>  
  
struct greater_than_four  
{  
    __host__ __device__  
    bool operator() (int x)  
    {  
        return x > 4;  
    }  
};  
  
struct greater_than_ten  
{  
    __host__ __device__  
    bool operator() (int x)  
    {  
        return x > 10;  
    }  
};  
  
...  
thrust::device_vector<int> input(4);  
  
input[0] = 0;  
input[1] = 5;  
input[2] = 3;  
input[3] = 7;  
  
thrust::device_vector<int>::iterator iter;  
  
iter = thrust::find_if(input.begin(), input.end(), greater_than_four()); // ↳  
  ↳ returns input.first() + 1
```

(continues on next page)

(continued from previous page)

```
iter = thrust::find_if(input.begin(), input.end(), greater_than_ten()); //  
↳ returns input.end()
```

**Return** The first iterator *i* such that `pred(*i)` is true, or `last`.

### Parameters

- `first`: Beginning of the sequence to search.
- `last`: End of the sequence to search.
- `pred`: A predicate used to test range elements.

### Template Parameters

- `InputIterator`: is a model of `Input Iterator`.
- `Predicate`: is a model of `Predicate`.

**See** `find`

**See** `find_if_not`

**See** `mismatch`

## Template Function `thrust::find_if_not(const thrust::detail::execution_policy_base<DerivedPolicy>&, InputIterator, InputIterator, Predicate)`

- Defined in `file_thrust_find.h`

## Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::find_if_not`” with arguments (`const thrust::detail::execution_policy_base<DerivedPolicy>&`, `InputIterator`, `InputIterator`, `Predicate`) in doxygen xml output for project “rocThrust” from directory: `./docBin/xml`. Potential matches:

```
- template<typename DerivedPolicy, typename InputIterator, typename Predicate> __  
↳ host__ __device__ InputIterator thrust::find_if_not(const __  
↳ thrust::detail::execution_policy_base< DerivedPolicy > &, InputIterator, __  
↳ InputIterator, Predicate)  
- template<typename InputIterator, typename Predicate>  
InputIterator thrust::find_if_not(InputIterator, InputIterator, Predicate)
```

## Template Function `thrust::find_if_not(InputIterator, InputIterator, Predicate)`

### Function Documentation

```
template<typename InputIterator, typename Predicate>  
InputIterator thrust::find_if_not(InputIterator first, InputIterator last, Predicate pred)  
find_if_not returns the first iterator i in the range [first, last) such that pred(*i) is false or  
last if no such iterator exists.
```

```
#include <thrust/find.h>
#include <thrust/device_vector.h>

struct greater_than_four
{
    __host__ __device__
    bool operator() (int x)
    {
        return x > 4;
    }
};

struct greater_than_ten
{
    __host__ __device__
    bool operator() (int x)
    {
        return x > 10;
    }
};

...
thrust::device_vector<int> input(4);

input[0] = 0;
input[1] = 5;
input[2] = 3;
input[3] = 7;

thrust::device_vector<int>::iterator iter;

iter = thrust::find_if_not(input.begin(), input.end(), greater_than_four()); //_
// returns input.first()

iter = thrust::find_if_not(input.begin(), input.end(), greater_than_ten()); //_
// returns input.first()
```

**Return** The first iterator *i* such that *pred(\*i)* is false, or *last*.

#### Parameters

- *first*: Beginning of the sequence to search.
- *last*: End of the sequence to search.
- *pred*: A predicate used to test range elements.

#### Template Parameters

- *InputIterator*: is a model of *Input Iterator*.
- *Predicate*: is a model of *Predicate*.

**See** [find](#)

**See** [find\\_if](#)

**See** [mismatch](#)

## Template Function `thrust::for_each(const thrust::detail::execution_policy_base<DerivedPolicy>&, InputIterator, InputIterator, UnaryFunction)`

- Defined in file `thrust_for_each.h`

### Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::for_each`” with arguments (`const thrust::detail::execution_policy_base<DerivedPolicy>&`, `InputIterator`, `InputIterator`, `UnaryFunction`) in doxygen xml output for project “rocThrust” from directory: `./docBin/xml`. Potential matches:

```
- template<typename DerivedPolicy, typename InputIterator, typename UnaryFunction> __
→host__ __device__ InputIterator thrust::for_each(const thrust::detail::execution_
→policy_base< DerivedPolicy > &, InputIterator, InputIterator, UnaryFunction)
- template<typename InputIterator, typename UnaryFunction>
  InputIterator thrust::for_each(InputIterator, InputIterator, UnaryFunction)
```

## Template Function `thrust::for_each(InputIterator, InputIterator, UnaryFunction)`

### Function Documentation

`template<typename InputIterator, typename UnaryFunction>`

`InputIterator thrust::for_each(InputIterator first, InputIterator last, UnaryFunction f)`

`for_each` applies the function object `f` to each element in the range `[first, last]`; `f`'s return value, if any, is ignored. Unlike the C++ Standard Template Library function `std::for_each`, this version offers no guarantee on order of execution. For this reason, this version of `for_each` does not return a copy of the function object.

The following code snippet demonstrates how to use `for_each` to print the elements of a `device_vector`.

**Return** last

**Parameters**

- `first`: The beginning of the sequence.
- `last`: The end of the sequence.
- `f`: The function object to apply to the range `[first, last]`.

**Template Parameters**

- `InputIterator`: is a model of `Input Iterator`, and `InputIterator`'s `value_type` is convertible to `UnaryFunction`'s `argument_type`.
- `UnaryFunction`: is a model of `Unary Function`, and `UnaryFunction` does not apply any non-constant operation through its argument.

```
#include <thrust/for_each.h>
#include <thrust/device_vector.h>
#include <stdio.h>

struct printf_functor
{
    __host__ __device__
```

(continues on next page)

(continued from previous page)

```

void operator() (int x)
{
    // note that using printf in a __device__ function requires
    // code compiled for a GPU with compute capability 2.0 or
    // higher (nvcc --arch=sm_20)
    printf("%d\n", x);
}
};

...
thrust::device_vector<int> d_vec(3);
d_vec[0] = 0; d_vec[1] = 1; d_vec[2] = 2;

thrust::for_each(d_vec.begin(), d_vec.end(), printf_functor());

// 0 1 2 is printed to standard output in some unspecified order

```

**See** `for_each_n`**See** [http://www.sgi.com/tech/stl/for\\_each.html](http://www.sgi.com/tech/stl/for_each.html)**Template Function `thrust::for_each_n(const thrust::detail::execution_policy_base<DerivedPolicy>&, InputIterator, Size, UnaryFunction)`**

- Defined in file `thrust_for_each.h`

**Function Documentation**

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::for_each_n`” with arguments `(const thrust::detail::execution_policy_base<DerivedPolicy>&, InputIterator, Size, UnaryFunction)` in doxygen xml output for project “rocThrust” from directory: ./docBin/xml. Potential matches:

```

- template<typename DerivedPolicy, typename InputIterator, typename Size, typename _  

  ↳UnaryFunction> __host__ __device__ InputIterator thrust::for_each_n(const  

  ↳thrust::detail::execution_policy_base< DerivedPolicy > &, InputIterator, Size, _  

  ↳UnaryFunction)
- template<typename InputIterator, typename Size, typename UnaryFunction>  

  InputIterator thrust::for_each_n(InputIterator, Size, UnaryFunction)

```

**Template Function `thrust::for_each_n(InputIterator, Size, UnaryFunction)`****Function Documentation**

```

template<typename InputIterator, typename Size, typename UnaryFunction>
InputIterator thrust::for_each_n(InputIterator first, Size n, UnaryFunction f)

```

`for_each_n` applies the function object `f` to each element in the range `[first, first + n]`; `f`'s return value, if any, is ignored. Unlike the C++ Standard Template Library function `std::for_each`, this version offers no guarantee on order of execution.

The following code snippet demonstrates how to use `for_each_n` to print the elements of a `device_vector`.

**Return** first + n

#### Parameters

- first: The beginning of the sequence.
- n: The size of the input sequence.
- f: The function object to apply to the range [first, first + n).

#### Template Parameters

- InputIterator: is a model of [Input Iterator](#), and InputIterator's value\_type is convertible to UnaryFunction's argument\_type.
- Size: is an integral type.
- UnaryFunction: is a model of [Unary Function](#), and UnaryFunction does not apply any non-constant operation through its argument.

```
#include <thrust/for_each.h>
#include <thrust/device_vector.h>
#include <stdio.h>

struct printf_functor
{
    __host__ __device__
    void operator() (int x)
    {
        // note that using printf in a __device__ function requires
        // code compiled for a GPU with compute capability 2.0 or
        // higher (nvcc --arch=sm_20)
        printf("%d\n", x);
    }
};

...
thrust::device_vector<int> d_vec(3);
d_vec[0] = 0; d_vec[1] = 1; d_vec[2] = 2;

thrust::for_each_n(d_vec.begin(), d_vec.size(), printf_functor());
// 0 1 2 is printed to standard output in some unspecified order
```

**See** [for\\_each](#)

**See** [http://www.sgi.com/tech/stl/for\\_each.html](http://www.sgi.com/tech/stl/for_each.html)

### Template Function thrust::free

- Defined in file\_thrust\_memory.h

#### Function Documentation

```
template<typename DerivedPolicy, typename Pointer> __host__ __device__ void thrust::free(const
```

free deallocates the storage previously allocated by `thrust::malloc`.

The following code snippet demonstrates how to use `free` to deallocate a range of memory previously allocated with `thrust::malloc`.

**Pre** `ptr` shall have been returned by a previous call to `thrust::malloc(system, n)` or `thrust::malloc<T>(system, n)` for some type `T`.

### Parameters

- `system`: The Thrust system with which the storage is associated.
- `ptr`: A pointer previously returned by `thrust::malloc`. If `ptr` is null, `free` does nothing.

### Template Parameters

- `DerivedPolicy`: The name of the derived execution policy.

```
#include <thrust/memory.h>
...
// allocate storage for 100 ints with thrust::malloc
const int N = 100;
thrust::device_system_tag device_sys;
thrust::pointer<int,thrust::device_system_tag> ptr = thrust::malloc<int>(device_
    sys, N);

// manipulate memory
...

// deallocate ptr with thrust::free
thrust::free(device_sys, ptr);
```

## Template Function `thrust::gather(const thrust::detail::execution_policy_base<DerivedPolicy>&, InputIterator, InputIterator, RandomAccessIterator, OutputIterator)`

- Defined in file `thrust_gather.h`

### Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::gather`” with arguments (`const thrust::detail::execution_policy_base<DerivedPolicy>&`, `InputIterator`, `InputIterator`, `RandomAccessIterator`, `OutputIterator`) in doxygen xml output for project “rocThrust” from directory: `./docBin/xml`. Potential matches:

```
- template<typename DerivedPolicy, typename InputIterator, typename_
    ↪RandomAccessIterator, typename OutputIterator> __host__ __device__ OutputIterator_
    ↪thrust::gather(const thrust::detail::execution_policy_base< DerivedPolicy > &,_
    ↪InputIterator, InputIterator, RandomAccessIterator, OutputIterator)
- template<typename InputIterator, typename RandomAccessIterator, typename_
    ↪OutputIterator>
    OutputIterator thrust::gather(InputIterator, InputIterator, RandomAccessIterator,_
    ↪OutputIterator)
```

## Template Function `thrust::gather(InputIterator, InputIterator, RandomAccessIterator, OutputIterator)`

### Function Documentation

```
template<typename InputIterator, typename RandomAccessIterator, typename OutputIterator>
```

*OutputIterator* `thrust::gather`(*InputIterator* `map_first`, *InputIterator* `map_last`, *RandomAccessIterator* `input_first`, *OutputIterator* `result`)

`gather` copies elements from a source array into a destination range according to a map. For each input iterator `i` in the range `[map_first, map_last)`, the value `input_first[*i]` is assigned to `*(result + (i - map_first))`. *RandomAccessIterator* must permit random access.

The following code snippet demonstrates how to use `gather` to reorder a range.

**Pre** The range `[map_first, map_last)` shall not overlap the range `[result, result + (map_last - map_first))`.

**Remark** `gather` is the inverse of `thrust::scatter`.

### Parameters

- `map_first`: Beginning of the range of gather locations.
- `map_last`: End of the range of gather locations.
- `input_first`: Beginning of the source range.
- `result`: Beginning of the destination range.

### Template Parameters

- `InputIterator`: must be a model of `Input Iterator` and `InputIterator`'s `value_type` must be convertible to `RandomAccessIterator`'s `difference_type`.
- `RandomAccessIterator`: must be a model of `Random Access Iterator` and `RandomAccessIterator`'s `value_type` must be convertible to `OutputIterator`'s `value_type`.
- `OutputIterator`: must be a model of `Output Iterator`.

```
#include <thrust/gather.h>
#include <thrust/device_vector.h>
...
// mark even indices with a 1; odd indices with a 0
int values[10] = {1, 0, 1, 0, 1, 0, 1, 0, 1, 0};
thrust::device_vector<int> d_values(values, values + 10);

// gather all even indices into the first half of the range
// and odd indices to the last half of the range
int map[10] = {0, 2, 4, 6, 8, 1, 3, 5, 7, 9};
thrust::device_vector<int> d_map(map, map + 10);

thrust::device_vector<int> d_output(10);
thrust::gather(d_map.begin(), d_map.end(),
              d_values.begin(),
              d_output.begin());
// d_output is now {1, 1, 1, 1, 1, 0, 0, 0, 0, 0}
```

**Template Function** `thrust::gather_if(const thrust::detail::execution_policy_base<DerivedPolicy>&, InputIterator1, InputIterator1, InputIterator2, RandomAccessIterator, OutputIterator)`

- Defined in file `thrust_gather.h`

## Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “thrust::gather\_if” with arguments (const thrust::detail::execution\_policy\_base<DerivedPolicy>&, InputIterator1, InputIterator1, InputIterator2, RandomAccessIterator, OutputIterator) in doxygen xml output for project “rocThrust” from directory: ./docBin/xml. Potential matches:

```
- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2,
→ typename RandomAccessIterator, typename OutputIterator, typename Predicate> __
→ host__ __device__ OutputIterator thrust::gather_if(const __
→ thrust::detail::execution_policy_base< DerivedPolicy > &, InputIterator1, __
→ InputIterator1, InputIterator2, RandomAccessIterator, OutputIterator, Predicate)
- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2,
→ typename RandomAccessIterator, typename OutputIterator> __host__ __device__ __
→ OutputIterator thrust::gather_if(const thrust::detail::execution_policy_base< __
→ DerivedPolicy > &, InputIterator1, InputIterator1, InputIterator2, __
→ RandomAccessIterator, OutputIterator)
- template<typename InputIterator1, typename InputIterator2, typename __
→ RandomAccessIterator, typename OutputIterator, typename Predicate>
→ OutputIterator thrust::gather_if(InputIterator1, InputIterator1, InputIterator2, __
→ RandomAccessIterator, OutputIterator, Predicate)
- template<typename InputIterator1, typename InputIterator2, typename __
→ RandomAccessIterator, typename OutputIterator>
→ OutputIterator thrust::gather_if(InputIterator1, InputIterator1, InputIterator2, __
→ RandomAccessIterator, OutputIterator)
```

## Template Function thrust::gather\_if(InputIterator1, InputIterator1, InputIterator2, RandomAccessIterator, OutputIterator)

### Function Documentation

```
template<typename InputIterator1, typename InputIterator2, typename RandomAccessIterator, typename OutputIterator> thrust::gather_if(InputIterator1 map_first, InputIterator1 map_last, InputIterator2 stencil, RandomAccessIterator input_first, OutputIterator result)
```

gather\_if conditionally copies elements from a source array into a destination range according to a map. For each input iterator  $i$  in the range  $[map\_first, map\_last]$ , such that the value of  $*(stencil + (i - map\_first))$  is true, the value  $input\_first[*i]$  is assigned to  $*(result + (i - map\_first))$ . RandomAccessIterator must permit random access.

The following code snippet demonstrates how to use gather\_if to gather selected values from an input range.

**Pre** The range  $[map\_first, map\_last]$  shall not overlap the range  $[result, result + (map\_last - map\_first)]$ .

**Pre** The range  $[stencil, stencil + (map\_last - map\_first)]$  shall not overlap the range  $[result, result + (map\_last - map\_first)]$ .

**Remark** gather\_if is the inverse of scatter\_if.

#### Parameters

- `map_first`: Beginning of the range of gather locations.
- `map_last`: End of the range of gather locations.
- `stencil`: Beginning of the range of predicate values.

- `input_first`: Beginning of the source range.
- `result`: Beginning of the destination range.

### Template Parameters

- `InputIterator1`: must be a model of `Input Iterator` and `InputIterator1`'s `value_type` must be convertible to `RandomAccessIterator`'s `difference_type`.
- `InputIterator2`: must be a model of `Input Iterator` and `InputIterator2`'s `value_type` must be convertible to `bool`.
- `RandomAccessIterator`: must be a model of `Random Access iterator` and `RandomAccessIterator`'s `value_type` must be convertible to `OutputIterator`'s `value_type`.
- `OutputIterator`: must be a model of `Output Iterator`.

```
#include <thrust/gather.h>
#include <thrust/device_vector.h>
...
int values[10] = {0, 1, 2, 3, 4, 5, 6, 7, 8, 9};
thrust::device_vector<int> d_values(values, values + 10);

// select elements at even-indexed locations
int stencil[10] = {1, 0, 1, 0, 1, 0, 1, 0, 1, 0};
thrust::device_vector<int> d_stencil(stencil, stencil + 10);

// map all even indices into the first half of the range
// and odd indices to the last half of the range
int map[10] = {0, 2, 4, 6, 8, 1, 3, 5, 7, 9};
thrust::device_vector<int> d_map(map, map + 10);

thrust::device_vector<int> d_output(10, 7);
thrust::gather_if(d_map.begin(), d_map.end(),
                  d_stencil.begin(),
                  d_values.begin(),
                  d_output.begin());
// d_output is now {0, 7, 4, 7, 8, 7, 3, 7, 7, 7}
```

**Template Function `thrust::gather_if(const thrust::detail::execution_policy_base<DerivedPolicy>&, InputIterator1, InputIterator1, InputIterator2, RandomAccessIterator, OutputIterator, Predicate)`**

### Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::gather_if`” with arguments (`const thrust::detail::execution_policy_base<DerivedPolicy>&`, `InputIterator1`, `InputIterator1`, `InputIterator2`, `RandomAccessIterator`, `OutputIterator`, `Predicate`) in doxygen xml output for project “rocThrust” from directory: `./docBin/xml`. Potential matches:

```
- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2,
         ~ typename RandomAccessIterator, typename OutputIterator, typename Predicate> __
         host__ __device__ OutputIterator thrust::gather_if(const __
         ~thrust::detail::execution_policy_base< DerivedPolicy > &, InputIterator1, __
         ~InputIterator1, InputIterator2, RandomAccessIterator, OutputIterator, Predicate)
- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2,
         ~ typename RandomAccessIterator, typename OutputIterator> __host__ __device__ __
         ~OutputIterator thrust::gather_if(const thrust::detail::execution_policy_base< __
         ~DerivedPolicy > &, InputIterator1, InputIterator1, InputIterator2, __
         ~RandomAccessIterator, OutputIterator)
- template<typename InputIterator1, typename InputIterator2, typename __
         ~RandomAccessIterator, typename OutputIterator, typename Predicate>
         OutputIterator thrust::gather_if(InputIterator1, InputIterator1, InputIterator2, __
         ~RandomAccessIterator, OutputIterator, Predicate)
- template<typename InputIterator1, typename InputIterator2, typename __
         ~RandomAccessIterator, typename OutputIterator>
         OutputIterator thrust::gather_if(InputIterator1, InputIterator1, InputIterator2, __
         ~RandomAccessIterator, OutputIterator)
```

## Template Function `thrust::gather_if(InputIterator1, InputIterator1, InputIterator2, RandomAccessIterator, OutputIterator, Predicate)`

### Function Documentation

```
template<typename InputIterator1, typename InputIterator2, typename RandomAccessIterator, typename Output
         OutputIterator> thrust::gather_if(InputIterator1 map_first, InputIterator1 map_last, InputIterator2
                                         stencil, RandomAccessIterator input_first, OutputIterator result,
                                         Predicate pred)
```

`gather_if` conditionally copies elements from a source array into a destination range according to a map. For each input iterator  $i$  in the range  $[map\_first, map\_last]$  such that the value of  $pred(* (stencil + (i - map\_first)))$  is true, the value  $input\_first[*i]$  is assigned to  $* (result + (i - map\_first))$ . `RandomAccessIterator` must permit random access.

The following code snippet demonstrates how to use `gather_if` to gather selected values from an input range based on an arbitrary selection function.

**Pre** The range  $[map\_first, map\_last]$  shall not overlap the range  $[result, result + (map\_last - map\_first)]$ .

**Pre** The range  $[stencil, stencil + (map\_last - map\_first)]$  shall not overlap the range  $[result, result + (map\_last - map\_first)]$ .

**Remark** `gather_if` is the inverse of `scatter_if`.

### Parameters

- `map_first`: Beginning of the range of gather locations.
- `map_last`: End of the range of gather locations.
- `stencil`: Beginning of the range of predicate values.
- `input_first`: Beginning of the source range.
- `result`: Beginning of the destination range.
- `pred`: Predicate to apply to the stencil values.

## Template Parameters

- `InputIterator1`: must be a model of `Input Iterator` and `InputIterator1`'s `value_type` must be convertible to `RandomAccessIterator`'s `difference_type`.
- `InputIterator2`: must be a model of `Input Iterator` and `InputIterator2`'s `value_type` must be convertible to `Predicate`'s `argument_type`.
- `RandomAccessIterator`: must be a model of `Random Access iterator` and `RandomAccessIterator`'s `value_type` must be convertible to `OutputIterator`'s `value_type`.
- `OutputIterator`: must be a model of `Output Iterator`.
- `Predicate`: must be a model of `Predicate`.

```
#include <thrust/gather.h>
#include <thrust/device_vector.h>

struct is_even
{
    __host__ __device__
    bool operator() (const int x)
    {
        return (x % 2) == 0;
    }
};

int values[10] = {0, 1, 2, 3, 4, 5, 6, 7, 8, 9};
thrust::device_vector<int> d_values(values, values + 10);

// we will select an element when our stencil is even
int stencil[10] = {0, 3, 4, 1, 4, 1, 2, 7, 8, 9};
thrust::device_vector<int> d_stencil(stencil, stencil + 10);

// map all even indices into the first half of the range
// and odd indices to the last half of the range
int map[10] = {0, 2, 4, 6, 8, 1, 3, 5, 7, 9};
thrust::device_vector<int> d_map(map, map + 10);

thrust::device_vector<int> d_output(10, 7);
thrust::gather_if(d_map.begin(), d_map.end(),
                  d_stencil.begin(),
                  d_values.begin(),
                  d_output.begin(),
                  is_even());
// d_output is now {0, 7, 4, 7, 8, 7, 3, 7, 7, 7}
```

## Template Function `thrust::gather_if(const thrust::detail::execution_policy_base<DerivedPolicy>&, ForwardIterator, ForwardIterator, Generator)`

- Defined in file `thrust/gather.h`

## Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “thrust::generate” with arguments (const thrust::detail::execution\_policy\_base<DerivedPolicy>&, ForwardIterator, ForwardIterator, Generator) in doxygen xml output for project “rocThrust” from directory: ./docBin/xml. Potential matches:

```
- template<typename DerivedPolicy, typename ForwardIterator, typename Generator>__  
  ↪host__ __device__ void thrust::generate(const thrust::detail::execution_policy_<  
  ↪base< DerivedPolicy > &, ForwardIterator, ForwardIterator, Generator)  
- template<typename ForwardIterator, typename Generator>  
  void thrust::generate(ForwardIterator, ForwardIterator, Generator)
```

## Template Function thrust::generate(ForwardIterator, ForwardIterator, Generator)

### Function Documentation

```
template<typename ForwardIterator, typename Generator>  
void thrust::generate(ForwardIterator first, ForwardIterator last, Generator gen)
```

generate assigns the result of invoking gen, a function object that takes no arguments, to each element in the range [first, last).

The following code snippet demonstrates how to fill a `host_vector` with random numbers, using the standard C library function `rand`.

#### Parameters

- `first`: The first element in the range of interest.
- `last`: The last element in the range of interest.
- `gen`: A function argument, taking no parameters, used to generate values to assign to elements in the range [first, last).

#### Template Parameters

- `ForwardIterator`: is a model of `Forward Iterator`, and `ForwardIterator` is mutable.
- `Generator`: is a model of `Generator`, and `Generator`'s `result_type` is convertible to `ForwardIterator`'s `value_type`.

```
#include <thrust/generate.h>  
#include <thrust/host_vector.h>  
#include <thrust/execution_policy.h>  
#include <cstdlib>  
...  
thrust::host_vector<int> v(10);  
srand(13);  
thrust::generate(v.begin(), v.end(), rand);  
  
// the elements of v are now pseudo-random numbers
```

See `generate_n`

See <http://www.sgi.com/tech/stl/generate.html>

## Template Function `thrust::generate_n(const thrust::detail::execution_policy_base<DerivedPolicy>&, OutputIterator, Size, Generator)`

- Defined in file `thrust_generate.h`

### Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::generate_n`” with arguments (`const thrust::detail::execution_policy_base<DerivedPolicy>&`, `OutputIterator`, `Size`, `Generator`) in doxygen xml output for project “rocThrust” from directory: `./docBin/xml`. Potential matches:

```
- template<typename DerivedPolicy, typename OutputIterator, typename Size, typename _Generator> __host__ __device__ OutputIterator thrust::generate_n(const __host__ __device__ thrust::detail::execution_policy_base< DerivedPolicy > &, OutputIterator, Size, _Generator)
- template<typename OutputIterator, typename Size, typename Generator> OutputIterator thrust::generate_n(OutputIterator, Size, Generator)
```

## Template Function `thrust::generate_n(OutputIterator, Size, Generator)`

### Function Documentation

```
template<typename OutputIterator, typename Size, typename Generator>
OutputIterator thrust::generate_n(OutputIterator first, Size n, Generator gen)
```

`generate_n` assigns the result of invoking `gen`, a function object that takes no arguments, to each element in the range `[first, first + n]`. The return value is `first + n`.

The following code snippet demonstrates how to fill a `host_vector` with random numbers, using the standard C library function `rand`.

#### Parameters

- `first`: The first element in the range of interest.
- `n`: The size of the range of interest.
- `gen`: A function argument, taking no parameters, used to generate values to assign to elements in the range `[first, first + n]`.

#### Template Parameters

- `OutputIterator`: is a model of `Output Iterator`.
- `Size`: is an integral type (either signed or unsigned).
- `Generator`: is a model of `Generator`, and `Generator`'s `result_type` is convertible to a type in `OutputIterator`'s set of `value_types`.

```
#include <thrust/generate.h>
#include <thrust/host_vector.h>
#include <stdlib.h>
...
thrust::host_vector<int> v(10);
srand(13);
thrust::generate_n(v.begin(), 10, rand);
```

(continues on next page)

(continued from previous page)

```
// the elements of v are now pseudo-random numbers
```

See [generate](#)

See <http://www.sgi.com/tech/stl/generate.html>

## Template Function `thrust::get(detail::cons<HT, TT>&)`

### Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “thrust::get” with arguments (detail::cons<HT, TT>&) in doxygen xml output for project “rocThrust” from directory: ./docBin/xml. Potential matches:

```
- template<int N, class HT, class TT>__host__ __device__ access_traits< typename
  tuple_element<N, detail::cons<HT, TT> >::type >::const_type thrust::get(const_
  detail::cons< HT, TT > &)
- template<int N, class HT, class TT>__host__ __device__ access_traits< typename
  tuple_element<N, detail::cons<HT, TT> >::type >::non_const_type_
  thrust::get(detail::cons< HT, TT > &)
```

## Template Function `thrust::get(const detail::cons<HT, TT>&)`

### Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “thrust::get” with arguments (const detail::cons<HT, TT>&) in doxygen xml output for project “rocThrust” from directory: ./docBin/xml. Potential matches:

```
- template<int N, class HT, class TT>__host__ __device__ access_traits< typename
  tuple_element<N, detail::cons<HT, TT> >::type >::const_type thrust::get(const_
  detail::cons< HT, TT > &)
- template<int N, class HT, class TT>__host__ __device__ access_traits< typename
  tuple_element<N, detail::cons<HT, TT> >::type >::non_const_type_
  thrust::get(detail::cons< HT, TT > &)
```

## Template Function `thrust::get_temporary_buffer`

- Defined in `file_thrust_memory.h`

### Function Documentation

```
template<typename T, typename DerivedPolicy>__host__ __device__ thrust::pair<thrust::pointer
  get_temporary_buffer returns a pointer to storage associated with a given Thrust system sufficient to
  store up to n objects of type T. If not enough storage is available to accomodate n objects, an implementation
  may return a smaller buffer. The number of objects the returned buffer can accomodate is also returned.
```

Thrust uses `get_temporary_buffer` internally when allocating temporary storage required by algorithm implementations.

The storage allocated with `get_temporary_buffer` must be returned to the system with `return_temporary_buffer`.

The following code snippet demonstrates how to use `get_temporary_buffer` to allocate a range of memory to accomodate integers associated with Thrust's device system.

**Return** A pair `p` such that `p.first` is a pointer to the allocated storage and `p.second` is the number of contiguous objects of type `T` that the storage can accomodate. If no storage can be allocated, `p.first` if no storage can be obtained. The storage must be returned to the system using `return_temporary_buffer`.

**Pre** `DerivedPolicy` must be publically derived from `thrust::execution_policy<DerivedPolicy>`.

### Parameters

- `system`: The Thrust system with which to associate the storage.
- `n`: The requested number of objects of type `T` the storage should accomodate.

### Template Parameters

- `DerivedPolicy`: The name of the derived execution policy.

```
#include <thrust/memory.h>
...
// allocate storage for 100 ints with thrust::get_temporary_buffer
const int N = 100;

typedef thrust::pair<
    thrust::pointer<int,thrust::device_system_tag>,
    std::ptrdiff_t
> ptr_and_size_t;

thrust::device_system_tag device_sys;
ptr_and_size_t ptr_and_size = thrust::get_temporary_buffer<int>(device_sys, N);

// manipulate up to 100 ints
for(int i = 0; i < ptr_and_size.second; ++i)
{
    *ptr_and_size.first = i;
}

// deallocate storage with thrust::return_temporary_buffer
thrust::return_temporary_buffer(device_sys, ptr_and_size.first);
```

**See** `malloc`

**See** `return_temporary_buffer`

**Template Function** `thrust::inclusive_scan(const thrust::detail::execution_policy_base<DerivedPolicy>&, InputIterator, InputIterator, OutputIterator)`

- Defined in file `thrust_scan.h`

## Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “thrust::inclusive\_scan” with arguments (const thrust::detail::execution\_policy\_base<DerivedPolicy>&, InputIterator, InputIterator, OutputIterator) in doxygen xml output for project “rocThrust” from directory: ./docBin/xml. Potential matches:

```
- template<typename DerivedPolicy, typename InputIterator, typename OutputIterator,
          typename AssociativeOperator> __host__ __device__ OutputIterator thrust::inclusive_
          scan(const thrust::detail::execution_policy_base< DerivedPolicy > &,_
          InputIterator, InputIterator, OutputIterator, AssociativeOperator)
- template<typename DerivedPolicy, typename InputIterator, typename OutputIterator>_
          __host__ __device__ OutputIterator thrust::inclusive_scan(const_
          thrust::detail::execution_policy_base< DerivedPolicy > &, InputIterator,_
          InputIterator, OutputIterator)
- template<typename InputIterator, typename OutputIterator, typename_
          AssociativeOperator>
          OutputIterator thrust::inclusive_scan(InputIterator, InputIterator,_
          OutputIterator, AssociativeOperator)
- template<typename InputIterator, typename OutputIterator>
          OutputIterator thrust::inclusive_scan(InputIterator, InputIterator,_
          OutputIterator)
```

## Template Function `thrust::inclusive_scan(InputIterator, InputIterator, OutputIterator)`

### Function Documentation

```
template<typename InputIterator, typename OutputIterator>
OutputIterator thrust::inclusive_scan (InputIterator first, InputIterator last, OutputIterator result)
inclusive_scan computes an inclusive prefix sum operation. The term ‘inclusive’ means that each result includes the corresponding input operand in the partial sum. More precisely, *first is assigned to *result and the sum of *first and *(first + 1) is assigned to *(result + 1), and so on. This version of inclusive_scan assumes plus as the associative operator. When the input and output sequences are the same, the scan is performed in-place.
```

inclusive\_scan is similar to std::partial\_sum in the STL. The primary difference between the two functions is that std::partial\_sum guarantees a serial summation order, while inclusive\_scan requires associativity of the binary operation to parallelize the prefix sum.

The following code snippet demonstrates how to use inclusive\_scan

**Return** The end of the output sequence.

**Pre** first may equal result but the range [first, last) and the range [result, result + (last - first)) shall not overlap otherwise.

### Parameters

- `first`: The beginning of the input sequence.
- `last`: The end of the input sequence.
- `result`: The beginning of the output sequence.

### Template Parameters

- `InputIterator`: is a model of `Input Iterator` and `InputIterator`'s `value_type` is convertible to `OutputIterator`'s `value_type`.

- `OutputIterator`: is a model of `Output Iterator`, and if `x` and `y` are objects of `OutputIterator`'s `value_type`, then `x + y` is defined. If `T` is `OutputIterator`'s `value_type`, then `T(0)` is defined.

```
#include <thrust/scan.h>

int data[6] = {1, 0, 2, 2, 1, 3};

thrust::inclusive_scan(data, data + 6, data); // in-place scan

// data is now {1, 1, 3, 5, 6, 9}
```

See [http://www.sgi.com/tech/stl/partial\\_sum.html](http://www.sgi.com/tech/stl/partial_sum.html)

**Template Function `thrust::inclusive_scan(const thrust::detail::execution_policy_base<DerivedPolicy>&, InputIterator, InputIterator, OutputIterator, AssociativeOperator)`**

### Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::inclusive_scan`” with arguments (`const thrust::detail::execution_policy_base<DerivedPolicy>&`, `InputIterator`, `InputIterator`, `OutputIterator`, `AssociativeOperator`) in doxygen xml output for project “rocThrust” from directory: ./docBin/xml. Potential matches:

```
- template<typename DerivedPolicy, typename InputIterator, typename OutputIterator,
          ~typename AssociativeOperator> __host__ __device__ OutputIterator thrust::inclusive_
          ~scan(const thrust::detail::execution_policy_base< DerivedPolicy > &,
          ~InputIterator, InputIterator, OutputIterator, AssociativeOperator)
- template<typename DerivedPolicy, typename InputIterator, typename OutputIterator>
          ~host__ __device__ OutputIterator thrust::inclusive_scan(const,
          ~thrust::detail::execution_policy_base< DerivedPolicy > &, InputIterator,
          ~InputIterator, OutputIterator)
- template<typename InputIterator, typename OutputIterator, typename
          ~AssociativeOperator>
          OutputIterator thrust::inclusive_scan(InputIterator, InputIterator,
          ~OutputIterator, AssociativeOperator)
- template<typename InputIterator, typename OutputIterator>
          OutputIterator thrust::inclusive_scan(InputIterator, InputIterator,
          ~OutputIterator)
```

**Template Function `thrust::inclusive_scan(InputIterator, InputIterator, OutputIterator, AssociativeOperator)`**

### Function Documentation

```
template<typename InputIterator, typename OutputIterator, typename AssociativeOperator>
OutputIterator thrust::inclusive_scan(InputIterator first, InputIterator last, OutputIterator result,
                                      AssociativeOperator binary_op)
```

`inclusive_scan` computes an inclusive prefix sum operation. The term ‘inclusive’ means that each result includes the corresponding input operand in the partial sum. When the input and output sequences are the same, the scan is performed in-place.

`inclusive_scan` is similar to `std::partial_sum` in the STL. The primary difference between the two functions is that `std::partial_sum` guarantees a serial summation order, while `inclusive_scan` requires associativity of the binary operation to parallelize the prefix sum.

The following code snippet demonstrates how to use `inclusive_scan`.

**Return** The end of the output sequence.

**Pre** `first` may equal `result` but the range `[first, last)` and the range `[result, result + (last - first))` shall not overlap otherwise.

### Parameters

- `first`: The beginning of the input sequence.
- `last`: The end of the input sequence.
- `result`: The beginning of the output sequence.
- `binary_op`: The associative operator used to ‘sum’ values.

### Template Parameters

- `InputIterator`: is a model of `Input Iterator` and `InputIterator`'s `value_type` is convertible to `OutputIterator`'s `value_type`.
- `OutputIterator`: is a model of `Output Iterator` and `OutputIterator`'s `value_type` is convertible to both `AssociativeOperator`'s `first_argument_type` and `second_argument_type`.
- `AssociativeOperator`: is a model of `Binary Function` and `AssociativeOperator`'s `result_type` is convertible to `OutputIterator`'s `value_type`.

```
int data[10] = {-5, 0, 2, -3, 2, 4, 0, -1, 2, 8};

thrust::maximum<int> binary_op;

thrust::inclusive_scan(data, data + 10, data, binary_op); // in-place scan

// data is now {-5, 0, 2, 2, 2, 4, 4, 4, 4, 8}
```

See [http://www.sgi.com/tech/stl/partial\\_sum.html](http://www.sgi.com/tech/stl/partial_sum.html)

**Template Function `thrust::inclusive_scan_by_key`(`const thrust::detail::execution_policy_base<DerivedPolicy>&, InputIterator1, InputIterator1, InputIterator2, OutputIterator)`**

- Defined in `file_thrust_scan.h`

### Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::inclusive_scan_by_key`” with arguments (`const thrust::detail::execution_policy_base<DerivedPolicy>&`, `InputIterator1`, `InputIterator1`, `InputIterator2`, `OutputIterator`) in doxygen xml output for project “rocThrust” from directory: `./docBin/xml`. Potential matches:

```

- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2,
  ~ typename OutputIterator, typename BinaryPredicate, typename AssociativeOperator>_
  ~_host__ __device__ OutputIterator thrust::inclusive_scan_by_key(const_
  ~thrust::detail::execution_policy_base< DerivedPolicy > &, InputIterator1,_
  ~InputIterator1, InputIterator2, OutputIterator, BinaryPredicate,_
  ~AssociativeOperator)
- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2,
  ~ typename OutputIterator, typename BinaryPredicate> __host__ __device__
  ~OutputIterator thrust::inclusive_scan_by_key(const thrust::detail::execution_
  ~policy_base< DerivedPolicy > &, InputIterator1, InputIterator1, InputIterator2,_
  ~OutputIterator, BinaryPredicate)
- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2,
  ~ typename OutputIterator> __host__ __device__ OutputIterator thrust::inclusive_
  ~scan_by_key(const thrust::detail::execution_policy_base< DerivedPolicy > &,_
  ~InputIterator1, InputIterator1, InputIterator2, OutputIterator)
- template<typename InputIterator1, typename InputIterator2, typename_
  ~OutputIterator, typename BinaryPredicate, typename AssociativeOperator>
  OutputIterator thrust::inclusive_scan_by_key(InputIterator1, InputIterator1,_
  ~InputIterator2, OutputIterator, BinaryPredicate, AssociativeOperator)
- template<typename InputIterator1, typename InputIterator2, typename_
  ~OutputIterator, typename BinaryPredicate>
  OutputIterator thrust::inclusive_scan_by_key(InputIterator1, InputIterator1,_
  ~InputIterator2, OutputIterator, BinaryPredicate)
- template<typename InputIterator1, typename InputIterator2, typename_
  ~OutputIterator>
  OutputIterator thrust::inclusive_scan_by_key(InputIterator1, InputIterator1,_
  ~InputIterator2, OutputIterator)

```

## Template Function `thrust::inclusive_scan_by_key(InputIterator1, InputIterator1, InputIterator2, OutputIterator)`

### Function Documentation

```
template<typename InputIterator1, typename InputIterator2, typename OutputIterator>
OutputIterator thrust::inclusive_scan_by_key(InputIterator1 first1, InputIterator1 last1, InputIterator2 first2, OutputIterator result)
```

`inclusive_scan_by_key` computes an inclusive key-value or ‘segmented’ prefix sum operation. The term ‘inclusive’ means that each result includes the corresponding input operand in the partial sum. The term ‘segmented’ means that the partial sums are broken into distinct segments. In other words, within each segment a separate inclusive scan operation is computed. Refer to the code sample below for example usage.

This version of `inclusive_scan_by_key` assumes `equal_to` as the binary predicate used to compare adjacent keys. Specifically, consecutive iterators `i` and `i+1` in the range `[first1, last1)` belong to the same segment if `*i == *(i+1)`, and belong to different segments otherwise.

This version of `inclusive_scan_by_key` assumes `plus` as the associative operator used to perform the prefix sum. When the input and output sequences are the same, the scan is performed in-place.

The following code snippet demonstrates how to use `inclusive_scan_by_key`

**Return** The end of the output sequence.

**Pre** `first1` may equal `result` but the range `[first1, last1)` and the range `[result, result + (last1 - first1))` shall not overlap otherwise.

**Pre** `first2` may equal `result` but the range `[first2, first2 + (last1 - first1)]` and range `[result, result + (last1 - first1))` shall not overlap otherwise.

### Parameters

- `first1`: The beginning of the key sequence.
- `last1`: The end of the key sequence.
- `first2`: The beginning of the input value sequence.
- `result`: The beginning of the output value sequence.

### Template Parameters

- `InputIterator1`: is a model of `Input Iterator`
- `InputIterator2`: is a model of `Input Iterator` and `InputIterator2`'s `value_type` is convertible to `OutputIterator`'s `value_type`.
- `OutputIterator`: is a model of `Output Iterator`, and if `x` and `y` are objects of `OutputIterator`'s `value_type`, then `binary_op(x, y)` is defined.

```
#include <thrust/scan.h>

int data[10] = {1, 1, 1, 1, 1, 1, 1, 1, 1, 1};
int keys[10] = {0, 0, 0, 1, 1, 2, 3, 3, 3, 3};

thrust::inclusive_scan_by_key(keys, keys + 10, vals, vals); // in-place scan

// data is now {1, 2, 3, 1, 2, 1, 1, 2, 3, 4};
```

See `inclusive_scan`

See `exclusive_scan_by_key`

**Template Function** `thrust::inclusive_scan_by_key(const thrust::detail::execution_policy_base<DerivedPolicy>&, InputIterator1, InputIterator1, InputIterator2, OutputIterator, BinaryPredicate)`

### Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::inclusive_scan_by_key`” with arguments (`const thrust::detail::execution_policy_base<DerivedPolicy>&`, `InputIterator1`, `InputIterator1`, `InputIterator2`, `OutputIterator`, `BinaryPredicate`) in doxygen xml output for project “rocThrust” from directory: `./docBin/xml`. Potential matches:

```

- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2,
  ~ typename OutputIterator, typename BinaryPredicate, typename AssociativeOperator>_
  ~_host__ __device__ OutputIterator thrust::inclusive_scan_by_key(const_
  ~thrust::detail::execution_policy_base< DerivedPolicy > &, InputIterator1,_
  ~InputIterator1, InputIterator2, OutputIterator, BinaryPredicate,_
  ~AssociativeOperator)
- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2,
  ~ typename OutputIterator, typename BinaryPredicate> __host__ __device__
  ~OutputIterator thrust::inclusive_scan_by_key(const thrust::detail::execution_
  ~policy_base< DerivedPolicy > &, InputIterator1, InputIterator1, InputIterator2,_
  ~OutputIterator, BinaryPredicate)
- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2,
  ~ typename OutputIterator> __host__ __device__ OutputIterator thrust::inclusive_
  ~scan_by_key(const thrust::detail::execution_policy_base< DerivedPolicy > &,_
  ~InputIterator1, InputIterator1, InputIterator2, OutputIterator)
- template<typename InputIterator1, typename InputIterator2, typename_
  ~OutputIterator, typename BinaryPredicate, typename AssociativeOperator>
  OutputIterator thrust::inclusive_scan_by_key(InputIterator1, InputIterator1,_
  ~InputIterator2, OutputIterator, BinaryPredicate, AssociativeOperator)
- template<typename InputIterator1, typename InputIterator2, typename_
  ~OutputIterator, typename BinaryPredicate>
  OutputIterator thrust::inclusive_scan_by_key(InputIterator1, InputIterator1,_
  ~InputIterator2, OutputIterator, BinaryPredicate)
- template<typename InputIterator1, typename InputIterator2, typename_
  ~OutputIterator>
  OutputIterator thrust::inclusive_scan_by_key(InputIterator1, InputIterator1,_
  ~InputIterator2, OutputIterator)

```

## Template Function `thrust::inclusive_scan_by_key(InputIterator1, InputIterator1, InputIterator2, OutputIterator, BinaryPredicate)`

### Function Documentation

```
template<typename InputIterator1, typename InputIterator2, typename OutputIterator, typename BinaryPredicate>
OutputIterator thrust::inclusive_scan_by_key (InputIterator1 first1, InputIterator1 last1, InputIt-
erator2 first2, OutputIterator result, BinaryPredi-
cate binary_pred)
```

`inclusive_scan_by_key` computes an inclusive key-value or ‘segmented’ prefix sum operation. The term ‘inclusive’ means that each result includes the corresponding input operand in the partial sum. The term ‘segmented’ means that the partial sums are broken into distinct segments. In other words, within each segment a separate inclusive scan operation is computed. Refer to the code sample below for example usage.

This version of `inclusive_scan_by_key` uses the binary predicate `pred` to compare adjacent keys. Specifically, consecutive iterators `i` and `i+1` in the range `[first1, last1]` belong to the same segment if `binary_pred(*i, *(i+1))` is true, and belong to different segments otherwise.

This version of `inclusive_scan_by_key` assumes `plus` as the associative operator used to perform the prefix sum. When the input and output sequences are the same, the scan is performed in-place.

The following code snippet demonstrates how to use `inclusive_scan_by_key`

**Return** The end of the output sequence.

**Pre** `first1` may equal `result` but the range `[first1, last1]` and the range `[result, result + (last1 - first1)]` shall not overlap otherwise.

**Pre** `first2` may equal `result` but the range `[first2, first2 + (last1 - first1)]` and range `[result, result + (last1 - first1))` shall not overlap otherwise.

### Parameters

- `first1`: The beginning of the key sequence.
- `last1`: The end of the key sequence.
- `first2`: The beginning of the input value sequence.
- `result`: The beginning of the output value sequence.
- `binary_pred`: The binary predicate used to determine equality of keys.

### Template Parameters

- `InputIterator1`: is a model of [Input Iterator](#)
- `InputIterator2`: is a model of [Input Iterator](#) and `InputIterator2`'s `value_type` is convertible to `OutputIterator`'s `value_type`.
- `OutputIterator`: is a model of [Output Iterator](#), and if `x` and `y` are objects of `OutputIterator`'s `value_type`, then `binary_op(x, y)` is defined.
- `BinaryPredicate`: is a model of [Binary Predicate](#).

```
#include <thrust/scan.h>
#include <thrust/functional.h>

int data[10] = {1, 1, 1, 1, 1, 1, 1, 1, 1, 1};
int keys[10] = {0, 0, 0, 1, 1, 2, 3, 3, 3, 3};

thrust::equal_to<int> binary_pred;

thrust::inclusive_scan_by_key(keys, keys + 10, vals, vals, binary_pred); // in-
//place scan

// data is now {1, 2, 3, 1, 2, 1, 1, 2, 3, 4};
```

[See inclusive\\_scan](#)

[See exclusive\\_scan\\_by\\_key](#)

**Template Function** `thrust::inclusive_scan_by_key(const thrust::detail::execution_policy_base<DerivedPolicy>&, InputIterator1, InputIterator1, InputIterator2, OutputIterator, BinaryPredicate, AssociativeOperator)`

### Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::inclusive_scan_by_key`” with arguments (`const thrust::detail::execution_policy_base<DerivedPolicy>&`, `InputIterator1`, `InputIterator1`, `InputIterator2`, `OutputIterator`, `BinaryPredicate`, `AssociativeOperator`) in doxygen xml output for project “rocThrust” from directory: `./docBin/xml`. Potential matches:

```

- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2,
  ~ typename OutputIterator, typename BinaryPredicate, typename AssociativeOperator>_
  ~_host__ __device__ OutputIterator thrust::inclusive_scan_by_key(const_
  ~thrust::detail::execution_policy_base< DerivedPolicy > &, InputIterator1,_
  ~InputIterator1, InputIterator2, OutputIterator, BinaryPredicate,_
  ~AssociativeOperator)
- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2,
  ~ typename OutputIterator, typename BinaryPredicate> __host__ __device__
  ~OutputIterator thrust::inclusive_scan_by_key(const thrust::detail::execution_
  ~policy_base< DerivedPolicy > &, InputIterator1, InputIterator1, InputIterator2,_
  ~OutputIterator, BinaryPredicate)
- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2,
  ~ typename OutputIterator> __host__ __device__ OutputIterator thrust::inclusive_
  ~scan_by_key(const thrust::detail::execution_policy_base< DerivedPolicy > &,_
  ~InputIterator1, InputIterator1, InputIterator2, OutputIterator)
- template<typename InputIterator1, typename InputIterator2, typename_
  ~OutputIterator, typename BinaryPredicate, typename AssociativeOperator>
  OutputIterator thrust::inclusive_scan_by_key(InputIterator1, InputIterator1,_
  ~InputIterator2, OutputIterator, BinaryPredicate, AssociativeOperator)
- template<typename InputIterator1, typename InputIterator2, typename_
  ~OutputIterator, typename BinaryPredicate>
  OutputIterator thrust::inclusive_scan_by_key(InputIterator1, InputIterator1,_
  ~InputIterator2, OutputIterator, BinaryPredicate)
- template<typename InputIterator1, typename InputIterator2, typename_
  ~OutputIterator>
  OutputIterator thrust::inclusive_scan_by_key(InputIterator1, InputIterator1,_
  ~InputIterator2, OutputIterator)

```

## Template Function `thrust::inclusive_scan_by_key(InputIterator1, InputIterator1, InputIterator2, OutputIterator, BinaryPredicate, AssociativeOperator)`

### Function Documentation

```
template<typename InputIterator1, typename InputIterator2, typename OutputIterator, typename BinaryPredicate,
OutputIterator thrust::inclusive_scan_by_key(InputIterator1 first1, InputIterator1 last1, InputIterator2 first2, OutputIterator result, BinaryPredicate binary_pred, AssociativeOperator binary_op)
```

`inclusive_scan_by_key` computes an inclusive key-value or ‘segmented’ prefix sum operation. The term ‘inclusive’ means that each result includes the corresponding input operand in the partial sum. The term ‘segmented’ means that the partial sums are broken into distinct segments. In other words, within each segment a separate inclusive scan operation is computed. Refer to the code sample below for example usage.

This version of `inclusive_scan_by_key` uses the binary predicate `pred` to compare adjacent keys. Specifically, consecutive iterators `i` and `i+1` in the range `[first1, last1]` belong to the same segment if `binary_pred(*i, *(i+1))` is true, and belong to different segments otherwise.

This version of `inclusive_scan_by_key` uses the associative operator `binary_op` to perform the prefix sum. When the input and output sequences are the same, the scan is performed in-place.

The following code snippet demonstrates how to use `inclusive_scan_by_key`

**Return** The end of the output sequence.

**Pre** `first1` may equal `result` but the range `[first1, last1]` and the range `[result, result + (last1 - first1)]` shall not overlap otherwise.

**Pre** `first2` may equal `result` but the range `[first2, first2 + (last1 - first1)]` and range `[result, result + (last1 - first1)]` shall not overlap otherwise.

### Parameters

- `first1`: The beginning of the key sequence.
- `last1`: The end of the key sequence.
- `first2`: The beginning of the input value sequence.
- `result`: The beginning of the output value sequence.
- `binary_pred`: The binary predicate used to determine equality of keys.
- `binary_op`: The associative operator used to ‘sum’ values.

### Template Parameters

- `InputIterator1`: is a model of [Input Iterator](#)
- `InputIterator2`: is a model of [Input Iterator](#) and `InputIterator2`'s `value_type` is convertible to `OutputIterator`'s `value_type`.
- `OutputIterator`: is a model of [Output Iterator](#), and if `x` and `y` are objects of `OutputIterator`'s `value_type`, then `binary_op(x, y)` is defined.
- `BinaryPredicate`: is a model of [Binary Predicate](#).
- `AssociativeOperator`: is a model of [Binary Function](#) and `AssociativeOperator`'s `result_type` is convertible to `OutputIterator`'s `value_type`.

```
#include <thrust/scan.h>
#include <thrust/functional.h>

int data[10] = {1, 1, 1, 1, 1, 1, 1, 1, 1, 1};
int keys[10] = {0, 0, 0, 1, 1, 2, 3, 3, 3, 3};

thrust::equal_to<int> binary_pred;
thrust::plus<int> binary_op;

thrust::inclusive_scan_by_key(keys, keys + 10, vals, vals, binary_pred, binary_
op); // in-place scan

// data is now {1, 2, 3, 1, 2, 1, 1, 2, 3, 4};
```

**See** [inclusive\\_scan](#)

**See** [exclusive\\_scan\\_by\\_key](#)

**Template Function** `thrust::inner_product(const thrust::detail::execution_policy_base<DerivedPolicy>&, InputIterator1, InputIterator1, InputIterator2, OutputType)`

- Defined in `file_thrust_inner_product.h`

## Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “thrust::inner\_product” with arguments (const thrust::detail::execution\_policy\_base<DerivedPolicy>&, InputIterator1, InputIterator1, InputIterator2, OutputType) in doxygen xml output for project “rocThrust” from directory: ./docBin/xml. Potential matches:

```
- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2,
→ typename OutputType, typename BinaryFunction1, typename BinaryFunction2>__host__
→ __device__ OutputType thrust::inner_product(const thrust::detail::execution_
→ policy_base< DerivedPolicy > &, InputIterator1, InputIterator1, InputIterator2,_
→ OutputType, BinaryFunction1, BinaryFunction2)
- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2,
→ typename OutputType>__host__ __device__ OutputType thrust::inner_product(const_
→ thrust::detail::execution_policy_base< DerivedPolicy > &, InputIterator1,_
→ InputIterator1, InputIterator2, OutputType)
- template<typename InputIterator1, typename InputIterator2, typename OutputType,>
→ typename BinaryFunction1, typename BinaryFunction2>
    OutputType thrust::inner_product(InputIterator1, InputIterator1, InputIterator2,_
→ OutputType, BinaryFunction1, BinaryFunction2)
- template<typename InputIterator1, typename InputIterator2, typename OutputType>
    OutputType thrust::inner_product(InputIterator1, InputIterator1, InputIterator2,_
→ OutputType)
```

## Template Function thrust::inner\_product(InputIterator1, InputIterator1, InputIterator2, OutputType)

### Function Documentation

```
template<typename InputIterator1, typename InputIterator2, typename OutputType>
OutputType thrust::inner_product (InputIterator1 first1, InputIterator1 last1, InputIterator2 first2,
                                OutputType init)
inner_product calculates an inner product of the ranges [first1, last1) and [first2, first2
+ (last1 - first1)).
```

Specifically, this version of inner\_product computes the sum  $\text{init} + (*\text{first1} * *\text{first2}) + (*(\text{first1}+1) * *(\text{first2}+1)) + \dots$

Unlike the C++ Standard Template Library function std::inner\_product, this version offers no guarantee on order of execution.

The following code demonstrates how to use inner\_product to compute the dot product of two vectors.

**Return** The inner product of sequences [first1, last1) and [first2, last2) plus init.

### Parameters

- first1: The beginning of the first sequence.
- last1: The end of the first sequence.
- first2: The beginning of the second sequence.
- init: Initial value of the result.

### Template Parameters

- InputIterator1: is a model of [Input Iterator](#),
- InputIterator2: is a model of [Input Iterator](#),

- OutputType: is a model of `Assignable`, and if x is an object of type OutputType, and y is an object of InputIterator1's value\_type, and z is an object of InputIterator2's value\_type, then  $x + y * z$  is defined and is convertible to OutputType.

```
#include <thrust/inner_product.h>
...
float vec1[3] = {1.0f, 2.0f, 5.0f};
float vec2[3] = {4.0f, 1.0f, 5.0f};

float result = thrust::inner_product(vec1, vec1 + 3, vec2, 0.0f);

// result == 31.0f
```

See [http://www.sgi.com/tech/stl/inner\\_product.html](http://www.sgi.com/tech/stl/inner_product.html)

**Template Function** `thrust::inner_product(const thrust::detail::execution_policy_base<DerivedPolicy>&, InputIterator1, InputIterator1, InputIterator2, OutputType, BinaryFunction1, BinaryFunction2)`

#### Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “thrust::inner\_product” with arguments (const thrust::detail::execution\_policy\_base<DerivedPolicy>&, InputIterator1, InputIterator1, InputIterator2, OutputType, BinaryFunction1, BinaryFunction2) in doxygen xml output for project “rocThrust” from directory: ./docBin/xml. Potential matches:

```
- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2,
→ typename OutputType, typename BinaryFunction1, typename BinaryFunction2>__host__  
→__device__ OutputType thrust::inner_product(const thrust::detail::execution_
→policy_base< DerivedPolicy > &, InputIterator1, InputIterator1, InputIterator2,_
→OutputType, BinaryFunction1, BinaryFunction2)
- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2,
→ typename OutputType>__host__ __device__ OutputType thrust::inner_product(const_
→thrust::detail::execution_policy_base< DerivedPolicy > &, InputIterator1,_
→InputIterator1, InputIterator2, OutputType)
- template<typename InputIterator1, typename InputIterator2, typename OutputType,>  
→typename BinaryFunction1, typename BinaryFunction2>
    OutputType thrust::inner_product(InputIterator1, InputIterator1, InputIterator2,_
→OutputType, BinaryFunction1, BinaryFunction2)
- template<typename InputIterator1, typename InputIterator2, typename OutputType>
    OutputType thrust::inner_product(InputIterator1, InputIterator1, InputIterator2,_
→OutputType)
```

**Template Function** `thrust::inner_product(InputIterator1, InputIterator1, InputIterator2, OutputType, BinaryFunction1, BinaryFunction2)`

#### Function Documentation

```
template<typename InputIterator1, typename InputIterator2, typename OutputType, typename BinaryFunction1,
OutputType> thrust::inner_product(InputIterator1 first1, InputIterator1 last1, InputIterator2 first2,
                                OutputType init, BinaryFunction1 binary_op1, BinaryFunction2
                                binary_op2)
```

inner\_product calculates an inner product of the ranges [first1, last1) and [first2, first2

```
+ (last1 - first1)).
```

This version of `inner_product` is identical to the first, except that it uses two user-supplied function objects instead of `operator+` and `operator*`.

Specifically, this version of `inner_product` computes the sum `binary_op1( init, binary_op2(*first1, *first2) ), ...`

Unlike the C++ Standard Template Library function `std::inner_product`, this version offers no guarantee on order of execution.

```
#include <thrust/inner_product.h>
...
float vec1[3] = {1.0f, 2.0f, 5.0f};
float vec2[3] = {4.0f, 1.0f, 5.0f};

float init = 0.0f;
thrust::plus<float> binary_op1;
thrust::multiplies<float> binary_op2;

float result = thrust::inner_product(vec1, vec1 + 3, vec2, init, binary_op1,
                                     binary_op2);

// result == 31.0f
```

**Return** The inner product of sequences `[first1, last1)` and `[first2, last2)`.

### Parameters

- `first1`: The beginning of the first sequence.
- `last1`: The end of the first sequence.
- `first2`: The beginning of the second sequence.
- `init`: Initial value of the result.
- `binary_op1`: Generalized addition operation.
- `binary_op2`: Generalized multiplication operation.

### Template Parameters

- `InputIterator1`: is a model of `Input Iterator`, and `InputIterator1`'s `value_type` is convertible to `BinaryFunction2`'s `first_argument_type`.
- `InputIterator2`: is a model of `Input Iterator`, and `InputIterator2`'s `value_type` is convertible to `BinaryFunction2`'s `second_argument_type`.
- `OutputType`: is a model of `Assignable`, and `OutputType` is convertible to `BinaryFunction1`'s `first_argument_type`.
- `BinaryFunction1`: is a model of `Binary Function`, and `BinaryFunction1`'s `return_type` is convertible to `OutputType`.
- `BinaryFunction2`: is a model of `Binary Function`, and `BinaryFunction2`'s `return_type` is convertible to `BinaryFunction1`'s `second_argument_type`.

See [http://www.sgi.com/tech/stl/inner\\_product.html](http://www.sgi.com/tech/stl/inner_product.html)

**Template Function `thrust::is_partitioned(const thrust::detail::execution_policy_base<DerivedPolicy>&, InputIterator, InputIterator, Predicate)`**

- Defined in file `thrust_partition.h`

**Function Documentation**

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::is_partitioned`” with arguments (`const thrust::detail::execution_policy_base<DerivedPolicy>&`, `InputIterator`, `InputIterator`, `Predicate`) in doxygen xml output for project “rocThrust” from directory: `./docBin/xml`. Potential matches:

```
- template<typename DerivedPolicy, typename InputIterator, typename Predicate> __  
→ host__ __device__ bool thrust::is_partitioned(const thrust::detail::execution_<  
→ policy_base< DerivedPolicy > &, InputIterator, InputIterator, Predicate)  
- template<typename InputIterator, typename Predicate>  
bool thrust::is_partitioned(InputIterator, InputIterator, Predicate)
```

**Template Function `thrust::is_partitioned(InputIterator, InputIterator, Predicate)`****Function Documentation**

```
template<typename InputIterator, typename Predicate>  
bool thrust::is_partitioned(InputIterator first, InputIterator last, Predicate pred)  
is_partitioned returns true if the given range is partitioned with respect to a predicate, and false otherwise.
```

Specifically, `is_partitioned` returns true if `[first, last)` is empty or if `[first, last)` is partitioned by `pred`, i.e. if all elements that satisfy `pred` appear before those that do not.

```
#include <thrust/partition.h>  
  
struct is_even  
{  
    __host__ __device__  
    bool operator()(const int &x)  
    {  
        return (x % 2) == 0;  
    }  
};  
...  
int A[] = {2, 4, 6, 8, 10, 1, 3, 5, 7, 9};  
int B[] = {1, 2, 3, 4, 5, 6, 7, 8, 9, 10};  
  
thrust::is_partitioned(A, A + 10, is_even()); // returns true  
thrust::is_partitioned(B, B + 10, is_even()); // returns false
```

**Return** true if the range `[first, last)` is partitioned with respect to `pred`, or if `[first, last)` is empty. false, otherwise.

**Parameters**

- `first`: The beginning of the range to consider.
- `last`: The end of the range to consider.
- `pred`: A function object which decides to which partition each element of the range [`first`, `last`) belongs.

### Template Parameters

- `InputIterator`: is a model of `Input Iterator`, and `InputIterator`'s `value_type` is convertible to `Predicate`'s `argument_type`.
- `Predicate`: is a model of `Predicate`.

See `partition`

## Template Function `thrust::is_sorted(const thrust::detail::execution_policy_base<DerivedPolicy>&, ForwardIterator, ForwardIterator)`

- Defined in file `thrust_sort.h`

### Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::is_sorted`” with arguments (`const thrust::detail::execution_policy_base<DerivedPolicy>&`, `ForwardIterator`, `ForwardIterator`) in doxygen xml output for project “rocThrust” from directory: `./docBin/xml`. Potential matches:

```
- template<typename DerivedPolicy, typename ForwardIterator, typename Compare> __
→host__ __device__ bool thrust::is_sorted(const thrust::detail::execution_policy_
→base< DerivedPolicy > &, ForwardIterator, ForwardIterator, Compare)
- template<typename DerivedPolicy, typename ForwardIterator> __host__ __device__ __
→bool thrust::is_sorted(const thrust::detail::execution_policy_base< DerivedPolicy _> &, ForwardIterator, ForwardIterator)
- template<typename ForwardIterator, typename Compare>
  bool thrust::is_sorted(ForwardIterator, ForwardIterator, Compare)
- template<typename ForwardIterator>
  bool thrust::is_sorted(ForwardIterator, ForwardIterator)
```

## Template Function `thrust::is_sorted(ForwardIterator, ForwardIterator)`

### Function Documentation

```
template<typename ForwardIterator>
bool thrust::is_sorted(ForwardIterator first, ForwardIterator last)
    is_sorted returns true if the range [first, last) is sorted in ascending order, and false otherwise.
    Specifically, this version of is_sorted returns false if for some iterator i in the range [first, last - 1) the expression * (i + 1) < *i is true.
```

The following code demonstrates how to use `is_sorted` to test whether the contents of a `device_vector` are stored in ascending order.

**Return** `true`, if the sequence is sorted; `false`, otherwise.

### Parameters

- `first`: The beginning of the sequence.
- `last`: The end of the sequence.

### Template Parameters

- `ForwardIterator`: is a model of `Forward Iterator`, `ForwardIterator`'s `value_type` is a model of `LessThan Comparable`, and the ordering on objects of `ForwardIterator`'s `value_type` is a *strict weak ordering*, as defined in the `LessThan Comparable` requirements.

```
#include <thrust/sort.h>
#include <thrust/device_vector.h>
#include <thrust/sort.h>
...
thrust::device_vector<int> v(6);
v[0] = 1;
v[1] = 4;
v[2] = 2;
v[3] = 8;
v[4] = 5;
v[5] = 7;

bool result = thrust::is_sorted(v.begin(), v.end());

// result == false

thrust::sort(v.begin(), v.end());
result = thrust::is_sorted(v.begin(), v.end());

// result == true
```

See [http://www.sgi.com/tech/stl/is\\_sorted.html](http://www.sgi.com/tech/stl/is_sorted.html)

See `is_sorted_until`

See `sort`

See `stable_sort`

See `less<T>`

**Template Function `thrust::is_sorted(const thrust::detail::execution_policy_base<DerivedPolicy>&, ForwardIterator, ForwardIterator, Compare)`**

### Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::is_sorted`” with arguments (`const thrust::detail::execution_policy_base<DerivedPolicy>&`, `ForwardIterator`, `ForwardIterator`, `Compare`) in doxygen xml output for project “rocThrust” from directory: `./docBin/xml`. Potential matches:

```
- template<typename DerivedPolicy, typename ForwardIterator, typename Compare> __
  host__ __device__ bool thrust::is_sorted(const thrust::detail::execution_policy_
  base< DerivedPolicy > &, ForwardIterator, ForwardIterator, Compare)
- template<typename DerivedPolicy, typename ForwardIterator> __host__ __device__ __
  bool thrust::is_sorted(const thrust::detail::execution_policy_base< DerivedPolicy > &,
  ForwardIterator, ForwardIterator)
- template<typename ForwardIterator, typename Compare>
  bool thrust::is_sorted(ForwardIterator, ForwardIterator, Compare)
- template<typename ForwardIterator>
  bool thrust::is_sorted(ForwardIterator, ForwardIterator)
```

## Template Function `thrust::is_sorted(ForwardIterator, ForwardIterator, Compare)`

### Function Documentation

```
template<typename ForwardIterator, typename Compare>
bool thrust::is_sorted(ForwardIterator first, ForwardIterator last, Compare comp)
    is_sorted returns true if the range [first, last) is sorted in ascending order according to a user-defined comparison operation, and false otherwise.
```

Specifically, this version of `is_sorted` returns false if for some iterator *i* in the range [*first*, *last* - 1) the expression `comp(*(i + 1), *i)` is true.

The following code snippet demonstrates how to use `is_sorted` to test whether the contents of a `device_vector` are stored in descending order.

**Return** true, if the sequence is sorted according to `comp`; false, otherwise.

#### Parameters

- `first`: The beginning of the sequence.
- `last`: The end of the sequence.
- `comp`: Comparison operator.

#### Template Parameters

- `ForwardIterator`: is a model of `Forward Iterator`, and `ForwardIterator`'s `value_type` is convertible to both `StrictWeakOrdering`'s `first_argument_type` and `second_argument_type`.
- `Compare`: is a model of `Strict Weak Ordering`.

```
#include <thrust/sort.h>
#include <thrust/functional.h>
#include <thrust/device_vector.h>
...
thrust::device_vector<int> v(6);
v[0] = 1;
v[1] = 4;
v[2] = 2;
v[3] = 8;
v[4] = 5;
v[5] = 7;

thrust::greater<int> comp;
bool result = thrust::is_sorted(v.begin(), v.end(), comp);

// result == false

thrust::sort(v.begin(), v.end(), comp);
result = thrust::is_sorted(v.begin(), v.end(), comp);

// result == true
```

See [http://www.sgi.com/tech/stl/is\\_sorted.html](http://www.sgi.com/tech/stl/is_sorted.html)

See [sort](#)

See [stable\\_sort](#)

See [less<T>](#)

### Template Function `thrust::is_sorted_until(const thrust::detail::execution_policy_base<DerivedPolicy>&, ForwardIterator, ForwardIterator)`

- Defined in file `thrust_sort.h`

## Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::is_sorted_until`” with arguments (`const thrust::detail::execution_policy_base<DerivedPolicy>&`, `ForwardIterator`, `ForwardIterator`) in doxygen xml output for project “rocThrust” from directory: `./docBin/xml`. Potential matches:

```
- template<typename DerivedPolicy, typename ForwardIterator, typename Compare> __
  host__ __device__ ForwardIterator thrust::is_sorted_until(const
  thrust::detail::execution_policy_base< DerivedPolicy > &, ForwardIterator, __
  ForwardIterator, Compare)
- template<typename DerivedPolicy, typename ForwardIterator> __host__ __device__
  ForwardIterator thrust::is_sorted_until(const thrust::detail::execution_policy_
  base< DerivedPolicy > &, ForwardIterator, ForwardIterator)
- template<typename ForwardIterator, typename Compare>
  ForwardIterator thrust::is_sorted_until(ForwardIterator, ForwardIterator, Compare)
- template<typename ForwardIterator>
  ForwardIterator thrust::is_sorted_until(ForwardIterator, ForwardIterator)
```

### Template Function `thrust::is_sorted_until(ForwardIterator, ForwardIterator)`

## Function Documentation

`template<typename ForwardIterator>`

`ForwardIterator thrust::is_sorted_until(ForwardIterator first, ForwardIterator last)`

This version of `is_sorted_until` returns the last iterator `i` in `[first, last]` for which the range `[first, last)` is sorted using operator`<`. If `distance(first, last) < 2`, `is_sorted_until` simply returns `last`.

The following code snippet demonstrates how to use `is_sorted_until` to find the first position in an array where the data becomes unsorted:

**Return** The last iterator in the input range for which it is sorted.

### Parameters

- `first`: The beginning of the range of interest.
- `last`: The end of the range of interest.

### Template Parameters

- `ForwardIterator`: is a model of `Forward Iterator` and `ForwardIterator`'s `value_type` is a model of `LessThan Comparable`.

```
#include <thrust/sort.h>

...
int A[8] = {0, 1, 2, 3, 0, 1, 2, 3};
int * B = thrust::is_sorted_until(A, A + 8);

// B - A is 4
// [A, B) is sorted
```

**See** [is\\_sorted](#)

**See** [sort](#)

**See** [sort\\_by\\_key](#)

**See** [stable\\_sort](#)

**See** [stable\\_sort\\_by\\_key](#)

**Template Function `thrust::is_sorted_until(const thrust::detail::execution_policy_base<DerivedPolicy>&, ForwardIterator, ForwardIterator, Compare)`**

## Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::is_sorted_until`” with arguments (`const thrust::detail::execution_policy_base<DerivedPolicy>&`, `ForwardIterator`, `ForwardIterator`, `Compare`) in doxygen xml output for project “rocThrust” from directory: `./docBin/xml`. Potential matches:

```
- template<typename DerivedPolicy, typename ForwardIterator, typename Compare> __
  host__ __device__ ForwardIterator thrust::is_sorted_until(const_
  thrust::detail::execution_policy_base< DerivedPolicy > &, ForwardIterator,_
  ForwardIterator, Compare)
- template<typename DerivedPolicy, typename ForwardIterator> __host__ __device__
  ForwardIterator thrust::is_sorted_until(const thrust::detail::execution_policy_<
  DerivedPolicy > &, ForwardIterator, ForwardIterator)
- template<typename ForwardIterator, typename Compare>
  ForwardIterator thrust::is_sorted_until(ForwardIterator, ForwardIterator, Compare)
- template<typename ForwardIterator>
  ForwardIterator thrust::is_sorted_until(ForwardIterator, ForwardIterator)
```

**Template Function `thrust::is_sorted_until(ForwardIterator, ForwardIterator, Compare)`**

## Function Documentation

```
template<typename ForwardIterator, typename Compare>
ForwardIterator thrust::is_sorted_until(ForwardIterator first, ForwardIterator last, Compare
                                         comp)
```

This version of `is_sorted_until` returns the last iterator `i` in `[first, last]` for which the range `[first, last)` is sorted using the function object `comp`. If `distance(first, last) < 2`, `is_sorted_until` simply returns `last`.

The following code snippet demonstrates how to use `is_sorted_until` to find the first position in an array where the data becomes unsorted in descending order:

**Return** The last iterator in the input range for which it is sorted.

#### Parameters

- `first`: The beginning of the range of interest.
- `last`: The end of the range of interest.
- `comp`: The function object to use for comparison.

#### Template Parameters

- `ForwardIterator`: is a model of `Forward Iterator` and `ForwardIterator`'s `value_type` is convertible to `Compare`'s `argument_type`.
- `Compare`: is a model of `Strict Weak Ordering`.

```
#include <thrust/sort.h>
#include <thrust/functional.h>

...

int A[8] = {3, 2, 1, 0, 3, 2, 1, 0};

thrust::greater<int> comp;
int * B = thrust::is_sorted_until(A, A + 8, comp);

// B - A is 4
// [A, B) is sorted in descending order
```

**See** `is_sorted`

**See** `sort`

**See** `sort_by_key`

**See** `stable_sort`

**See** `stable_sort_by_key`

### Template Function `thrust::log`

- Defined in file `_thrust_complex.h`

#### Function Documentation

```
template<typename T> __host__ __device__ complex<T> thrust::log(const complex < T > & z)
```

Returns the complex natural logarithm of a `complex` number.

#### Parameters

- `z`: The `complex` argument.

### Template Function `thrust::log10`

- Defined in file `_thrust_complex.h`

## Function Documentation

```
template<typename T> __host__ __device__ complex<T> thrust::log10(const complex < T > & z)
```

Returns the complex base 10 logarithm of a complex number.

### Parameters

- z: The complex argument.

**Template Function thrust::lower\_bound(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, ForwardIterator, ForwardIterator, const LessThanComparable&)**

- Defined in file\_thrust\_binary\_search.h

## Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “thrust::lower\_bound” with arguments (const thrust::detail::execution\_policy\_base<DerivedPolicy>&, ForwardIterator, ForwardIterator, const LessThanComparable&) in doxygen xml output for project “rocThrust” from directory: ./docBin/xml. Potential matches:

```
- template<class ForwardIterator, class InputIterator, class OutputIterator, class StrictWeakOrdering>
  OutputIterator thrust::lower_bound(ForwardIterator, ForwardIterator,
  ~InputIterator, InputIterator, OutputIterator, StrictWeakOrdering)
- template<class ForwardIterator, class InputIterator, class OutputIterator>
  OutputIterator thrust::lower_bound(ForwardIterator, ForwardIterator,
  ~InputIterator, InputIterator, OutputIterator)
- template<class ForwardIterator, class LessThanComparable>
  ForwardIterator thrust::lower_bound(ForwardIterator, ForwardIterator, const LessThanComparable&)
- template<class ForwardIterator, class T, class StrictWeakOrdering>
  ForwardIterator thrust::lower_bound(ForwardIterator, ForwardIterator, const T&,
  ~StrictWeakOrdering)
- template<typename DerivedPolicy, typename ForwardIterator, typename InputIterator,
  ~typename OutputIterator, typename StrictWeakOrdering> __host__ __device__
  ~OutputIterator thrust::lower_bound(const thrust::detail::execution_policy_base<
  ~DerivedPolicy > &, ForwardIterator, ForwardIterator, InputIterator, InputIterator,
  ~OutputIterator, StrictWeakOrdering)
- template<typename DerivedPolicy, typename ForwardIterator, typename InputIterator,
  ~typename OutputIterator> __host__ __device__ OutputIterator thrust::lower_
  ~bound(const thrust::detail::execution_policy_base< DerivedPolicy > &,
  ~ForwardIterator, ForwardIterator, InputIterator, InputIterator, OutputIterator)
- template<typename DerivedPolicy, typename ForwardIterator, typename
  ~LessThanComparable> __host__ __device__ ForwardIterator thrust::lower_bound(const
  ~thrust::detail::execution_policy_base< DerivedPolicy > &, ForwardIterator,
  ~ForwardIterator, const LessThanComparable &)
- template<typename DerivedPolicy, typename ForwardIterator, typename T, typename
  ~StrictWeakOrdering> __host__ __device__ ForwardIterator thrust::lower_bound(const
  ~thrust::detail::execution_policy_base< DerivedPolicy > &, ForwardIterator,
  ~ForwardIterator, const T &, StrictWeakOrdering)
```

**Template Function `thrust::lower_bound(ForwardIterator, ForwardIterator, const LessThanComparable&)`****Function Documentation**

```
template<class ForwardIterator, class LessThanComparable>
ForwardIterator thrust::lower_bound(ForwardIterator first, ForwardIterator last, const
LessThanComparable &value)
```

`lower_bound` is a version of binary search: it attempts to find the element value in an ordered range `[first, last]`. Specifically, it returns the first position where `value` could be inserted without violating the ordering. This version of `lower_bound` uses operator`<` for comparison and returns the furthermost iterator `i` in `[first, last]` such that, for every iterator `j` in `[first, i)`, `*j < value`.

The following code snippet demonstrates how to use `lower_bound` to search for values in a ordered range.

**Return** The furthermost iterator `i`, such that `*i < value`.

**Parameters**

- `first`: The beginning of the ordered sequence.
- `last`: The end of the ordered sequence.
- `value`: The value to be searched.

**Template Parameters**

- `ForwardIterator`: is a model of `Forward Iterator`.
- `LessThanComparable`: is a model of `LessThanComparable`.

```
#include <thrust/binary_search.h>
#include <thrust/device_vector.h>
...
thrust::device_vector<int> input(5);

input[0] = 0;
input[1] = 2;
input[2] = 5;
input[3] = 7;
input[4] = 8;

thrust::lower_bound(input.begin(), input.end(), 0); // returns input.begin()
thrust::lower_bound(input.begin(), input.end(), 1); // returns input.begin() + 1
thrust::lower_bound(input.begin(), input.end(), 2); // returns input.begin() + 1
thrust::lower_bound(input.begin(), input.end(), 3); // returns input.begin() + 2
thrust::lower_bound(input.begin(), input.end(), 8); // returns input.begin() + 4
thrust::lower_bound(input.begin(), input.end(), 9); // returns input.end()
```

**See** [http://www.sgi.com/tech/stl/lower\\_bound.html](http://www.sgi.com/tech/stl/lower_bound.html)

**See** `upper_bound`

**See** `equal_range`

**See** `binary_search`

**Template Function `thrust::lower_bound(const thrust::detail::execution_policy_base<DerivedPolicy>&, ForwardIterator, ForwardIterator, const T&, StrictWeakOrdering)`**

## Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “thrust::lower\_bound” with arguments (const thrust::detail::execution\_policy\_base<DerivedPolicy>&, ForwardIterator, ForwardIterator, const T&, StrictWeakOrdering) in doxygen xml output for project “rocThrust” from directory: ./docBin/xml. Potential matches:

```
- template<class ForwardIterator, class InputIterator, class OutputIterator, class StrictWeakOrdering>
    OutputIterator thrust::lower_bound(ForwardIterator, ForwardIterator,
                                     InputIterator, InputIterator, OutputIterator, StrictWeakOrdering)
- template<class ForwardIterator, class InputIterator, class OutputIterator>
    OutputIterator thrust::lower_bound(ForwardIterator, ForwardIterator,
                                     InputIterator, InputIterator, OutputIterator)
- template<class ForwardIterator, class LessThanComparable>
    ForwardIterator thrust::lower_bound(ForwardIterator, ForwardIterator, const LessThanComparable&)
- template<class ForwardIterator, class T, class StrictWeakOrdering>
    ForwardIterator thrust::lower_bound(ForwardIterator, ForwardIterator, const T&,
                                     StrictWeakOrdering)
- template<typename DerivedPolicy, typename ForwardIterator, typename InputIterator,
          typename OutputIterator, typename StrictWeakOrdering>__host__ __device__
    OutputIterator thrust::lower_bound(const thrust::detail::execution_policy_base<DerivedPolicy> &, ForwardIterator, ForwardIterator, InputIterator, InputIterator,
                                     OutputIterator, StrictWeakOrdering)
- template<typename DerivedPolicy, typename ForwardIterator, typename InputIterator,
          typename OutputIterator>__host__ __device__
    OutputIterator thrust::lower_bound(ForwardIterator, ForwardIterator, InputIterator, InputIterator, OutputIterator)
- template<typename DerivedPolicy, typename ForwardIterator, typename LessThanComparable>__host__ __device__
    ForwardIterator thrust::lower_bound(DerivedPolicy > &, ForwardIterator, ForwardIterator, const LessThanComparable &)
- template<typename DerivedPolicy, typename ForwardIterator, typename T, typename StrictWeakOrdering>__host__ __device__
    ForwardIterator thrust::lower_bound(DerivedPolicy > &, ForwardIterator, ForwardIterator, const T &, StrictWeakOrdering)
```

## Template Function thrust::lower\_bound(ForwardIterator, ForwardIterator, const T&, StrictWeakOrdering)

### Function Documentation

```
template<class ForwardIterator, class T, class StrictWeakOrdering>
ForwardIterator thrust::lower_bound(ForwardIterator first, ForwardIterator last, const T &value,
                                   StrictWeakOrdering comp)
```

lower\_bound is a version of binary search: it attempts to find the element value in an ordered range [first, last). Specifically, it returns the first position where value could be inserted without violating the ordering. This version of lower\_bound uses function object comp for comparison and returns the furthermost iterator i in [first, last) such that, for every iterator j in [first, i), comp(\*j, value) is true.

The following code snippet demonstrates how to use lower\_bound to search for values in a ordered range.

**Return** The furthermost iterator i, such that comp(\*i, value) is true.

## Parameters

- `first`: The beginning of the ordered sequence.
- `last`: The end of the ordered sequence.
- `value`: The value to be searched.
- `comp`: The comparison operator.

## Template Parameters

- `ForwardIterator`: is a model of [Forward Iterator](#).
- `T`: is comparable to `ForwardIterator`'s `value_type`.
- `StrictWeakOrdering`: is a model of [Strict Weak Ordering](#).

```
#include <thrust/binary_search.h>
#include <thrust/device_vector.h>
#include <thrust/functional.h>
...
thrust::device_vector<int> input(5);

input[0] = 0;
input[1] = 2;
input[2] = 5;
input[3] = 7;
input[4] = 8;

thrust::lower_bound(input.begin(), input.end(), 0, thrust::less<int>()); // ↵
// returns input.begin()
thrust::lower_bound(input.begin(), input.end(), 1, thrust::less<int>()); // ↵
// returns input.begin() + 1
thrust::lower_bound(input.begin(), input.end(), 2, thrust::less<int>()); // ↵
// returns input.begin() + 1
thrust::lower_bound(input.begin(), input.end(), 3, thrust::less<int>()); // ↵
// returns input.begin() + 2
thrust::lower_bound(input.begin(), input.end(), 8, thrust::less<int>()); // ↵
// returns input.begin() + 4
thrust::lower_bound(input.begin(), input.end(), 9, thrust::less<int>()); // ↵
// returns input.end()
```

**See** [http://www.sgi.com/tech/stl/lower\\_bound.html](http://www.sgi.com/tech/stl/lower_bound.html)

**See** [upper\\_bound](#)

**See** [equal\\_range](#)

**See** [binary\\_search](#)

**Template Function** `thrust::lower_bound(const thrust::detail::execution_policy_base<DerivedPolicy>&, ForwardIterator, ForwardIterator, InputIterator, InputIterator, OutputIterator)`

## Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “thrust::lower\_bound” with arguments (const thrust::detail::execution\_policy\_base<DerivedPolicy>&, ForwardIterator, ForwardIterator, InputIterator, InputIterator, OutputIterator) in doxygen xml output for project “rocThrust” from directory: ./docBin/xml. Potential matches:

```
- template<class ForwardIterator, class InputIterator, class OutputIterator, class StrictWeakOrdering>
    OutputIterator thrust::lower_bound(ForwardIterator, ForwardIterator, InputIterator, InputIterator, OutputIterator, StrictWeakOrdering)
- template<class ForwardIterator, class InputIterator, class OutputIterator>
    OutputIterator thrust::lower_bound(ForwardIterator, ForwardIterator, InputIterator, InputIterator, OutputIterator)
- template<class ForwardIterator, class LessThanComparable>
    ForwardIterator thrust::lower_bound(ForwardIterator, ForwardIterator, const LessThanComparable&)
- template<class ForwardIterator, class T, class StrictWeakOrdering>
    ForwardIterator thrust::lower_bound(ForwardIterator, ForwardIterator, const T&, StrictWeakOrdering)
- template<typename DerivedPolicy, typename ForwardIterator, typename InputIterator,
          typename OutputIterator, typename StrictWeakOrdering>__host__ __device__
    OutputIterator thrust::lower_bound(const thrust::detail::execution_policy_base<DerivedPolicy> &, ForwardIterator, ForwardIterator, InputIterator, InputIterator, OutputIterator, StrictWeakOrdering)
- template<typename DerivedPolicy, typename ForwardIterator, typename InputIterator,
          typename OutputIterator>__host__ __device__ OutputIterator thrust::lower_bound(
    const thrust::detail::execution_policy_base<DerivedPolicy> &, ForwardIterator, ForwardIterator, InputIterator, InputIterator, OutputIterator)
- template<typename DerivedPolicy, typename ForwardIterator, typename LessThanComparable>__host__ __device__ ForwardIterator thrust::lower_bound(
    const thrust::detail::execution_policy_base<DerivedPolicy> &, ForwardIterator, ForwardIterator, const LessThanComparable &)
- template<typename DerivedPolicy, typename ForwardIterator, typename T, typename StrictWeakOrdering>__host__ __device__ ForwardIterator thrust::lower_bound(
    const thrust::detail::execution_policy_base<DerivedPolicy> &, ForwardIterator, ForwardIterator, const T &, StrictWeakOrdering)
```

## Template Function thrust::lower\_bound(ForwardIterator, ForwardIterator, InputIterator, InputIterator, OutputIterator)

### Function Documentation

```
template<class ForwardIterator, class InputIterator, class OutputIterator>
OutputIterator thrust::lower_bound(ForwardIterator first, ForwardIterator last, InputIterator values_first, InputIterator values_last, OutputIterator result)
lower_bound is a vectorized version of binary search: for each iterator v in [values_first, values_last) it attempts to find the value *v in an ordered range [first, last). Specifically, it returns the index of first position where value could be inserted without violating the ordering.
```

The following code snippet demonstrates how to use lower\_bound to search for multiple values in a ordered range.

**Pre** The ranges [first, last) and [result, result + (last - first)) shall not overlap.

#### Parameters

- first: The beginning of the ordered sequence.

- `last`: The end of the ordered sequence.
- `values_first`: The beginning of the search values sequence.
- `values_last`: The end of the search values sequence.
- `result`: The beginning of the output sequence.

### Template Parameters

- `ForwardIterator`: is a model of [Forward Iterator](#).
- `InputIterator`: is a model of [Input Iterator](#). and `InputIterator`'s `value_type` is [LessThanComparable](#).
- `OutputIterator`: is a model of [Output Iterator](#). and `ForwardIterator`'s `difference_type` is convertible to `OutputIterator`'s `value_type`.

```
#include <thrust/binary_search.h>
#include <thrust/device_vector.h>
...
thrust::device_vector<int> input(5);

input[0] = 0;
input[1] = 2;
input[2] = 5;
input[3] = 7;
input[4] = 8;

thrust::device_vector<int> values(6);
values[0] = 0;
values[1] = 1;
values[2] = 2;
values[3] = 3;
values[4] = 8;
values[5] = 9;

thrust::device_vector<unsigned int> output(6);

thrust::lower_bound(input.begin(), input.end(),
                    values.begin(), values.end(),
                    output.begin());

// output is now [0, 1, 1, 2, 4, 5]
```

**See** [http://www.sgi.com/tech/stl/lower\\_bound.html](http://www.sgi.com/tech/stl/lower_bound.html)

**See** [upper\\_bound](#)

**See** [equal\\_range](#)

**See** [binary\\_search](#)

**Template Function** `thrust::lower_bound(const thrust::detail::execution_policy_base<DerivedPolicy>&, ForwardIterator, ForwardIterator, InputIterator, InputIterator, OutputIterator, StrictWeakOrdering)`

## Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “thrust::lower\_bound” with arguments (const thrust::detail::execution\_policy\_base<DerivedPolicy>&, ForwardIterator, ForwardIterator, InputIterator, InputIterator, OutputIterator, StrictWeakOrdering) in doxygen xml output for project “rocThrust” from directory: ./docBin/xml. Potential matches:

```
- template<class ForwardIterator, class InputIterator, class OutputIterator, class StrictWeakOrdering>
    OutputIterator thrust::lower_bound(ForwardIterator, ForwardIterator, InputIterator, InputIterator, OutputIterator, StrictWeakOrdering)
- template<class ForwardIterator, class InputIterator, class OutputIterator>
    OutputIterator thrust::lower_bound(ForwardIterator, ForwardIterator, InputIterator, InputIterator, OutputIterator)
- template<class ForwardIterator, class LessThanComparable>
    ForwardIterator thrust::lower_bound(ForwardIterator, ForwardIterator, const LessThanComparable&)
- template<class ForwardIterator, class T, class StrictWeakOrdering>
    ForwardIterator thrust::lower_bound(ForwardIterator, ForwardIterator, const T&, StrictWeakOrdering)
- template<typename DerivedPolicy, typename ForwardIterator, typename InputIterator,
          typename OutputIterator, typename StrictWeakOrdering>__host__ __device__
    OutputIterator thrust::lower_bound(const thrust::detail::execution_policy_base<DerivedPolicy> &, ForwardIterator, ForwardIterator, InputIterator, InputIterator, OutputIterator, StrictWeakOrdering)
- template<typename DerivedPolicy, typename ForwardIterator, typename InputIterator,
          typename OutputIterator>__host__ __device__ OutputIterator thrust::lower_bound(const thrust::detail::execution_policy_base<DerivedPolicy> &, ForwardIterator, InputIterator, InputIterator, OutputIterator)
- template<typename DerivedPolicy, typename ForwardIterator, typename LessThanComparable>__host__ __device__ ForwardIterator thrust::lower_bound(const thrust::detail::execution_policy_base<DerivedPolicy> &, ForwardIterator, ForwardIterator, const LessThanComparable &)
- template<typename DerivedPolicy, typename ForwardIterator, typename T, typename StrictWeakOrdering>__host__ __device__ ForwardIterator thrust::lower_bound(const thrust::detail::execution_policy_base<DerivedPolicy> &, ForwardIterator, ForwardIterator, const T &, StrictWeakOrdering)
```

### Template Function thrust::lower\_bound(ForwardIterator, ForwardIterator, InputIterator, InputIterator, OutputIterator, StrictWeakOrdering)

#### Function Documentation

```
template<class ForwardIterator, class InputIterator, class OutputIterator, class StrictWeakOrdering>
OutputIterator thrust::lower_bound(ForwardIterator first, ForwardIterator last, InputIterator values_first, InputIterator values_last, OutputIterator result, StrictWeakOrdering comp)
```

lower\_bound is a vectorized version of binary search: for each iterator v in [values\_first, values\_last) it attempts to find the value \*v in an ordered range [first, last). Specifically, it returns the index of first position where value could be inserted without violating the ordering. This version of lower\_bound uses function object comp for comparison.

The following code snippet demonstrates how to use lower\_bound to search for multiple values in a ordered range.

**Pre** The ranges `[first, last)` and `[result, result + (last - first))` shall not overlap.

### Parameters

- `first`: The beginning of the ordered sequence.
- `last`: The end of the ordered sequence.
- `values_first`: The beginning of the search values sequence.
- `values_last`: The end of the search values sequence.
- `result`: The beginning of the output sequence.
- `comp`: The comparison operator.

### Template Parameters

- `ForwardIterator`: is a model of [Forward Iterator](#).
- `InputIterator`: is a model of [Input Iterator](#). and `InputIterator`'s `value_type` is comparable to `ForwardIterator`'s `value_type`.
- `OutputIterator`: is a model of [Output Iterator](#). and `ForwardIterator`'s `difference_type` is convertible to `OutputIterator`'s `value_type`.
- `StrictWeakOrdering`: is a model of [Strict Weak Ordering](#).

```
#include <thrust/binary_search.h>
#include <thrust/device_vector.h>
#include <thrust/functional.h>
...
thrust::device_vector<int> input(5);

input[0] = 0;
input[1] = 2;
input[2] = 5;
input[3] = 7;
input[4] = 8;

thrust::device_vector<int> values(6);
values[0] = 0;
values[1] = 1;
values[2] = 2;
values[3] = 3;
values[4] = 8;
values[5] = 9;

thrust::device_vector<unsigned int> output(6);

thrust::lower_bound(input.begin(), input.end(),
                    values.begin(), values.end(),
                    output.begin(),
                    thrust::less<int>());
// output is now [0, 1, 1, 2, 4, 5]
```

**See** [http://www.sgi.com/tech/stl/lower\\_bound.html](http://www.sgi.com/tech/stl/lower_bound.html)

**See** `upper_bound`

**See** `equal_range`

**See** `binary_search`

### Template Function `thrust::make_pair`

- Defined in file `thrust_pair.h`

#### Function Documentation

```
template<typename T1, typename T2> __host__ __device__ pair<T1,T2> thrust::make_pair(T1 x, T2 y)
```

This convenience function creates a pair from two objects.

**Return** A newly-constructed pair copied from a and b.

#### Parameters

- x: The first object to copy from.
- y: The second object to copy from.

#### Template Parameters

- T1: There are no requirements on the type of T1.
- T2: There are no requirements on the type of T2.

### Template Function `thrust::make_tuple(const T0&`

- Defined in file `thrust_tuple.h`

#### Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::make_tuple`” with arguments (`const T0&`) in doxygen xml output for project “rocThrust” from directory: ./docBin/xml. Potential matches:

```
- template<class T0, class T1> __host__ __device__ detail::make_tuple_mapper<T0, T1>
  ::type thrust::make_tuple(const T0 &, const T1 &)
- template<class T0> __host__ __device__ detail::make_tuple_mapper<T0>::type
  thrust::make_tuple(const T0 &)
```

### Template Function `thrust::make_tuple(const T0&, const T1&`

#### Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::make_tuple`” with arguments (`const T0&`, `const T1&`) in doxygen xml output for project “rocThrust” from directory: ./docBin/xml. Potential matches:

```
- template<class T0, class T1> __host__ __device__ detail::make_tuple_mapper<T0, T1>
  ::type thrust::make_tuple(const T0 &, const T1 &)
- template<class T0> __host__ __device__ detail::make_tuple_mapper<T0>::type
  thrust::make_tuple(const T0 &)
```

**Template Function** `thrust::malloc(const thrust::detail::execution_policy_base<DerivedPolicy>&, std::size_t)`

- Defined in file\_thrust\_memory.h

## Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “thrust::malloc” with arguments (const thrust::detail::execution\_policy\_base<DerivedPolicy>&, std::size\_t) in doxygen xml output for project “roc-Thrust” from directory: ./docBin/xml. Potential matches:

```
- template<typename DerivedPolicy> __host__ __device__ pointer<void, DerivedPolicy> __  
  → thrust::malloc(const thrust::detail::execution_policy_base< DerivedPolicy > &, __  
  → std::size_t)  
- template<typename T, typename DerivedPolicy> __host__ __device__ pointer<T,  
  → DerivedPolicy> thrust::malloc(const thrust::detail::execution_policy_base<  
  → DerivedPolicy > &, std::size_t)
```

**Template Function** `thrust::malloc(const thrust::detail::execution_policy_base<DerivedPolicy>&, std::size_t)`

## Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “thrust::malloc” with arguments (const thrust::detail::execution\_policy\_base<DerivedPolicy>&, std::size\_t) in doxygen xml output for project “roc-Thrust” from directory: ./docBin/xml. Potential matches:

```
- template<typename DerivedPolicy> __host__ __device__ pointer<void, DerivedPolicy> __  
  → thrust::malloc(const thrust::detail::execution_policy_base< DerivedPolicy > &, __  
  → std::size_t)  
- template<typename T, typename DerivedPolicy> __host__ __device__ pointer<T,  
  → DerivedPolicy> thrust::malloc(const thrust::detail::execution_policy_base<  
  → DerivedPolicy > &, std::size_t)
```

**Template Function** `thrust::max_element(const thrust::detail::execution_policy_base<DerivedPolicy>&, ForwardIterator, ForwardIterator)`

- Defined in file\_thrust\_extrema.h

## Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “thrust::max\_element” with arguments (const thrust::detail::execution\_policy\_base<DerivedPolicy>&, ForwardIterator, ForwardIterator) in doxygen xml output for project “rocThrust” from directory: ./docBin/xml. Potential matches:

```
- template<typename DerivedPolicy, typename ForwardIterator, typename
BinaryPredicate>__host__ __device__ ForwardIterator thrust::max_element(const
thrust::detail::execution_policy_base< DerivedPolicy > &, ForwardIterator,
ForwardIterator, BinaryPredicate)
- template<typename DerivedPolicy, typename ForwardIterator>__host__ __device__
ForwardIterator thrust::max_element(const thrust::detail::execution_policy_base<
DerivedPolicy > &, ForwardIterator, ForwardIterator)
- template<typename ForwardIterator, typename BinaryPredicate>
ForwardIterator thrust::max_element(ForwardIterator, ForwardIterator,
BinaryPredicate)
- template<typename ForwardIterator>
ForwardIterator thrust::max_element(ForwardIterator, ForwardIterator)
```

## Template Function thrust::max\_element(ForwardIterator, ForwardIterator)

### Function Documentation

template<typename **ForwardIterator**>  
**ForwardIterator** thrust::**:max\_element** (**ForwardIterator** *first*, **ForwardIterator** *last*)  
*max\_element* finds the largest element in the range [*first*, *last*). It returns the first iterator *i* in [*first*, *last*) such that no other iterator in [*first*, *last*) points to a value larger than *\*i*. The return value is *last* if and only if [*first*, *last*) is an empty range.

The two versions of *max\_element* differ in how they define whether one element is greater than another. This version compares objects using operator<. Specifically, this version of *max\_element* returns the first iterator *i* in [*first*, *last*) such that, for every iterator *j* in [*first*, *last*), *\*i* < *\*j* is false.

```
#include <thrust/extrema.h>
...
int data[6] = {1, 0, 2, 2, 1, 3};
int *result = thrust::max_element(data, data + 6);

// *result == 3
```

**Return** An iterator pointing to the largest element of the range [*first*, *last*), if it is not an empty range; *last*, otherwise.

### Parameters

- *first*: The beginning of the sequence.
- *last*: The end of the sequence.

### Template Parameters

- **ForwardIterator**: is a model of **Forward Iterator**, and **ForwardIterator**'s **value\_type** is a model of **LessThan Comparable**.

See [http://www.sgi.com/tech/stl/max\\_element.html](http://www.sgi.com/tech/stl/max_element.html)

**Template Function `thrust::max_element(const thrust::detail::execution_policy_base<DerivedPolicy>&, ForwardIterator, ForwardIterator, BinaryPredicate)`****Function Documentation**

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::max_element`” with arguments (`const thrust::detail::execution_policy_base<DerivedPolicy>&`, `ForwardIterator`, `ForwardIterator`, `BinaryPredicate`) in doxygen xml output for project “rocThrust” from directory: `./docBin/xml`. Potential matches:

```
- template<typename DerivedPolicy, typename ForwardIterator, typename __host__ __device__ ForwardIterator thrust::max_element(const
→BinaryPredicate>__host__ __device__ ForwardIterator thrust::max_element(const
→thrust::detail::execution_policy_base< DerivedPolicy > &, ForwardIterator,
→ForwardIterator, BinaryPredicate))
- template<typename DerivedPolicy, typename ForwardIterator>__host__ __device__
→ForwardIterator thrust::max_element(const thrust::detail::execution_policy_base<
→DerivedPolicy > &, ForwardIterator, ForwardIterator))
- template<typename ForwardIterator, typename BinaryPredicate>
  ForwardIterator thrust::max_element(ForwardIterator, ForwardIterator,
→BinaryPredicate))
- template<typename ForwardIterator>
  ForwardIterator thrust::max_element(ForwardIterator, ForwardIterator)
```

**Template Function `thrust::max_element(ForwardIterator, ForwardIterator, BinaryPredicate)`****Function Documentation**

```
template<typename ForwardIterator, typename BinaryPredicate>
ForwardIterator thrust::max_element(ForwardIterator first, ForwardIterator last, BinaryPredicate
                                         comp)
max_element finds the largest element in the range [first, last). It returns the first iterator i in [first, last) such that no other iterator in [first, last) points to a value larger than *i. The return value is last if and only if [first, last) is an empty range.
```

The two versions of `max_element` differ in how they define whether one element is less than another. This version compares objects using a function object `comp`. Specifically, this version of `max_element` returns the first iterator i in [first, last) such that, for every iterator j in [first, last), `comp(*i, *j)` is false.

The following code snippet demonstrates how to use `max_element` to find the largest element of a collection of key-value pairs.

**Return** An iterator pointing to the largest element of the range [first, last), if it is not an empty range; last, otherwise.

**Parameters**

- `first`: The beginning of the sequence.
- `last`: The end of the sequence.
- `comp`: A binary predicate used for comparison.

**Template Parameters**

- `ForwardIterator`: is a model of `Forward Iterator`, and `ForwardIterator`'s `value_type` is convertible to both `comp`'s `first_argument_type` and `second_argument_type`.

- `BinaryPredicate`: is a model of `Binary Predicate`.

```
#include <thrust/extrema.h>

struct key_value
{
    int key;
    int value;
};

struct compare_key_value
{
    __host__ __device__
    bool operator()(key_value lhs, key_value rhs)
    {
        return lhs.key < rhs.key;
    }
};

...
key_value data[4] = { {4,5}, {0,7}, {2,3}, {6,1} };

key_value *largest = thrust::max_element(data, data + 4, compare_key_value());

// largest == data + 3
// *largest == {6,1}
```

See [http://www.sgi.com/tech/stl/max\\_element.html](http://www.sgi.com/tech/stl/max_element.html)

### Template Function `thrust::merge(const thrust::detail::execution_policy_base<DerivedPolicy>&, InputIterator1, InputIterator1, InputIterator2, InputIterator2, OutputIterator)`

- Defined in file\_thrust\_merge.h

## Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::merge`” with arguments (`const thrust::detail::execution_policy_base<DerivedPolicy>&`, `InputIterator1`, `InputIterator1`, `InputIterator2`, `InputIterator2`, `OutputIterator`) in doxygen xml output for project “rocThrust” from directory: ./docBin/xml. Potential matches:

```
- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2,
  ↵ typename OutputIterator, typename StrictWeakCompare> __host__ __device__ __
  ↵ OutputIterator thrust::merge(const thrust::detail::execution_policy_base<
  ↵ DerivedPolicy > &, InputIterator1, InputIterator1, InputIterator2, InputIterator2,
  ↵ OutputIterator, StrictWeakCompare)
- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2,
  ↵ typename OutputIterator> __host__ __device__ OutputIterator thrust::merge(const
  ↵ thrust::detail::execution_policy_base< DerivedPolicy > &, InputIterator1,
  ↵ InputIterator1, InputIterator2, InputIterator2, OutputIterator)
- template<typename InputIterator1, typename InputIterator2, typename
  ↵ OutputIterator, typename StrictWeakCompare>
  OutputIterator thrust::merge(InputIterator1, InputIterator1, InputIterator2,
  ↵ InputIterator2, OutputIterator, StrictWeakCompare)
- template<typename InputIterator1, typename InputIterator2, typename
  ↵ OutputIterator>
  OutputIterator thrust::merge(InputIterator1, InputIterator1, InputIterator2,
  ↵ InputIterator2, OutputIterator)
```

## Template Function `thrust::merge(InputIterator1, InputIterator1, InputIterator2, InputIterator2, OutputIterator)`

### Function Documentation

```
template<typename InputIterator1, typename InputIterator2, typename OutputIterator>
OutputIterator thrust::merge(InputIterator1 first1, InputIterator1 last1, InputIterator2 first2, InputIterator2 last2, OutputIterator result)
    merge combines two sorted ranges [first1, last1) and [first2, last2) into a single sorted
    range. That is, it copies from [first1, last1) and [first2, last2) into [result, result
    + (last1 - first1) + (last2 - first2)) such that the resulting range is in ascending order.
    merge is stable, meaning both that the relative order of elements within each input range is preserved, and
    that for equivalent elements in both input ranges the element from the first range precedes the element from the
    second. The return value is result + (last1 - first1) + (last2 - first2).
```

This version of `merge` compares elements using `operator<`.

The following code snippet demonstrates how to use `merge` to compute the merger of two sorted sets of integers.

**Return** The end of the output range.

**Pre** The ranges `[first1, last1)` and `[first2, last2)` shall be sorted with respect to `operator<`.

**Pre** The resulting range shall not overlap with either input range.

#### Parameters

- `first1`: The beginning of the first input range.
- `last1`: The end of the first input range.
- `first2`: The beginning of the second input range.
- `last2`: The end of the second input range.
- `result`: The beginning of the merged output.

#### Template Parameters

- `InputIterator1`: is a model of `Input Iterator`, `InputIterator1` and `InputIterator2` have the same `value_type`, `InputIterator1`'s `value_type` is a model of `LessThan Comparable`, the ordering on `InputIterator1`'s `value_type` is a strict weak ordering, as defined in the `LessThan Comparable` requirements, and `InputIterator1`'s `value_type` is convertible to a type in `OutputIterator`'s set of `value_types`.
- `InputIterator2`: is a model of `Input Iterator`, `InputIterator2` and `InputIterator1` have the same `value_type`, `InputIterator2`'s `value_type` is a model of `LessThan Comparable`, the ordering on `InputIterator2`'s `value_type` is a strict weak ordering, as defined in the `LessThan Comparable` requirements, and `InputIterator2`'s `value_type` is convertible to a type in `OutputIterator`'s set of `value_types`.
- `OutputIterator`: is a model of `Output Iterator`.

```
#include <thrust/merge.h>
...
int A1[6] = {1, 3, 5, 7, 9, 11};
int A2[7] = {1, 1, 2, 3, 5, 8, 13};
```

(continues on next page)

(continued from previous page)

```
int result[13];

int *result_end = thrust::merge(A1, A1 + 6, A2, A2 + 7, result);
// result = {1, 1, 1, 2, 3, 3, 5, 5, 7, 8, 9, 11, 13}
```

See <http://www.sgi.com/tech/stl/merge.html>

See `set_union`

See `sort`

See `is_sorted`

**Template Function `thrust::merge(const thrust::detail::execution_policy_base<DerivedPolicy>&, InputIterator1, InputIterator1, InputIterator2, InputIterator2, OutputIterator, StrictWeakCompare)`**

## Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::merge`” with arguments (`const thrust::detail::execution_policy_base<DerivedPolicy>&`, `InputIterator1`, `InputIterator1`, `InputIterator2`, `InputIterator2`, `OutputIterator`, `StrictWeakCompare`) in doxygen xml output for project “rocThrust” from directory: `./docBin/xml`. Potential matches:

```
- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2,
          typename OutputIterator, typename StrictWeakCompare> __host__ __device__
          OutputIterator thrust::merge(const thrust::detail::execution_policy_base<
          DerivedPolicy > &, InputIterator1, InputIterator1, InputIterator2, InputIterator2,
          OutputIterator, StrictWeakCompare)
- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2,
          typename OutputIterator> __host__ __device__ OutputIterator thrust::merge(const_
          thrust::detail::execution_policy_base< DerivedPolicy > &, InputIterator1,_
          InputIterator1, InputIterator2, InputIterator2, OutputIterator)
- template<typename InputIterator1, typename InputIterator2, typename_
          OutputIterator, typename StrictWeakCompare>
          OutputIterator thrust::merge(InputIterator1, InputIterator1, InputIterator2,_
          InputIterator2, OutputIterator, StrictWeakCompare)
- template<typename InputIterator1, typename InputIterator2, typename_
          OutputIterator>
          OutputIterator thrust::merge(InputIterator1, InputIterator1, InputIterator2,_
          InputIterator2, OutputIterator)
```

**Template Function `thrust::merge(InputIterator1, InputIterator1, InputIterator2, InputIterator2, OutputIterator, StrictWeakCompare)`**

## Function Documentation

```
template<typename InputIterator1, typename InputIterator2, typename OutputIterator, typename StrictWeakCompare>
OutputIterator thrust::merge(InputIterator1 first1, InputIterator1 last1, InputIterator2 first2, InputIterator2 last2, OutputIterator result, StrictWeakCompare comp)
```

`merge` combines two sorted ranges  $[first1, last1]$  and  $[first2, last2]$  into a single sorted range. That is, it copies from  $[first1, last1]$  and  $[first2, last2]$  into  $[result, result + (last1 - first1) + (last2 - first2)]$  such that the resulting range is in ascending order.

`merge` is stable, meaning both that the relative order of elements within each input range is preserved, and that for equivalent elements in both input ranges the element from the first range precedes the element from the second. The return value is `result + (last1 - first1) + (last2 - first2)`.

This version of `merge` compares elements using a function object `comp`.

The following code snippet demonstrates how to use `merge` to compute the merger of two sets of integers sorted in descending order.

**Return** The end of the output range.

**Pre** The ranges `[first1, last1]` and `[first2, last2]` shall be sorted with respect to `comp`.

**Pre** The resulting range shall not overlap with either input range.

### Parameters

- `first1`: The beginning of the first input range.
- `last1`: The end of the first input range.
- `first2`: The beginning of the second input range.
- `last2`: The end of the second input range.
- `result`: The beginning of the merged output.
- `comp`: Comparison operator.

### Template Parameters

- `InputIterator1`: is a model of `Input Iterator`, `InputIterator1`'s `value_type` is convertible to `StrictWeakCompare`'s `first_argument_type`. and `InputIterator1`'s `value_type` is convertible to a type in `OutputIterator`'s set of `value_types`.
- `InputIterator2`: is a model of `Input Iterator`, `InputIterator2`'s `value_type` is convertible to `StrictWeakCompare`'s `second_argument_type`. and `InputIterator2`'s `value_type` is convertible to a type in `OutputIterator`'s set of `value_types`.
- `OutputIterator`: is a model of `Output Iterator`.
- `StrictWeakCompare`: is a model of `Strict Weak Ordering`.

```
#include <thrust/merge.h>
#include <thrust/functional.h>
...
int A1[6] = {11, 9, 7, 5, 3, 1};
int A2[7] = {13, 8, 5, 3, 2, 1, 1};

int result[13];

int *result_end = thrust::merge(A1, A1 + 6, A2, A2 + 7, result, thrust::greater
                                <int>());
// result = {13, 11, 9, 8, 7, 5, 5, 3, 3, 2, 1, 1, 1}
```

**See** <http://www.sgi.com/tech/stl/merge.html>

**See** `sort`

**See** `is_sorted`

**Template Function `thrust::merge_by_key(const thrust::detail::execution_policy_base<DerivedPolicy>&, InputIterator1, InputIterator1, InputIterator2, InputIterator2, InputIterator3, InputIterator4, OutputIterator1, OutputIterator2)`**

- Defined in file `thrust_merge.h`

## Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::merge_by_key`” with arguments (`const thrust::detail::execution_policy_base<DerivedPolicy>&`, `InputIterator1`, `InputIterator1`, `InputIterator2`, `InputIterator2`, `InputIterator3`, `InputIterator4`, `OutputIterator1`, `OutputIterator2`) in doxygen xml output for project “rocThrust” from directory: `./docBin/xml`. Potential matches:

```
- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2,
         ~typename InputIterator3, typename InputIterator4, typename OutputIterator1,
         ~typename OutputIterator2, typename Compare> __host__ __device__ thrust::pair
         <OutputIterator1,OutputIterator2> thrust::merge_by_key(const
         ~thrust::detail::execution_policy_base< DerivedPolicy > &, InputIterator1,
         ~InputIterator1, InputIterator2, InputIterator2, InputIterator3, InputIterator4,
         ~OutputIterator1, OutputIterator2, Compare)
- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2,
         ~typename InputIterator3, typename InputIterator4, typename OutputIterator1,
         ~typename OutputIterator2> __host__ __device__ thrust::pair<OutputIterator1,
         ~OutputIterator2> thrust::merge_by_key(const thrust::detail::execution_policy_base
         < DerivedPolicy > &, InputIterator1, InputIterator1, InputIterator2,
         ~InputIterator2, InputIterator3, InputIterator4, OutputIterator1, OutputIterator2)
- template<typename InputIterator1, typename InputIterator2, typename
         ~InputIterator3, typename InputIterator4, typename OutputIterator1, typename
         ~OutputIterator2, typename StrictWeakCompare>
         thrust::pair<OutputIterator1, OutputIterator2> thrust::merge_by_
         key(InputIterator1, InputIterator1, InputIterator2, InputIterator2,
         ~InputIterator3, InputIterator4, OutputIterator1, OutputIterator2,
         ~StrictWeakCompare)
- template<typename InputIterator1, typename InputIterator2, typename
         ~InputIterator3, typename InputIterator4, typename OutputIterator1, typename
         ~OutputIterator2>
         thrust::pair<OutputIterator1, OutputIterator2> thrust::merge_by_
         key(InputIterator1, InputIterator1, InputIterator2, InputIterator2,
         ~InputIterator3, InputIterator4, OutputIterator1, OutputIterator2)
```

**Template Function `thrust::merge_by_key(InputIterator1, InputIterator1, InputIterator2, InputIterator2, InputIterator3, InputIterator4, OutputIterator1, OutputIterator2)`**

## Function Documentation

```
template<typename InputIterator1, typename InputIterator2, typename InputIterator3, typename InputIterator4, typename OutputIterator1, typename OutputIterator2>
```

```
thrust::pair<OutputIterator1, OutputIterator2> thrust::merge_by_key(InputIterator1 keys_first1, InputIterator1 keys_last1, InputIterator2 keys_first2, InputIterator2 keys_last2, InputIterator3 values_first1, InputIterator4 values_first2, OutputIterator1 keys_result, OutputIterator2 values_result)
```

`merge_by_key` performs a key-value merge. That is, `merge_by_key` copies elements from  $[keys\_first1, keys\_last1]$  and  $[keys\_first2, keys\_last2]$  into a single range,  $[keys\_result, keys\_result + (keys\_last1 - keys\_first1) + (keys\_last2 - keys\_first2)]$  such that the resulting range is in ascending key order.

At the same time, `merge_by_key` copies elements from the two associated ranges  $[values\_first1 + (keys\_last1 - keys\_first1)]$  and  $[values\_first2 + (keys\_last2 - keys\_first2)]$  into a single range,  $[values\_result, values\_result + (keys\_last1 - keys\_first1) + (keys\_last2 - keys\_first2)]$  such that the resulting range is in ascending order implied by each input element's associated key.

`merge_by_key` is stable, meaning both that the relative order of elements within each input range is preserved, and that for equivalent elements in all input key ranges the element from the first range precedes the element from the second.

The return value is  $(keys\_result + (keys\_last1 - keys\_first1) + (keys\_last2 - keys\_first2))$  and  $(values\_result + (keys\_last1 - keys\_first1) + (keys\_last2 - keys\_first2))$ .

The following code snippet demonstrates how to use `merge_by_key` to compute the merger of two sets of integers sorted in ascending order.

**Return** A pair `p` such that `p.first` is the end of the output range of keys, and such that `p.second` is the end of the output range of values.

**Pre** The ranges  $[keys\_first1, keys\_last1]$  and  $[keys\_first2, keys\_last2]$  shall be sorted with respect to operator`<`.

**Pre** The resulting ranges shall not overlap with any input range.

### Parameters

- `keys_first1`: The beginning of the first input range of keys.
- `keys_last1`: The end of the first input range of keys.
- `keys_first2`: The beginning of the second input range of keys.
- `keys_last2`: The end of the second input range of keys.
- `values_first1`: The beginning of the first input range of values.
- `values_first2`: The beginning of the first input range of values.
- `keys_result`: The beginning of the merged output range of keys.
- `values_result`: The beginning of the merged output range of values.

### Template Parameters

- `InputIterator1`: is a model of `Input Iterator`, `InputIterator1` and `InputIterator2` have the same `value_type`, `InputIterator1`'s `value_type` is a model of `LessThan Comparable`, the ordering on `InputIterator1`'s `value_type` is a strict weak ordering, as defined in the `LessThan Comparable` requirements, and `InputIterator1`'s `value_type` is convertible to a type in `OutputIterator`'s set of `value_types`.

- InputIterator2: is a model of Input Iterator, InputIterator2 and InputIterator1 have the same value\_type, InputIterator2's value\_type is a model of LessThan Comparable, the ordering on InputIterator2's value\_type is a strict weak ordering, as defined in the LessThan Comparable requirements, and InputIterator2's value\_type is convertible to a type in OutputIterator's set of value\_types.
- InputIterator3: is a model of Input Iterator, and InputIterator3's value\_type is convertible to a type in OutputIterator2's set of value\_types.
- InputIterator4: is a model of Input Iterator, and InputIterator4's value\_type is convertible to a type in OutputIterator2's set of value\_types.
- OutputIterator1: is a model of Output Iterator.
- OutputIterator2: is a model of Output Iterator.

```
#include <thrust/merge.h>
#include <thrust/functional.h>
...
int A_keys[6] = {1, 3, 5, 7, 9, 11};
int A_vals[6] = {0, 0, 0, 0, 0, 0};

int B_keys[7] = {1, 1, 2, 3, 5, 8, 13};
int B_vals[7] = {1, 1, 1, 1, 1, 1, 1};

int keys_result[13];
int vals_result[13];

thrust::pair<int*, int*> end = thrust::merge_by_key(A_keys, A_keys + 6, B_keys, B_
keys + 7, A_vals, B_vals, keys_result, vals_result);

// keys_result = {1, 1, 1, 2, 3, 3, 5, 5, 7, 8, 9, 11, 13}
// vals_result = {0, 1, 1, 1, 0, 1, 0, 1, 0, 1, 0, 0, 1}
```

**See** merge

**See** sort\_by\_key

**See** is\_sorted

**Template Function** `thrust::merge_by_key(const thrust::detail::execution_policy_base<DerivedPolicy>&, InputIterator1, InputIterator1, InputIterator2, InputIterator2, InputIterator3, InputIterator4, OutputIterator1, OutputIterator2, Compare)`

## Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “thrust::merge\_by\_key” with arguments (const thrust::detail::execution\_policy\_base<DerivedPolicy>&, InputIterator1, InputIterator1, InputIterator2, InputIterator2, InputIterator3, InputIterator4, OutputIterator1, OutputIterator2, Compare) in doxygen xml output for project “rocThrust” from directory: ./docBin/xml. Potential matches:

```
- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2,
→ typename InputIterator3, typename InputIterator4, typename OutputIterator1,
→ typename OutputIterator2, typename Compare> __host__ __device__ thrust::pair
→<OutputIterator1,OutputIterator2> thrust::merge_by_key(const_
→thrust::detail::execution_policy_base< DerivedPolicy > &, InputIterator1,
→InputIterator1, InputIterator2, InputIterator2, InputIterator3, InputIterator4,
→OutputIterator1, OutputIterator2, Compare)
- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2,
→ typename InputIterator3, typename InputIterator4, typename OutputIterator1,
→ typename OutputIterator2> __host__ __device__ thrust::pair<OutputIterator1,
→OutputIterator2> thrust::merge_by_key(const_ thrust::detail::execution_policy_base
→< DerivedPolicy > &, InputIterator1, InputIterator1, InputIterator2,
→InputIterator2, InputIterator3, InputIterator4, OutputIterator1, OutputIterator2)
- template<typename InputIterator1, typename InputIterator2, typename_
→InputIterator3, typename InputIterator4, typename OutputIterator1, typename_
→OutputIterator2, typename StrictWeakCompare>
    thrust::pair<OutputIterator1, OutputIterator2> thrust::merge_by_
→key(InputIterator1, InputIterator1, InputIterator2, InputIterator2,
→InputIterator3, InputIterator4, OutputIterator1, OutputIterator2,
→StrictWeakCompare)
- template<typename InputIterator1, typename InputIterator2, typename_
→InputIterator3, typename InputIterator4, typename OutputIterator1, typename_
→OutputIterator2>
    thrust::pair<OutputIterator1, OutputIterator2> thrust::merge_by_
→key(InputIterator1, InputIterator1, InputIterator2, InputIterator2,
→InputIterator3, InputIterator4, OutputIterator1, OutputIterator2)
```

**Template Function `thrust::merge_by_key(InputIterator1, InputIterator1, InputIterator2, InputIterator2, InputIterator3, InputIterator4, OutputIterator1, OutputIterator2, StrictWeakCompare)`**

## Function Documentation

```
template<typename InputIterator1, typename InputIterator2, typename InputIterator3, typename InputIterator4,
thrust::pair<OutputIterator1, OutputIterator2> thrust::merge_by_key (InputIterator1 keys_first1, In-
putIterator1 keys_last1, InputIterator2 keys_first2, InputIterator2 keys_last2, InputItera-
tor3 values_first1, InputIterator4 values_first2, OutputIterator1 keys_result, OutputItera-
tor2 values_result, StrictWeak-
Compare comp)
```

`merge_by_key` performs a key-value merge. That is, `merge_by_key` copies elements from  $[keys\_first1, keys\_last1]$  and  $[keys\_first2, keys\_last2]$  into a single range,  $[keys\_result, keys\_result + (keys\_last1 - keys\_first1) + (keys\_last2 - keys\_first2)]$  such that the resulting range is in ascending key order.

At the same time, `merge_by_key` copies elements from the two associated ranges  $[values\_first1 + (keys\_last1 - keys\_first1)]$  and  $[values\_first2 + (keys\_last2 - keys\_first2)]$  into a single range,  $[values\_result, values\_result + (keys\_last1 - keys\_first1) + (keys\_last2 - keys\_first2)]$  such that the resulting range is in ascending order implied by each input element's associated key.

`merge_by_key` is stable, meaning both that the relative order of elements within each input range is preserved,

and that for equivalent elements in all input key ranges the element from the first range precedes the element from the second.

The return value is  $\min(\text{keys\_result} + (\text{keys\_last1} - \text{keys\_first1}) + (\text{keys\_last2} - \text{keys\_first2}), \text{values\_result} + (\text{keys\_last1} - \text{keys\_first1}) + (\text{keys\_last2} - \text{keys\_first2}))$ .

This version of `merge_by_key` compares key elements using a function object `comp`.

The following code snippet demonstrates how to use `merge_by_key` to compute the merger of two sets of integers sorted in descending order.

**Return** A pair `p` such that `p.first` is the end of the output range of keys, and such that `p.second` is the end of the output range of values.

**Pre** The ranges `[keys_first1, keys_last1]` and `[keys_first2, keys_last2]` shall be sorted with respect to `comp`.

**Pre** The resulting ranges shall not overlap with any input range.

### Parameters

- `keys_first1`: The beginning of the first input range of keys.
- `keys_last1`: The end of the first input range of keys.
- `keys_first2`: The beginning of the second input range of keys.
- `keys_last2`: The end of the second input range of keys.
- `values_first1`: The beginning of the first input range of values.
- `values_first2`: The beginning of the first input range of values.
- `keys_result`: The beginning of the merged output range of keys.
- `values_result`: The beginning of the merged output range of values.
- `comp`: Comparison operator.

### Template Parameters

- `InputIterator1`: is a model of `Input Iterator`, `InputIterator1`'s `value_type` is convertible to `StrictWeakCompare`'s `first_argument_type`. and `InputIterator1`'s `value_type` is convertible to a type in `OutputIterator1`'s set of `value_types`.
- `InputIterator2`: is a model of `Input Iterator`, `InputIterator2`'s `value_type` is convertible to `StrictWeakCompare`'s `second_argument_type`. and `InputIterator2`'s `value_type` is convertible to a type in `OutputIterator1`'s set of `value_types`.
- `InputIterator3`: is a model of `Input Iterator`, and `InputIterator3`'s `value_type` is convertible to a type in `OutputIterator2`'s set of `value_types`.
- `InputIterator4`: is a model of `Input Iterator`, and `InputIterator4`'s `value_type` is convertible to a type in `OutputIterator2`'s set of `value_types`.
- `OutputIterator1`: is a model of `Output Iterator`.
- `OutputIterator2`: is a model of `Output Iterator`.
- `StrictWeakCompare`: is a model of `Strict Weak Ordering`.

```
#include <thrust/merge.h>
#include <thrust/functional.h>
...
int A_keys[6] = {11, 9, 7, 5, 3, 1};
```

(continues on next page)

(continued from previous page)

```

int A_vals[6] = { 0, 0, 0, 0, 0, 0};

int B_keys[7] = {13, 8, 5, 3, 2, 1, 1};
int B_vals[7] = { 1, 1, 1, 1, 1, 1, 1};

int keys_result[13];
int vals_result[13];

thrust::pair<int*,int*> end = thrust::merge_by_key(A_keys, A_keys + 6, B_keys, B_
keys + 7, A_vals, B_vals, keys_result, vals_result, thrust::greater<int>());

// keys_result = {13, 11, 9, 8, 7, 5, 5, 3, 3, 2, 1, 1, 1}
// vals_result = { 1, 0, 0, 1, 0, 0, 1, 0, 1, 1, 0, 1, 1}

```

**See** merge**See** sort\_by\_key**See** is\_sorted**Template Function thrust::min\_element(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, ForwardIterator, ForwardIterator)**

- Defined in file\_thrust\_extrema.h

**Function Documentation**

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “thrust::min\_element” with arguments (const thrust::detail::execution\_policy\_base<DerivedPolicy>&, ForwardIterator, ForwardIterator) in doxygen xml output for project “rocThrust” from directory: ./docBin/xml. Potential matches:

```

- template<typename DerivedPolicy, typename ForwardIterator, typename_
BinaryPredicate>__host__ __device__ ForwardIterator thrust::min_element(const_
thrust::detail::execution_policy_base< DerivedPolicy > &, ForwardIterator,_
ForwardIterator, BinaryPredicate)
- template<typename DerivedPolicy, typename ForwardIterator>__host__ __device___
ForwardIterator thrust::min_element(const thrust::detail::execution_policy_base<_
DerivedPolicy > &, ForwardIterator, ForwardIterator)
- template<typename ForwardIterator, typename BinaryPredicate>
ForwardIterator thrust::min_element(ForwardIterator, ForwardIterator,_
BinaryPredicate)
- template<typename ForwardIterator>
ForwardIterator thrust::min_element(ForwardIterator, ForwardIterator)

```

**Template Function thrust::min\_element(ForwardIterator, ForwardIterator)****Function Documentation**template<typename **ForwardIterator**>

*ForwardIterator* `thrust::min_element(ForwardIterator first, ForwardIterator last)`

`min_element` finds the smallest element in the range `[first, last]`. It returns the first iterator `i` in `[first, last]` such that no other iterator in `[first, last]` points to a value smaller than `*i`. The return value is `last` if and only if `[first, last]` is an empty range.

The two versions of `min_element` differ in how they define whether one element is less than another. This version compares objects using `operator<`. Specifically, this version of `min_element` returns the first iterator `i` in `[first, last]` such that, for every iterator `j` in `[first, last]`,  $*j < *i$  is false.

```
#include <thrust/extrema.h>
...
int data[6] = {1, 0, 2, 2, 1, 3};
int *result = thrust::min_element(data, data + 6);

// result is data + 1
// *result is 0
```

**Return** An iterator pointing to the smallest element of the range `[first, last]`, if it is not an empty range; `last`, otherwise.

#### Parameters

- `first`: The beginning of the sequence.
- `last`: The end of the sequence.

#### Template Parameters

- `ForwardIterator`: is a model of `Forward Iterator`, and `ForwardIterator`'s `value_type` is a model of `LessThan Comparable`.

See [http://www.sgi.com/tech/stl/min\\_element.html](http://www.sgi.com/tech/stl/min_element.html)

**Template Function** `thrust::min_element(const thrust::detail::execution_policy_base<DerivedPolicy>&, ForwardIterator, ForwardIterator, BinaryPredicate)`

#### Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::min_element`” with arguments (`const thrust::detail::execution_policy_base<DerivedPolicy>&`, `ForwardIterator`, `ForwardIterator`, `BinaryPredicate`) in doxygen xml output for project “rocThrust” from directory: `./docBin/xml`. Potential matches:

```
- template<typename DerivedPolicy, typename ForwardIterator, typename_
↳BinaryPredicate>__host__ __device__ ForwardIterator thrust::min_element(const_
↳thrust::detail::execution_policy_base< DerivedPolicy > &, ForwardIterator,_
↳ForwardIterator, BinaryPredicate)
- template<typename DerivedPolicy, typename ForwardIterator>__host__ __device__
↳ForwardIterator thrust::min_element(const thrust::detail::execution_policy_base<_
↳DerivedPolicy > &, ForwardIterator, ForwardIterator)
- template<typename ForwardIterator, typename BinaryPredicate>
  ForwardIterator thrust::min_element(ForwardIterator, ForwardIterator,_
  ↳BinaryPredicate)
- template<typename ForwardIterator>
  ForwardIterator thrust::min_element(ForwardIterator, ForwardIterator)
```

## Template Function `thrust::min_element(ForwardIterator, ForwardIterator, BinaryPredicate)`

### Function Documentation

```
template<typename ForwardIterator, typename BinaryPredicate>
ForwardIterator thrust::min_element (ForwardIterator first, ForwardIterator last, BinaryPredicate
                                         comp)
```

`min_element` finds the smallest element in the range  $[first, last]$ . It returns the first iterator *i* in  $[first, last]$  such that no other iterator in  $[first, last]$  points to a value smaller than  $*i$ . The return value is *last* if and only if  $[first, last]$  is an empty range.

The two versions of `min_element` differ in how they define whether one element is less than another. This version compares objects using a function object `comp`. Specifically, this version of `min_element` returns the first iterator *i* in  $[first, last]$  such that, for every iterator *j* in  $[first, last]$ , `comp(*j, *i)` is false.

The following code snippet demonstrates how to use `min_element` to find the smallest element of a collection of key-value pairs.

**Return** An iterator pointing to the smallest element of the range  $[first, last]$ , if it is not an empty range; *last*, otherwise.

### Parameters

- *first*: The beginning of the sequence.
- *last*: The end of the sequence.
- *comp*: A binary predicate used for comparison.

### Template Parameters

- `ForwardIterator`: is a model of `Forward Iterator`, and `ForwardIterator`'s `value_type` is convertible to both `comp`'s `first_argument_type` and `second_argument_type`.
- `BinaryPredicate`: is a model of `Binary Predicate`.

```
#include <thrust/extrema.h>

struct key_value
{
    int key;
    int value;
};

struct compare_key_value
{
    __host__ __device__
    bool operator() (key_value lhs, key_value rhs)
    {
        return lhs.key < rhs.key;
    }
};

...
key_value data[4] = { {4,5}, {0,7}, {2,3}, {6,1} };

key_value *smallest = thrust::min_element(data, data + 4, compare_key_value());
```

(continues on next page)

(continued from previous page)

```
// smallest == data + 1
// *smallest == {0, 7}
```

See [http://www.sgi.com/tech/stl/min\\_element.html](http://www.sgi.com/tech/stl/min_element.html)

### Template Function `thrust::minmax_element(const thrust::detail::execution_policy_base<DerivedPolicy>&, ForwardIterator, ForwardIterator)`

- Defined in file `thrust_extrema.h`

#### Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::minmax_element`” with arguments (`const thrust::detail::execution_policy_base<DerivedPolicy>&`, `ForwardIterator`, `ForwardIterator`) in doxygen xml output for project “rocThrust” from directory: `./docBin/xml`. Potential matches:

```
- template<typename DerivedPolicy, typename ForwardIterator, typename_
  ↪BinaryPredicate>__host__ __device__ thrust::pair<ForwardIterator,ForwardIterator>_
  ↪thrust::minmax_element(const thrust::detail::execution_policy_base< DerivedPolicy_>_
  ↪> &, ForwardIterator, ForwardIterator, BinaryPredicate)
- template<typename DerivedPolicy, typename ForwardIterator>__host__ __device___
  ↪thrust::pair<ForwardIterator,ForwardIterator> thrust::minmax_element(const_
  ↪thrust::detail::execution_policy_base< DerivedPolicy > &, ForwardIterator,_
  ↪ForwardIterator)
- template<typename ForwardIterator, typename BinaryPredicate>
  thrust::pair<ForwardIterator, ForwardIterator> thrust::minmax_
  ↪element(ForwardIterator, ForwardIterator, BinaryPredicate)
- template<typename ForwardIterator>
  thrust::pair<ForwardIterator, ForwardIterator> thrust::minmax_
  ↪element(ForwardIterator, ForwardIterator)
```

### Template Function `thrust::minmax_element(ForwardIterator, ForwardIterator)`

#### Function Documentation

```
template<typename ForwardIterator>
thrust::pair<ForwardIterator, ForwardIterator> thrust::minmax_element(ForwardIterator first, For-
wardIterator last)
```

`minmax_element` finds the smallest and largest elements in the range `[first, last]`. It returns a pair of iterators (`imin, imax`) where `imin` is the same iterator returned by `min_element` and `imax` is the same iterator returned by `max_element`. This function is potentially more efficient than separate calls to `min_element` and `max_element`.

```
#include <thrust/extrema.h>
...
int data[6] = {1, 0, 2, 2, 1, 3};
thrust::pair<int *, int *> result = thrust::minmax_element(data, data + 6);

// result.first is data + 1
```

(continues on next page)

(continued from previous page)

```
// result.second is data + 5
// *result.first is 0
// *result.second is 3
```

**Return** A pair of iterator pointing to the smallest and largest elements of the range [first, last), if it is not an empty range; last, otherwise.

### Parameters

- first: The beginning of the sequence.
- last: The end of the sequence.

### Template Parameters

- ForwardIterator: is a model of [Forward Iterator](#), and ForwardIterator's value\_type is a model of [LessThan Comparable](#).

**See** [min\\_element](#)

**See** [max\\_element](#)

**See** <http://www.open-std.org/jtc1/sc22/wg21/docs/papers/2005/n1840.pdf>

## Template Function `thrust::minmax_element(const thrust::detail::execution_policy_base<DerivedPolicy>&, ForwardIterator, ForwardIterator, BinaryPredicate)`

### Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “thrust::minmax\_element” with arguments (const thrust::detail::execution\_policy\_base<DerivedPolicy>&, ForwardIterator, ForwardIterator, BinaryPredicate) in doxygen xml output for project “rocThrust” from directory: ./docBin/xml. Potential matches:

```
- template<typename DerivedPolicy, typename ForwardIterator, typename
  ↳BinaryPredicate>__host__ __device__ thrust::pair<ForwardIterator,ForwardIterator>
  ↳thrust::minmax_element(const thrust::detail::execution_policy_base< DerivedPolicy,
  ↳> &, ForwardIterator, ForwardIterator, BinaryPredicate)
- template<typename DerivedPolicy, typename ForwardIterator>__host__ __device__
  ↳thrust::pair<ForwardIterator,ForwardIterator> thrust::minmax_element(const
  ↳thrust::detail::execution_policy_base< DerivedPolicy > &, ForwardIterator,<
  ↳ForwardIterator)
- template<typename ForwardIterator, typename BinaryPredicate>
  thrust::pair<ForwardIterator, ForwardIterator> thrust::minmax_
  ↳element(ForwardIterator, ForwardIterator, BinaryPredicate)
- template<typename ForwardIterator>
  thrust::pair<ForwardIterator, ForwardIterator> thrust::minmax_
  ↳element(ForwardIterator, ForwardIterator)
```

## Template Function `thrust::minmax_element(ForwardIterator, ForwardIterator, BinaryPredicate)`

### Function Documentation

`template<typename ForwardIterator, typename BinaryPredicate>`

```
thrust::pair<ForwardIterator, ForwardIterator> thrust::minmax_element(ForwardIterator first,
                                                               ForwardIterator last,
                                                               BinaryPredicate comp)
```

`minmax_element` finds the smallest and largest elements in the range `[first, last]`. It returns a pair of iterators (`imin, imax`) where `imin` is the same iterator returned by `min_element` and `imax` is the same iterator returned by `max_element`. This function is potentially more efficient than separate calls to `min_element` and `max_element`.

The following code snippet demonstrates how to use `minmax_element` to find the smallest and largest elements of a collection of key-value pairs.

**Return** A pair of iterator pointing to the smallest and largest elements of the range `[first, last]`, if it is not an empty range; `last`, otherwise.

### Parameters

- `first`: The beginning of the sequence.
- `last`: The end of the sequence.
- `comp`: A binary predicate used for comparison.

### Template Parameters

- `ForwardIterator`: is a model of `Forward Iterator`, and `ForwardIterator`'s `value_type` is convertible to both `comp`'s `first_argument_type` and `second_argument_type`.
- `BinaryPredicate`: is a model of `Binary Predicate`.

```
#include <thrust/extrema.h>
#include <thrust/pair.h>

struct key_value
{
    int key;
    int value;
};

struct compare_key_value
{
    __host__ __device__
    bool operator()(key_value lhs, key_value rhs)
    {
        return lhs.key < rhs.key;
    }
};

...
key_value data[4] = { {4,5}, {0,7}, {2,3}, {6,1} };

thrust::pair<key_value*,key_value*> extrema = thrust::minmax_element(data, data + 4, compare_key_value());

// extrema.first == data + 1
// *extrema.first == {0,7}
// extrema.second == data + 3
// *extrema.second == {6,1}
```

See `min_element`

See `max_element`

See <http://www.open-std.org/jtc1/sc22/wg21/docs/papers/2005/n1840.pdf>

### Template Function `thrust::mismatch(const thrust::detail::execution_policy_base<DerivedPolicy>&, InputIterator1, InputIterator1, InputIterator2)`

- Defined in file `thrust_mismatch.h`

#### Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::mismatch`” with arguments `(const thrust::detail::execution_policy_base<DerivedPolicy>&, InputIterator1, InputIterator1, InputIterator2)` in doxygen xml output for project “rocThrust” from directory: `./docBin/xml`. Potential matches:

```
- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2,
          typename BinaryPredicate> __host__ __device__ thrust::pair<InputIterator1,
          InputIterator2> thrust::mismatch(const thrust::detail::execution_policy_base<
          DerivedPolicy > &, InputIterator1, InputIterator1, InputIterator2, typename
          BinaryPredicate)
- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2>
  __host__ __device__ thrust::pair<InputIterator1, InputIterator2> thrust::mismatch(const
  thrust::detail::execution_policy_base< DerivedPolicy > &, typename
  InputIterator1, InputIterator1, InputIterator2)
- template<typename InputIterator1, typename InputIterator2, typename
  BinaryPredicate>
  thrust::pair<InputIterator1, InputIterator2> thrust::mismatch(InputIterator1, typename
  InputIterator1, InputIterator2, BinaryPredicate)
- template<typename InputIterator1, typename InputIterator2>
  thrust::pair<InputIterator1, InputIterator2> thrust::mismatch(InputIterator1, typename
  InputIterator1, InputIterator2)
```

### Template Function `thrust::mismatch(InputIterator1, InputIterator1, InputIterator2)`

#### Function Documentation

```
template<typename InputIterator1, typename InputIterator2>
thrust::pair<InputIterator1, InputIterator2> thrust::mismatch(InputIterator1 first1, InputIterator1 last1,
                                                               InputIterator2 first2)
mismatch finds the first position where the two ranges [first1, last1) and [first2, first2 +
(last1 - first1)) differ. The two versions of mismatch use different tests for whether elements differ.

This version of mismatch finds the first iterator i in [first1, last1) such that *i == *(first2 +
(i - first1)) is false. The return value is a pair whose first element is i and whose second element is
*(first2 + (i - first1)). If no such iterator i exists, the return value is a pair whose first element
is last1 and whose second element is *(first2 + (last1 - first1)).
```

```
#include <thrust/mismatch.h>
#include <thrust/device_vector.h>
...
thrust::device_vector<int> vec1(4);
thrust::device_vector<int> vec2(4);
```

(continues on next page)

(continued from previous page)

```

vec1[0] = 0;  vec2[0] = 0;
vec1[1] = 5;  vec2[1] = 5;
vec1[2] = 3;  vec2[2] = 8;
vec1[3] = 7;  vec2[3] = 7;

typedef thrust::device_vector<int>::iterator Iterator;
thrust::pair<Iterator, Iterator> result;

result = thrust::mismatch(vec1.begin(), vec1.end(), vec2.begin());

// result.first is vec1.begin() + 2
// result.second is vec2.begin() + 2

```

**Return** The first position where the sequences differ.

#### Parameters

- `first1`: The beginning of the first sequence.
- `last1`: The end of the first sequence.
- `first2`: The beginning of the second sequence.

#### Template Parameters

- `InputIterator1`: is a model of `Input Iterator` and `InputIterator1`'s `value_type` is equality comparable to `InputIterator2`'s `value_type`.
- `InputIterator2`: is a model of `Input Iterator`.

**See** `find`

**See** `find_if`

**Template Function** `thrust::mismatch(const thrust::detail::execution_policy_base<DerivedPolicy>&, InputIterator1, InputIterator1, InputIterator2, BinaryPredicate)`

#### Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::mismatch`” with arguments (`const thrust::detail::execution_policy_base<DerivedPolicy>&`, `InputIterator1`, `InputIterator1`, `InputIterator2`, `BinaryPredicate`) in doxygen xml output for project “rocThrust” from directory: `./docBin/xml`. Potential matches:

```

- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2,
  ↵ typename BinaryPredicate>_host_ _device_ thrust::pair<InputIterator1,
  ↵ InputIterator2> thrust::mismatch(const thrust::detail::execution_policy_base<
  ↵ DerivedPolicy > &, InputIterator1, InputIterator1, InputIterator2,
  ↵ BinaryPredicate)
- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2>
  ↵ _host_ _device_ thrust::pair<InputIterator1, InputIterator2>,
  ↵ thrust::mismatch(const thrust::detail::execution_policy_base< DerivedPolicy > &,
  ↵ InputIterator1, InputIterator1, InputIterator2)
- template<typename InputIterator1, typename InputIterator2, typename
  ↵ BinaryPredicate>
  thrust::pair<InputIterator1, InputIterator2> thrust::mismatch(InputIterator1,
  ↵ InputIterator1, InputIterator2, BinaryPredicate)
- template<typename InputIterator1, typename InputIterator2>
  thrust::pair<InputIterator1, InputIterator2> thrust::mismatch(InputIterator1,
  ↵ InputIterator1, InputIterator2)

```

## Template Function `thrust::mismatch(InputIterator1, InputIterator1, InputIterator2, BinaryPredicate)`

### Function Documentation

```
template<typename InputIterator1, typename InputIterator2, typename BinaryPredicate>
thrust::pair<InputIterator1, InputIterator2> thrust::mismatch(InputIterator1 first1, InputIterator1 last1,
```

```
          InputIterator2 first2, BinaryPredicate pred)
```

`mismatch` finds the first position where the two ranges  $[first1, last1]$  and  $[first2, first2 + (last1 - first1)]$  differ. The two versions of `mismatch` use different tests for whether elements differ.

This version of `mismatch` finds the first iterator `i` in  $[first1, last1]$  such that `pred(*i, *(first2 + (i - first1)))` is false. The return value is a pair whose first element is `i` and whose second element is `*(first2 + (i - first1))`. If no such iterator `i` exists, the return value is a pair whose first element is `last1` and whose second element is `*(first2 + (last1 - first1))`.

```
#include <thrust/mismatch.h>
#include <thrust/device_vector.h>
...
thrust::device_vector<int> vec1(4);
thrust::device_vector<int> vec2(4);

vec1[0] = 0;  vec2[0] = 0;
vec1[1] = 5;  vec2[1] = 5;
vec1[2] = 3;  vec2[2] = 8;
vec1[3] = 7;  vec2[3] = 7;

typedef thrust::device_vector<int>::iterator Iterator;
thrust::pair<Iterator, Iterator> result;

result = thrust::mismatch(vec1.begin(), vec1.end(), vec2.begin(), thrust::equal_to<int>());
// result.first is vec1.begin() + 2
// result.second is vec2.begin() + 2
```

**Return** The first position where the sequences differ.

#### Parameters

- `first1`: The beginning of the first sequence.
- `last1`: The end of the first sequence.
- `first2`: The beginning of the second sequence.
- `pred`: The binary predicate to compare elements.

#### Template Parameters

- `InputIterator1`: is a model of `Input Iterator`.
- `InputIterator2`: is a model of `Input Iterator`.
- `Predicate`: is a model of `Input Iterator`.

**See** `find`

See `find_if`

### Template Function `thrust::none_of(const thrust::detail::execution_policy_base<DerivedPolicy>&, InputIterator, InputIterator, Predicate)`

- Defined in file `thrust_logical.h`

#### Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::none_of`” with arguments (`const thrust::detail::execution_policy_base<DerivedPolicy>&`, `InputIterator`, `InputIterator`, `Predicate`) in doxygen xml output for project “rocThrust” from directory: `./docBin/xml`. Potential matches:

```
- template<typename DerivedPolicy, typename InputIterator, typename Predicate> __
  host __ device __ bool thrust::none_of(const thrust::detail::execution_policy_base< DerivedPolicy > &, InputIterator, InputIterator, Predicate)
- template<typename InputIterator, typename Predicate>
  bool thrust::none_of(InputIterator, InputIterator, Predicate)
```

### Template Function `thrust::none_of(InputIterator, InputIterator, Predicate)`

#### Function Documentation

```
template<typename InputIterator, typename Predicate>
bool thrust::none_of(InputIterator first, InputIterator last, Predicate pred)
```

`none_of` determines whether no element in a range satisfies a predicate. Specifically, `none_of` returns `true` if there is no iterator `i` in the range `[first, last)` such that `pred(*i)` is `true`, and `false` otherwise.

```
#include <thrust/logical.h>
#include <thrust/functional.h>
...
bool A[3] = {true, true, false};

thrust::none_of(A, A + 2, thrust::identity<bool>()); // returns false
thrust::none_of(A, A + 3, thrust::identity<bool>()); // returns false

thrust::none_of(A + 2, A + 3, thrust::identity<bool>()); // returns true

// empty range
thrust::none_of(A, A, thrust::identity<bool>()); // returns true
```

**Return** `true`, if no element satisfies the predicate; `false`, otherwise.

#### Parameters

- `first`: The beginning of the sequence.
- `last`: The end of the sequence.
- `pred`: A predicate used to test range elements.

#### Template Parameters

- `InputIterator`: is a model of `Input Iterator`,
- `Predicate`: must be a model of `Predicate`.

**See** `all_of`

**See** `any_of`

**See** `transform_reduce`

## Template Function `thrust::norm`

- Defined in file `thrust_complex.h`

### Function Documentation

```
template<typename T> __host__ __device__ T thrust::norm(const complex < T > & z)
```

Returns the square of the magnitude of a complex.

#### Parameters

- `z`: The complex from which to calculate the norm.

## Template Function `thrust::not1`

- Defined in file `thrust_functional.h`

### Function Documentation

```
template<typename Predicate> __host__ __device__ unary_negate<Predicate> thrust::not1(const Predicate pred)
```

`not1` is a helper function to simplify the creation of Adaptable Predicates: it takes an Adaptable Predicate `pred` as an argument and returns a new Adaptable Predicate that represents the negation of `pred`. That is: if `pred` is an object of a type which models Adaptable Predicate, then the the type of the result `npred` of `not1(pred)` is also a model of Adaptable Predicate and `npred(x)` always returns the same value as `!pred(x)`.

**Return** A new object, `npred` such that `npred(x)` always returns the same value as `!pred(x)`.

**See** `unary_negate`

**See** `not2`

#### Parameters

- `pred`: The Adaptable Predicate to negate.

#### Template Parameters

- `Predicate`: is a model of Adaptable Predicate.

## Template Function `thrust::not2`

- Defined in file `thrust_functional.h`

## Function Documentation

```
template<typename BinaryPredicate> __host__ __device__ binary_negate<BinaryPredicate> thrust::not2(BinaryPredicate pred)
```

not2 is a helper function to simplify the creation of Adaptable Binary Predicates: it takes an Adaptable Binary Predicate pred as an argument and returns a new Adaptable Binary Predicate that represents the negation of pred. That is: if pred is an object of a type which models Adaptable Binary Predicate, then the the type of the result npred of not2 (pred) is also a model of Adaptable Binary Predicate and npred(x, y) always returns the same value as !pred(x, y).

**Return** A new object, npred such that npred(x, y) always returns the same value as !pred(x, y).

**See** [binary\\_negate](#)

**See** [not1](#)

### Parameters

- pred: The Adaptable Binary Predicate to negate.

### Template Parameters

- Binary: Predicate is a model of Adaptable Binary Predicate.

## Template Function `thrust::operator!=(const complex<T0>&, const complex<T1>&)`

## Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “thrust::operator!=” with arguments (const complex<T0>&, const complex<T1>&) in doxygen xml output for project “rocThrust” from directory: ./docBin/xml. Potential matches:

```
- template<typename T0, typename T1> __host__ __device__ THRUST_STD_COMPLEX_DEVICE bool__thrust::operator!=(const complex<T0> &, const std::complex<T1> &)
- template<typename T0, typename T1> __host__ __device__ THRUST_STD_COMPLEX_DEVICE bool__thrust::operator!=(const std::complex<T0> &, const complex<T1> &)
- template<typename T0, typename T1> __host__ __device__ bool thrust::operator!=(const complex<T0> &, const complex<T1> &)
- template<typename T0, typename T1> __host__ __device__ bool thrust::operator!=(const complex<T0> &, const T1 &)
- template<typename T0, typename T1> __host__ __device__ bool thrust::operator!=(const T0 &, const complex<T1> &)
- template<typename T1, typename T2> __host__ __device__ bool thrust::operator!=(const pair<T1, T2> &, const pair<T1, T2> &)
```

## Template Function `thrust::operator!=(const complex<T0>&, const std::complex<T1>&)`

## Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “thrust::operator!=” with arguments (const complex<T0>&, const std::complex<T1>&) in doxygen xml output for project “rocThrust” from directory: ./docBin/xml. Potential matches:

```

- template<typename T0, typename T1>__host__ THRUST_STD_COMPLEX_DEVICE bool_
→thrust::operator!=(const complex < T0 > &, const std::complex< T1 > &)
- template<typename T0, typename T1>__host__ THRUST_STD_COMPLEX_DEVICE bool_
→thrust::operator!=(const std::complex< T0 > &, const complex < T1 > &)
- template<typename T0, typename T1>__host__ __device__ bool thrust::operator!
→=(const complex < T0 > &, const complex < T1 > &)
- template<typename T0, typename T1>__host__ __device__ bool thrust::operator!
→=(const complex < T0 > &, const T1 &)
- template<typename T0, typename T1>__host__ __device__ bool thrust::operator!
→=(const T0 &, const complex < T1 > &)
- template<typename T1, typename T2>__host__ __device__ bool thrust::operator!
→=(const pair < T1, T2 > &, const pair < T1, T2 > &)

```

## Template Function `thrust::operator!=(const std::complex<T0>&, const complex<T1>&)`

### Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::operator!=`” with arguments (`const std::complex<T0>&`, `const complex<T1>&`) in doxygen xml output for project “rocThrust” from directory: `./docBin/xml`. Potential matches:

```

- template<typename T0, typename T1>__host__ THRUST_STD_COMPLEX_DEVICE bool_
→thrust::operator!=(const complex < T0 > &, const std::complex< T1 > &)
- template<typename T0, typename T1>__host__ THRUST_STD_COMPLEX_DEVICE bool_
→thrust::operator!=(const std::complex< T0 > &, const complex < T1 > &)
- template<typename T0, typename T1>__host__ __device__ bool thrust::operator!
→=(const complex < T0 > &, const complex < T1 > &)
- template<typename T0, typename T1>__host__ __device__ bool thrust::operator!
→=(const complex < T0 > &, const T1 &)
- template<typename T0, typename T1>__host__ __device__ bool thrust::operator!
→=(const T0 &, const complex < T1 > &)
- template<typename T1, typename T2>__host__ __device__ bool thrust::operator!
→=(const pair < T1, T2 > &, const pair < T1, T2 > &)

```

## Template Function `thrust::operator!=(const T0&, const complex<T1>&)`

### Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::operator!=`” with arguments (`const T0&`, `const complex<T1>&`) in doxygen xml output for project “rocThrust” from directory: `./docBin/xml`. Potential matches:

```

- template<typename T0, typename T1>__host__ THRUST_STD_COMPLEX_DEVICE bool_
→thrust::operator!=(const complex < T0 > &, const std::complex< T1 > &)
- template<typename T0, typename T1>__host__ THRUST_STD_COMPLEX_DEVICE bool_
→thrust::operator!=(const std::complex< T0 > &, const complex < T1 > &)
- template<typename T0, typename T1>__host__ __device__ bool thrust::operator!
→=(const complex < T0 > &, const complex < T1 > &)
- template<typename T0, typename T1>__host__ __device__ bool thrust::operator!
→=(const complex < T0 > &, const T1 &)
- template<typename T0, typename T1>__host__ __device__ bool thrust::operator!
→=(const T0 &, const complex < T1 > &)
192 template<typename T1, typename T2>__host__ __device__ bool thrust::operator!
→=(const pair < T1, T2 > &, const pair < T1, T2 > &)

```

## Template Function `thrust::operator!=(const complex<T0>&, const T1&)`

### Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::operator!=`” with arguments `(const complex<T0>&, const T1&)` in doxygen xml output for project “rocThrust” from directory: ./docBin/xml. Potential matches:

```
- template<typename T0, typename T1>__host__ THRUST_STD_COMPLEX_DEVICE bool_
→thrust::operator!=(const complex < T0 > &, const std::complex< T1 > &)
- template<typename T0, typename T1>__host__ THRUST_STD_COMPLEX_DEVICE bool_
→thrust::operator!=(const std::complex< T0 > &, const complex < T1 > &)
- template<typename T0, typename T1>__host__ __device__ bool thrust::operator!
→=(const complex < T0 > &, const complex < T1 > &)
- template<typename T0, typename T1>__host__ __device__ bool thrust::operator!
→=(const complex < T0 > &, const T1 &)
- template<typename T0, typename T1>__host__ __device__ bool thrust::operator!
→=(const T0 &, const complex < T1 > &)
- template<typename T1, typename T2>__host__ __device__ bool thrust::operator!
→=(const pair < T1, T2 > &, const pair < T1, T2 > &)
```

## Template Function `thrust::operator!=(const pair<T1, T2>&, const pair<T1, T2>&)`

### Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::operator!=`” with arguments `(const pair<T1, T2>&, const pair<T1, T2>&)` in doxygen xml output for project “rocThrust” from directory: ./docBin/xml. Potential matches:

```
- template<typename T0, typename T1>__host__ THRUST_STD_COMPLEX_DEVICE bool_
→thrust::operator!=(const complex < T0 > &, const std::complex< T1 > &)
- template<typename T0, typename T1>__host__ THRUST_STD_COMPLEX_DEVICE bool_
→thrust::operator!=(const std::complex< T0 > &, const complex < T1 > &)
- template<typename T0, typename T1>__host__ __device__ bool thrust::operator!
→=(const complex < T0 > &, const complex < T1 > &)
- template<typename T0, typename T1>__host__ __device__ bool thrust::operator!
→=(const complex < T0 > &, const T1 &)
- template<typename T0, typename T1>__host__ __device__ bool thrust::operator!
→=(const T0 &, const complex < T1 > &)
- template<typename T1, typename T2>__host__ __device__ bool thrust::operator!
→=(const pair < T1, T2 > &, const pair < T1, T2 > &)
```

## Template Function `thrust::operator*(const complex<T0>&, const complex<T1>&)`

- Defined in file\_thrust\_complex.h

## Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “thrust::operator\*” with arguments (const complex<T0>&, const complex<T1>&) in doxygen xml output for project “rocThrust” from directory: ./docBin/xml. Potential matches:

```
- template<typename T0, typename T1>__host__ __device__ complex<typename<br/>  
→detail::promoted_numerical_type<T0, T1>::type> thrust::operator*(const complex <  
→T0 > &, const complex < T1 > &)  
- template<typename T0, typename T1>__host__ __device__ complex<typename<br/>  
→detail::promoted_numerical_type<T0, T1>::type> thrust::operator*(const complex <  
→T0 > &, const T1 &)  
- template<typename T0, typename T1>__host__ __device__ complex<typename<br/>  
→detail::promoted_numerical_type<T0, T1>::type> thrust::operator*(const T0 &, <  
→const complex < T1 > &)
```

### Template Function thrust::operator\*(const complex<T0>&, const T1&)

## Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “thrust::operator\*” with arguments (const complex<T0>&, const T1&) in doxygen xml output for project “rocThrust” from directory: ./docBin/xml. Potential matches:

```
- template<typename T0, typename T1>__host__ __device__ complex<typename<br/>  
→detail::promoted_numerical_type<T0, T1>::type> thrust::operator*(const complex <  
→T0 > &, const complex < T1 > &)  
- template<typename T0, typename T1>__host__ __device__ complex<typename<br/>  
→detail::promoted_numerical_type<T0, T1>::type> thrust::operator*(const complex <  
→T0 > &, const T1 &)  
- template<typename T0, typename T1>__host__ __device__ complex<typename<br/>  
→detail::promoted_numerical_type<T0, T1>::type> thrust::operator*(const T0 &, <  
→const complex < T1 > &)
```

### Template Function thrust::operator\*(const T0&, const complex<T1>&)

## Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “thrust::operator\*” with arguments (const T0&, const complex<T1>&) in doxygen xml output for project “rocThrust” from directory: ./docBin/xml. Potential matches:

```
- template<typename T0, typename T1>__host__ __device__ complex<typename<br/>  
→detail::promoted_numerical_type<T0, T1>::type> thrust::operator*(const complex <  
→T0 > &, const complex < T1 > &)  
- template<typename T0, typename T1>__host__ __device__ complex<typename<br/>  
→detail::promoted_numerical_type<T0, T1>::type> thrust::operator*(const complex <  
→T0 > &, const T1 &)  
- template<typename T0, typename T1>__host__ __device__ complex<typename<br/>  
→detail::promoted_numerical_type<T0, T1>::type> thrust::operator*(const T0 &, <  
→const complex < T1 > &)
```

## Template Function `thrust::operator+(const complex<T0>&, const complex<T1>&)`

- Defined in file `thrust_complex.h`

### Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::operator+`” with arguments `(const complex<T0>&, const complex<T1>&)` in doxygen xml output for project “rocThrust” from directory: `./docBin/xml`. Potential matches:

```
- template<typename T0, typename T1>__host__ __device__ complex<typename
→detail::promoted_numerical_type<T0, T1>::type> thrust::operator+(const complex <_
→T0 > &, const complex < T1 > &)
- template<typename T0, typename T1>__host__ __device__ complex<typename
→detail::promoted_numerical_type<T0, T1>::type> thrust::operator+(const complex <_
→T0 > &, const T1 &)
- template<typename T0, typename T1>__host__ __device__ complex<typename
→detail::promoted_numerical_type<T0, T1>::type> thrust::operator+(const T0 &,_
→const complex < T1 > &)
- template<typename T>__host__ __device__ complex<T> thrust::operator+(const complex < T > &)
```

## Template Function `thrust::operator+(const complex<T0>&, const T1&)`

### Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::operator+`” with arguments `(const complex<T0>&, const T1&)` in doxygen xml output for project “rocThrust” from directory: `./docBin/xml`. Potential matches:

```
- template<typename T0, typename T1>__host__ __device__ complex<typename
→detail::promoted_numerical_type<T0, T1>::type> thrust::operator+(const complex <_
→T0 > &, const complex < T1 > &)
- template<typename T0, typename T1>__host__ __device__ complex<typename
→detail::promoted_numerical_type<T0, T1>::type> thrust::operator+(const complex <_
→T0 > &, const T1 &)
- template<typename T0, typename T1>__host__ __device__ complex<typename
→detail::promoted_numerical_type<T0, T1>::type> thrust::operator+(const T0 &,_
→const complex < T1 > &)
- template<typename T>__host__ __device__ complex<T> thrust::operator+(const complex < T > &)
```

## Template Function `thrust::operator+(const T0&, const complex<T1>&)`

## Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “thrust::operator+” with arguments (const T0&, const complex<T1>&) in doxygen xml output for project “rocThrust” from directory: ./docBin/xml. Potential matches:

```
- template<typename T0, typename T1> __host__ __device__ complex<typename __  
→detail::promoted_numerical_type<T0, T1>::type> thrust::operator+(const complex <  
→T0 > &, const complex < T1 > &)  
- template<typename T0, typename T1> __host__ __device__ complex<typename __  
→detail::promoted_numerical_type<T0, T1>::type> thrust::operator+(const complex <  
→T0 > &, const T1 &)  
- template<typename T0, typename T1> __host__ __device__ complex<typename __  
→detail::promoted_numerical_type<T0, T1>::type> thrust::operator+(const T0 &, __  
→const complex < T1 > &)  
- template<typename T> __host__ __device__ complex<T> thrust::operator+(const __  
→complex < T > &)
```

## Template Function thrust::operator+(const complex<T>&)

### Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “thrust::operator+” with arguments (const complex<T>&) in doxygen xml output for project “rocThrust” from directory: ./docBin/xml. Potential matches:

```
- template<typename T0, typename T1> __host__ __device__ complex<typename __  
→detail::promoted_numerical_type<T0, T1>::type> thrust::operator+(const complex <  
→T0 > &, const complex < T1 > &)  
- template<typename T0, typename T1> __host__ __device__ complex<typename __  
→detail::promoted_numerical_type<T0, T1>::type> thrust::operator+(const complex <  
→T0 > &, const T1 &)  
- template<typename T0, typename T1> __host__ __device__ complex<typename __  
→detail::promoted_numerical_type<T0, T1>::type> thrust::operator+(const T0 &, __  
→const complex < T1 > &)  
- template<typename T> __host__ __device__ complex<T> thrust::operator+(const __  
→complex < T > &)
```

## Template Function thrust::operator-(const complex<T0>&, const complex<T1>&)

- Defined in file\_thrust\_complex.h

### Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “thrust::operator-” with arguments (const complex<T0>&, const complex<T1>&) in doxygen xml output for project “rocThrust” from directory: ./docBin/xml. Potential matches:

```

- template<typename T0, typename T1> __host__ __device__ complex<typename<
→detail::promoted_numerical_type<T0, T1>::type> thrust::operator-(const complex <_
→T0 > &, const complex < T1 > &)
- template<typename T0, typename T1> __host__ __device__ complex<typename<
→detail::promoted_numerical_type<T0, T1>::type> thrust::operator-(const complex <_
→T0 > &, const T1 &)
- template<typename T0, typename T1> __host__ __device__ complex<typename<
→detail::promoted_numerical_type<T0, T1>::type> thrust::operator-(const T0 &,_
→const complex < T1 > &)
- template<typename T> __host__ __device__ complex<T> thrust::operator-(const complex <_
→complex < T > &)

```

## Template Function thrust::operator-(const complex<T0>&, const T1&)

### Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “thrust::operator-” with arguments (const complex<T0>&, const T1&) in doxygen xml output for project “rocThrust” from directory: ./docBin/xml. Potential matches:

```

- template<typename T0, typename T1> __host__ __device__ complex<typename<
→detail::promoted_numerical_type<T0, T1>::type> thrust::operator-(const complex <_
→T0 > &, const complex < T1 > &)
- template<typename T0, typename T1> __host__ __device__ complex<typename<
→detail::promoted_numerical_type<T0, T1>::type> thrust::operator-(const complex <_
→T0 > &, const T1 &)
- template<typename T0, typename T1> __host__ __device__ complex<typename<
→detail::promoted_numerical_type<T0, T1>::type> thrust::operator-(const T0 &,_
→const complex < T1 > &)
- template<typename T> __host__ __device__ complex<T> thrust::operator-(const complex <_
→complex < T > &)

```

## Template Function thrust::operator-(const T0&, const complex<T1>&)

### Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “thrust::operator-” with arguments (const T0&, const complex<T1>&) in doxygen xml output for project “rocThrust” from directory: ./docBin/xml. Potential matches:

```

- template<typename T0, typename T1> __host__ __device__ complex<typename<
→detail::promoted_numerical_type<T0, T1>::type> thrust::operator-(const complex <_
→T0 > &, const complex < T1 > &)
- template<typename T0, typename T1> __host__ __device__ complex<typename<
→detail::promoted_numerical_type<T0, T1>::type> thrust::operator-(const complex <_
→T0 > &, const T1 &)
- template<typename T0, typename T1> __host__ __device__ complex<typename<
→detail::promoted_numerical_type<T0, T1>::type> thrust::operator-(const T0 &,_
→const complex < T1 > &)
- template<typename T> __host__ __device__ complex<T> thrust::operator-(const complex <_
→complex < T > &)

```

## Template Function `thrust::operator-(const complex<T>&)`

### Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::operator-`” with arguments (`const complex<T>&`) in doxygen xml output for project “rocThrust” from directory: ./docBin/xml. Potential matches:

```
- template<typename T0, typename T1>__host__ __device__ complex<typename __
→detail::promoted_numerical_type<T0, T1>::type> thrust::operator-(const complex <_
→T0 > &, const complex < T1 > &)
- template<typename T0, typename T1>__host__ __device__ complex<typename __
→detail::promoted_numerical_type<T0, T1>::type> thrust::operator-(const complex <_
→T0 > &, const T1 &)
- template<typename T0, typename T1>__host__ __device__ complex<typename __
→detail::promoted_numerical_type<T0, T1>::type> thrust::operator-(const T0 &, __
→const complex < T1 > &)
- template<typename T>__host__ __device__ complex<T> thrust::operator-(const __
→complex < T > &)
```

## Template Function `thrust::operator/(const complex<T0>&, const complex<T1>&)`

- Defined in file `thrust_complex.h`

### Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::operator/`” with arguments (`const complex<T0>&`, `const complex<T1>&`) in doxygen xml output for project “rocThrust” from directory: ./docBin/xml. Potential matches:

```
- template<typename T0, typename T1>__host__ __device__ complex<typename __
→detail::promoted_numerical_type<T0, T1>::type> thrust::operator/(const complex <_
→T0 > &, const complex < T1 > &)
- template<typename T0, typename T1>__host__ __device__ complex<typename __
→detail::promoted_numerical_type<T0, T1>::type> thrust::operator/(const complex <_
→T0 > &, const T1 &)
- template<typename T0, typename T1>__host__ __device__ complex<typename __
→detail::promoted_numerical_type<T0, T1>::type> thrust::operator/(const T0 &, __
→const complex < T1 > &)
```

## Template Function `thrust::operator/(const complex<T0>&, const T1&)`

## Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “thrust::operator/” with arguments (const complex<T0>&, const T1&) in doxygen xml output for project “rocThrust” from directory: ./docBin/xml.  
Potential matches:

```
- template<typename T0, typename T1>__host__ __device__ complex<typename<
→detail::promoted_numerical_type<T0, T1>::type> thrust::operator/(const complex <_
→T0 > &, const complex < T1 > &)
- template<typename T0, typename T1>__host__ __device__ complex<typename<
→detail::promoted_numerical_type<T0, T1>::type> thrust::operator/(const complex <_
→T0 > &, const T1 &)
- template<typename T0, typename T1>__host__ __device__ complex<typename<
→detail::promoted_numerical_type<T0, T1>::type> thrust::operator/(const T0 &,_
→const complex < T1 > &)
```

## Template Function thrust::operator/(const T0&, const complex<T1>&)

### Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “thrust::operator/” with arguments (const T0&, const complex<T1>&) in doxygen xml output for project “rocThrust” from directory: ./docBin/xml.  
Potential matches:

```
- template<typename T0, typename T1>__host__ __device__ complex<typename<
→detail::promoted_numerical_type<T0, T1>::type> thrust::operator/(const complex <_
→T0 > &, const complex < T1 > &)
- template<typename T0, typename T1>__host__ __device__ complex<typename<
→detail::promoted_numerical_type<T0, T1>::type> thrust::operator/(const complex <_
→T0 > &, const T1 &)
- template<typename T0, typename T1>__host__ __device__ complex<typename<
→detail::promoted_numerical_type<T0, T1>::type> thrust::operator/(const T0 &,_
→const complex < T1 > &)
```

## Template Function thrust::operator<

- Defined in file\_thrust\_tuple.h

### Function Documentation

**template<typename T1, typename T2>\_\_host\_\_ \_\_device\_\_ bool thrust::operator<(const pair <**

This operator tests two pairs for ascending ordering.

**Return** true if and only if x.first < y.first || !(y.first < x.first) && x.second < y.second).

#### Parameters

- x: The first pair to compare.
- y: The second pair to compare.

**Template Parameters**

- T1: is a model of LessThan Comparable.
- T2: is a model of LessThan Comparable.

**Template Function thrust::operator<<****Function Documentation**

```
template<typename T, typename CharT, typename Traits>
std::basic_ostream<CharT, Traits> &thrust::operator<<(std::basic_ostream<CharT, Traits> &os,
                                                       const complex<T> &z)
```

Writes to an output stream a complex number in the form (real, imaginary).

**Parameters**

- os: The output stream.
- z: The complex number to output.

**Template Function thrust::operator<=**

- Defined in file\_thrust\_tuple.h

**Function Documentation**

```
template<typename T1, typename T2> __host__ __device__ bool thrust::operator<=(const pair <T1, T2> &x, const pair <T1, T2> &y)
```

This operator tests two pairs for ascending ordering or equivalence.

**Return** true if and only if !(y < x).

**Parameters**

- x: The first pair to compare.
- y: The second pair to compare.

**Template Parameters**

- T1: is a model of LessThan Comparable.
- T2: is a model of LessThan Comparable.

**Template Function thrust::operator==(const complex<T0>&, const complex<T1>&)****Function Documentation**

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “thrust::operator==” with arguments (const complex<T0>&, const complex<T1>&) in doxygen xml output for project “rocThrust” from directory: /docBin/xml. Potential matches:

```

- template<typename T0, typename T1> __host__ THRUST_STD_COMPLEX_DEVICE bool
→thrust::operator==(const complex < T0 > &, const std::complex< T1 > &)
- template<typename T0, typename T1> __host__ THRUST_STD_COMPLEX_DEVICE bool
→thrust::operator==(const std::complex< T0 > &, const complex < T1 > &)
- template<typename T0, typename T1> __host__ __device__ bool
→thrust::operator==(const complex < T0 > &, const complex < T1 > &)
- template<typename T0, typename T1> __host__ __device__ bool
→thrust::operator==(const complex < T0 > &, const T1 &)
- template<typename T0, typename T1> __host__ __device__ bool
→thrust::operator==(const T0 &, const complex < T1 > &)
- template<typename T1, typename T2> __host__ __device__ bool
→thrust::operator==(const pair < T1, T2 > &, const pair < T1, T2 > &)

```

## Template Function `thrust::operator==(const complex<T0>&, const std::complex<T1>&)`

### Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::operator==`” with arguments (`const complex<T0>&`, `const std::complex<T1>&`) in doxygen xml output for project “rocThrust” from directory: `/docBin/xml`. Potential matches:

```

- template<typename T0, typename T1> __host__ THRUST_STD_COMPLEX_DEVICE bool
→thrust::operator==(const complex < T0 > &, const std::complex< T1 > &)
- template<typename T0, typename T1> __host__ THRUST_STD_COMPLEX_DEVICE bool
→thrust::operator==(const std::complex< T0 > &, const complex < T1 > &)
- template<typename T0, typename T1> __host__ __device__ bool
→thrust::operator==(const complex < T0 > &, const complex < T1 > &)
- template<typename T0, typename T1> __host__ __device__ bool
→thrust::operator==(const complex < T0 > &, const T1 &)
- template<typename T0, typename T1> __host__ __device__ bool
→thrust::operator==(const T0 &, const complex < T1 > &)
- template<typename T1, typename T2> __host__ __device__ bool
→thrust::operator==(const pair < T1, T2 > &, const pair < T1, T2 > &)

```

## Template Function `thrust::operator==(const std::complex<T0>&, const complex<T1>&)`

### Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::operator==`” with arguments (`const std::complex<T0>&`, `const complex<T1>&`) in doxygen xml output for project “rocThrust” from directory: `/docBin/xml`. Potential matches:

```

- template<typename T0, typename T1> __host__ THRUST_STD_COMPLEX_DEVICE bool
→thrust::operator==(const complex < T0 > &, const std::complex< T1 > &)
- template<typename T0, typename T1> __host__ THRUST_STD_COMPLEX_DEVICE bool
→thrust::operator==(const std::complex< T0 > &, const complex < T1 > &)
- template<typename T0, typename T1> __host__ __device__ bool
→thrust::operator==(const complex < T0 > &, const complex < T1 > &)
- template<typename T0, typename T1> __host__ __device__ bool
→thrust::operator==(const complex < T0 > &, const T1 &)
template<typename T0, typename T1> __host__ __device__ bool
→thrust::operator==(const T0 &, const complex < T1 > &)
template<typename T1, typename T2> __host__ __device__ bool
→thrust::operator==(const pair < T1, T2 > &, const pair < T1, T2 > &)

```

## Template Function `thrust::operator==(const T0&, const complex<T1>&)`

### Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::operator==`” with arguments (`const T0&`, `const complex<T1>&`) in doxygen xml output for project “rocThrust” from directory: ./docBin/xml. Potential matches:

```
- template<typename T0, typename T1>__host__ THRUST_STD_COMPLEX_DEVICE bool_
→thrust::operator==(const complex < T0 > &, const std::complex< T1 > &)
- template<typename T0, typename T1>__host__ THRUST_STD_COMPLEX_DEVICE bool_
→thrust::operator==(const std::complex< T0 > &, const complex < T1 > &)
- template<typename T0, typename T1>__host__ __device__ bool_
→thrust::operator==(const complex < T0 > &, const complex < T1 > &)
- template<typename T0, typename T1>__host__ __device__ bool_
→thrust::operator==(const complex < T0 > &, const T1 &)
- template<typename T0, typename T1>__host__ __device__ bool_
→thrust::operator==(const T0 &, const complex < T1 > &)
- template<typename T1, typename T2>__host__ __device__ bool_
→thrust::operator==(const pair < T1, T2 > &, const pair < T1, T2 > &)
```

## Template Function `thrust::operator==(const complex<T0>&, const T1&)`

### Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::operator==`” with arguments (`const complex<T0>&`, `const T1&`) in doxygen xml output for project “rocThrust” from directory: ./docBin/xml. Potential matches:

```
- template<typename T0, typename T1>__host__ THRUST_STD_COMPLEX_DEVICE bool_
→thrust::operator==(const complex < T0 > &, const std::complex< T1 > &)
- template<typename T0, typename T1>__host__ THRUST_STD_COMPLEX_DEVICE bool_
→thrust::operator==(const std::complex< T0 > &, const complex < T1 > &)
- template<typename T0, typename T1>__host__ __device__ bool_
→thrust::operator==(const complex < T0 > &, const complex < T1 > &)
- template<typename T0, typename T1>__host__ __device__ bool_
→thrust::operator==(const complex < T0 > &, const T1 &)
- template<typename T0, typename T1>__host__ __device__ bool_
→thrust::operator==(const T0 &, const complex < T1 > &)
- template<typename T1, typename T2>__host__ __device__ bool_
→thrust::operator==(const pair < T1, T2 > &, const pair < T1, T2 > &)
```

## Template Function `thrust::operator==(const pair<T1, T2>&, const pair<T1, T2>&)`

## Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “thrust::operator==” with arguments (const pair<T1, T2>&, const pair<T1, T2>&) in doxygen xml output for project “rocThrust” from directory: ./docBin/xml. Potential matches:

```
- template<typename T0, typename T1>__host__ __device__ bool thrust::operator==(const complex< T0 > &, const std::complex< T1 > &)
- template<typename T0, typename T1>__host__ __device__ bool thrust::operator==(const std::complex< T0 > &, const complex< T1 > &)
- template<typename T0, typename T1>__host__ __device__ bool thrust::operator==(const complex< T0 > &, const complex< T1 > &)
- template<typename T0, typename T1>__host__ __device__ bool thrust::operator==(const complex< T0 > &, const complex< T1 > &)
- template<typename T0, typename T1>__host__ __device__ bool thrust::operator==(const complex< T0 > &, const T1 &)
- template<typename T0, typename T1>__host__ __device__ bool thrust::operator==(const T0 &, const complex< T1 > &)
- template<typename T1, typename T2>__host__ __device__ bool thrust::operator==(const pair< T1, T2 > &, const pair< T1, T2 > &)
```

## Template Function thrust::operator>

### Function Documentation

```
template<typename T1, typename T2>__host__ __device__ bool thrust::operator>(const pair <
```

This operator tests two pairs for descending ordering.

**Return** true if and only if  $y < x$ .

#### Parameters

- $x$ : The first pair to compare.
- $y$ : The second pair to compare.

#### Template Parameters

- $T1$ : is a model of LessThan Comparable.
- $T2$ : is a model of LessThan Comparable.

## Template Function thrust::operator>=

### Function Documentation

```
template<typename T1, typename T2>__host__ __device__ bool thrust::operator>=(const pair <
```

This operator tests two pairs for descending ordering or equivalence.

**Return** true if and only if  $!(x < y)$ .

#### Parameters

- $x$ : The first pair to compare.
- $y$ : The second pair to compare.

#### Template Parameters

- T1: is a model of LessThan Comparable.
- T2: is a model of LessThan Comparable.

### Template Function `thrust::operator>>`

- Defined in file `_thrust_complex.h`

#### Function Documentation

```
template<typename T, typename CharT, typename Traits>
std::basic_istream<CharT, Traits> &thrust::operator>>(std::basic_istream<CharT, Traits> &is, complex<T> &z)
```

Reads a complex number from an input stream.

The recognized formats are:

- real
- (real)
- (real, imaginary)

The values read must be convertible to the `complex`'s `value_type`

#### Parameters

- `is`: The input stream.
- `z`: The complex number to set.

### Template Function `thrust::partition(const thrust::detail::execution_policy_base<DerivedPolicy>&, ForwardIterator, ForwardIterator, Predicate)`

- Defined in file `_thrust_partition.h`

#### Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::partition`” with arguments (`const thrust::detail::execution_policy_base<DerivedPolicy>&`, `ForwardIterator`, `ForwardIterator`, `Predicate`) in doxygen xml output for project “rocThrust” from directory: `./docBin/xml`. Potential matches:

```
- template<typename DerivedPolicy, typename ForwardIterator, typename InputIterator,
          typename Predicate> __host__ __device__ ForwardIterator thrust::partition(const
          thrust::detail::execution_policy_base< DerivedPolicy > &, ForwardIterator,
          ForwardIterator, InputIterator, Predicate)
- template<typename DerivedPolicy, typename ForwardIterator, typename Predicate> __
          host__ __device__ ForwardIterator thrust::partition(const
          thrust::detail::execution_policy_base< DerivedPolicy > &, ForwardIterator,
          ForwardIterator, Predicate)
- template<typename ForwardIterator, typename InputIterator, typename Predicate>
          ForwardIterator thrust::partition(ForwardIterator, ForwardIterator, InputIterator,
          Predicate)
- template<typename ForwardIterator, typename Predicate>
          ForwardIterator thrust::partition(ForwardIterator, ForwardIterator, Predicate)
```

## Template Function `thrust::partition(ForwardIterator, ForwardIterator, Predicate)`

### Function Documentation

```
template<typename ForwardIterator, typename Predicate>
ForwardIterator thrust::partition(ForwardIterator first, ForwardIterator last, Predicate pred)
    partition reorders the elements [first, last) based on the function object pred, such that all of the
    elements that satisfy pred precede the elements that fail to satisfy it. The postcondition is that, for some iterator
    middle in the range [first, last), pred(*i) is true for every iterator i in the range [first,
    middle) and false for every iterator i in the range [middle, last). The return value of partition
    is middle.
```

Note that the relative order of elements in the two reordered sequences is not necessarily the same as it was in the original sequence. A different algorithm, `stable_partition`, does guarantee to preserve the relative order.

The following code snippet demonstrates how to use `partition` to reorder a sequence so that even numbers precede odd numbers.

**Return** An iterator referring to the first element of the second partition, that is, the sequence of the elements which do not satisfy `pred`.

### Parameters

- `first`: The beginning of the sequence to reorder.
- `last`: The end of the sequence to reorder.
- `pred`: A function object which decides to which partition each element of the sequence [first, last) belongs.

### Template Parameters

- `ForwardIterator`: is a model of `Forward Iterator`, and `ForwardIterator`'s `value_type` is convertible to `Predicate`'s `argument_type`, and `ForwardIterator` is mutable.
- `Predicate`: is a model of `Predicate`.

```
#include <thrust/partition.h>
...
struct is_even
{
    __host__ __device__
    bool operator()(const int &x)
    {
        return (x % 2) == 0;
    }
};
...
int A[] = {1, 2, 3, 4, 5, 6, 7, 8, 9, 10};
const int N = sizeof(A) / sizeof(int);
thrust::partition(A, A + N,
                  is_even());
// A is now {2, 4, 6, 8, 10, 1, 3, 5, 7, 9}
```

See <http://www.sgi.com/tech/stl/partition.html>

See `stable_partition`

See `partition_copy`

**Template Function `thrust::partition(const thrust::detail::execution_policy_base<DerivedPolicy>&, ForwardIterator, ForwardIterator, InputIterator, Predicate)`**

## Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::partition`” with arguments (`const thrust::detail::execution_policy_base<DerivedPolicy>&`, `ForwardIterator`, `ForwardIterator`, `InputIterator`, `Predicate`) in doxygen xml output for project “rocThrust” from directory: `./docBin/xml`. Potential matches:

```
- template<typename DerivedPolicy, typename ForwardIterator, typename InputIterator,
→ typename Predicate> __host__ __device__ ForwardIterator thrust::partition(const
→ thrust::detail::execution_policy_base< DerivedPolicy > &, ForwardIterator, ↴
→ ForwardIterator, InputIterator, Predicate)
- template<typename DerivedPolicy, typename ForwardIterator, typename Predicate> __
→ host__ __device__ ForwardIterator thrust::partition(const
→ thrust::detail::execution_policy_base< DerivedPolicy > &, ForwardIterator, ↴
→ ForwardIterator, Predicate)
- template<typename ForwardIterator, typename InputIterator, typename Predicate>
  ForwardIterator thrust::partition(ForwardIterator, ForwardIterator, InputIterator,
→ Predicate)
- template<typename ForwardIterator, typename Predicate>
  ForwardIterator thrust::partition(ForwardIterator, ForwardIterator, Predicate)
```

**Template Function `thrust::partition(ForwardIterator, ForwardIterator, InputIterator, Predicate)`**

## Function Documentation

```
template<typename ForwardIterator, typename InputIterator, typename PredicateForwardIterator thrust::partition(ForwardIterator first, ForwardIterator last, InputIterator stencil,
Predicate pred)
```

`partition` reorders the elements  $[first, last]$  based on the function object `pred` applied to a stencil range  $[stencil, stencil + (last - first)]$ , such that all of the elements whose corresponding stencil element satisfies `pred` precede all of the elements whose corresponding stencil element fails to satisfy it. The postcondition is that, for some iterator `middle` in the range  $[first, last]$ , `pred(*stencil_i)` is true for every iterator `stencil_i` in the range  $[stencil, stencil + (middle - first)]$  and false for every iterator `stencil_i` in the range  $[stencil + (middle - first), stencil + (last - first)]$ . The return value of `stable_partition` is `middle`.

Note that the relative order of elements in the two reordered sequences is not necessarily the same as it was in the original sequence. A different algorithm, `stable_partition`, does guarantee to preserve the relative order.

The following code snippet demonstrates how to use `partition` to reorder a sequence so that even numbers precede odd numbers.

**Return** An iterator referring to the first element of the second partition, that is, the sequence of the elements whose stencil elements do not satisfy `pred`.

**Pre** The ranges  $[first, last]$  and  $[stencil, stencil + (last - first)]$  shall not overlap.

### Parameters

- `first`: The beginning of the sequence to reorder.

- `last`: The end of the sequence to reorder.
- `stencil`: The beginning of the stencil sequence.
- `pred`: A function object which decides to which partition each element of the sequence [`first`, `last`) belongs.

### Template Parameters

- `ForwardIterator`: is a model of `Forward Iterator`, and `ForwardIterator` is mutable.
- `InputIterator`: is a model of `Input Iterator`, and `InputIterator`'s `value_type` is convertible to `Predicate`'s `argument_type`.
- `Predicate`: is a model of `Predicate`.

```
#include <thrust/partition.h>
...
struct is_even
{
    __host__ __device__
    bool operator()(const int &x)
    {
        return (x % 2) == 0;
    }
};

int A[] = {0, 1, 0, 1, 0, 1, 0, 1, 0, 1};
int S[] = {1, 2, 3, 4, 5, 6, 7, 8, 9, 10};
const int N = sizeof(A) / sizeof(int);
thrust::partition(A, A + N, S, is_even());
// A is now {1, 1, 1, 1, 1, 0, 0, 0, 0, 0}
// S is unmodified
```

See <http://www.sgi.com/tech/stl/partition.html>

See `stable_partition`

See `partition_copy`

**Template Function `thrust::partition_copy(const thrust::detail::execution_policy_base<DerivedPolicy>&, InputIterator, InputIterator, OutputIterator1, OutputIterator2, Predicate)`**

- Defined in `file_thrust_partition.h`

### Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::partition_copy`” with arguments (`const thrust::detail::execution_policy_base<DerivedPolicy>&`, `InputIterator`, `InputIterator`, `OutputIterator1`, `OutputIterator2`, `Predicate`) in doxygen xml output for project “rocThrust” from directory: ./docBin/xml. Potential matches:

```
- template<typename DerivedPolicy, typename InputIterator, typename OutputIterator1,
→ typename OutputIterator2, typename Predicate> __host__ __device__ thrust::pair
→<OutputIterator1,OutputIterator2> thrust::partition_copy(const
→thrust::detail::execution_policy_base< DerivedPolicy > &, InputIterator,
→InputIterator, OutputIterator1, OutputIterator2, Predicate)
- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2,
→ typename OutputIterator1, typename OutputIterator2, typename Predicate> __host__
→ __device__ thrust::pair<OutputIterator1,OutputIterator2> thrust::partition_
→copy(const thrust::detail::execution_policy_base< DerivedPolicy > &,
→InputIterator1, InputIterator1, InputIterator2, OutputIterator1, OutputIterator2,
→Predicate)
- template<typename InputIterator, typename OutputIterator1, typename
→OutputIterator2, typename Predicate>
    thrust::pair<OutputIterator1, OutputIterator2> thrust::partition_
→copy(InputIterator, InputIterator, OutputIterator1, OutputIterator2, Predicate)
- template<typename InputIterator1, typename InputIterator2, typename
→OutputIterator1, typename OutputIterator2, typename Predicate>
    thrust::pair<OutputIterator1, OutputIterator2> thrust::partition_
→copy(InputIterator1, InputIterator1, InputIterator2, OutputIterator1,
→OutputIterator2, Predicate)
```

## Template Function `thrust::partition_copy(InputIterator, InputIterator, OutputIterator1, OutputIterator2, Predicate)`

### Function Documentation

```
template<typename InputIterator, typename OutputIterator1, typename OutputIterator2, typename Predicate>
thrust::pair<OutputIterator1, OutputIterator2> thrust::partition_copy (InputIterator first, InputIterator last, OutputIterator1 out_true, OutputIterator2 out_false, Predicate pred)
```

`partition_copy` differs from `partition` only in that the reordered sequence is written to difference output sequences, rather than in place.

`partition_copy` copies the elements `[first, last)` based on the function object `pred`. All of the elements that satisfy `pred` are copied to the range beginning at `out_true` and all the elements that fail to satisfy it are copied to the range beginning at `out_false`.

The following code snippet demonstrates how to use `partition_copy` to separate a sequence into two output sequences of even and odd numbers.

**Return** A pair `p` such that `p.first` is the end of the output range beginning at `out_true` and `p.second` is the end of the output range beginning at `out_false`.

**Pre** The input range shall not overlap with either output range.

#### Parameters

- `first`: The beginning of the sequence to reorder.
- `last`: The end of the sequence to reorder.
- `out_true`: The destination of the resulting sequence of elements which satisfy `pred`.
- `out_false`: The destination of the resulting sequence of elements which fail to satisfy `pred`.

- `pred`: A function object which decides to which partition each element of the sequence [`first`, `last`) belongs.

### Template Parameters

- `InputIterator`: is a model of `Input Iterator`, and `InputIterator`'s `value_type` is convertible to `Predicate`'s `argument_type` and `InputIterator`'s `value_type` is convertible to `OutputIterator1` and `OutputIterator2`'s `value_types`.
- `OutputIterator1`: is a model of `Output Iterator`.
- `OutputIterator2`: is a model of `Output Iterator`.
- `Predicate`: is a model of `Predicate`.

```
#include <thrust/partition.h>
...
struct is_even
{
    __host__ __device__
    bool operator() (const int &x)
    {
        return (x % 2) == 0;
    }
};
...
int A[] = {1, 2, 3, 4, 5, 6, 7, 8, 9, 10};
int result[10];
const int N = sizeof(A) / sizeof(int);
int *evens = result;
int *odds = result + 5;
thrust::partition_copy(A, A + N, evens, odds, is_even());
// A remains {1, 2, 3, 4, 5, 6, 7, 8, 9, 10}
// result is now {2, 4, 6, 8, 10, 1, 3, 5, 7, 9}
// evens points to {2, 4, 6, 8, 10}
// odds points to {1, 3, 5, 7, 9}
```

**Note** The relative order of elements in the two reordered sequences is not necessarily the same as it was in the original sequence. A different algorithm, `stable_partition_copy`, does guarantee to preserve the relative order.

**See** <http://www.open-std.org/jtc1/sc22/wg21/docs/papers/2008/n2569.pdf>

**See** `stable_partition_copy`

**See** `partition`

**Template Function** `thrust::partition_copy(const thrust::detail::execution_policy_base<DerivedPolicy>&, InputIterator1, InputIterator1, InputIterator2, OutputIterator1, OutputIterator2, Predicate)`

### Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::partition_copy`” with arguments (`const thrust::detail::execution_policy_base<DerivedPolicy>&`, `InputIterator1`, `InputIterator1`, `InputIterator2`, `OutputIterator1`, `OutputIterator2`, `Predicate`) in doxygen xml output for project “rocThrust” from directory: `./docBin/xml`. Potential matches:

```
- template<typename DerivedPolicy, typename InputIterator, typename OutputIterator1,
         typename OutputIterator2, typename Predicate> __host__ __device__ thrust::pair<
         <OutputIterator1,OutputIterator2> thrust:::partition_copy(const
         thrust:::detail::execution_policy_base< DerivedPolicy > &, InputIterator,
         InputIterator, OutputIterator1, OutputIterator2, Predicate)
- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2,
         typename OutputIterator1, typename OutputIterator2, typename Predicate> __host__ __device__ thrust:::pair<
         <OutputIterator1,OutputIterator2> thrust:::partition_
         copy(const thrust:::detail::execution_policy_base< DerivedPolicy > &,
         InputIterator1, InputIterator1, InputIterator2, OutputIterator1, OutputIterator2,
         Predicate)
- template<typename InputIterator, typename OutputIterator1, typename
         OutputIterator2, typename Predicate>
         thrust:::pair<OutputIterator1, OutputIterator2> thrust:::partition_
         copy(InputIterator, InputIterator, OutputIterator1, OutputIterator2, Predicate)
- template<typename InputIterator1, typename InputIterator2, typename
         OutputIterator1, typename OutputIterator2, typename Predicate>
         thrust:::pair<OutputIterator1, OutputIterator2> thrust:::partition_
         copy(InputIterator1, InputIterator1, InputIterator2, OutputIterator1,
         OutputIterator2, Predicate)
```

## Template Function `thrust::partition_copy(InputIterator1, InputIterator1, InputIterator2, OutputIterator1, OutputIterator2, Predicate)`

### Function Documentation

```
template<typename InputIterator1, typename InputIterator2, typename OutputIterator1, typename OutputIterator2>
thrust::pair<OutputIterator1, OutputIterator2> thrust:::partition_copy (InputIterator1 first, InputIterator1 last, InputIterator2 stencil, OutputIterator1 out_true, OutputIterator2 out_false, Predicate pred)
```

`partition_copy` differs from `partition` only in that the reordered sequence is written to difference output sequences, rather than in place.

`partition_copy` copies the elements `[first, last)` based on the function object `pred` which is applied to a range of stencil elements. All of the elements whose corresponding stencil element satisfies `pred` are copied to the range beginning at `out_true` and all the elements whose stencil element fails to satisfy it are copied to the range beginning at `out_false`.

The following code snippet demonstrates how to use `partition_copy` to separate a sequence into two output sequences of even and odd numbers.

**Return** A pair `p` such that `p.first` is the end of the output range beginning at `out_true` and `p.second` is the end of the output range beginning at `out_false`.

**Pre** The input ranges shall not overlap with either output range.

### Parameters

- `first`: The beginning of the sequence to reorder.
- `last`: The end of the sequence to reorder.
- `stencil`: The beginning of the stencil sequence.
- `out_true`: The destination of the resulting sequence of elements which satisfy `pred`.

- `out_false`: The destination of the resulting sequence of elements which fail to satisfy `pred`.
- `pred`: A function object which decides to which partition each element of the sequence [`first`, `last`) belongs.

### Template Parameters

- `InputIterator1`: is a model of `Input Iterator`, and `InputIterator1`'s `value_type` is convertible to `OutputIterator1` and `OutputIterator2`'s `value_types`.
- `InputIterator2`: is a model of `Input Iterator`, and `InputIterator2`'s `value_type` is convertible to `Predicate`'s `argument_type`.
- `OutputIterator1`: is a model of `Output Iterator`.
- `OutputIterator2`: is a model of `Output Iterator`.
- `Predicate`: is a model of `Predicate`.

```
#include <thrust/partition.h>
#include <thrust/functional.h>
...
int A[] = {1, 2, 3, 4, 5, 6, 7, 8, 9, 10};
int S[] = {0, 1, 0, 1, 0, 1, 0, 1, 0, 1};
int result[10];
const int N = sizeof(A) / sizeof(int);
int *evens = result;
int *odds = result + 5;
thrust::stable_partition_copy(A, A + N, S, evens, odds, thrust::identity<int>());
// A remains {1, 2, 3, 4, 5, 6, 7, 8, 9, 10}
// S remains {0, 1, 0, 1, 0, 1, 0, 1, 0, 1}
// result is now {2, 4, 6, 8, 10, 1, 3, 5, 7, 9}
// evens points to {2, 4, 6, 8, 10}
// odds points to {1, 3, 5, 7, 9}
```

**Note** The relative order of elements in the two reordered sequences is not necessarily the same as it was in the original sequence. A different algorithm, `stable_partition_copy`, does guarantee to preserve the relative order.

**See** <http://www.open-std.org/jtc1/sc22/wg21/docs/papers/2008/n2569.pdf>

**See** `stable_partition_copy`

**See** `partition`

### Template Function `thrust::partition_point(const thrust::detail::execution_policy_base<DerivedPolicy>&, ForwardIterator, ForwardIterator, Predicate)`

- Defined in file `_thrust_partition.h`

### Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::partition_point`” with arguments (`const thrust::detail::execution_policy_base<DerivedPolicy>&`, `ForwardIterator`, `ForwardIterator`, `Predicate`) in doxygen xml output for project “rocThrust” from directory: `./docBin/xml`. Potential matches:

```
- template<typename DerivedPolicy, typename ForwardIterator, typename Predicate> __
- host __ device__ ForwardIterator thrust::partition_point(const __
- thrust::detail::execution_policy_base< DerivedPolicy > &, ForwardIterator, __
- ForwardIterator, Predicate)
- template<typename ForwardIterator, typename Predicate>
  ForwardIterator thrust::partition_point(ForwardIterator, ForwardIterator, __
  Predicate)
```

## Template Function `thrust::partition_point(ForwardIterator, ForwardIterator, Predicate)`

### Function Documentation

```
template<typename ForwardIterator, typename Predicate>
ForwardIterator thrust::partition_point(ForwardIterator first, ForwardIterator last, Predicate
                                         pred)
```

`partition_point` returns an iterator pointing to the end of the true partition of a partitioned range. `partition_point` requires the input range  $[first, last)$  to be a partition; that is, all elements which satisfy `pred` shall appear before those that do not.

```
#include <thrust/partition.h>

struct is_even
{
    __host__ __device__
    bool operator()(const int &x)
    {
        return (x % 2) == 0;
    }
};

...

int A[] = {2, 4, 6, 8, 10, 1, 3, 5, 7, 9};
int *B = thrust::partition_point(A, A + 10, is_even());
// B - A is 5
// [A, B) contains only even values
```

**Return** An iterator `mid` such that `all_of(first, mid, pred)` and `none_of(mid, last, pred)` are both true.

**Pre** The range  $[first, last)$  shall be partitioned by `pred`.

**Note** Though similar, `partition_point` is not redundant with `find_if_not`. `partition_point`'s precondition provides an opportunity for a faster implementation.

### Parameters

- `first`: The beginning of the range to consider.
- `last`: The end of the range to consider.
- `pred`: A function object which decides to which partition each element of the range  $[first, last)$  belongs.

### Template Parameters

- `ForwardIterator`: is a model of `Forward Iterator`, and `ForwardIterator`'s `value_type` is convertible to `Predicate`'s `argument_type`.
- `Predicate`: is a model of `Predicate`.

**See** `partition`

**See** `find_if_not`

## Template Function `thrust::polar`

- Defined in file `thrust_complex.h`

### Function Documentation

```
template<typename T0, typename T1> __host__ __device__ complex<typename detail::promoted_nu
>Returns a complex with the specified magnitude and phase.
```

#### Parameters

- `m`: The magnitude of the returned `complex`.
- `theta`: The phase of the returned `complex` in radians.

## Template Function `thrust::pow(const complex<T0>&, const complex<T1>&)`

- Defined in file `thrust_complex.h`

### Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::pow`” with arguments (`const complex<T0>&`, `const complex<T1>&`) in doxygen xml output for project “rocThrust” from directory: `./docBin/xml`. Potential matches:

```
- template<typename T0, typename T1> __host__ __device__ complex<typename detail::promoted_nu
  ↵> thrust::pow(const complex<T0>&, const complex<T1>&)
- template<typename T0, typename T1> __host__ __device__ complex<typename detail::promoted_nu
  ↵> thrust::pow(const complex<T0>&, const T1 &)
- template<typename T0, typename T1> __host__ __device__ complex<typename detail::promoted_nu
  ↵> thrust::pow(const T0 &, const complex<T1>&)
```

## Template Function `thrust::pow(const complex<T0>&, const T1&)`

## Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “thrust::pow” with arguments (const complex<T0>&, const T1&) in doxygen xml output for project “rocThrust” from directory: ./docBin/xml.  
Potential matches:

```
- template<typename T0, typename T1>__host__ __device__ complex<typename>
→detail::promoted_numerical_type<T0, T1>::type> thrust::pow(const complex < T0 > &
→, const complex < T1 > &)
- template<typename T0, typename T1>__host__ __device__ complex<typename>
→detail::promoted_numerical_type<T0, T1>::type> thrust::pow(const complex < T0 > &
→, const T1 &)
- template<typename T0, typename T1>__host__ __device__ complex<typename>
→detail::promoted_numerical_type<T0, T1>::type> thrust::pow(const T0 &, const
→complex < T1 > &)
```

### Template Function thrust::pow(const T0&, const complex<T1>&)

## Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “thrust::pow” with arguments (const T0&, const complex<T1>&) in doxygen xml output for project “rocThrust” from directory: ./docBin/xml.  
Potential matches:

```
- template<typename T0, typename T1>__host__ __device__ complex<typename>
→detail::promoted_numerical_type<T0, T1>::type> thrust::pow(const complex < T0 > &
→, const complex < T1 > &)
- template<typename T0, typename T1>__host__ __device__ complex<typename>
→detail::promoted_numerical_type<T0, T1>::type> thrust::pow(const complex < T0 > &
→, const T1 &)
- template<typename T0, typename T1>__host__ __device__ complex<typename>
→detail::promoted_numerical_type<T0, T1>::type> thrust::pow(const T0 &, const
→complex < T1 > &)
```

### Template Function thrust::proj

- Defined in file\_thrust\_complex.h

## Function Documentation

```
template<typename T>__host__ __device__ complex<T> thrust::proj(const T & z)
```

Returns the projection of a complex on the Riemann sphere. For all finite complex it returns the argument. For complexes with a non finite part returns (INFINITY, +/-0) where the sign of the zero matches the sign of the imaginary part of the argument.

### Parameters

- z: The complex argument.

## Template Function `thrust::raw_pointer_cast`

- Defined in file\_thrust\_memory.h

### Function Documentation

```
template<typename Pointer> __host__ __device__ thrust::detail::pointer_traits<Pointer>::raw_
    raw_pointer_cast creates a "raw" pointer from a pointer-like type, simply returning the wrapped pointer,
    should it exist.
```

**Return** `ptr.get()`, if the expression is well formed; `ptr`, otherwise.

**See** `raw_reference_cast`

#### Parameters

- `ptr`: The pointer of interest.

## Template Function `thrust::raw_reference_cast(T&)`

- Defined in file\_thrust\_memory.h

### Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::raw_reference_cast`” with arguments (`T&`) in doxygen xml output for project “rocThrust” from directory: ./docBin/xml. Potential matches:

```
- template<typename T> __host__ __device__ detail::raw_reference<T>::type_
    ↳ thrust::raw_reference_cast(T &)
- template<typename T> __host__ __device__ detail::raw_reference<const T>::type_
    ↳ thrust::raw_reference_cast(const T &)
```

## Template Function `thrust::raw_reference_cast(const T&)`

### Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::raw_reference_cast`” with arguments (`const T&`) in doxygen xml output for project “rocThrust” from directory: ./docBin/xml. Potential matches:

```
- template<typename T> __host__ __device__ detail::raw_reference<T>::type_
    ↳ thrust::raw_reference_cast(T &)
- template<typename T> __host__ __device__ detail::raw_reference<const T>::type_
    ↳ thrust::raw_reference_cast(const T &)
```

**Template Function `thrust::reduce(const thrust::detail::execution_policy_base<DerivedPolicy>&, InputIterator, InputIterator)`**

- Defined in file `thrust_reduce.h`

**Function Documentation**

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::reduce`” with arguments (`const thrust::detail::execution_policy_base<DerivedPolicy>&`, `InputIterator`, `InputIterator`) in doxygen xml output for project “rocThrust” from directory: `./docBin/xml`. Potential matches:

```
- template<typename DerivedPolicy, typename InputIterator, typename T, typename _BinaryFunction> __host__ __device__ T thrust::reduce(const _thrust::detail::execution_policy_base< DerivedPolicy > &, InputIterator, _InputIterator, T, BinaryFunction)
- template<typename DerivedPolicy, typename InputIterator, typename T> __host__ __device__ T thrust::reduce(const thrust::detail::execution_policy_base< DerivedPolicy > &, InputIterator, InputIterator, T)
- template<typename DerivedPolicy, typename InputIterator> __host__ __device__ thrust::iterator_traits<InputIterator>::value_type thrust::reduce(const _thrust::detail::execution_policy_base< DerivedPolicy > &, InputIterator, _InputIterator)
- template<typename InputIterator, typename T, typename BinaryFunction> T thrust::reduce(InputIterator, InputIterator, T, BinaryFunction)
- template<typename InputIterator, typename T> T thrust::reduce(InputIterator, InputIterator, T)
- template<typename InputIterator> thrust::iterator_traits<InputIterator>::value_type thrust::reduce(InputIterator, _InputIterator)
```

**Template Function `thrust::reduce(InputIterator, InputIterator)`****Function Documentation**

`template<typename InputIterator>`

`thrust::iterator_traits<InputIterator>::value_type thrust ::reduce (InputIterator first, InputIterator last)`

`reduce` is a generalization of summation: it computes the sum (or some other binary operation) of all the elements in the range `[first, last]`. This version of `reduce` uses 0 as the initial value of the reduction. `reduce` is similar to the C++ Standard Template Library’s `std::accumulate`. The primary difference between the two functions is that `std::accumulate` guarantees the order of summation, while `reduce` requires associativity of the binary operation to parallelize the reduction.

Note that `reduce` also assumes that the binary reduction operator (in this case `operator+`) is commutative. If the reduction operator is not commutative then `thrust::reduce` should not be used. Instead, one could use `inclusive_scan` (which does not require commutativity) and select the last element of the output array.

The following code snippet demonstrates how to use `reduce` to compute the sum of a sequence of integers.

**Return** The result of the reduction.

**Parameters**

- `first`: The beginning of the sequence.
- `last`: The end of the sequence.

## Template Parameters

- `InputIterator`: is a model of `Input Iterator` and if `x` and `y` are objects of `InputIterator`'s `value_type`, then `x + y` is defined and is convertible to `InputIterator`'s `value_type`. If `T` is `InputIterator`'s `value_type`, then `T(0)` is defined.

```
#include <thrust/reduce.h>
...
int data[6] = {1, 0, 2, 2, 1, 3};
int result = thrust::reduce(data, data + 6);

// result == 9
```

See <http://www.sgi.com/tech/stl/accumulate.html>

## Template Function `thrust::reduce(const thrust::detail::execution_policy_base<DerivedPolicy>&, InputIterator, InputIterator, T)`

### Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::reduce`” with arguments (`const thrust::detail::execution_policy_base<DerivedPolicy>&`, `InputIterator`, `InputIterator`, `T`) in doxygen xml output for project “rocThrust” from directory: `./docBin/xml`. Potential matches:

```
- template<typename DerivedPolicy, typename InputIterator, typename T, typename BinaryFunction> __host__ __device__ T thrust::reduce(const thrust::detail::execution_policy_base< DerivedPolicy > &, InputIterator, InputIterator, T, BinaryFunction)
- template<typename DerivedPolicy, typename InputIterator, typename T> __host__ __device__ T thrust::reduce(const thrust::detail::execution_policy_base< DerivedPolicy > &, InputIterator, InputIterator, T)
- template<typename DerivedPolicy, typename InputIterator> __host__ __device__ thrust::iterator_traits<InputIterator>::value_type thrust::reduce(const thrust::detail::execution_policy_base< DerivedPolicy > &, InputIterator, InputIterator)
- template<typename InputIterator, typename T, typename BinaryFunction> T thrust::reduce(InputIterator, InputIterator, T, BinaryFunction)
- template<typename InputIterator, typename T> T thrust::reduce(InputIterator, InputIterator, T)
- template<typename InputIterator> thrust::iterator_traits<InputIterator>::value_type thrust::reduce(InputIterator, InputIterator)
```

## Template Function `thrust::reduce(InputIterator, InputIterator, T)`

### Function Documentation

```
template<typename InputIterator, typename T>
T thrust::reduce(InputIterator first, InputIterator last, T init)
```

`reduce` is a generalization of summation: it computes the sum (or some other binary operation) of all the elements in the range `[first, last]`. This version of `reduce` uses `init` as the initial value of the reduction. `reduce` is similar to the C++ Standard Template Library's `std::accumulate`. The primary difference

between the two functions is that `std::accumulate` guarantees the order of summation, while `reduce` requires associativity of the binary operation to parallelize the reduction.

Note that `reduce` also assumes that the binary reduction operator (in this case `operator+`) is commutative. If the reduction operator is not commutative then `thrust::reduce` should not be used. Instead, one could use `inclusive_scan` (which does not require commutativity) and select the last element of the output array.

The following code snippet demonstrates how to use `reduce` to compute the sum of a sequence of integers including an initialization value.

**Return** The result of the reduction.

#### Parameters

- `first`: The beginning of the input sequence.
- `last`: The end of the input sequence.
- `init`: The initial value.

#### Template Parameters

- `InputIterator`: is a model of `Input Iterator` and if `x` and `y` are objects of `InputIterator`'s `value_type`, then `x + y` is defined and is convertible to `T`.
- `T`: is convertible to `InputIterator`'s `value_type`.

```
#include <thrust/reduce.h>
...
int data[6] = {1, 0, 2, 2, 1, 3};
int result = thrust::reduce(data, data + 6, 1);
// result == 10
```

See <http://www.sgi.com/tech/stl/accumulate.html>

### Template Function `thrust::reduce(const thrust::detail::execution_policy_base<DerivedPolicy>&, InputIterator, InputIterator, T, BinaryFunction)`

#### Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::reduce`” with arguments (`const thrust::detail::execution_policy_base<DerivedPolicy>&`, `InputIterator`, `InputIterator`, `T`, `BinaryFunction`) in doxygen xml output for project “rocThrust” from directory: `./docBin/xml`. Potential matches:

```
- template<typename DerivedPolicy, typename InputIterator, typename T, typename_
↳BinaryFunction>__host__ __device__ T thrust::reduce(const_
↳thrust::detail::execution_policy_base< DerivedPolicy > &, InputIterator,_
↳InputIterator, T, BinaryFunction)
- template<typename DerivedPolicy, typename InputIterator, typename T>__host__ ___
↳device__ T thrust::reduce(const thrust::detail::execution_policy_base<_
↳DerivedPolicy > &, InputIterator, InputIterator, T)
- template<typename DerivedPolicy, typename InputIterator>__host__ __device___
↳thrust::iterator_traits<InputIterator>::value_type thrust::reduce(const_
↳thrust::detail::execution_policy_base< DerivedPolicy > &, InputIterator,_
↳InputIterator)
- template<typename InputIterator, typename T, typename BinaryFunction>
 T thrust::reduce(InputIterator, InputIterator, T, BinaryFunction)
- template<typename InputIterator, typename T>
 T thrust::reduce(InputIterator, InputIterator, T)
- template<typename InputIterator>
 thrust::iterator_traits<InputIterator>::value_type thrust::reduce(InputIterator,_
 ↳InputIterator)
```

## Template Function `thrust::reduce(InputIterator, InputIterator, T, BinaryFunction)`

### Function Documentation

```
template<typename InputIterator, typename T, typename BinaryFunction>
T thrust::reduce(InputIterator first, InputIterator last, T init, BinaryFunction binary_op)
```

`reduce` is a generalization of summation: it computes the sum (or some other binary operation) of all the elements in the range `[first, last]`. This version of `reduce` uses `init` as the initial value of the reduction and `binary_op` as the binary function used for summation. `reduce` is similar to the C++ Standard Template Library's `std::accumulate`. The primary difference between the two functions is that `std::accumulate` guarantees the order of summation, while `reduce` requires associativity of `binary_op` to parallelize the reduction.

Note that `reduce` also assumes that the binary reduction operator (in this case `binary_op`) is commutative. If the reduction operator is not commutative then `thrust::reduce` should not be used. Instead, one could use `inclusive_scan` (which does not require commutativity) and select the last element of the output array.

The following code snippet demonstrates how to use `reduce` to compute the maximum value of a sequence of integers.

**Return** The result of the reduction.

#### Parameters

- `first`: The beginning of the input sequence.
- `last`: The end of the input sequence.
- `init`: The initial value.
- `binary_op`: The binary function used to ‘sum’ values.

#### Template Parameters

- `InputIterator`: is a model of `Input Iterator` and `InputIterator`'s `value_type` is convertible to `T`.
- `T`: is a model of `Assignable`, and is convertible to `BinaryFunction`'s `first_argument_type` and `second_argument_type`.
- `BinaryFunction`: is a model of `Binary Function`, and `BinaryFunction`'s `result_type` is convertible to `OutputType`.

```
#include <thrust/reduce.h>
#include <thrust/functional.h>
...
int data[6] = {1, 0, 2, 2, 1, 3};
int result = thrust::reduce(data, data + 6,
                           -1,
                           thrust::maximum<int>());
// result == 3
```

See <http://www.sgi.com/tech/stl/accumulate.html>

See `transform_reduce`

**Template Function** `thrust::reduce_by_key(const thrust::detail::execution_policy_base<DerivedPolicy>&, InputIterator1, InputIterator1, InputIterator2, OutputIterator1, OutputIterator2)`

- Defined in file `thrust_reduce.h`

## Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::reduce_by_key`” with arguments (`const thrust::detail::execution_policy_base<DerivedPolicy>&`, `InputIterator1`, `InputIterator1`, `InputIterator2`, `OutputIterator1`, `OutputIterator2`) in doxygen xml output for project “rocThrust” from directory: `./docBin/xml`. Potential matches:

```
- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2,
          typename OutputIterator1, typename OutputIterator2, typename BinaryPredicate,
          typename BinaryFunction> __host__ __device__ thrust::pair<OutputIterator1,
          OutputIterator2> thrust::reduce_by_key(const thrust::detail::execution_policy_base<
          DerivedPolicy > &, InputIterator1, InputIterator1, InputIterator2,
          OutputIterator1, OutputIterator2, BinaryPredicate, BinaryFunction)
- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2,
          typename OutputIterator1, typename OutputIterator2, typename BinaryPredicate> __
          host__ __device__ thrust::pair<OutputIterator1,OutputIterator2> thrust::reduce_by_
          key(const thrust::detail::execution_policy_base< DerivedPolicy > &,
          InputIterator1, InputIterator1, InputIterator2, OutputIterator1, OutputIterator2,
          BinaryPredicate)
- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2,
          typename OutputIterator1, typename OutputIterator2> __host__ __device__ __
          thrust::pair<OutputIterator1,OutputIterator2> thrust::reduce_by_key(const
          thrust::detail::execution_policy_base< DerivedPolicy > &, InputIterator1,
          InputIterator1, InputIterator2, OutputIterator1, OutputIterator2)
- template<typename InputIterator1, typename InputIterator2, typename
          OutputIterator1, typename OutputIterator2, typename BinaryPredicate, typename
          BinaryFunction>
          thrust::pair<OutputIterator1, OutputIterator2> thrust::reduce_by_
          key(InputIterator1, InputIterator1, InputIterator2, OutputIterator1,
          OutputIterator2, BinaryPredicate, BinaryFunction)
- template<typename InputIterator1, typename InputIterator2, typename
          OutputIterator1, typename OutputIterator2, typename BinaryPredicate>
          thrust::pair<OutputIterator1, OutputIterator2> thrust::reduce_by_
          key(InputIterator1, InputIterator1, InputIterator2, OutputIterator1,
          OutputIterator2, BinaryPredicate)
- template<typename InputIterator1, typename InputIterator2, typename
          OutputIterator1, typename OutputIterator2>
          thrust::pair<OutputIterator1, OutputIterator2> thrust::reduce_by_
          key(InputIterator1, InputIterator1, InputIterator2, OutputIterator1,
          OutputIterator2)
```

**Template Function** `thrust::reduce_by_key(InputIterator1, InputIterator1, InputIterator2, OutputIterator1, OutputIterator2)`

## Function Documentation

```
template<typename InputIterator1, typename InputIterator2, typename OutputIterator1, typename OutputIterator2>
```

```
thrust::pair<OutputIterator1, OutputIterator2> thrust::reduce_by_key (InputIterator1 keys_first, InputIterator1 keys_last, InputIterator2 values_first, OutputIterator1 keys_output, OutputIterator2 values_output)
```

`reduce_by_key` is a generalization of `reduce` to key-value pairs. For each group of consecutive keys in the range `[keys_first, keys_last)` that are equal, `reduce_by_key` copies the first element of the group to the `keys_output`. The corresponding values in the range are reduced using the `plus` and the result copied to `values_output`.

This version of `reduce_by_key` uses the function object `equal_to` to test for equality and `plus` to reduce values with equal keys.

The following code snippet demonstrates how to use `reduce_by_key` to compact a sequence of key/value pairs and sum values with equal keys.

**Return** A pair of iterators at end of the ranges `[keys_output, keys_output_last)` and `[values_output, values_output_last)`.

**Pre** The input ranges shall not overlap either output range.

### Parameters

- `keys_first`: The beginning of the input key range.
- `keys_last`: The end of the input key range.
- `values_first`: The beginning of the input value range.
- `keys_output`: The beginning of the output key range.
- `values_output`: The beginning of the output value range.

### Template Parameters

- `InputIterator1`: is a model of `Input Iterator`,
- `InputIterator2`: is a model of `Input Iterator`,
- `OutputIterator1`: is a model of `Output Iterator` and `InputIterator1`'s `value_type` is convertible to `OutputIterator1`'s `value_type`.
- `OutputIterator2`: is a model of `Output Iterator` and `InputIterator2`'s `value_type` is convertible to `OutputIterator2`'s `value_type`.

```
#include <thrust/reduce.h>
...
const int N = 7;
int A[N] = {1, 3, 3, 3, 2, 2, 1}; // input keys
int B[N] = {9, 8, 7, 6, 5, 4, 3}; // input values
int C[N]; // output keys
int D[N]; // output values

thrust::pair<int*, int*> new_end;
new_end = thrust::reduce_by_key(A, A + N, B, C, D);

// The first four keys in C are now {1, 3, 2, 1} and new_end.first - C is 4.
// The first four values in D are now {9, 21, 9, 3} and new_end.second - D is 4.
```

**See** `reduce`

**See** `unique_copy`

See [unique\\_by\\_key](#)

See [unique\\_by\\_key\\_copy](#)

**Template Function `thrust::reduce_by_key(const thrust::detail::execution_policy_base<DerivedPolicy>&, InputIterator1, InputIterator1, InputIterator2, OutputIterator1, OutputIterator2, BinaryPredicate)`**

## Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::reduce_by_key`” with arguments (`const thrust::detail::execution_policy_base<DerivedPolicy>&`, `InputIterator1`, `InputIterator1`, `InputIterator2`, `OutputIterator1`, `OutputIterator2`, `BinaryPredicate`) in doxygen xml output for project “rocThrust” from directory: `./docBin/xml`. Potential matches:

```
- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2,
          typename OutputIterator1, typename OutputIterator2, typename BinaryPredicate,
          typename BinaryFunction> __host__ __device__ thrust::pair<OutputIterator1,
          OutputIterator2> thrust::reduce_by_key(const thrust::detail::execution_policy_base
          < DerivedPolicy > &, InputIterator1, InputIterator1, InputIterator2,
          OutputIterator1, OutputIterator2, BinaryPredicate, BinaryFunction)
- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2,
          typename OutputIterator1, typename OutputIterator2, typename BinaryPredicate>
          __host__ __device__ thrust::pair<OutputIterator1,OutputIterator2> thrust::reduce_by_
          key(const thrust::detail::execution_policy_base< DerivedPolicy > &,
          InputIterator1, InputIterator1, InputIterator2, OutputIterator1, OutputIterator2,
          BinaryPredicate)
- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2,
          typename OutputIterator1, typename OutputIterator2> __host__ __device__
          thrust::pair<OutputIterator1,OutputIterator2> thrust::reduce_by_key(const
          thrust::detail::execution_policy_base< DerivedPolicy > &, InputIterator1,
          InputIterator1, InputIterator2, OutputIterator1, OutputIterator2)
- template<typename InputIterator1, typename InputIterator2, typename
          OutputIterator1, typename OutputIterator2, typename BinaryPredicate, typename
          BinaryFunction>
          thrust::pair<OutputIterator1, OutputIterator2> thrust::reduce_by_
          key(InputIterator1, InputIterator1, InputIterator2, OutputIterator1,
          OutputIterator2, BinaryPredicate, BinaryFunction)
- template<typename InputIterator1, typename InputIterator2, typename
          OutputIterator1, typename OutputIterator2, typename BinaryPredicate>
          thrust::pair<OutputIterator1, OutputIterator2> thrust::reduce_by_
          key(InputIterator1, InputIterator1, InputIterator2, OutputIterator1,
          OutputIterator2, BinaryPredicate)
- template<typename InputIterator1, typename InputIterator2, typename
          OutputIterator1, typename OutputIterator2>
          thrust::pair<OutputIterator1, OutputIterator2> thrust::reduce_by_
          key(InputIterator1, InputIterator1, InputIterator2, OutputIterator1,
          OutputIterator2)
```

**Template Function `thrust::reduce_by_key(InputIterator1, InputIterator1, InputIterator2, OutputIterator1, OutputIterator2, BinaryPredicate)`**

## Function Documentation

```
template<typename InputIterator1, typename InputIterator2, typename OutputIterator1, typename OutputIterator2>
thrust::pair<OutputIterator1, OutputIterator2> thrust::reduce_by_key(InputIterator1 keys_first, InputIterator1 keys_last, InputIterator2 values_first, OutputIterator1 keys_output, OutputIterator2 values_output, BinaryPredicate binary_pred)
```

`reduce_by_key` is a generalization of `reduce` to key-value pairs. For each group of consecutive keys in the range `[keys_first, keys_last)` that are equal, `reduce_by_key` copies the first element of the group to the `keys_output`. The corresponding values in the range are reduced using the `plus` and the result copied to `values_output`.

This version of `reduce_by_key` uses the function object `binary_pred` to test for equality and `plus` to reduce values with equal keys.

The following code snippet demonstrates how to use `reduce_by_key` to compact a sequence of key/value pairs and sum values with equal keys.

**Return** A pair of iterators at end of the ranges `[keys_output, keys_output_last)` and `[values_output, values_output_last)`.

**Pre** The input ranges shall not overlap either output range.

### Parameters

- `keys_first`: The beginning of the input key range.
- `keys_last`: The end of the input key range.
- `values_first`: The beginning of the input value range.
- `keys_output`: The beginning of the output key range.
- `values_output`: The beginning of the output value range.
- `binary_pred`: The binary predicate used to determine equality.

### Template Parameters

- `InputIterator1`: is a model of `Input Iterator`,
- `InputIterator2`: is a model of `Input Iterator`,
- `OutputIterator1`: is a model of `Output Iterator` and `InputIterator1`'s `value_type` is convertible to `OutputIterator1`'s `value_type`.
- `OutputIterator2`: is a model of `Output Iterator` and `InputIterator2`'s `value_type` is convertible to `OutputIterator2`'s `value_type`.
- `BinaryPredicate`: is a model of `Binary Predicate`.

```
#include <thrust/reduce.h>
...
const int N = 7;
int A[N] = {1, 3, 3, 3, 2, 2, 1}; // input keys
int B[N] = {9, 8, 7, 6, 5, 4, 3}; // input values
int C[N]; // output keys
int D[N]; // output values

thrust::pair<int*, int*> new_end;
```

(continues on next page)

(continued from previous page)

```

thrust::equal_to<int> binary_pred;
new_end = thrust::reduce_by_key(A, A + N, B, C, D, binary_pred);

// The first four keys in C are now {1, 3, 2, 1} and new_end.first - C is 4.
// The first four values in D are now {9, 21, 9, 3} and new_end.second - D is 4.

```

**See** reduce**See** unique\_copy**See** unique\_by\_key**See** unique\_by\_key\_copy

**Template Function** `thrust::reduce_by_key(const thrust::detail::execution_policy_base<DerivedPolicy>&, InputIterator1, InputIterator1, InputIterator2, OutputIterator1, OutputIterator2, BinaryPredicate, BinaryFunction)`

## Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “thrust::reduce\_by\_key” with arguments (const thrust::detail::execution\_policy\_base<DerivedPolicy>&, InputIterator1, InputIterator1, InputIterator2, OutputIterator1, OutputIterator2, BinaryPredicate, BinaryFunction) in doxygen xml output for project “roc-Thrust” from directory: ./docBin/xml. Potential matches:

```

- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2,
  → typename OutputIterator1, typename OutputIterator2, typename BinaryPredicate,
  →typename BinaryFunction> __host__ __device__ thrust::pair<OutputIterator1,
  →OutputIterator2> thrust::reduce_by_key(const thrust::detail::execution_policy_base<
  ←< DerivedPolicy > &, InputIterator1, InputIterator1, InputIterator2,
  →OutputIterator1, OutputIterator2, BinaryPredicate, BinaryFunction)

- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2,
  → typename OutputIterator1, typename OutputIterator2, typename BinaryPredicate> __
  →host__ __device__ thrust::pair<OutputIterator1, OutputIterator2> thrust::reduce_by_
  →key(const thrust::detail::execution_policy_base< DerivedPolicy > &,
  →InputIterator1, InputIterator1, InputIterator2, OutputIterator1, OutputIterator2,
  →BinaryPredicate)

- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2,
  → typename OutputIterator1, typename OutputIterator2> __host__ __device__ __
  →thrust::pair<OutputIterator1, OutputIterator2> thrust::reduce_by_key(const_
  →thrust::detail::execution_policy_base< DerivedPolicy > &, InputIterator1,
  →InputIterator1, InputIterator2, OutputIterator1, OutputIterator2)

- template<typename InputIterator1, typename InputIterator2, typename_
  →OutputIterator1, typename OutputIterator2, typename BinaryPredicate, typename_
  →BinaryFunction>
  →thrust::pair<OutputIterator1, OutputIterator2> thrust::reduce_by_
  →key(InputIterator1, InputIterator1, InputIterator2, OutputIterator1,
  →OutputIterator2, BinaryPredicate, BinaryFunction)

- template<typename InputIterator1, typename InputIterator2, typename_
  →OutputIterator1, typename OutputIterator2, typename BinaryPredicate>
  →thrust::pair<OutputIterator1, OutputIterator2> thrust::reduce_by_
  →key(InputIterator1, InputIterator1, InputIterator2, OutputIterator1,
  →OutputIterator2, BinaryPredicate)

- template<typename InputIterator1, typename InputIterator2, typename_
  →OutputIterator1, typename OutputIterator2>
  →thrust::pair<OutputIterator1, OutputIterator2> thrust::reduce_by_
  →key(InputIterator1, InputIterator1, InputIterator2, OutputIterator1,
  →OutputIterator2)

```

## Template Function `thrust::reduce_by_key(InputIterator1, InputIterator1, InputIterator2, OutputIterator1, OutputIterator2, BinaryPredicate, BinaryFunction)`

### Function Documentation

```
template<typename InputIterator1, typename InputIterator2, typename OutputIterator1, typename OutputIterator2>
thrust::pair<OutputIterator1, OutputIterator2> thrust::reduce_by_key(InputIterator1 keys_first, InputIterator1 keys_last, InputIterator2 values_first, OutputIterator1 keys_output, OutputIterator2 values_output, BinaryPredicate binary_pred, BinaryFunction binary_op)
```

`reduce_by_key` is a generalization of `reduce` to key-value pairs. For each group of consecutive keys in the range `[keys_first, keys_last)` that are equal, `reduce_by_key` copies the first element of the group to the `keys_output`. The corresponding values in the range are reduced using the `BinaryFunction` `binary_op` and the result copied to `values_output`. Specifically, if consecutive key iterators `i` and `(i + 1)` are such that `binary_pred(*i, *(i+1))` is true, then the corresponding values are reduced to a single value with `binary_op`.

This version of `reduce_by_key` uses the function object `binary_pred` to test for equality and `binary_op` to reduce values with equal keys.

The following code snippet demonstrates how to use `reduce_by_key` to compact a sequence of key/value pairs and sum values with equal keys.

**Return** A pair of iterators at end of the ranges `[keys_output, keys_output_last)` and `[values_output, values_output_last)`.

**Pre** The input ranges shall not overlap either output range.

### Parameters

- `keys_first`: The beginning of the input key range.
- `keys_last`: The end of the input key range.
- `values_first`: The beginning of the input value range.
- `keys_output`: The beginning of the output key range.
- `values_output`: The beginning of the output value range.
- `binary_pred`: The binary predicate used to determine equality.
- `binary_op`: The binary function used to accumulate values.

### Template Parameters

- `InputIterator1`: is a model of `Input Iterator`,
- `InputIterator2`: is a model of `Input Iterator`,
- `OutputIterator1`: is a model of `Output Iterator` and `InputIterator1`'s `value_type` is convertible to `OutputIterator1`'s `value_type`.
- `OutputIterator2`: is a model of `Output Iterator` and `InputIterator2`'s `value_type` is convertible to `OutputIterator2`'s `value_type`.

- `BinaryPredicate`: is a model of `Binary Predicate`.
- `BinaryFunction`: is a model of `Binary Function` and `BinaryFunction`'s `result_type` is convertible to `OutputIterator2`'s `value_type`.

```
#include <thrust/reduce.h>
...
const int N = 7;
int A[N] = {1, 3, 3, 3, 2, 2, 1}; // input keys
int B[N] = {9, 8, 7, 6, 5, 4, 3}; // input values
int C[N]; // output keys
int D[N]; // output values

thrust::pair<int*, int*> new_end;
thrust::equal_to<int> binary_pred;
thrust::plus<int> binary_op;
new_end = thrust::reduce_by_key(A, A + N, B, C, D, binary_pred, binary_op);

// The first four keys in C are now {1, 3, 2, 1} and new_end.first - C is 4.
// The first four values in D are now {9, 21, 9, 3} and new_end.second - D is 4.
```

**See** `reduce`

**See** `unique_copy`

**See** `unique_by_key`

**See** `unique_by_key_copy`

**Template Function** `thrust::remove(const thrust::detail::execution_policy_base<DerivedPolicy>&, ForwardIterator, ForwardIterator, const T&)`

## Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::remove`” with arguments (`const thrust::detail::execution_policy_base<DerivedPolicy>&`, `ForwardIterator`, `ForwardIterator`, `const T&`) in doxygen xml output for project “rocThrust” from directory: `./docBin/xml`. Potential matches:

```
- template<typename DerivedPolicy, typename ForwardIterator, typename T> __host__ __
  __device__ ForwardIterator thrust::remove(const thrust::detail::execution_policy_
  __base< DerivedPolicy > &, ForwardIterator, ForwardIterator, const T &)
- template<typename ForwardIterator, typename T>
  ForwardIterator thrust::remove(ForwardIterator, ForwardIterator, const T &)
```

**Template Function** `thrust::remove(ForwardIterator, ForwardIterator, const T&)`

## Function Documentation

```
template<typename ForwardIterator, typename T>
ForwardIterator thrust::remove(ForwardIterator first, ForwardIterator last, const T &value)
remove removes from the range [first, last) all elements that are equal to value. That is, remove re-
turns an iterator new_last such that the range [first, new_last) contains no elements equal to value.
The iterators in the range [new_first, last) are all still dereferenceable, but the elements that they point
```

to are unspecified. `remove` is stable, meaning that the relative order of elements that are not equal to `value` is unchanged.

The following code snippet demonstrates how to use `remove` to remove a number of interest from a range.

**Return** A `ForwardIterator` pointing to the end of the resulting range of elements which are not equal to `value`.

### Parameters

- `first`: The beginning of the range of interest.
- `last`: The end of the range of interest.
- `value`: The value to remove from the range [`first`, `last`). Elements which are equal to `value` are removed from the sequence.

### Template Parameters

- `ForwardIterator`: is a model of `Forward Iterator`, and `ForwardIterator` is mutable.
- `T`: is a model of `Equality Comparable`, and objects of type `T` can be compared for equality with objects of `ForwardIterator`'s `value_type`.

```
#include <thrust/remove.h>
...
const int N = 6;
int A[N] = {3, 1, 4, 1, 5, 9};
int *new_end = thrust::remove(A, A + N, 1);
// The first four values of A are now {3, 4, 5, 9}
// Values beyond new_end are unspecified
```

**Note** The meaning of “removal” is somewhat subtle. `remove` does not destroy any iterators, and does not change the distance between `first` and `last`. (There’s no way that it could do anything of the sort.) So, for example, if `V` is a `device_vector`, `remove(V.begin(), V.end(), 0)` does not change `V.size()`: `V` will contain just as many elements as it did before. `remove` returns an iterator that points to the end of the resulting range after elements have been removed from it; it follows that the elements after that iterator are of no interest, and may be discarded. If you are removing elements from a `Sequence`, you may simply `erase` them. That is, a reasonable way of removing elements from a `Sequence` is `S.erase(remove(S.begin(), S.end(), x), S.end())`.

**See** <http://www.sgi.com/tech/stl/remove.html>

**See** `remove_if`

**See** `remove_copy`

**See** `remove_copy_if`

## Template Function `thrust::remove_copy(const thrust::detail::execution_policy_base<DerivedPolicy>&, InputIterator, InputIterator, OutputIterator, const T&)`

- Defined in file `thrust_remove.h`

## Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “thrust::remove\_copy” with arguments (const thrust::detail::execution\_policy\_base<DerivedPolicy>&, InputIterator, InputIterator, OutputIterator, const T&) in doxygen xml output for project “rocThrust” from directory: ./docBin/xml. Potential matches:

```
- template<typename DerivedPolicy, typename InputIterator, typename OutputIterator,
         →typename T> __host__ __device__ OutputIterator thrust::remove_copy(const
         →thrust::detail::execution_policy_base< DerivedPolicy > &, InputIterator,
         →InputIterator, OutputIterator, const T &)
- template<typename InputIterator, typename OutputIterator, typename T>
  OutputIterator thrust::remove_copy(InputIterator, InputIterator, OutputIterator,
         →const T &)
```

## Template Function `thrust::remove_copy(InputIterator, InputIterator, OutputIterator, const T&)`

### Function Documentation

```
template<typename InputIterator, typename OutputIterator, typename T>
OutputIterator thrust::remove_copy(InputIterator first, InputIterator last, OutputIterator result,
                                  const T &value)
```

`remove_copy` copies elements that are not equal to `value` from the range `[first, last]` to a range beginning at `result`. The return value is the end of the resulting range. This operation is stable, meaning that the relative order of the elements that are copied is the same as in the range `[first, last]`.

The following code snippet demonstrates how to use `remove_copy` to copy a sequence of numbers to an output range while omitting a value of interest.

**Return** An `OutputIterator` pointing to the end of the resulting range of elements which are not equal to `value`.

**Pre** The range `[first, last]` shall not overlap the range `[result, result + (last - first)]`.

### Parameters

- `first`: The beginning of the range of interest.
- `last`: The end of the range of interest.
- `result`: The resulting range is copied to the sequence beginning at this location.
- `value`: The value to omit from the copied range.

### Template Parameters

- `InputIterator`: is a model of `Input Iterator`, and `InputIterator`'s `value_type` is convertible to a type in `OutputIterator`'s set of `value_types`.
- `OutputIterator`: is a model of `Output Iterator`.
- `T`: is a model of `Equality Comparable`, and objects of type `T` can be compared for equality with objects of `InputIterator`'s `value_type`.

```
#include <thrust/remove.h>
...
const int N = 6;
int V[N] = {-2, 0, -1, 0, 1, 2};
```

(continues on next page)

(continued from previous page)

```
int result[N-2];
thrust::remove_copy(V, V + N, result, 0);
// V remains {-2, 0, -1, 0, 1, 2}
// result is now {-2, -1, 1, 2}
```

See [http://www.sgi.com/tech/stl/remove\\_copy.html](http://www.sgi.com/tech/stl/remove_copy.html)

See remove

See remove\_if

See remove\_copy\_if

### Template Function thrust::remove\_copy\_if(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, InputIterator, InputIterator, OutputIterator, Predicate)

- Defined in file\_thrust\_remove.h

#### Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “thrust::remove\_copy\_if” with arguments (const thrust::detail::execution\_policy\_base<DerivedPolicy>&, InputIterator, InputIterator, OutputIterator, Predicate) in doxygen xml output for project “rocThrust” from directory: ./docBin/xml. Potential matches:

```
- template<typename DerivedPolicy, typename InputIterator, typename OutputIterator,
          typename Predicate> __host__ __device__ OutputIterator thrust::remove_copy_
          if(const thrust::detail::execution_policy_base< DerivedPolicy > &, InputIterator,
             InputIterator, OutputIterator, Predicate)
- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2,
          typename OutputIterator, typename Predicate> __host__ __device__ OutputIterator_
          thrust::remove_copy_if(const thrust::detail::execution_policy_base< DerivedPolicy >
          &, InputIterator1, InputIterator1, InputIterator2, OutputIterator, Predicate)
- template<typename InputIterator, typename OutputIterator, typename Predicate>
  OutputIterator thrust::remove_copy_if(InputIterator, InputIterator,_
  OutputIterator, Predicate)
- template<typename InputIterator1, typename InputIterator2, typename_
  OutputIterator, typename Predicate>
  OutputIterator thrust::remove_copy_if(InputIterator1, InputIterator1,_
  InputIterator2, OutputIterator, Predicate)
```

### Template Function thrust::remove\_copy\_if(InputIterator, InputIterator, OutputIterator, Predicate)

#### Function Documentation

```
template<typename InputIterator, typename OutputIterator, typename Predicate>
OutputIterator thrust::remove_copy_if(InputIterator first, InputIterator last, OutputIterator result,
                                     Predicate pred)
```

remove\_copy\_if copies elements from the range [first, last) to a range beginning at result, except that elements for which pred is true are not copied. The return value is the end of the resulting range. This operation is stable, meaning that the relative order of the elements that are copied is the same as the range [first, last).

The following code snippet demonstrates how to use `remove_copy_if` to copy a sequence of numbers to an output range while omitting even numbers.

**Return** An `OutputIterator` pointing to the end of the resulting range.

**Pre** The range `[first, last)` shall not overlap the range `[result, result + (last - first))`.

### Parameters

- `first`: The beginning of the range of interest.
- `last`: The end of the range of interest.
- `result`: The resulting range is copied to the sequence beginning at this location.
- `pred`: A predicate to evaluate for each element of the range `[first, last)`. Elements for which `pred` evaluates to `false` are not copied to the resulting sequence.

### Template Parameters

- `InputIterator`: is a model of `Input Iterator`, `InputIterator`'s `value_type` is convertible to a type in `OutputIterator`'s set of `value_types`, and `InputIterator`'s `value_type` is convertible to `Predicate`'s `argument_type`.
- `OutputIterator`: is a model of `Output Iterator`.
- `Predicate`: is a model of `Predicate`.

```
#include <thrust/remove.h>
...
struct is_even
{
    __host__ __device__
    bool operator() (const int x)
    {
        return (x % 2) == 0;
    }
};
...
const int N = 6;
int V[N] = {-2, 0, -1, 0, 1, 2};
int result[2];
thrust::remove_copy_if(V, V + N, result, is_even());
// V remains {-2, 0, -1, 0, 1, 2}
// result is now {1, 1}
```

See [http://www.sgi.com/tech/stl/remove\\_copy\\_if.html](http://www.sgi.com/tech/stl/remove_copy_if.html)

See `remove`

See `remove_copy`

See `remove_if`

**Template Function** `thrust::remove_copy_if(const thrust::detail::execution_policy_base<DerivedPolicy>&, InputIterator1, InputIterator1, InputIterator2, OutputIterator, Predicate)`

## Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “thrust::remove\_copy\_if” with arguments (const thrust::detail::execution\_policy\_base<DerivedPolicy>&, InputIterator1, InputIterator1, InputIterator2, OutputIterator, Predicate) in doxygen xml output for project “rocThrust” from directory: ./docBin/xml. Potential matches:

```
- template<typename DerivedPolicy, typename InputIterator, typename OutputIterator,
→typename Predicate> __host__ __device__ OutputIterator thrust::remove_copy_
→if(const thrust::detail::execution_policy_base< DerivedPolicy > &, InputIterator,
→InputIterator, OutputIterator, Predicate)
- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2,
→ typename OutputIterator, typename Predicate> __host__ __device__ OutputIterator_
→thrust::remove_copy_if(const thrust::detail::execution_policy_base< DerivedPolicy >
→&, InputIterator1, InputIterator1, InputIterator2, OutputIterator, Predicate)
- template<typename InputIterator, typename OutputIterator, typename Predicate>
OutputIterator thrust::remove_copy_if(InputIterator, InputIterator,
→OutputIterator, Predicate)
- template<typename InputIterator1, typename InputIterator2, typename_
→OutputIterator, typename Predicate>
OutputIterator thrust::remove_copy_if(InputIterator1, InputIterator1,
→InputIterator2, OutputIterator, Predicate)
```

## Template Function thrust::remove\_copy\_if(InputIterator1, InputIterator1, InputIterator2, OutputIterator, Predicate)

### Function Documentation

```
template<typename InputIterator1, typename InputIterator2, typename OutputIterator, typename Predicate>
OutputIterator thrust::remove_copy_if(InputIterator1 first, InputIterator1 last, InputIterator2 stencil,
→OutputIterator result, Predicate pred)
```

remove\_copy\_if copies elements from the range [first, last) to a range beginning at result, except that elements for which pred of the corresponding stencil value is true are not copied. The return value is the end of the resulting range. This operation is stable, meaning that the relative order of the elements that are copied is the same as the range [first, last).

The following code snippet demonstrates how to use remove\_copy\_if to copy a sequence of numbers to an output range while omitting specific elements.

**Return** An OutputIterator pointing to the end of the resulting range.

**Pre** The range [stencil, stencil + (last - first)) shall not overlap the range [result, result + (last - first)).

### Parameters

- **first:** The beginning of the range of interest.
- **last:** The end of the range of interest.
- **stencil:** The beginning of the stencil sequence.
- **result:** The resulting range is copied to the sequence beginning at this location.
- **pred:** A predicate to evaluate for each element of the range [first, last). Elements for which pred evaluates to false are not copied to the resulting sequence.

### Template Parameters

- `InputIterator1`: is a model of `Input Iterator`, `InputIterator1`'s `value_type` is convertible to a type in `OutputIterator`'s set of `value_types`.
- `InputIterator2`: is a model of `Input Iterator`, and `InputIterator2`'s `value_type` is convertible to `Predicate`'s `argument_type`.
- `OutputIterator`: is a model of `Output Iterator`.
- `Predicate`: is a model of `Predicate`.

```
#include <thrust/remove.h>
...
const int N = 6;
int V[N] = {-2, 0, -1, 0, 1, 2};
int S[N] = { 1, 1, 0, 1, 0, 1};
int result[2];
thrust::remove_copy_if(V, V + N, S, result, thrust::identity<int>());
// V remains {-2, 0, -1, 0, 1, 2}
// result is now {-1, 1}
```

See [http://www.sgi.com/tech/stl/remove\\_copy\\_if.html](http://www.sgi.com/tech/stl/remove_copy_if.html)

See `remove`

See `remove_copy`

See `remove_if`

See `copy_if`

### Template Function `thrust::remove_if(const thrust::detail::execution_policy_base<DerivedPolicy>&, ForwardIterator, ForwardIterator, Predicate)`

- Defined in file `thrust_remove.h`

### Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::remove_if`” with arguments (`const thrust::detail::execution_policy_base<DerivedPolicy>&`, `ForwardIterator`, `ForwardIterator`, `Predicate`) in doxygen xml output for project “rocThrust” from directory: `./docBin/xml`. Potential matches:

```
- template<typename DerivedPolicy, typename ForwardIterator, typename InputIterator,
→ typename Predicate> __host__ __device__ ForwardIterator thrust::remove_if(const
→ thrust::detail::execution_policy_base< DerivedPolicy > &, ForwardIterator,
→ ForwardIterator, InputIterator, Predicate)
- template<typename DerivedPolicy, typename ForwardIterator, typename Predicate> __
→ host__ __device__ ForwardIterator thrust::remove_if(const
→ thrust::detail::execution_policy_base< DerivedPolicy > &, ForwardIterator,
→ ForwardIterator, Predicate)
- template<typename ForwardIterator, typename InputIterator, typename Predicate>
  ForwardIterator thrust::remove_if(ForwardIterator, ForwardIterator, InputIterator,
→ Predicate)
- template<typename ForwardIterator, typename Predicate>
  ForwardIterator thrust::remove_if(ForwardIterator, ForwardIterator, Predicate)
```

## Template Function `thrust::remove_if(ForwardIterator, ForwardIterator, Predicate)`

### Function Documentation

```
template<typename ForwardIterator, typename Predicate>
ForwardIterator thrust::remove_if(ForwardIterator first, ForwardIterator last, Predicate pred)
remove_if removes from the range [first, last) every element x such that pred(x) is true. That is, remove_if returns an iterator new_last such that the range [first, new_last) contains no elements for which pred is true. The iterators in the range [new_last, last) are all still dereferenceable, but the elements that they point to are unspecified. remove_if is stable, meaning that the relative order of elements that are not removed is unchanged.
```

The following code snippet demonstrates how to use `remove_if` to remove all even numbers from an array of integers.

**Return** A `ForwardIterator` pointing to the end of the resulting range of elements for which `pred` evaluated to `true`.

### Parameters

- `first`: The beginning of the range of interest.
- `last`: The end of the range of interest.
- `pred`: A predicate to evaluate for each element of the range `[first, last)`. Elements for which `pred` evaluates to `true` are removed from the sequence.

### Template Parameters

- `ForwardIterator`: is a model of `Forward Iterator`, `ForwardIterator` is `mutable`, and `ForwardIterator`'s `value_type` is convertible to `Predicate`'s `argument_type`.
- `Predicate`: is a model of `Predicate`.

```
#include <thrust/remove.h>
...
struct is_even
{
    __host__ __device__
    bool operator()(const int x)
    {
        return (x % 2) == 0;
    }
};
...
const int N = 6;
int A[N] = {1, 4, 2, 8, 5, 7};
int *new_end = thrust::remove_if(A, A + N, is_even());
// The first three values of A are now {1, 5, 7}
// Values beyond new_end are unspecified
```

**Note** The meaning of “removal” is somewhat subtle. `remove_if` does not destroy any iterators, and does not change the distance between `first` and `last`. (There’s no way that it could do anything of the sort.) So, for example, if `V` is a `device_vector`, `remove_if(V.begin(), V.end(), pred)` does not change `V.size()`: `V` will contain just as many elements as it did before. `remove_if` returns an iterator that points to the end of the resulting range after elements have been removed from it; it follows that the elements after that iterator are of no interest, and may be discarded. If you are removing elements from a `Sequence`, you may simply erase them. That is, a reasonable way of removing elements from a `Sequence` is `S.erase(remove_if(S.begin(), S.end(), pred), S.end())`.

See [http://www.sgi.com/tech/stl/remove\\_if.html](http://www.sgi.com/tech/stl/remove_if.html)

See remove

See remove\_copy

See remove\_copy\_if

## Template Function `thrust::remove_if(const thrust::detail::execution_policy_base<DerivedPolicy>&, ForwardIterator, ForwardIterator, InputIterator, Predicate)`

### Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::remove_if`” with arguments (`const thrust::detail::execution_policy_base<DerivedPolicy>&`, `ForwardIterator`, `ForwardIterator`, `InputIterator`, `Predicate`) in doxygen xml output for project “rocThrust” from directory: `./docBin/xml`. Potential matches:

```
- template<typename DerivedPolicy, typename ForwardIterator, typename InputIterator,
          typename Predicate> __host__ __device__ ForwardIterator thrust::remove_if(const
          thrust::detail::execution_policy_base< DerivedPolicy > &, ForwardIterator,
          ForwardIterator, InputIterator, Predicate)
- template<typename DerivedPolicy, typename ForwardIterator, typename Predicate> __
          host__ __device__ ForwardIterator thrust::remove_if(const
          thrust::detail::execution_policy_base< DerivedPolicy > &, ForwardIterator,
          ForwardIterator, Predicate)
- template<typename ForwardIterator, typename InputIterator, typename Predicate>
          ForwardIterator thrust::remove_if(ForwardIterator, ForwardIterator, InputIterator,
          Predicate)
- template<typename ForwardIterator, typename Predicate>
          ForwardIterator thrust::remove_if(ForwardIterator, ForwardIterator, Predicate)
```

## Template Function `thrust::remove_if(ForwardIterator, ForwardIterator, InputIterator, Predicate)`

### Function Documentation

```
template<typename ForwardIterator, typename InputIterator, typename Predicate>
ForwardIterator thrust::remove_if(ForwardIterator first, ForwardIterator last, InputIterator stencil,
                                 Predicate pred)
```

`remove_if` removes from the range  $[first, last]$  every element  $x$  such that  $pred(x)$  is true. That is, `remove_if` returns an iterator `new_last` such that the range  $[first, new\_last)$  contains no elements for which `pred` of the corresponding `stencil` value is true. The iterators in the range  $[new\_last, last)$  are all still dereferenceable, but the elements that they point to are unspecified. `remove_if` is stable, meaning that the relative order of elements that are not removed is unchanged.

The following code snippet demonstrates how to use `remove_if` to remove specific elements from an array of integers.

**Return** A `ForwardIterator` pointing to the end of the resulting range of elements for which `pred` evaluated to true.

**Pre** The range  $[first, last)$  shall not overlap the range  $[result, result + (last - first))$ .

**Pre** The range  $[stencil, stencil + (last - first))$  shall not overlap the range  $[result, result + (last - first))$ .

## Parameters

- `first`: The beginning of the range of interest.
- `last`: The end of the range of interest.
- `stencil`: The beginning of the stencil sequence.
- `pred`: A predicate to evaluate for each element of the range [`stencil`, `stencil + (last - first)`). Elements for which `pred` evaluates to `true` are removed from the sequence [`first`, `last`)

## Template Parameters

- `ForwardIterator`: is a model of `Forward Iterator` and `ForwardIterator` is mutable.
- `InputIterator`: is a model of `Input Iterator`, and `InputIterator`'s `value_type` is convertible to `Predicate`'s `argument_type`.
- `Predicate`: is a model of `Predicate`.

```
#include <thrust/remove.h>
...
const int N = 6;
int A[N] = {1, 4, 2, 8, 5, 7};
int S[N] = {0, 1, 1, 1, 0, 0};

int *new_end = thrust::remove_if(A, A + N, S, thrust::identity<int>());
// The first three values of A are now {1, 5, 7}
// Values beyond new_end are unspecified
```

**Note** The range [`first`, `last`) is not permitted to overlap with the range [`stencil`, `stencil + (last - first)`).

See [http://www.sgi.com/tech/stl/remove\\_if.html](http://www.sgi.com/tech/stl/remove_if.html)

See `remove`

See `remove_copy`

See `remove_copy_if`

**Template Function** `thrust::replace(const thrust::detail::execution_policy_base<DerivedPolicy>&, ForwardIterator, ForwardIterator, const T&, const T&)`

- Defined in file `_thrust_replace.h`

## Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::replace`” with arguments (`const thrust::detail::execution_policy_base<DerivedPolicy>&`, `ForwardIterator`, `ForwardIterator`, `const T&`, `const T&`) in doxygen xml output for project “rocThrust” from directory: `./docBin/xml`. Potential matches:

```
- template<typename DerivedPolicy, typename ForwardIterator, typename T> __host__ __
  __device__ void thrust::replace(const thrust::detail::execution_policy_base<↳
  ↳DerivedPolicy > &, ForwardIterator, ForwardIterator, const T &, const T &)
- template<typename ForwardIterator, typename T>
  void thrust::replace(ForwardIterator, ForwardIterator, const T&, const T&)
```

## Template Function `thrust::replace(ForwardIterator, ForwardIterator, const T&, const T&)`

### Function Documentation

```
template<typename ForwardIterator, typename T>
void thrust::replace(ForwardIterator first, ForwardIterator last, const T &old_value, const T &new_value)
```

`replace` replaces every element in the range [first, last) equal to `old_value` with `new_value`. That is: for every iterator *i*, if `*i == old_value` then it performs the assignment `*i = new_value`.

The following code snippet demonstrates how to use `replace` to replace a value of interest in a `device_vector` with another.

#### Parameters

- `first`: The beginning of the sequence of interest.
- `last`: The end of the sequence of interest.
- `old_value`: The value to replace.
- `new_value`: The new value to replace `old_value`.

#### Template Parameters

- `ForwardIterator`: is a model of `Forward Iterator`, and `ForwardIterator` is mutable.
- `T`: is a model of `Assignable`, `T` is a model of `EqualityComparable`, objects of `T` may be compared for equality with objects of `ForwardIterator`'s `value_type`, and `T` is convertible to `ForwardIterator`'s `value_type`.

```
#include <thrust/replace.h>
#include <thrust/device_vector.h>

...

thrust::device_vector<int> A(4);
A[0] = 1;
A[1] = 2;
A[2] = 3;
A[3] = 1;

thrust::replace(A.begin(), A.end(), 1, 99);

// A contains [99, 2, 3, 99]
```

See <http://www.sgi.com/tech/stl/replace.html>

See `replace_if`

See `replace_copy`

See `replace_copy_if`

**Template Function `thrust::replace_copy(const thrust::detail::execution_policy_base<DerivedPolicy>&, InputIterator, InputIterator, OutputIterator, const T&, const T&)`**

- Defined in file `thrust_replace.h`

## Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::replace_copy`” with arguments (`const thrust::detail::execution_policy_base<DerivedPolicy>&`, `InputIterator`, `InputIterator`, `OutputIterator`, `const T&`, `const T&`) in doxygen xml output for project “rocThrust” from directory: `./docBin/xml`. Potential matches:

```
- template<typename DerivedPolicy, typename InputIterator, typename OutputIterator,
         typename T> __host__ __device__ OutputIterator thrust::replace_copy(const
         thrust::detail::execution_policy_base< DerivedPolicy > &, InputIterator,
         InputIterator, OutputIterator, const T &, const T &)
- template<typename InputIterator, typename OutputIterator, typename T>
  OutputIterator thrust::replace_copy(InputIterator, InputIterator, OutputIterator,
         const T &, const T &)
```

**Template Function `thrust::replace_copy(InputIterator, InputIterator, OutputIterator, const T&, const T&)`**

## Function Documentation

```
template<typename InputIterator, typename OutputIterator, typename T>
OutputIterator thrust::replace_copy(InputIterator first, InputIterator last, OutputIterator result,
                                   const T &old_value, const T &new_value)
replace_copy copies elements from the range [first, last) to the range [result, result +
(last-first)), except that any element equal to old_value is not copied; new_value is copied instead.
```

More precisely, for every integer n such that  $0 \leq n < \text{last}-\text{first}$ , replace\_copy performs the assignment  $*(\text{result}+n) = \text{new\_value}$  if  $*(\text{first}+n) == \text{old\_value}$ , and  $*(\text{result}+n) = *(\text{first}+n)$  otherwise.

```
#include <thrust/reduce.h>
#include <thrust/device_vector.h>
...
thrust::device_vector<int> A(4);
A[0] = 1;
A[1] = 2;
A[2] = 3;
A[3] = 1;

thrust::device_vector<int> B(4);

thrust::replace_copy(A.begin(), A.end(), B.begin(), 1, 99);
// B contains [99, 2, 3, 99]
```

**Return** `result + (last-first)`

**Pre** `first` may equal `result`, but the ranges `[first, last)` and `[result, result + (last - first))` shall not overlap otherwise.

### Parameters

- `first`: The beginning of the sequence to copy from.
- `last`: The end of the sequence to copy from.
- `result`: The beginning of the sequence to copy to.
- `old_value`: The value to replace.
- `new_value`: The replacement value for which `*i == old_value` evaluates to `true`.

### Template Parameters

- `InputIterator`: is a model of `Input Iterator`.
- `OutputIterator`: is a model of `Output Iterator`.
- `T`: is a model of `Assignable`, `T` is a model of `Equality Comparable`, `T` may be compared for equality with `InputIterator`'s `value_type`, and `T` is convertible to `OutputIterator`'s `value_type`.

**See** [http://www.sgi.com/tech/stl/replace\\_copy.html](http://www.sgi.com/tech/stl/replace_copy.html)

**See** `copy`

**See** `replace`

**See** `replace_if`

**See** `replace_copy_if`

**Template Function** `thrust::replace_copy_if(const thrust::detail::execution_policy_base<DerivedPolicy>&, InputIterator, InputIterator, OutputIterator, Predicate, const T&)`

- Defined in file `thrust_replace.h`

### Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::replace_copy_if`” with arguments (`const thrust::detail::execution_policy_base<DerivedPolicy>&`, `InputIterator`, `InputIterator`, `OutputIterator`, `Predicate`, `const T&`) in doxygen xml output for project “rocThrust” from directory: `./docBin/xml`. Potential matches:

```
- template<typename DerivedPolicy, typename InputIterator, typename OutputIterator,
          typename Predicate, typename T> __host__ __device__ OutputIterator thrust::replace_
          <copy_if(const thrust::detail::execution_policy_base< DerivedPolicy > &, __
          InputIterator, InputIterator, OutputIterator, Predicate, const T &)
- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2,
          typename OutputIterator, typename Predicate, typename T> __host__ __device__
          OutputIterator thrust::replace_copy_if(const thrust::detail::execution_policy_base
          < DerivedPolicy > &, InputIterator1, InputIterator1, InputIterator2,
          OutputIterator, Predicate, const T &)
- template<typename InputIterator, typename OutputIterator, typename Predicate,
          typename T>
          OutputIterator thrust::replace_copy_if(InputIterator, InputIterator,
          OutputIterator, Predicate, const T &)
- template<typename InputIterator1, typename InputIterator2, typename
          OutputIterator, typename Predicate, typename T>
          OutputIterator thrust::replace_copy_if(InputIterator1, InputIterat
```

**Template Function `thrust::replace_copy_if(InputIterator, InputIterator, OutputIterator, Predicate, const T&)`**

### Function Documentation

```
template<typename InputIterator, typename OutputIterator, typename Predicate, typename T>
OutputIterator thrust::replace_copy_if(InputIterator first, InputIterator last, OutputIterator result,
                                     Predicate pred, const T &new_value)
replace_copy_if copies elements from the range [first, last) to the range [result, result
+ (last-first)), except that any element for which pred is true is not copied; new_value is copied
instead.
```

More precisely, for every integer n such that  $0 \leq n < \text{last}-\text{first}$ , `replace_copy_if` performs the assignment  $\ast(\text{result}+n) = \text{new\_value}$  if `pred( $\ast(\text{first}+n)$ )`, and  $\ast(\text{result}+n) = \ast(\text{first}+n)$  otherwise.

```
#include <thrust/reduce.h>
#include <thrust/device_vector.h>

struct is_less_than_zero
{
    __host__ __device__
    bool operator()(int x)
    {
        return x < 0;
    }
};

...

thrust::device_vector<int> A(4);
A[0] = 1;
A[1] = -3;
A[2] = 2;
A[3] = -1;

thrust::device_vector<int> B(4);
is_less_than_zero pred;

thrust::replace_copy_if(A.begin(), A.end(), B.begin(), pred, 0);

// B contains [1, 0, 2, 0]
```

**Return**  $\text{result} + (\text{last}-\text{first})$

**Pre** `first` may equal `result`, but the ranges  $[\text{first}, \text{last})$  and  $[\text{result}, \text{result} + (\text{last} - \text{first}))$  shall not overlap otherwise.

#### Parameters

- `first`: The beginning of the sequence to copy from.
- `last`: The end of the sequence to copy from.
- `result`: The beginning of the sequence to copy to.

- `pred`: The predicate to test on every value of the range [`first`, `last`).
- `new_value`: The replacement value to assign `pred(*i)` evaluates to true.

### Template Parameters

- `InputIterator`: is a model of `Input Iterator`, and `InputIterator`'s `value_type` is convertible to `Predicate`'s `argument_type`.
- `OutputIterator`: is a model of `Output Iterator`.
- `Predicate`: is a model of `Predicate`.
- `T`: is a model of `Assignable`, and `T` is convertible to `OutputIterator`'s `value_type`.

See [http://www.sgi.com/tech/stl/replace\\_copy\\_if.html](http://www.sgi.com/tech/stl/replace_copy_if.html)

See `replace`

See `replace_if`

See `replace_copy`

**Template Function `thrust::replace_copy_if(const thrust::detail::execution_policy_base<DerivedPolicy>&, InputIterator1, InputIterator1, InputIterator2, OutputIterator, Predicate, const T&)`**

### Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::replace_copy_if`” with arguments (`const thrust::detail::execution_policy_base<DerivedPolicy>&`, `InputIterator1`, `InputIterator1`, `InputIterator2`, `OutputIterator`, `Predicate`, `const T&`) in doxygen xml output for project “rocThrust” from directory: `/docBin/xml`. Potential matches:

```
- template<typename DerivedPolicy, typename InputIterator, typename OutputIterator,
          typename Predicate, typename T>__host__ __device__ OutputIterator thrust::replace_
          copy_if(const thrust::detail::execution_policy_base< DerivedPolicy > &,
          InputIterator, InputIterator, OutputIterator, Predicate, const T &)
- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2,
          typename OutputIterator, typename Predicate, typename T>__host__ __device__
          OutputIterator thrust::replace_copy_if(const thrust::detail::execution_policy_base
          < DerivedPolicy > &, InputIterator1, InputIterator1, InputIterator2,
          OutputIterator, Predicate, const T &)
- template<typename InputIterator, typename OutputIterator, typename Predicate,
          typename T>
          OutputIterator thrust::replace_copy_if(InputIterator, InputIterator,
          OutputIterator, Predicate, const T&)
- template<typename InputIterator1, typename InputIterator2, typename
          OutputIterator, typename Predicate, typename T>
          OutputIterator thrust::replace_copy_if(InputIterator1, InputIterator1,
          InputIterator2, OutputIterator, Predicate, const T&)
```

**Template Function `thrust::replace_copy_if(InputIterator1, InputIterator1, InputIterator2, OutputIterator, Predicate, const T&)`**

## Function Documentation

```
template<typename InputIterator1, typename InputIterator2, typename OutputIterator, typename Predicate, typename OutputIterator>
OutputIterator thrust::replace_copy_if(InputIterator1 first, InputIterator1 last, InputIterator2 stencil,
                                      OutputIterator result, Predicate pred, const T& new_value)
```

This version of `replace_copy_if` copies elements from the range  $[first, last)$  to the range  $[result, result + (last - first))$ , except that any element whose corresponding stencil element causes `pred` to be true is not copied; `new_value` is copied instead.

More precisely, for every integer  $n$  such that  $0 \leq n < last - first$ , `replace_copy_if` performs the assignment  $*(result + n) = new\_value$  if  $pred(*stencil + n))$ , and  $*(result + n) = *first + n$  otherwise.

```
#include <thrust/reduce.h>
#include <thrust/device_vector.h>

struct is_less_than_zero
{
    __host__ __device__
    bool operator()(int x)
    {
        return x < 0;
    }
};

...

thrust::device_vector<int> A(4);
A[0] = 10;
A[1] = 20;
A[2] = 30;
A[3] = 40;

thrust::device_vector<int> S(4);
S[0] = -1;
S[1] = 0;
S[2] = -1;
S[3] = 0;

thrust::device_vector<int> B(4);
is_less_than_zero pred;

thrust::replace_if(A.begin(), A.end(), S.begin(), B.begin(), pred, 0);

// B contains [0, 20, 0, 40]
```

**Return**  $result + (last - first)$

**Pre**  $first$  may equal  $result$ , but the ranges  $[first, last)$  and  $[result, result + (last - first))$  shall not overlap otherwise.

**Pre**  $stencil$  may equal  $result$ , but the ranges  $[stencil, stencil + (last - first))$  and  $[result, result + (last - first))$  shall not overlap otherwise.

### Parameters

- $first$ : The beginning of the sequence to copy from.

- `last`: The end of the sequence to copy from.
- `stencil`: The beginning of the stencil sequence.
- `result`: The beginning of the sequence to copy to.
- `pred`: The predicate to test on every value of the range `[stencil, stencil + (last - first)]`.
- `new_value`: The replacement value to assign when `pred(*s)` evaluates to `true`.

### Template Parameters

- `InputIterator1`: is a model of `Input Iterator`.
- `InputIterator2`: is a model of `Input Iterator` and `InputIterator2`'s `value_type` is convertible to `Predicate`'s `argument_type`.
- `OutputIterator`: is a model of `Output Iterator`.
- `Predicate`: is a model of `Predicate`.
- `T`: is a model of `Assignable`, and `T` is convertible to `OutputIterator`'s `value_type`.

**See** `replace_copy`

**See** `replace_if`

**Template Function** `thrust::replace_if(const thrust::detail::execution_policy_base<DerivedPolicy>&, ForwardIterator, ForwardIterator, Predicate, const T&)`

- Defined in file `thrust_replace.h`

### Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::replace_if`” with arguments (`const thrust::detail::execution_policy_base<DerivedPolicy>&`, `ForwardIterator`, `ForwardIterator`, `Predicate`, `const T&`) in doxygen xml output for project “rocThrust” from directory: `./docBin/xml`. Potential matches:

```
- template<typename DerivedPolicy, typename ForwardIterator, typename InputIterator,
          typename Predicate, typename T> __host__ __device__ void thrust::replace_if(const
          thrust::detail::execution_policy_base< DerivedPolicy > &, ForwardIterator,
          ForwardIterator, InputIterator, Predicate, const T &)
- template<typename DerivedPolicy, typename ForwardIterator, typename Predicate,
          typename T> __host__ __device__ void thrust::replace_if(const
          thrust::detail::execution_policy_base< DerivedPolicy > &, ForwardIterator,
          ForwardIterator, Predicate, const T &)
- template<typename ForwardIterator, typename InputIterator, typename Predicate,
          typename T>
          void thrust::replace_if(ForwardIterator, ForwardIterator, InputIterator,
          Predicate, const T &)
- template<typename ForwardIterator, typename Predicate, typename T>
          void thrust::replace_if(ForwardIterator, ForwardIterator, Predicate, const T &)
```

## Template Function `thrust::replace_if(ForwardIterator, ForwardIterator, Predicate, const T&)`

### Function Documentation

```
template<typename ForwardIterator, typename Predicate, typename T>
void thrust::replace_if(ForwardIterator first, ForwardIterator last, Predicate pred, const T
                        &new_value)
```

`replace_if` replaces every element in the range  $[first, last]$  for which `pred` returns `true` with `new_value`. That is: for every iterator *i*, if `pred(*i)` is `true` then it performs the assignment  $*i = new\_value$ .

The following code snippet demonstrates how to use `replace_if` to replace a `device_vector`'s negative elements with 0.

#### Parameters

- `first`: The beginning of the sequence of interest.
- `last`: The end of the sequence of interest.
- `pred`: The predicate to test on every value of the range  $[first, last]$ .
- `new_value`: The new value to replace elements which `pred(*i)` evaluates to `true`.

#### Template Parameters

- `ForwardIterator`: is a model of `Forward Iterator`, `ForwardIterator` is `mutable`, and `ForwardIterator`'s `value_type` is convertible to `Predicate`'s `argument_type`.
- `Predicate`: is a model of `Predicate`.
- `T`: is a model of `Assignable`, and `T` is convertible to `ForwardIterator`'s `value_type`.

```
#include <thrust/replace.h>
#include <thrust/device_vector.h>
...
struct is_less_than_zero
{
    __host__ __device__
    bool operator() (int x)
    {
        return x < 0;
    }
};

...
thrust::device_vector<int> A(4);
A[0] = 1;
A[1] = -3;
A[2] = 2;
A[3] = -1;

is_less_than_zero pred;

thrust::replace_if(A.begin(), A.end(), pred, 0);

// A contains [1, 0, 2, 0]
```

See [http://www.sgi.com/tech/stl/replace\\_if.html](http://www.sgi.com/tech/stl/replace_if.html)

See [replace](#)

See [replace\\_copy](#)

See [replace\\_copy\\_if](#)

**Template Function `thrust::replace_if(const thrust::detail::execution_policy_base<DerivedPolicy>&, ForwardIterator, ForwardIterator, InputIterator, Predicate, const T&)`**

## Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::replace_if`” with arguments (`const thrust::detail::execution_policy_base<DerivedPolicy>&`, `ForwardIterator`, `ForwardIterator`, `InputIterator`, `Predicate`, `const T&`) in doxygen xml output for project “rocThrust” from directory: ./docBin/xml. Potential matches:

```
- template<typename DerivedPolicy, typename ForwardIterator, typename InputIterator,
  ~ typename Predicate, typename T>__host__ __device__ void thrust::replace_if(const_
  ~thrust::detail::execution_policy_base< DerivedPolicy > &, ForwardIterator,_
  ~ForwardIterator, InputIterator, Predicate, const T &)
- template<typename DerivedPolicy, typename ForwardIterator, typename Predicate,_
  ~typename T>__host__ __device__ void thrust::replace_if(const_
  ~thrust::detail::execution_policy_base< DerivedPolicy > &, ForwardIterator,_
  ~ForwardIterator, Predicate, const T &)
- template<typename ForwardIterator, typename InputIterator, typename Predicate,_
  ~typename T>
  void thrust::replace_if(ForwardIterator, ForwardIterator, InputIterator,_
  ~Predicate, const T &)
- template<typename ForwardIterator, typename Predicate, typename T>
  void thrust::replace_if(ForwardIterator, ForwardIterator, Predicate, const T &)
```

**Template Function `thrust::replace_if(ForwardIterator, ForwardIterator, InputIterator, Predicate, const T&)`**

## Function Documentation

```
template<typename ForwardIterator, typename InputIterator, typename Predicate, typename T>
void thrust::replace_if(ForwardIterator first, ForwardIterator last, InputIterator stencil, Predicate
  pred, const T &new_value)
```

`replace_if` replaces every element in the range `[first, last]` for which `pred(*s)` returns true with `new_value`. That is: for every iterator `i` in the range `[first, last]`, and `s` in the range `[stencil, stencil + (last - first)]`, if `pred(*s)` is true then it performs the assignment `*i = new_value`.

The following code snippet demonstrates how to use `replace_if` to replace a `device_vector`'s element with 0 when its corresponding stencil element is less than zero.

### Parameters

- `first`: The beginning of the sequence of interest.
- `last`: The end of the sequence of interest.
- `stencil`: The beginning of the stencil sequence.
- `pred`: The predicate to test on every value of the range `[first, last]`.

- `new_value`: The new value to replace elements which `pred(*i)` evaluates to true.

### Template Parameters

- `ForwardIterator`: is a model of `Forward Iterator`, and `ForwardIterator` is mutable.
- `InputIterator`: is a model of `Input Iterator`, and `InputIterator`'s `value_type` is convertible to `Predicate`'s `argument_type`.
- `Predicate`: is a model of `Predicate`.
- `T`: is a model of `Assignable`, and `T` is convertible to `ForwardIterator`'s `value_type`.

```
#include <thrust/replace.h>
#include <thrust/device_vector.h>

struct is_less_than_zero
{
    __host__ __device__
    bool operator()(int x)
    {
        return x < 0;
    }
};

...

thrust::device_vector<int> A(4);
A[0] = 10;
A[1] = 20;
A[2] = 30;
A[3] = 40;

thrust::device_vector<int> S(4);
S[0] = -1;
S[1] = 0;
S[2] = -1;
S[3] = 0;

is_less_than_zero pred;
thrust::replace_if(A.begin(), A.end(), S.begin(), pred, 0);

// A contains [0, 20, 0, 40]
```

**See** [http://www.sgi.com/tech/stl/replace\\_if.html](http://www.sgi.com/tech/stl/replace_if.html)

**See** `replace`

**See** `replace_copy`

**See** `replace_copy_if`

### Template Function `thrust::return_temporary_buffer`

- Defined in file `thrust/memory.h`

## Function Documentation

```
template<typename DerivedPolicy, typename Pointer> __host__ __device__ void thrust::return_temporary_buffer(Pointer p)
```

return临时缓冲区会话释放与先前由get临时缓冲区分配的Thrust系统关联的存储。

Thrust在内部使用return临时缓冲区当释放所需的临时存储时由算法实现。

以下代码示例演示如何使用return临时缓冲区来释放先前由get临时缓冲区分配的一组内存。

**Pre** p应当先前由thrust::get临时缓冲区分配。

### Parameters

- system: Thrust系统与之关联的存储。
- p: 之前由thrust::get临时缓冲区返回的指针。如果ptr为null, return临时缓冲区做 nothing。

### Template Parameters

- DerivedPolicy: 所谓的执行策略名称。

```
#include <thrust/memory.h>
...
// allocate storage for 100 ints with thrust::get临时缓冲区
const int N = 100;

typedef thrust::pair<
    thrust::pointer<int, thrust::device_system_tag>,
    std::ptrdiff_t
> ptr_and_size_t;

thrust::device_system_tag device_sys;
ptr_and_size_t ptr_and_size = thrust::get临时缓冲区<int>(device_sys, N);

// manipulate up to 100 ints
for(int i = 0; i < ptr_and_size.second; ++i)
{
    *ptr_and_size.first = i;
}

// deallocate storage with thrust::return临时缓冲区
thrust::return临时缓冲区(device_sys, ptr_and_size.first);
```

See [free](#)

See [get临时缓冲区](#)

**Template Function** `thrust::reverse(const thrust::detail::execution_policy_base<DerivedPolicy>&, BidirectionalIterator, BidirectionalIterator)`

- 定义在file\_thrust\_reverse.h

## Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “thrust::reverse” with arguments (const thrust::detail::execution\_policy\_base<DerivedPolicy>&, BidirectionalIterator, BidirectionalIterator) in doxygen xml output for project “rocThrust” from directory: ./docBin/xml. Potential matches:

```
- template<typename BidirectionalIterator>
  void thrust::reverse(BidirectionalIterator, BidirectionalIterator)
- template<typename DerivedPolicy, typename BidirectionalIterator>__host__ __device__
  void thrust::reverse(const thrust::detail::execution_policy_base< DerivedPolicy > &, BidirectionalIterator, BidirectionalIterator)
```

### Template Function thrust::reverse(BidirectionalIterator, BidirectionalIterator)

#### Function Documentation

```
template<typename BidirectionalIterator>
void thrust::reverse(BidirectionalIterator first, BidirectionalIterator last)
    reverse reverses a range. That is: for every i such that 0 <= i <= (last - first) / 2, it exchanges *(first + i) and *(last - (i + 1)).
```

The following code snippet demonstrates how to use `reverse` to reverse a `device_vector` of integers.

#### Parameters

- `first`: The beginning of the range to reverse.
- `last`: The end of the range to reverse.

#### Template Parameters

- `BidirectionalIterator`: is a model of `Bidirectional Iterator` and `BidirectionalIterator` is mutable.

```
#include <thrust/reverse.h>
...
const int N = 6;
int data[N] = {0, 1, 2, 3, 4, 5};
thrust::device_vector<int> v(data, data + N);
thrust::reverse(v.begin(), v.end());
// v is now {5, 4, 3, 2, 1, 0}
```

See <http://www.sgi.com/tech/stl/reverse.html>

See `reverse_copy`

See `reverse_iterator`

### Template Function thrust::reverse\_copy(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, BidirectionalIterator, BidirectionalIterator, OutputIterator)

- Defined in file `thrust_reverse.h`

## Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “thrust::reverse\_copy” with arguments (const thrust::detail::execution\_policy\_base<DerivedPolicy>&, BidirectionalIterator, BidirectionalIterator, OutputIterator) in doxygen xml output for project “rocThrust” from directory: ./docBin/xml. Potential matches:

```
- template<typename BidirectionalIterator, typename OutputIterator>
  OutputIterator thrust::reverse_copy(BidirectionalIterator, BidirectionalIterator,
  ↳OutputIterator)
- template<typename DerivedPolicy, typename BidirectionalIterator, typename_
  ↳OutputIterator>__host__ __device__ OutputIterator thrust::reverse_copy(const_
  ↳thrust::detail::execution_policy_base< DerivedPolicy > &, BidirectionalIterator,
  ↳BidirectionalIterator, OutputIterator)
```

## Template Function `thrust::reverse_copy(BidirectionalIterator, BidirectionalIterator, OutputIterator)`

### Function Documentation

```
template<typename BidirectionalIterator, typename OutputIterator>
OutputIterator thrust::reverse_copy(BidirectionalIterator first, BidirectionalIterator last, OutputIter-
  ator result)
reverse_copy differs from reverse only in that the reversed range is written to a different output range, rather
than inplace.
```

`reverse_copy` copies elements from the range  $[first, last]$  to the range  $[result, result + (last - first)]$  such that the copy is a reverse of the original range. Specifically: for every  $i$  such that  $0 \leq i < (last - first)$ , `reverse_copy` performs the assignment  $*(\text{result} + (last - first) - i) = *(\text{first} + i)$ .

The return value is  $\text{result} + (last - first)$ .

The following code snippet demonstrates how to use `reverse_copy` to reverse an input `device_vector` of integers to an output `device_vector`.

**Pre** The range  $[first, last]$  and the range  $[result, result + (last - first)]$  shall not overlap.

### Parameters

- `first`: The beginning of the range to reverse.
- `last`: The end of the range to reverse.
- `result`: The beginning of the output range.

### Template Parameters

- `BidirectionalIterator`: is a model of `Bidirectional Iterator`, and `BidirectionalIterator`'s `value_type` is convertible to `OutputIterator`'s `value_type`.
- `OutputIterator`: is a model of `Output Iterator`.

```
#include <thrust/reverse.h>
...
const int N = 6;
int data[N] = {0, 1, 2, 3, 4, 5};
```

(continues on next page)

(continued from previous page)

```
thrust::device_vector<int> input(data, data + N);
thrust::device_vector<int> output(N);
thrust::reverse_copy(v.begin(), v.end(), output.begin());
// input is still {0, 1, 2, 3, 4, 5}
// output is now {5, 4, 3, 2, 1, 0}
```

**See** [http://www.sgi.com/tech/stl/reverse\\_copy.html](http://www.sgi.com/tech/stl/reverse_copy.html)

**See** `reverse`

**See** `reverse_iterator`

### Template Function `thrust::scatter(const thrust::detail::execution_policy_base<DerivedPolicy>&, InputIterator1, InputIterator1, InputIterator2, RandomAccessIterator)`

- Defined in file `thrust_scatter.h`

#### Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::scatter`” with arguments (`const thrust::detail::execution_policy_base<DerivedPolicy>&`, `InputIterator1`, `InputIterator1`, `InputIterator2`, `RandomAccessIterator`) in doxygen xml output for project “rocThrust” from directory: `./docBin/xml`. Potential matches:

```
- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2,
→ typename RandomAccessIterator> __host__ __device__ void thrust::scatter(const
→ thrust::detail::execution_policy_base< DerivedPolicy > &, InputIterator1,_
→ InputIterator1, InputIterator2, RandomAccessIterator)
- template<typename InputIterator1, typename InputIterator2, typename_
→ RandomAccessIterator>
→ void thrust::scatter(InputIterator1, InputIterator1, InputIterator2,_
→ RandomAccessIterator)
```

### Template Function `thrust::scatter(InputIterator1, InputIterator1, InputIterator2, RandomAccessIterator)`

#### Function Documentation

```
template<typename InputIterator1, typename InputIterator2, typename RandomAccessIterator>
void thrust::scatter(InputIterator1 first, InputIterator1 last, InputIterator2 map, RandomAccessItera-
tor result)
```

`scatter` copies elements from a source range into an output array according to a map. For each iterator `i` in the range `[first, last)`, the value `*i` is assigned to `output[*map + (i - first)]`. The output iterator must permit random access. If the same index appears more than once in the range `[map, map + (last - first))`, the result is undefined.

The following code snippet demonstrates how to use `scatter` to reorder a range.

**Pre** The iterator `result + i` shall not refer to any element referenced by any iterator `j` in the range `[first, last)` for all iterators `i` in the range `[map, map + (last - first))`.

**Pre** The iterator `result + i` shall not refer to any element referenced by any iterator `j` in the range `[map, map + (last - first))` for all iterators `i` in the range `[map, map + (last - first))`.

**Pre** The expression `result[*i]` shall be valid for all iterators in the range `[map, map + (last - first))`.

### Parameters

- `first`: Beginning of the sequence of values to scatter.
- `last`: End of the sequence of values to scatter.
- `map`: Beginning of the sequence of output indices.
- `result`: Destination of the source elements.

### Template Parameters

- `InputIterator1`: must be a model of `Input Iterator` and `InputIterator1`'s `value_type` must be convertible to `RandomAccessIterator`'s `value_type`.
- `InputIterator2`: must be a model of `Input Iterator` and `InputIterator2`'s `value_type` must be convertible to `RandomAccessIterator`'s `difference_type`.
- `RandomAccessIterator`: must be a model of `Random Access iterator`.

```
#include <thrust/scatter.h>
#include <thrust/device_vector.h>
...
// mark even indices with a 1; odd indices with a 0
int values[10] = {1, 0, 1, 0, 1, 0, 1, 0, 1, 0};
thrust::device_vector<int> d_values(values, values + 10);

// scatter all even indices into the first half of the
// range, and odd indices vice versa
int map[10] = {0, 5, 1, 6, 2, 7, 3, 8, 4, 9};
thrust::device_vector<int> d_map(map, map + 10);

thrust::device_vector<int> d_output(10);
thrust::scatter(d_values.begin(), d_values.end(),
                d_map.begin(), d_output.begin());
// d_output is now {1, 1, 1, 1, 1, 0, 0, 0, 0, 0}
```

**Note** `scatter` is the inverse of `thrust::gather`.

## Template Function `thrust::scatter_if(const thrust::detail::execution_policy_base<DerivedPolicy>&, InputIterator1, InputIterator1, InputIterator2, InputIterator3, RandomAccessIterator)`

- Defined in file `_thrust_scatter.h`

### Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::scatter_if`” with arguments `(const thrust::detail::execution_policy_base<DerivedPolicy>&, InputIterator1, InputIterator1, InputIterator2, InputIterator3, RandomAccessIterator)` in doxygen xml output for project “rocThrust” from directory: `./docBin/xml`. Potential matches:

```

- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2,
  ~ typename InputIterator3, typename RandomAccessIterator, typename Predicate> __
__host__ __device__ void thrust::scatter_if(const thrust::detail::execution_policy_
__base< DerivedPolicy > &, InputIterator1, InputIterator1, InputIterator2, __
InputIterator3, RandomAccessIterator, Predicate)
- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2,
  ~ typename InputIterator3, typename RandomAccessIterator> __host__ __device__ void __
thrust::scatter_if(const thrust::detail::execution_policy_base< DerivedPolicy > &,
  ~ InputIterator1, InputIterator1, InputIterator2, InputIterator3, __
RandomAccessIterator)
- template<typename InputIterator1, typename InputIterator2, typename __
InputIterator3, typename RandomAccessIterator, typename Predicate>
  void thrust::scatter_if(InputIterator1, InputIterator1, InputIterator2, __
InputIterator3, RandomAccessIterator, Predicate)
- template<typename InputIterator1, typename InputIterator2, typename __
InputIterator3, typename RandomAccessIterator>
  void thrust::scatter_if(InputIterator1, InputIterator1, InputIterator2, __
InputIterator3, RandomAccessIterator)

```

## Template Function `thrust::scatter_if(InputIterator1, InputIterator1, InputIterator2, InputIterator3, RandomAccessIterator)`

### Function Documentation

```
template<typename InputIterator1, typename InputIterator2, typename InputIterator3, typename RandomAccessIterator>
void thrust::scatter_if(InputIterator1 first, InputIterator1 last, InputIterator2 map, InputIterator3 stencil, RandomAccessIterator output)
```

`scatter_if` conditionally copies elements from a source range into an output array according to a map. For each iterator  $i$  in the range  $[first, last]$  such that  $*(stencil + (i - first))$  is true, the value  $*i$  is assigned to  $output[*(map + (i - first))]$ . The output iterator must permit random access. If the same index appears more than once in the range  $[map, map + (last - first)]$  the result is undefined.

```
#include <thrust/scatter.h>
...
int V[8] = {10, 20, 30, 40, 50, 60, 70, 80};
int M[8] = {0, 5, 1, 6, 2, 7, 3, 4};
int S[8] = {1, 0, 1, 0, 1, 0, 1, 0};
int D[8] = {0, 0, 0, 0, 0, 0, 0, 0};

thrust::scatter_if(V, V + 8, M, S, D);

// D contains [10, 30, 50, 70, 0, 0, 0, 0];
```

**Pre** The iterator  $result + i$  shall not refer to any element referenced by any iterator  $j$  in the range  $[first, last)$  for all iterators  $i$  in the range  $[map, map + (last - first))$ .

**Pre** The iterator  $result + i$  shall not refer to any element referenced by any iterator  $j$  in the range  $[map, map + (last - first))$  for all iterators  $i$  in the range  $[map, map + (last - first))$ .

**Pre** The iterator  $result + i$  shall not refer to any element referenced by any iterator  $j$  in the range  $[stencil, stencil + (last - first))$  for all iterators  $i$  in the range  $[map, map + (last - first))$ .

**Pre** The expression `result[*i]` shall be valid for all iterators `i` in the range `[map, map + (last - first))` for which the following condition holds: `*(stencil + i) != false`.

### Parameters

- `first`: Beginning of the sequence of values to scatter.
- `last`: End of the sequence of values to scatter.
- `map`: Beginning of the sequence of output indices.
- `stencil`: Beginning of the sequence of predicate values.
- `output`: Beginning of the destination range.

### Template Parameters

- `InputIterator1`: must be a model of `Input Iterator` and `InputIterator1`'s `value_type` must be convertible to `RandomAccessIterator`'s `value_type`.
- `InputIterator2`: must be a model of `Input Iterator` and `InputIterator2`'s `value_type` must be convertible to `RandomAccessIterator`'s `difference_type`.
- `InputIterator3`: must be a model of `Input Iterator` and `InputIterator3`'s `value_type` must be convertible to `bool`.
- `RandomAccessIterator`: must be a model of `Random Access iterator`.

**Note** `scatter_if` is the inverse of `thrust::gather_if`.

**Template Function** `thrust::scatter_if(const thrust::detail::execution_policy_base<DerivedPolicy>&, InputIterator1, InputIterator1, InputIterator2, InputIterator3, RandomAccessIterator, Predicate)`

### Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::scatter_if`” with arguments (`const thrust::detail::execution_policy_base<DerivedPolicy>&`, `InputIterator1`, `InputIterator1`, `InputIterator2`, `InputIterator3`, `RandomAccessIterator`, `Predicate`) in doxygen xml output for project “rocThrust” from directory: `./docBin/xml`. Potential matches:

```
- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2,
→ typename InputIterator3, typename RandomAccessIterator, typename Predicate> __
→ host__ __device__ void thrust::scatter_if(const thrust::detail::execution_policy_
→ base< DerivedPolicy > &, InputIterator1, InputIterator1, InputIterator2, __
→ InputIterator3, RandomAccessIterator, Predicate)
- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2,
→ typename InputIterator3, typename RandomAccessIterator> __host__ __device__ void __
→ thrust::scatter_if(const thrust::detail::execution_policy_base< DerivedPolicy > &,
→ InputIterator1, InputIterator1, InputIterator2, InputIterator3, __
→ RandomAccessIterator)
- template<typename InputIterator1, typename InputIterator2, typename __
→ InputIterator3, typename RandomAccessIterator, typename Predicate>
→ void thrust::scatter_if(InputIterator1, InputIterator1, InputIterator2, __
→ InputIterator3, RandomAccessIterator, Predicate)
- template<typename InputIterator1, typename InputIterator2, typename __
→ InputIterator3, typename RandomAccessIterator>
→ void thrust::scatter_if(InputIterator1, InputIterator1, InputIterator2, __
→ InputIterator3, RandomAccessIterator)
```

## Template Function `thrust::scatter_if(InputIterator1, InputIterator1, InputIterator2, InputIterator3, RandomAccessIterator, Predicate)`

### Function Documentation

```
template<typename InputIterator1, typename InputIterator2, typename InputIterator3, typename RandomAccessIterator, typename Predicate>
void thrust::scatter_if(InputIterator1 first, InputIterator1 last, InputIterator2 map, InputIterator3 stencil, RandomAccessIterator output, Predicate pred)
```

`scatter_if` conditionally copies elements from a source range into an output array according to a map. For each iterator *i* in the range  $[first, last]$  such that  $pred(*(\text{stencil} + (i - first)))$  is true, the value  $*i$  is assigned to  $\text{output}[*(\text{map} + (i - first))]$ . The output iterator must permit random access. If the same index appears more than once in the range  $[map, map + (last - first)]$  the result is undefined.

```
#include <thrust/scatter.h>

struct is_even
{
    __host__ __device__
    bool operator()(int x)
    {
        return (x % 2) == 0;
    }
};

...
int V[8] = {10, 20, 30, 40, 50, 60, 70, 80};
int M[8] = {0, 5, 1, 6, 2, 7, 3, 4};
int S[8] = {2, 1, 2, 1, 2, 1, 2, 1};
int D[8] = {0, 0, 0, 0, 0, 0, 0, 0};

is_even pred;
thrust::scatter_if(V, V + 8, M, S, D, pred);

// D contains [10, 30, 50, 70, 0, 0, 0, 0];
```

**Pre** The iterator  $\text{result} + i$  shall not refer to any element referenced by any iterator  $j$  in the range  $[first, last]$  for all iterators  $i$  in the range  $[map, map + (last - first)]$ .

**Pre** The iterator  $\text{result} + i$  shall not refer to any element referenced by any iterator  $j$  in the range  $[map, map + (last - first)]$  for all iterators  $i$  in the range  $[map, map + (last - first)]$ .

**Pre** The iterator  $\text{result} + i$  shall not refer to any element referenced by any iterator  $j$  in the range  $[\text{stencil}, \text{stencil} + (last - first)]$  for all iterators  $i$  in the range  $[map, map + (last - first)]$ .

**Pre** The expression  $\text{result}[*i]$  shall be valid for all iterators  $i$  in the range  $[map, map + (last - first)]$  for which the following condition holds:  $pred(*(\text{stencil} + i)) != \text{false}$ .

### Parameters

- **first**: Beginning of the sequence of values to scatter.
- **last**: End of the sequence of values to scatter.
- **map**: Beginning of the sequence of output indices.
- **stencil**: Beginning of the sequence of predicate values.

- **output**: Beginning of the destination range.
- **pred**: Predicate to apply to the stencil values.

### Template Parameters

- **InputIterator1**: must be a model of [Input Iterator](#) and **InputIterator1**'s `value_type` must be convertible to [RandomAccessIterator](#)'s `value_type`.
- **InputIterator2**: must be a model of [Input Iterator](#) and **InputIterator2**'s `value_type` must be convertible to [RandomAccessIterator](#)'s `difference_type`.
- **InputIterator3**: must be a model of [Input Iterator](#) and **InputIterator3**'s `value_type` must be convertible to [Predicate](#)'s `argument_type`.
- **RandomAccessIterator**: must be a model of [Random Access iterator](#).
- **Predicate**: must be a model of [Predicate](#).

**Note** `scatter_if` is the inverse of `thrust::gather_if`.

## Template Function `thrust::sequence(const thrust::detail::execution_policy_base<DerivedPolicy>&, ForwardIterator, ForwardIterator)`

- Defined in file `thrust_sequence.h`

### Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::sequence`” with arguments (`const thrust::detail::execution_policy_base<DerivedPolicy>&`, `ForwardIterator`, `ForwardIterator`) in doxygen xml output for project “rocThrust” from directory: `./docBin/xml`. Potential matches:

```
- template<typename DerivedPolicy, typename ForwardIterator, typename T> __host__ __device__ void thrust::sequence(const thrust::detail::execution_policy_base<DerivedPolicy > &, ForwardIterator, ForwardIterator, T)
- template<typename DerivedPolicy, typename ForwardIterator, typename T> __host__ __device__ void thrust::sequence(const thrust::detail::execution_policy_base<DerivedPolicy > &, ForwardIterator, ForwardIterator, T, T)
- template<typename DerivedPolicy, typename ForwardIterator> __host__ __device__ void thrust::sequence(const thrust::detail::execution_policy_base< DerivedPolicy > &, ForwardIterator, ForwardIterator)
- template<typename ForwardIterator, typename T> void thrust::sequence(ForwardIterator, ForwardIterator, T)
- template<typename ForwardIterator, typename T> void thrust::sequence(ForwardIterator, ForwardIterator, T, T)
- template<typename ForwardIterator> void thrust::sequence(ForwardIterator, ForwardIterator)
```

## Template Function `thrust::sequence(ForwardIterator, ForwardIterator)`

### Function Documentation

`template<typename ForwardIterator>`

```
void thrust::sequence(ForwardIterator first, ForwardIterator last)
sequence fills the range [first, last) with a sequence of numbers.
```

For each iterator *i* in the range [first, last), this version of sequence performs the assignment  $*i = (i - \text{first})$ .

The following code snippet demonstrates how to use sequence to fill a range with a sequence of numbers.

### Parameters

- *first*: The beginning of the sequence.
- *last*: The end of the sequence.

### Template Parameters

- *ForwardIterator*: is a model of *Forward Iterator*, and *ForwardIterator* is mutable, and if *x* and *y* are objects of *ForwardIterator*'s *value\_type*, then *x + y* is defined, and if *T* is *ForwardIterator*'s *value\_type*, then *T(0)* is defined.

```
#include <thrust/sequence.h>
...
const int N = 10;
int A[N];
thrust::sequence(A, A + 10);
// A is now {0, 1, 2, 3, 4, 5, 6, 7, 8, 9}
```

**Note** Unlike the similar C++ STL function `std::iota`, `sequence` offers no guarantee on order of execution.

See <http://www.sgi.com/tech/stl/iota.html>

## Template Function `thrust::sequence(const thrust::detail::execution_policy_base<DerivedPolicy>&, ForwardIterator, ForwardIterator, T)`

### Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::sequence`” with arguments (`const thrust::detail::execution_policy_base<DerivedPolicy>&`, `ForwardIterator`, `ForwardIterator`, `T`) in doxygen xml output for project “rocThrust” from directory: ./docBin/xml. Potential matches:

```
- template<typename DerivedPolicy, typename ForwardIterator, typename T> __host__ __device__
void thrust::sequence(const thrust::detail::execution_policy_base<DerivedPolicy> &, ForwardIterator, ForwardIterator, T)
- template<typename DerivedPolicy, typename ForwardIterator, typename T> __host__ __device__
void thrust::sequence(const thrust::detail::execution_policy_base<DerivedPolicy> &, ForwardIterator, ForwardIterator, T, T)
- template<typename DerivedPolicy, typename ForwardIterator> __host__ __device__
void thrust::sequence(const thrust::detail::execution_policy_base<DerivedPolicy> &, ForwardIterator, ForwardIterator)
- template<typename ForwardIterator, typename T>
void thrust::sequence(ForwardIterator, ForwardIterator, T)
- template<typename ForwardIterator, typename T>
void thrust::sequence(ForwardIterator, ForwardIterator, T, T)
- template<typename ForwardIterator>
void thrust::sequence(ForwardIterator, ForwardIterator)
```

**Template Function thrust::sequence(ForwardIterator, ForwardIterator, T)****Function Documentation**

```
template<typename ForwardIterator, typename T>
void thrust::sequence(ForwardIterator first, ForwardIterator last, T init)
    sequence fills the range [first, last) with a sequence of numbers.
```

For each iterator *i* in the range [first, last), this version of sequence performs the assignment *\*i* = *init* + (*i* - first).

The following code snippet demonstrates how to use sequence to fill a range with a sequence of numbers starting from the value 1.

**Parameters**

- *first*: The beginning of the sequence.
- *last*: The end of the sequence.
- *init*: The first value of the sequence of numbers.

**Template Parameters**

- *ForwardIterator*: is a model of [Forward Iterator](#), and *ForwardIterator* is mutable, and if *x* and *y* are objects of *ForwardIterator*'s *value\_type*, then *x* + *y* is defined, and if *T* is *ForwardIterator*'s *value\_type*, then *T*(0) is defined.
- *T*: is a model of [Assignable](#), and *T* is convertible to *ForwardIterator*'s *value\_type*.

```
#include <thrust/sequence.h>
...
const int N = 10;
int A[N];
thrust::sequence(A, A + 10, 1);
// A is now {1, 2, 3, 4, 5, 6, 7, 8, 9, 10}
```

**Note** Unlike the similar C++ STL function `std::iota`, sequence offers no guarantee on order of execution.

See <http://www.sgi.com/tech/stl/iota.html>

**Template Function thrust::sequence(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, ForwardIterator, ForwardIterator, T, T)****Function Documentation**

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “thrust::sequence” with arguments (const thrust::detail::execution\_policy\_base<DerivedPolicy>&, ForwardIterator, ForwardIterator, T, T) in doxygen xml output for project “rocThrust” from directory: ./docBin/xml. Potential matches:

```

- template<typename DerivedPolicy, typename ForwardIterator, typename T> __host__ __
  __device__ void thrust::sequence(const thrust::detail::execution_policy_base<
  DerivedPolicy > &, ForwardIterator, ForwardIterator, T)
- template<typename DerivedPolicy, typename ForwardIterator, typename T> __host__ __
  __device__ void thrust::sequence(const thrust::detail::execution_policy_base<
  DerivedPolicy > &, ForwardIterator, ForwardIterator, T, T)
- template<typename DerivedPolicy, typename ForwardIterator> __host__ __device__ __
  __void thrust::sequence(const thrust::detail::execution_policy_base< DerivedPolicy >
  &, ForwardIterator, ForwardIterator)
- template<typename ForwardIterator, typename T>
  void thrust::sequence(ForwardIterator, ForwardIterator, T)
- template<typename ForwardIterator, typename T>
  void thrust::sequence(ForwardIterator, ForwardIterator, T, T)
- template<typename ForwardIterator>
  void thrust::sequence(ForwardIterator, ForwardIterator)

```

## Template Function `thrust::sequence(ForwardIterator, ForwardIterator, T, T)`

### Function Documentation

```

template<typename ForwardIterator, typename T>
void thrust::sequence(ForwardIterator first, ForwardIterator last, T init, T step)
  sequence fills the range [first, last) with a sequence of numbers.

```

For each iterator *i* in the range [first, last), this version of sequence performs the assignment  $*i = init + step * (i - first)$ .

The following code snippet demonstrates how to use sequence to fill a range with a sequence of numbers starting from the value 1 with a step size of 3.

#### Parameters

- *first*: The beginning of the sequence.
- *last*: The end of the sequence.
- *init*: The first value of the sequence of numbers
- *step*: The difference between consecutive elements.

#### Template Parameters

- *ForwardIterator*: is a model of `Forward Iterator`, and `ForwardIterator` is mutable, and if *x* and *y* are objects of `ForwardIterator`'s `value_type`, then *x* + *y* is defined, and if *T* is `ForwardIterator`'s `value_type`, then *T*(0) is defined.
- *T*: is a model of `Assignable`, and *T* is convertible to `ForwardIterator`'s `value_type`.

```

#include <thrust/sequence.h>
...
const int N = 10;
int A[N];
thrust::sequence(A, A + 10, 1, 3);
// A is now {1, 4, 7, 10, 13, 16, 19, 22, 25, 28}

```

**Note** Unlike the similar C++ STL function `std::iota`, sequence offers no guarantee on order of execution.

See <http://www.sgi.com/tech/stl/iota.html>

### Template Function `thrust::set_difference(const thrust::detail::execution_policy_base<DerivedPolicy>&, InputIterator1, InputIterator1, InputIterator2, InputIterator2, OutputIterator)`

- Defined in file `thrust_set_operations.h`

#### Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::set_difference`” with arguments (`const thrust::detail::execution_policy_base<DerivedPolicy>&`, `InputIterator1`, `InputIterator1`, `InputIterator2`, `InputIterator2`, `OutputIterator`) in doxygen xml output for project “rocThrust” from directory: `./docBin/xml`. Potential matches:

```
- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2,
→ typename OutputIterator, typename StrictWeakCompare> __host__ __device__
→OutputIterator thrust::set_difference(const thrust::detail::execution_policy_base
→< DerivedPolicy > &, InputIterator1, InputIterator1, InputIterator2,
→InputIterator2, OutputIterator, StrictWeakCompare)
- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2,
→ typename OutputIterator> __host__ __device__ OutputIterator thrust::set_
→difference(const thrust::detail::execution_policy_base< DerivedPolicy > &,
→InputIterator1, InputIterator1, InputIterator2, InputIterator2, OutputIterator)
- template<typename InputIterator1, typename InputIterator2, typename_
→OutputIterator, typename StrictWeakCompare>
→OutputIterator thrust::set_difference(InputIterator1, InputIterator1,
→InputIterator2, InputIterator2, OutputIterator, StrictWeakCompare)
- template<typename InputIterator1, typename InputIterator2, typename_
→OutputIterator>
→OutputIterator thrust::set_difference(InputIterator1, InputIterator1,
→InputIterator2, InputIterator2, OutputIterator)
```

### Template Function `thrust::set_difference(InputIterator1, InputIterator1, InputIterator2, InputIterator2, OutputIterator)`

#### Function Documentation

```
template<typename InputIterator1, typename InputIterator2, typename OutputIterator>
OutputIterator thrust::set_difference(InputIterator1 first1, InputIterator1 last1, InputIterator2
first2, InputIterator2 last2, OutputIterator result)
set_difference constructs a sorted range that is the set difference of the sorted ranges [first1,
last1) and [first2, last2). The return value is the end of the output range.
```

In the simplest case, `set_difference` performs the “difference” operation from set theory: the output range contains a copy of every element that is contained in  $[first1, last1)$  and not contained in  $[first2, last1)$ . The general case is more complicated, because the input ranges may contain duplicate elements. The generalization is that if  $[first1, last1)$  contains  $m$  elements that are equivalent to each other and if  $[first2, last2)$  contains  $n$  elements that are equivalent to them, the last  $\max(m-n, 0)$  elements from  $[first1, last1)$  range shall be copied to the output range.

This version of `set_difference` compares elements using operator`<`.

The following code snippet demonstrates how to use `set_difference` to compute the set difference of two sets of integers sorted in ascending order.

**Return** The end of the output range.

**Pre** The ranges `[first1, last1)` and `[first2, last2)` shall be sorted with respect to `operator<`.

**Pre** The resulting range shall not overlap with either input range.

### Parameters

- `first1`: The beginning of the first input range.
- `last1`: The end of the first input range.
- `first2`: The beginning of the second input range.
- `last2`: The end of the second input range.
- `result`: The beginning of the output range.

### Template Parameters

- `InputIterator1`: is a model of `Input Iterator`, `InputIterator1` and `InputIterator2` have the same `value_type`, `InputIterator1`'s `value_type` is a model of `LessThan Comparable`, the ordering on `InputIterator1`'s `value_type` is a strict weak ordering, as defined in the `LessThan Comparable` requirements, and `InputIterator1`'s `value_type` is convertible to a type in `OutputIterator`'s set of `value_types`.
- `InputIterator2`: is a model of `Input Iterator`, `InputIterator2` and `InputIterator1` have the same `value_type`, `InputIterator2`'s `value_type` is a model of `LessThan Comparable`, the ordering on `InputIterator2`'s `value_type` is a strict weak ordering, as defined in the `LessThan Comparable` requirements, and `InputIterator2`'s `value_type` is convertible to a type in `OutputIterator`'s set of `value_types`.
- `OutputIterator`: is a model of `Output Iterator`.

```
#include <thrust/set_operations.h>
...
int A1[6] = {0, 1, 3, 4, 5, 6, 9};
int A2[5] = {1, 3, 5, 7, 9};

int result[3];

int *result_end = thrust::set_difference(A1, A1 + 6, A2, A2 + 5, result);
// result is now {0, 4, 6}
```

**See** [http://www.sgi.com/tech/stl/set\\_difference.html](http://www.sgi.com/tech/stl/set_difference.html)

**See** `includes`

**See** `set_union`

**See** `set_intersection`

**See** `set_symmetric_difference`

**See** `sort`

**See** `is_sorted`

**Template Function `thrust::set_difference(const thrust::detail::execution_policy_base<DerivedPolicy>&, InputIterator1, InputIterator1, InputIterator2, InputIterator2, OutputIterator, StrictWeakCompare)`**

## Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::set_difference`” with arguments (`const thrust::detail::execution_policy_base<DerivedPolicy>&`, `InputIterator1`, `InputIterator1`, `InputIterator2`, `InputIterator2`, `OutputIterator`, `StrictWeakCompare`) in doxygen xml output for project “rocThrust” from directory: `./docBin/xml`. Potential matches:

```
- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2,
          typename OutputIterator, typename StrictWeakCompare> __host__ __device__
          OutputIterator thrust::set_difference(const thrust::detail::execution_policy_base<
          DerivedPolicy > &, InputIterator1, InputIterator1, InputIterator2, InputIterator2,
          OutputIterator, StrictWeakCompare)
- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2,
          typename OutputIterator> __host__ __device__ OutputIterator thrust::set_
          difference(const thrust::detail::execution_policy_base< DerivedPolicy > &,
          InputIterator1, InputIterator1, InputIterator2, InputIterator2, OutputIterator)
- template<typename InputIterator1, typename InputIterator2, typename_
          OutputIterator, typename StrictWeakCompare>
          OutputIterator thrust::set_difference(InputIterator1, InputIterator1,
          InputIterator2, InputIterator2, OutputIterator, StrictWeakCompare)
- template<typename InputIterator1, typename InputIterator2, typename_
          OutputIterator>
          OutputIterator thrust::set_difference(InputIterator1, InputIterator1,
          InputIterator2, InputIterator2, OutputIterator)
```

**Template Function `thrust::set_difference(InputIterator1, InputIterator1, InputIterator2, InputIterator2, OutputIterator, StrictWeakCompare)`**

## Function Documentation

```
template<typename InputIterator1, typename InputIterator2, typename OutputIterator, typename StrictWeakCompare>
OutputIterator thrust::set_difference(InputIterator1 first1, InputIterator1 last1, InputIterator2
                                     first2, InputIterator2 last2, OutputIterator result, StrictWeak-
                                     Compare comp)
```

`set_difference` constructs a sorted range that is the set difference of the sorted ranges `[first1, last1]` and `[first2, last2]`. The return value is the end of the output range.

In the simplest case, `set_difference` performs the “difference” operation from set theory: the output range contains a copy of every element that is contained in `[first1, last1]` and not contained in `[first2, last1]`. The general case is more complicated, because the input ranges may contain duplicate elements. The generalization is that if `[first1, last1]` contains  $m$  elements that are equivalent to each other and if `[first2, last2]` contains  $n$  elements that are equivalent to them, the last  $\max(m-n, 0)$  elements from `[first1, last1]` range shall be copied to the output range.

This version of `set_difference` compares elements using a function object `comp`.

The following code snippet demonstrates how to use `set_difference` to compute the set difference of two sets of integers sorted in descending order.

**Return** The end of the output range.

**Pre** The ranges `[first1, last1]` and `[first2, last2]` shall be sorted with respect to `comp`.

**Pre** The resulting range shall not overlap with either input range.

### Parameters

- `first1`: The beginning of the first input range.
- `last1`: The end of the first input range.
- `first2`: The beginning of the second input range.
- `last2`: The end of the second input range.
- `result`: The beginning of the output range.
- `comp`: Comparison operator.

### Template Parameters

- `InputIterator1`: is a model of [Input Iterator](#), `InputIterator1`'s `value_type` is convertible to `StrictWeakCompare`'s `first_argument_type`. and `InputIterator1`'s `value_type` is convertible to a type in `OutputIterator`'s set of `value_types`.
- `InputIterator2`: is a model of [Input Iterator](#), `InputIterator2`'s `value_type` is convertible to `StrictWeakCompare`'s `second_argument_type`. and `InputIterator2`'s `value_type` is convertible to a type in `OutputIterator`'s set of `value_types`.
- `OutputIterator`: is a model of [Output Iterator](#).
- `StrictWeakCompare`: is a model of [Strict Weak Ordering](#).

```
#include <thrust/set_operations.h>
#include <thrust/functional.h>
...
int A1[6] = {9, 6, 5, 4, 3, 1, 0};
int A2[5] = {9, 7, 5, 3, 1};

int result[3];

int *result_end = thrust::set_difference(A1, A1 + 6, A2, A2 + 5, result,
                                         thrust::greater<int>());
// result is now {6, 4, 0}
```

**See** [http://www.sgi.com/tech/stl/set\\_difference.html](http://www.sgi.com/tech/stl/set_difference.html)

**See** `includes`

**See** `set_union`

**See** `set_intersection`

**See** `set_symmetric_difference`

**See** `sort`

**See** `is_sorted`

**Template Function** `thrust::set_difference_by_key(const thrust::detail::execution_policy_base<DerivedPolicy>&, InputIterator1, InputIterator1, InputIterator2, InputIterator2, InputIterator3, InputIterator4, OutputIterator1, OutputIterator2)`

- Defined in file `thrust_set_operations.h`

## Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “thrust::set\_difference\_by\_key” with arguments (const thrust::detail::execution\_policy\_base<DerivedPolicy>&, InputIterator1, InputIterator1, InputIterator2, InputIterator2, InputIterator3, InputIterator4, OutputIterator1, OutputIterator2) in doxygen xml output for project “rocThrust” from directory: ./docBin/xml. Potential matches:

```
- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2,
          typename InputIterator3, typename InputIterator4, typename OutputIterator1,
          typename OutputIterator2, typename StrictWeakCompare>__host__ __device__
          thrust::pair<OutputIterator1,OutputIterator2> thrust::set_difference_by_key(const
          thrust::detail::execution_policy_base< DerivedPolicy > &, InputIterator1,
          InputIterator1, InputIterator2, InputIterator2, InputIterator3, InputIterator4,
          OutputIterator1, OutputIterator2, StrictWeakCompare)
- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2,
          typename InputIterator3, typename InputIterator4, typename OutputIterator1,
          typename OutputIterator2>__host__ __device__ thrust::pair<OutputIterator1,
          OutputIterator2> thrust::set_difference_by_key(const thrust::detail::execution_
          policy_base< DerivedPolicy > &, InputIterator1, InputIterator1, InputIterator2,
          InputIterator2, InputIterator3, InputIterator4, OutputIterator1, OutputIterator2)
- template<typename InputIterator1, typename InputIterator2, typename
          InputIterator3, typename InputIterator4, typename OutputIterator1, typename
          OutputIterator2>
          thrust::pair<OutputIterator1, OutputIterator2> thrust::set_difference_by_
          key(InputIterator1, InputIterator1, InputIterator2, InputIterator2,
          InputIterator3, InputIterator4, OutputIterator1, OutputIterator2,
          StrictWeakCompare)
- template<typename InputIterator1, typename InputIterator2, typename
          InputIterator3, typename InputIterator4, typename OutputIterator1, typename
          OutputIterator2>
          thrust::pair<OutputIterator1, OutputIterator2> thrust::set_difference_by_
          key(InputIterator1, InputIterator1, InputIterator2, InputIterator2,
          InputIterator3, InputIterator4, OutputIterator1, OutputIterator2)
```

**Template Function `thrust::set_difference_by_key(InputIterator1, InputIterator1, InputIterator2, InputIterator2, InputIterator3, InputIterator4, OutputIterator1, OutputIterator2)`**

## Function Documentation

```
template<typename InputIterator1, typename InputIterator2, typename InputIterator3, typename InputIterator4, typename OutputIterator1, typename OutputIterator2>
```

```
thrust::pair<OutputIterator1, OutputIterator2> thrust::set_difference_by_key(InputIterator1
    keys_first1, In-
    putIterator1
    keys_last1, In-
    putIterator2
    keys_first2, In-
    putIterator2
    keys_last2, In-
    putIterator3
    values_first1,
    InputIterator4
    values_first2,
    OutputItera-
    tor1 keys_result,
    OutputIterator2
    values_result)
```

`set_difference_by_key` performs a key-value difference operation from set theory. `set_difference_by_key` constructs a sorted range that is the difference of the sorted ranges  $[keys\_first1, keys\_last1]$  and  $[keys\_first2, keys\_last2]$ . Associated with each element from the input and output key ranges is a value element. The associated input value ranges need not be sorted.

In the simplest case, `set_difference_by_key` performs the “difference” operation from set theory: the keys output range contains a copy of every element that is contained in  $[keys\_first1, keys\_last1]$  and not contained in  $[keys\_first2, keys\_last2]$ . The general case is more complicated, because the input ranges may contain duplicate elements. The generalization is that if  $[keys\_first1, keys\_last1]$  contains  $m$  elements that are equivalent to each other and if  $[keys\_first2, keys\_last2]$  contains  $n$  elements that are equivalent to them, the last  $\max(m-n, 0)$  elements from  $[keys\_first1, keys\_last1]$  range shall be copied to the output range.

Each time a key element is copied from  $[keys\_first1, keys\_last1]$  or  $[keys\_first2, keys\_last2]$  is copied to the keys output range, the corresponding value element is copied from the corresponding values input range (beginning at `values_first1` or `values_first2`) to the values output range.

This version of `set_difference_by_key` compares key elements using operator`<`.

The following code snippet demonstrates how to use `set_difference_by_key` to compute the set difference of two sets of integers sorted in ascending order with their values.

**Return** A pair `p` such that `p.first` is the end of the output range of keys, and such that `p.second` is the end of the output range of values.

**Pre** The ranges  $[keys\_first1, keys\_last1]$  and  $[keys\_first2, keys\_last2]$  shall be sorted with respect to operator`<`.

**Pre** The resulting ranges shall not overlap with any input range.

### Parameters

- `keys_first1`: The beginning of the first input range of keys.
- `keys_last1`: The end of the first input range of keys.
- `keys_first2`: The beginning of the second input range of keys.
- `keys_last2`: The end of the second input range of keys.
- `values_first1`: The beginning of the first input range of values.
- `values_first2`: The beginning of the first input range of values.

- `keys_result`: The beginning of the output range of keys.
- `values_result`: The beginning of the output range of values.

### Template Parameters

- `InputIterator1`: is a model of `Input Iterator`, `InputIterator1` and `InputIterator2` have the same `value_type`, `InputIterator1`'s `value_type` is a model of `LessThan Comparable`, the ordering on `InputIterator1`'s `value_type` is a strict weak ordering, as defined in the `LessThan Comparable` requirements, and `InputIterator1`'s `value_type` is convertible to a type in `OutputIterator`'s set of `value_types`.
- `InputIterator2`: is a model of `Input Iterator`, `InputIterator2` and `InputIterator1` have the same `value_type`, `InputIterator2`'s `value_type` is a model of `LessThan Comparable`, the ordering on `InputIterator2`'s `value_type` is a strict weak ordering, as defined in the `LessThan Comparable` requirements, and `InputIterator2`'s `value_type` is convertible to a type in `OutputIterator`'s set of `value_types`.
- `InputIterator3`: is a model of `Input Iterator`, and `InputIterator3`'s `value_type` is convertible to a type in `OutputIterator2`'s set of `value_types`.
- `InputIterator4`: is a model of `Input Iterator`, and `InputIterator4`'s `value_type` is convertible to a type in `OutputIterator2`'s set of `value_types`.
- `OutputIterator1`: is a model of `Output Iterator`.
- `OutputIterator2`: is a model of `Output Iterator`.

```
#include <thrust/set_operations.h>
...
int A_keys[6] = {0, 1, 3, 4, 5, 6, 9};
int A_vals[6] = {0, 0, 0, 0, 0, 0, 0};

int B_keys[5] = {1, 3, 5, 7, 9};
int B_vals[5] = {1, 1, 1, 1, 1};

int keys_result[3];
int vals_result[3];

thrust::pair<int*,int*> end = thrust::set_difference_by_key(A_keys, A_keys + 6, B_
    ↵keys, B_keys + 5, A_vals, B_vals, keys_result, vals_result);
// keys_result is now {0, 4, 6}
// vals_result is now {0, 0, 0}
```

**See** `set_union_by_key`

**See** `set_intersection_by_key`

**See** `set_symmetric_difference_by_key`

**See** `sort_by_key`

**See** `is_sorted`

**Template Function** `thrust::set_difference_by_key(const thrust::detail::execution_policy_base<DerivedPolicy>&, InputIterator1, InputIterator1, InputIterator2, InputIterator2, InputIterator3, InputIterator4, OutputIterator1, OutputIterator2, StrictWeakCompare)`

## Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “thrust::set\_difference\_by\_key” with arguments (const thrust::detail::execution\_policy\_base<DerivedPolicy>&, InputIterator1, InputIterator1, InputIterator2, InputIterator2, InputIterator3, InputIterator4, OutputIterator1, OutputIterator2, StrictWeakCompare) in doxygen xml output for project “rocThrust” from directory: ./docBin/xml. Potential matches:

```
- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2,
→ typename InputIterator3, typename InputIterator4, typename OutputIterator1,
→typename OutputIterator2, typename StrictWeakCompare>__host__ __device__
→thrust::pair<OutputIterator1,OutputIterator2> thrust::set_difference_by_key(const_
→thrust::detail::execution_policy_base< DerivedPolicy > &, InputIterator1,
→InputIterator1, InputIterator2, InputIterator3, InputIterator4,
→OutputIterator1, OutputIterator2, StrictWeakCompare)
- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2,
→ typename InputIterator3, typename InputIterator4, typename OutputIterator1,
→typename OutputIterator2>__host__ __device__ thrust::pair<OutputIterator1,
→OutputIterator2> thrust::set_difference_by_key(const thrust::detail::execution_
→policy_base< DerivedPolicy > &, InputIterator1, InputIterator1, InputIterator2,
→InputIterator2, InputIterator3, InputIterator4, OutputIterator1, OutputIterator2)
- template<typename InputIterator1, typename InputIterator2, typename_
→InputIterator3, typename InputIterator4, typename OutputIterator1, typename_
→OutputIterator2, typename StrictWeakCompare>
    thrust::pair<OutputIterator1, OutputIterator2> thrust::set_difference_by_
→key(InputIterator1, InputIterator1, InputIterator2, InputIterator2,
→InputIterator3, InputIterator4, OutputIterator1, OutputIterator2,
→StrictWeakCompare)
- template<typename InputIterator1, typename InputIterator2, typename_
→InputIterator3, typename InputIterator4, typename OutputIterator1, typename_
→OutputIterator2>
    thrust::pair<OutputIterator1, OutputIterator2> thrust::set_difference_by_
→key(InputIterator1, InputIterator1, InputIterator2, InputIterator2,
→InputIterator3, InputIterator4, OutputIterator1, OutputIterator2)
```

**Template Function `thrust::set_difference_by_key(InputIterator1, InputIterator1, InputIterator2, InputIterator2, InputIterator3, InputIterator4, OutputIterator1, OutputIterator2, StrictWeakCompare)`**

## Function Documentation

```
template<typename InputIterator1, typename InputIterator2, typename InputIterator3, typename InputIterator4, typename OutputIterator1, typename OutputIterator2, typename StrictWeakCompare>
```

```
thrust::pair<OutputIterator1, OutputIterator2> thrust::set_difference_by_key(InputIterator1
    keys_first1, In-
    putIterator1
    keys_last1, In-
    putIterator2
    keys_first2, In-
    putIterator2
    keys_last2, In-
    putIterator3
    values_first1,
    InputIterator4
    values_first2,
    OutputItera-
    tor1 keys_result,
    OutputIterator2
    values_result,
    StrictWeakCom-
    pare comp)
```

`set_difference_by_key` performs a key-value difference operation from set theory. `set_difference_by_key` constructs a sorted range that is the difference of the sorted ranges  $[keys\_first1, keys\_last1]$  and  $[keys\_first2, keys\_last2]$ . Associated with each element from the input and output key ranges is a value element. The associated input value ranges need not be sorted.

In the simplest case, `set_difference_by_key` performs the “difference” operation from set theory: the keys output range contains a copy of every element that is contained in  $[keys\_first1, keys\_last1]$  and not contained in  $[keys\_first2, keys\_last2]$ . The general case is more complicated, because the input ranges may contain duplicate elements. The generalization is that if  $[keys\_first1, keys\_last1]$  contains  $m$  elements that are equivalent to each other and if  $[keys\_first2, keys\_last2]$  contains  $n$  elements that are equivalent to them, the last  $\max(m-n, 0)$  elements from  $[keys\_first1, keys\_last1]$  range shall be copied to the output range.

Each time a key element is copied from  $[keys\_first1, keys\_last1]$  or  $[keys\_first2, keys\_last2]$  is copied to the keys output range, the corresponding value element is copied from the corresponding values input range (beginning at `values_first1` or `values_first2`) to the values output range.

This version of `set_difference_by_key` compares key elements using a function object `comp`.

The following code snippet demonstrates how to use `set_difference_by_key` to compute the set difference of two sets of integers sorted in descending order with their values.

**Return** A pair `p` such that `p.first` is the end of the output range of keys, and such that `p.second` is the end of the output range of values.

**Pre** The ranges  $[keys\_first1, keys\_last1]$  and  $[keys\_first2, keys\_last2]$  shall be sorted with respect to `comp`.

**Pre** The resulting ranges shall not overlap with any input range.

### Parameters

- `keys_first1`: The beginning of the first input range of keys.
- `keys_last1`: The end of the first input range of keys.
- `keys_first2`: The beginning of the second input range of keys.
- `keys_last2`: The end of the second input range of keys.
- `values_first1`: The beginning of the first input range of values.

- `values_first2`: The beginning of the first input range of values.
- `keys_result`: The beginning of the output range of keys.
- `values_result`: The beginning of the output range of values.
- `comp`: Comparison operator.

### Template Parameters

- `InputIterator1`: is a model of `Input Iterator`, `InputIterator1` and `InputIterator2` have the same `value_type`, `InputIterator1`'s `value_type` is a model of `LessThan Comparable`, the ordering on `InputIterator1`'s `value_type` is a strict weak ordering, as defined in the `LessThan Comparable` requirements, and `InputIterator1`'s `value_type` is convertible to a type in `OutputIterator`'s set of `value_types`.
- `InputIterator2`: is a model of `Input Iterator`, `InputIterator2` and `InputIterator1` have the same `value_type`, `InputIterator2`'s `value_type` is a model of `LessThan Comparable`, the ordering on `InputIterator2`'s `value_type` is a strict weak ordering, as defined in the `LessThan Comparable` requirements, and `InputIterator2`'s `value_type` is convertible to a type in `OutputIterator`'s set of `value_types`.
- `InputIterator3`: is a model of `Input Iterator`, and `InputIterator3`'s `value_type` is convertible to a type in `OutputIterator2`'s set of `value_types`.
- `InputIterator4`: is a model of `Input Iterator`, and `InputIterator4`'s `value_type` is convertible to a type in `OutputIterator2`'s set of `value_types`.
- `OutputIterator1`: is a model of `Output Iterator`.
- `OutputIterator2`: is a model of `Output Iterator`.
- `StrictWeakCompare`: is a model of `Strict Weak Ordering`.

```
#include <thrust/set_operations.h>
#include <thrust/functional.h>
...
int A_keys[6] = {9, 6, 5, 4, 3, 1, 0};
int A_vals[6] = {0, 0, 0, 0, 0, 0, 0};

int B_keys[5] = {9, 7, 5, 3, 1};
int B_vals[5] = {1, 1, 1, 1, 1};

int keys_result[3];
int vals_result[3];

thrust::pair<int*,int*> end = thrust::set_difference_by_key(A_keys, A_keys + 6, B_
    ↪keys, B_keys + 5, A_vals, B_vals, keys_result, vals_result, thrust::greater<int>
    ↪());
// keys_result is now {0, 4, 6}
// vals_result is now {0, 0, 0}
```

**See** `set_union_by_key`

**See** `set_intersection_by_key`

**See** `set_symmetric_difference_by_key`

**See** `sort_by_key`

**See** `is_sorted`

**Template Function `thrust::set_intersection(const thrust::detail::execution_policy_base<DerivedPolicy>&, InputIterator1, InputIterator1, InputIterator2, InputIterator2, OutputIterator)`**

- Defined in file `_thrust_set_operations.h`

**Function Documentation**

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::set_intersection`” with arguments (`const thrust::detail::execution_policy_base<DerivedPolicy>&`, `InputIterator1`, `InputIterator1`, `InputIterator2`, `InputIterator2`, `OutputIterator`) in doxygen xml output for project “rocThrust” from directory: `./docBin/xml`. Potential matches:

```
- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2,
→ typename OutputIterator, typename StrictWeakCompare> __host__ __device__
→OutputIterator thrust::set_intersection(const thrust::detail::execution_policy_
→base< DerivedPolicy > &, InputIterator1, InputIterator1, InputIterator2,_
→InputIterator2, OutputIterator, StrictWeakCompare)
- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2,
→ typename OutputIterator> __host__ __device__ OutputIterator thrust::set_
→intersection(const thrust::detail::execution_policy_base< DerivedPolicy > &,
→InputIterator1, InputIterator1, InputIterator2, InputIterator2, OutputIterator)
- template<typename InputIterator1, typename InputIterator2, typename_
→OutputIterator, typename StrictWeakCompare>
→OutputIterator thrust::set_intersection(InputIterator1, InputIterator1,_
→InputIterator2, InputIterator2, OutputIterator, StrictWeakCompare)
- template<typename InputIterator1, typename InputIterator2, typename_
→OutputIterator>
→OutputIterator thrust::set_intersection(InputIterator1, InputIterator1,_
→InputIterator2, InputIterator2, OutputIterator)
```

**Template Function `thrust::set_intersection(InputIterator1, InputIterator1, InputIterator2, InputIterator2, OutputIterator)`****Function Documentation**

```
template<typename InputIterator1, typename InputIterator2, typename OutputIterator>
OutputIterator thrust::set_intersection(InputIterator1 first1, InputIterator1 last1, InputIterator2
                                         first2, InputIterator2 last2, OutputIterator result)
set_intersection constructs a sorted range that is the intersection of sorted ranges [first1, last1)
and [first2, last2). The return value is the end of the output range.
```

In the simplest case, `set_intersection` performs the “intersection” operation from set theory: the output range contains a copy of every element that is contained in both `[first1, last1)` and `[first2, last2)`. The general case is more complicated, because the input ranges may contain duplicate elements. The generalization is that if a value appears  $m$  times in `[first1, last1)` and  $n$  times in `[first2, last2)` (where  $m$  may be zero), then it appears  $\min(m, n)$  times in the output range. `set_intersection` is stable, meaning that both elements are copied from the first range rather than the second, and that the relative order of elements in the output range is the same as in the first input range.

This version of `set_intersection` compares objects using operator`<`.

The following code snippet demonstrates how to use `set_intersection` to compute the set intersection of two sets of integers sorted in ascending order.

**Return** The end of the output range.

**Pre** The ranges [first1, last1) and [first2, last2) shall be sorted with respect to operator<.

**Pre** The resulting range shall not overlap with either input range.

#### Parameters

- first1: The beginning of the first input range.
- last1: The end of the first input range.
- first2: The beginning of the second input range.
- last2: The end of the second input range.
- result: The beginning of the output range.

#### Template Parameters

- InputIterator1: is a model of [Input Iterator](#), InputIterator1 and InputIterator2 have the same value\_type, InputIterator1's value\_type is a model of [LessThan Comparable](#), the ordering on InputIterator1's value\_type is a strict weak ordering, as defined in the [LessThan Comparable](#) requirements, and InputIterator1's value\_type is convertible to a type in OutputIterator's set of value\_types.
- InputIterator2: is a model of [Input Iterator](#), InputIterator2 and InputIterator1 have the same value\_type, InputIterator2's value\_type is a model of [LessThan Comparable](#), the ordering on InputIterator2's value\_type is a strict weak ordering, as defined in the [LessThan Comparable](#) requirements, and InputIterator2's value\_type is convertible to a type in OutputIterator's set of value\_types.
- OutputIterator: is a model of [Output Iterator](#).

```
#include <thrust/set_operations.h>
...
int A1[6] = {1, 3, 5, 7, 9, 11};
int A2[7] = {1, 1, 2, 3, 5, 8, 13};

int result[7];

int *result_end = thrust::set_intersection(A1, A1 + 6, A2, A2 + 7, result);
// result is now {1, 3, 5}
```

**See** [http://www.sgi.com/tech/stl/set\\_intersection.html](http://www.sgi.com/tech/stl/set_intersection.html)

**See** [includes](#)

**See** [set\\_union](#)

**See** [set\\_intersection](#)

**See** [set\\_symmetric\\_difference](#)

**See** [sort](#)

**See** [is\\_sorted](#)

**Template Function** `thrust::set_intersection(const thrust::detail::execution_policy_base<DerivedPolicy>&, InputIterator1, InputIterator1, InputIterator2, InputIterator2, OutputIterator, StrictWeakCompare)`

## Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “thrust::set\_intersection” with arguments (const thrust::detail::execution\_policy\_base<DerivedPolicy>&, InputIterator1, InputIterator1, InputIterator2, InputIterator2, OutputIterator, StrictWeakCompare) in doxygen xml output for project “rocThrust” from directory: ./docBin/xml. Potential matches:

```
- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2,
→ typename OutputIterator, typename StrictWeakCompare> __host__ __device__
→OutputIterator thrust::set_intersection(const thrust::detail::execution_policy_
→base< DerivedPolicy > &, InputIterator1, InputIterator1, InputIterator2,
→InputIterator2, OutputIterator, StrictWeakCompare)
- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2,
→ typename OutputIterator> __host__ __device__ OutputIterator thrust::set_
→intersection(const thrust::detail::execution_policy_base< DerivedPolicy > &,
→InputIterator1, InputIterator1, InputIterator2, InputIterator2, OutputIterator)
- template<typename InputIterator1, typename InputIterator2, typename_
→OutputIterator, typename StrictWeakCompare>
→OutputIterator thrust::set_intersection(InputIterator1, InputIterator1,
→InputIterator2, InputIterator2, OutputIterator, StrictWeakCompare)
- template<typename InputIterator1, typename InputIterator2, typename_
→OutputIterator>
→OutputIterator thrust::set_intersection(InputIterator1, InputIterator1,
→InputIterator2, InputIterator2, OutputIterator)
```

### Template Function `thrust::set_intersection(InputIterator1, InputIterator1, InputIterator2, InputIterator2, OutputIterator, StrictWeakCompare)`

#### Function Documentation

```
template<typename InputIterator1, typename InputIterator2, typename OutputIterator, typename StrictWeakCompare>
OutputIterator thrust::set_intersection(InputIterator1 first1, InputIterator1 last1, InputIterator2 first2, InputIterator2 last2, OutputIterator result, StrictWeakCompare comp)
```

`set_intersection` constructs a sorted range that is the intersection of sorted ranges `[first1, last1)` and `[first2, last2)`. The return value is the end of the output range.

In the simplest case, `set_intersection` performs the “intersection” operation from set theory: the output range contains a copy of every element that is contained in both `[first1, last1)` and `[first2, last2)`. The general case is more complicated, because the input ranges may contain duplicate elements. The generalization is that if a value appears  $m$  times in `[first1, last1)` and  $n$  times in `[first2, last2)` (where  $m$  may be zero), then it appears  $\min(m, n)$  times in the output range. `set_intersection` is stable, meaning that both elements are copied from the first range rather than the second, and that the relative order of elements in the output range is the same as in the first input range.

This version of `set_intersection` compares elements using a function object `comp`.

The following code snippet demonstrates how to use `set_intersection` to compute the set intersection of sets of integers sorted in descending order.

**Return** The end of the output range.

**Pre** The ranges `[first1, last1)` and `[first2, last2)` shall be sorted with respect to `comp`.

**Pre** The resulting range shall not overlap with either input range.

## Parameters

- `first1`: The beginning of the first input range.
- `last1`: The end of the first input range.
- `first2`: The beginning of the second input range.
- `last2`: The end of the second input range.
- `result`: The beginning of the output range.
- `comp`: Comparison operator.

## Template Parameters

- `InputIterator1`: is a model of `Input Iterator`, `InputIterator1` and `InputIterator2` have the same `value_type`, `InputIterator1`'s `value_type` is a model of `LessThan Comparable`, the ordering on `InputIterator1`'s `value_type` is a strict weak ordering, as defined in the `LessThan Comparable` requirements, and `InputIterator1`'s `value_type` is convertible to a type in `OutputIterator`'s set of `value_types`.
- `InputIterator2`: is a model of `Input Iterator`, `InputIterator2` and `InputIterator1` have the same `value_type`, `InputIterator2`'s `value_type` is a model of `LessThan Comparable`, the ordering on `InputIterator2`'s `value_type` is a strict weak ordering, as defined in the `LessThan Comparable` requirements, and `InputIterator2`'s `value_type` is convertible to a type in `OutputIterator`'s set of `value_types`.
- `OutputIterator`: is a model of `Output Iterator`.

```
#include <thrust/set_operations.h>
...
int A1[6] = {11, 9, 7, 5, 3, 1};
int A2[7] = {13, 8, 5, 3, 2, 1, 1};

int result[3];

int *result_end = thrust::set_intersection(A1, A1 + 6, A2, A2 + 7, result,
                                           thrust::greater<int>());
// result is now {5, 3, 1}
```

See [http://www.sgi.com/tech/stl/set\\_intersection.html](http://www.sgi.com/tech/stl/set_intersection.html)

See `includes`

See `set_union`

See `set_intersection`

See `set_symmetric_difference`

See `sort`

See `is_sorted`

**Template Function `thrust::set_intersection_by_key(const thrust::detail::execution_policy_base<DerivedPolicy>&, InputIterator1, InputIterator1, InputIterator2, InputIterator2, InputIterator3, OutputIterator1, OutputIterator2)`**

- Defined in file `thrust_set_operations.h`

## Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “thrust::set\_intersection\_by\_key” with arguments (const thrust::detail::execution\_policy\_base<DerivedPolicy>&, InputIterator1, InputIterator1, InputIterator2, InputIterator2, InputIterator3, OutputIterator1, OutputIterator2) in doxygen xml output for project “rocThrust” from directory: ./docBin/xml. Potential matches:

```
- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2,
          typename InputIterator3, typename OutputIterator1, typename OutputIterator2, 
          typename StrictWeakCompare> __host__ __device__ thrust::pair<OutputIterator1,
          OutputIterator2> thrust::set_intersection_by_key(const thrust::detail::execution_
          policy_base< DerivedPolicy > &, InputIterator1, InputIterator1, InputIterator2, 
          InputIterator2, InputIterator3, OutputIterator1, OutputIterator2, 
          StrictWeakCompare)
- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2,
          typename InputIterator3, typename OutputIterator1, typename OutputIterator2> __
          host__ __device__ thrust::pair<OutputIterator1,OutputIterator2> thrust::set_
          intersection_by_key(const thrust::detail::execution_policy_base< DerivedPolicy > &
          , InputIterator1, InputIterator1, InputIterator2, InputIterator2, InputIterator3, 
          OutputIterator1, OutputIterator2)
- template<typename InputIterator1, typename InputIterator2, typename_
          InputIterator3, typename OutputIterator1, typename OutputIterator2, typename_
          StrictWeakCompare>
          thrust::pair<OutputIterator1, OutputIterator2> thrust::set_intersection_by_
          key(InputIterator1, InputIterator1, InputIterator2, InputIterator2, 
          InputIterator3, OutputIterator1, OutputIterator2, StrictWeakCompare)
- template<typename InputIterator1, typename InputIterator2, typename_
          InputIterator3, typename OutputIterator1, typename OutputIterator2>
          thrust::pair<OutputIterator1, OutputIterator2> thrust::set_intersection_by_
          key(InputIterator1, InputIterator1, InputIterator2, InputIterator2, 
          InputIterator3, OutputIterator1, OutputIterator2)
```

**Template Function** `thrust::set_intersection_by_key(InputIterator1, InputIterator1, InputIterator2, InputIterator2, InputIterator3, OutputIterator1, OutputIterator2)`

## Function Documentation

```
template<typename InputIterator1, typename InputIterator2, typename InputIterator3, typename OutputIterat
```

```
thrust::pair<OutputIterator1, OutputIterator2> thrust::set_intersection_by_key(InputIterator1
    keys_first1,
    InputIterator1
    keys_last1,
    InputIterator2
    keys_first2,
    InputIterator2
    keys_last2,
    InputIterator3
    values_first1,
    OutputIter-
    erator1
    keys_result,
    OutputIter-
    ator2      val-
    ues_result)
```

`set_intersection_by_key` performs a key-value intersection operation from set theory. `set_intersection_by_key` constructs a sorted range that is the intersection of the sorted ranges `[keys_first1, keys_last1]` and `[keys_first2, keys_last2]`. Associated with each element from the input and output key ranges is a value element. The associated input value ranges need not be sorted.

In the simplest case, `set_intersection_by_key` performs the “intersection” operation from set theory: the keys output range contains a copy of every element that is contained in both `[keys_first1, keys_last1]` `[keys_first2, keys_last2]`. The general case is more complicated, because the input ranges may contain duplicate elements. The generalization is that if an element appears  $m$  times in `[keys_first1, keys_last1]` and  $n$  times in `[keys_first2, keys_last2]` (where  $m$  may be zero), then it appears  $\min(m, n)$  times in the keys output range. `set_intersection_by_key` is stable, meaning both that elements are copied from the first input range rather than the second, and that the relative order of elements in the output range is the same as the first input range.

Each time a key element is copied from `[keys_first1, keys_last1]` to the keys output range, the corresponding value element is copied from `[values_first1, values_last1]` to the values output range.

This version of `set_intersection_by_key` compares objects using operator`<`.

The following code snippet demonstrates how to use `set_intersection_by_key` to compute the set intersection of two sets of integers sorted in ascending order with their values.

**Return** A pair `p` such that `p.first` is the end of the output range of keys, and such that `p.second` is the end of the output range of values.

**Note** Unlike the other key-value set operations, `set_intersection_by_key` is unique in that it has no `values_first2` parameter because elements from the second input range are never copied to the output range.

**Pre** The ranges `[keys_first1, keys_last1]` and `[keys_first2, keys_last2]` shall be sorted with respect to operator`<`.

**Pre** The resulting ranges shall not overlap with any input range.

### Parameters

- `keys_first1`: The beginning of the first input range of keys.
- `keys_last1`: The end of the first input range of keys.
- `keys_first2`: The beginning of the second input range of keys.
- `keys_last2`: The end of the second input range of keys.

- `values_first1`: The beginning of the first input range of values.
- `keys_result`: The beginning of the output range of keys.
- `values_result`: The beginning of the output range of values.

### Template Parameters

- `InputIterator1`: is a model of [Input Iterator](#), `InputIterator1` and `InputIterator2` have the same `value_type`, `InputIterator1`'s `value_type` is a model of [LessThan Comparable](#), the ordering on `InputIterator1`'s `value_type` is a strict weak ordering, as defined in the [LessThan Comparable requirements](#), and `InputIterator1`'s `value_type` is convertible to a type in `OutputIterator`'s set of `value_types`.
- `InputIterator2`: is a model of [Input Iterator](#), `InputIterator2` and `InputIterator1` have the same `value_type`, `InputIterator2`'s `value_type` is a model of [LessThan Comparable](#), the ordering on `InputIterator2`'s `value_type` is a strict weak ordering, as defined in the [LessThan Comparable requirements](#), and `InputIterator2`'s `value_type` is convertible to a type in `OutputIterator`'s set of `value_types`.
- `InputIterator3`: is a model of [Input Iterator](#), and `InputIterator3`'s `value_type` is convertible to a type in `OutputIterator2`'s set of `value_types`.
- `OutputIterator1`: is a model of [Output Iterator](#).
- `OutputIterator2`: is a model of [Output Iterator](#).

```
#include <thrust/set_operations.h>
...
int A_keys[6] = {1, 3, 5, 7, 9, 11};
int A_vals[6] = {0, 0, 0, 0, 0, 0};

int B_keys[7] = {1, 1, 2, 3, 5, 8, 13};

int keys_result[7];
int vals_result[7];

thrust::pair<int*, int*> end = thrust::set_intersection_by_key(A_keys, A_keys + 6, ↵
    B_keys, B_keys + 7, A_vals, keys_result, vals_result);

// keys_result is now {1, 3, 5}
// vals_result is now {0, 0, 0}
```

**See** `set_union_by_key`

**See** `set_difference_by_key`

**See** `set_symmetric_difference_by_key`

**See** `sort_by_key`

**See** `is_sorted`

**Template Function** `thrust::set_intersection_by_key(const thrust::detail::execution_policy_base<DerivedPolicy>&, InputIterator1, InputIterator1, InputIterator2, InputIterator2, InputIterator3, OutputIterator1, OutputIterator2, StrictWeakCompare)`

## Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “thrust::set\_intersection\_by\_key” with arguments (const thrust::detail::execution\_policy\_base<DerivedPolicy>&, InputIterator1, InputIterator1, InputIterator2, InputIterator2, InputIterator3, OutputIterator1, OutputIterator2, StrictWeakCompare) in doxygen xml output for project “rocThrust” from directory: ./docBin/xml. Potential matches:

```
- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2,
→ typename InputIterator3, typename OutputIterator1, typename OutputIterator2,_
→typename StrictWeakCompare>__host__ __device__ thrust::pair<OutputIterator1,
→OutputIterator2> thrust::set_intersection_by_key(const thrust::detail::execution_
→policy_base< DerivedPolicy > &, InputIterator1, InputIterator1, InputIterator2,_
→InputIterator2, InputIterator3, OutputIterator1, OutputIterator2,_
→StrictWeakCompare)
- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2,
→ typename InputIterator3, typename OutputIterator1, typename OutputIterator2>__
→host__ __device__ thrust::pair<OutputIterator1,OutputIterator2> thrust::set_
→intersection_by_key(const thrust::detail::execution_policy_base< DerivedPolicy > &
→, InputIterator1, InputIterator1, InputIterator2, InputIterator2, InputIterator3,_
→OutputIterator1, OutputIterator2)
- template<typename InputIterator1, typename InputIterator2, typename_
→InputIterator3, typename OutputIterator1, typename OutputIterator2, typename_
→StrictWeakCompare>
    thrust::pair<OutputIterator1, OutputIterator2> thrust::set_intersection_by_
→key(InputIterator1, InputIterator1, InputIterator2, InputIterator2,_
→InputIterator3, OutputIterator1, OutputIterator2, StrictWeakCompare)
- template<typename InputIterator1, typename InputIterator2, typename_
→InputIterator3, typename OutputIterator1, typename OutputIterator2>
    thrust::pair<OutputIterator1, OutputIterator2> thrust::set_intersection_by_
→key(InputIterator1, InputIterator1, InputIterator2, InputIterator2,_
→InputIterator3, OutputIterator1, OutputIterator2)
```

**Template Function thrust::set\_intersection\_by\_key(InputIterator1, InputIterator1, InputIterator2, InputIterator2, InputIterator3, OutputIterator1, OutputIterator2, StrictWeakCompare)**

## Function Documentation

```
template<typename InputIterator1, typename InputIterator2, typename InputIterator3, typename OutputIterat
```

```
thrust::pair<OutputIterator1, OutputIterator2> thrust::set_intersection_by_key (InputIterator1
    keys_first1,
    InputIterator1
    keys_last1,
    InputIterator2
    keys_first2,
    InputIterator2
    keys_last2,
    InputIterator3
    values_first1,
    OutputIter-
    erator1
    keys_result,
    OutputIter-
    ator2      val-
    ues_result,
    StrictWeak-
    Compare
    comp)
```

`set_intersection_by_key` performs a key-value intersection operation from set theory. `set_intersection_by_key` constructs a sorted range that is the intersection of the sorted ranges `[keys_first1, keys_last1]` and `[keys_first2, keys_last2]`. Associated with each element from the input and output key ranges is a value element. The associated input value ranges need not be sorted.

In the simplest case, `set_intersection_by_key` performs the “intersection” operation from set theory: the keys output range contains a copy of every element that is contained in both `[keys_first1, keys_last1]` `[keys_first2, keys_last2]`. The general case is more complicated, because the input ranges may contain duplicate elements. The generalization is that if an element appears  $m$  times in `[keys_first1, keys_last1]` and  $n$  times in `[keys_first2, keys_last2]` (where  $m$  may be zero), then it appears  $\min(m, n)$  times in the keys output range. `set_intersection_by_key` is stable, meaning both that elements are copied from the first input range rather than the second, and that the relative order of elements in the output range is the same as the first input range.

Each time a key element is copied from `[keys_first1, keys_last1]` to the keys output range, the corresponding value element is copied from `[values_first1, values_last1]` to the values output range.

This version of `set_intersection_by_key` compares objects using a function object `comp`.

The following code snippet demonstrates how to use `set_intersection_by_key` to compute the set intersection of two sets of integers sorted in descending order with their values.

**Return** A pair `p` such that `p.first` is the end of the output range of keys, and such that `p.second` is the end of the output range of values.

**Note** Unlike the other key-value set operations, `set_intersection_by_key` is unique in that it has no `values_first2` parameter because elements from the second input range are never copied to the output range.

**Pre** The ranges `[keys_first1, keys_last1]` and `[keys_first2, keys_last2]` shall be sorted with respect to `comp`.

**Pre** The resulting ranges shall not overlap with any input range.

### Parameters

- `keys_first1`: The beginning of the first input range of keys.
- `keys_last1`: The end of the first input range of keys.

- `keys_first2`: The beginning of the second input range of keys.
- `keys_last2`: The end of the second input range of keys.
- `values_first1`: The beginning of the first input range of values.
- `keys_result`: The beginning of the output range of keys.
- `values_result`: The beginning of the output range of values.
- `comp`: Comparison operator.

### Template Parameters

- `InputIterator1`: is a model of [Input Iterator](#), `InputIterator1` and `InputIterator2` have the same `value_type`, `InputIterator1`'s `value_type` is a model of [LessThan Comparable](#), the ordering on `InputIterator1`'s `value_type` is a strict weak ordering, as defined in the [LessThan Comparable requirements](#), and `InputIterator1`'s `value_type` is convertible to a type in `OutputIterator`'s set of `value_types`.
- `InputIterator2`: is a model of [Input Iterator](#), `InputIterator2` and `InputIterator1` have the same `value_type`, `InputIterator2`'s `value_type` is a model of [LessThan Comparable](#), the ordering on `InputIterator2`'s `value_type` is a strict weak ordering, as defined in the [LessThan Comparable requirements](#), and `InputIterator2`'s `value_type` is convertible to a type in `OutputIterator`'s set of `value_types`.
- `InputIterator3`: is a model of [Input Iterator](#), and `InputIterator3`'s `value_type` is convertible to a type in `OutputIterator2`'s set of `value_types`.
- `OutputIterator1`: is a model of [Output Iterator](#).
- `OutputIterator2`: is a model of [Output Iterator](#).
- `StrictWeakCompare`: is a model of [Strict Weak Ordering](#).

```
#include <thrust/set_operations.h>
#include <thrust/functional.h>

...
int A_keys[6] = {11, 9, 7, 5, 3, 1};
int A_vals[6] = { 0, 0, 0, 0, 0, 0};

int B_keys[7] = {13, 8, 5, 3, 2, 1, 1};

int keys_result[7];
int vals_result[7];

thrust::pair<int*,int*> end = thrust::set_intersection_by_key(A_keys, A_keys + 6, ↵
    B_keys, B_keys + 7, A_vals, keys_result, vals_result, thrust::greater<int>());

// keys_result is now {5, 3, 1}
// vals_result is now {0, 0, 0}
```

**See** `set_union_by_key`

**See** `set_difference_by_key`

**See** `set_symmetric_difference_by_key`

**See** `sort_by_key`

**See** `is_sorted`

**Template Function `thrust::set_symmetric_difference(const thrust::detail::execution_policy_base<DerivedPolicy>&, InputIterator1, InputIterator1, InputIterator2, InputIterator2, OutputIterator)`**

- Defined in file `_thrust_set_operations.h`

**Function Documentation**

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::set_symmetric_difference`” with arguments (`const thrust::detail::execution_policy_base<DerivedPolicy>&`, `InputIterator1`, `InputIterator1`, `InputIterator2`, `InputIterator2`, `OutputIterator`) in doxygen xml output for project “rocThrust” from directory: `./docBin/xml`. Potential matches:

```
- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2,
→ typename OutputIterator, typename StrictWeakCompare> __host__ __device__
→OutputIterator thrust::set_symmetric_difference(const thrust::detail::execution_
→policy_base< DerivedPolicy > &, InputIterator1, InputIterator1, InputIterator2, □
→InputIterator2, OutputIterator, StrictWeakCompare)
- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2,
→ typename OutputIterator> __host__ __device__ OutputIterator thrust::set_symmetric_
→difference (const thrust::detail::execution_policy_base< DerivedPolicy > &, □
→InputIterator1, InputIterator1, InputIterator2, InputIterator2, OutputIterator)
- template<typename InputIterator1, typename InputIterator2, typename_
→OutputIterator, typename StrictWeakCompare>
→OutputIterator thrust::set_symmetric_difference(InputIterator1, InputIterator1, □
→InputIterator2, InputIterator2, OutputIterator, StrictWeakCompare)
- template<typename InputIterator1, typename InputIterator2, typename_
→OutputIterator>
→OutputIterator thrust::set_symmetric_difference(InputIterator1, InputIterator1, □
→InputIterator2, InputIterator2, OutputIterator)
```

**Template Function `thrust::set_symmetric_difference(InputIterator1, InputIterator1, InputIterator2, InputIterator2, OutputIterator)`****Function Documentation**

```
template<typename InputIterator1, typename InputIterator2, typename OutputIterator>
OutputIterator thrust::set_symmetric_difference(InputIterator1 first1, InputIterator1 last1, InputIterator2 first2, InputIterator2 last2, OutputIterator result)
```

`set_symmetric_difference` constructs a sorted range that is the set symmetric difference of the sorted ranges `[first1, last1]` and `[first2, last2]`. The return value is the end of the output range.

In the simplest case, `set_symmetric_difference` performs a set theoretic calculation: it constructs the union of the two sets A - B and B - A, where A and B are the two input ranges. That is, the output range contains a copy of every element that is contained in `[first1, last1]` but not `[first2, last1]`, and a copy of every element that is contained in `[first2, last2]` but not `[first1, last1]`. The general case is more complicated, because the input ranges may contain duplicate elements. The generalization is that if `[first1, last1]` contains  $m$  elements that are equivalent to each other and `[first2, last1]` contains  $n$  elements that are equivalent to them, then  $|m - n|$  of those elements shall be copied to the output range: the last  $m - n$  elements from `[first1, last1]` if  $m > n$ , and the last  $n - m$  of these elements from `[first2, last2]` if  $m < n$ .

This version of `set_union` compares elements using operator`<`.

The following code snippet demonstrates how to use `set_symmetric_difference` to compute the symmetric difference of two sets of integers sorted in ascending order.

**Return** The end of the output range.

**Pre** The ranges `[first1, last1)` and `[first2, last2)` shall be sorted with respect to operator`<`.

**Pre** The resulting range shall not overlap with either input range.

### Parameters

- `first1`: The beginning of the first input range.
- `last1`: The end of the first input range.
- `first2`: The beginning of the second input range.
- `last2`: The end of the second input range.
- `result`: The beginning of the output range.

### Template Parameters

- `InputIterator1`: is a model of `Input Iterator`, `InputIterator1` and `InputIterator2` have the same `value_type`, `InputIterator1`'s `value_type` is a model of `LessThan Comparable`, the ordering on `InputIterator1`'s `value_type` is a strict weak ordering, as defined in the `LessThan Comparable` requirements, and `InputIterator1`'s `value_type` is convertible to a type in `OutputIterator`'s set of `value_types`.
- `InputIterator2`: is a model of `Input Iterator`, `InputIterator2` and `InputIterator1` have the same `value_type`, `InputIterator2`'s `value_type` is a model of `LessThan Comparable`, the ordering on `InputIterator2`'s `value_type` is a strict weak ordering, as defined in the `LessThan Comparable` requirements, and `InputIterator2`'s `value_type` is convertible to a type in `OutputIterator`'s set of `value_types`.
- `OutputIterator`: is a model of `Output Iterator`.

```
#include <thrust/set_operations.h>
...
int A1[6] = {0, 1, 2, 2, 4, 6, 7};
int A2[5] = {1, 1, 2, 5, 8};

int result[6];

int *result_end = thrust::set_symmetric_difference(A1, A1 + 6, A2, A2 + 5,
    ↵result);
// result = {0, 4, 5, 6, 7, 8}
```

**See** [http://www.sgi.com/tech/stl/set\\_symmetric\\_difference.html](http://www.sgi.com/tech/stl/set_symmetric_difference.html)

**See** `merge`

**See** `includes`

**See** `set_difference`

**See** `set_union`

**See** `set_intersection`

**See** `sort`

**See** `is_sorted`

**Template Function `thrust::set_symmetric_difference(const thrust::detail::execution_policy_base<DerivedPolicy>&, InputIterator1, InputIterator1, InputIterator2, InputIterator2, OutputIterator, StrictWeakCompare)`**

## Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::set_symmetric_difference`” with arguments (`const thrust::detail::execution_policy_base<DerivedPolicy>&`, `InputIterator1`, `InputIterator1`, `InputIterator2`, `InputIterator2`, `OutputIterator`, `StrictWeakCompare`) in doxygen xml output for project “rocThrust” from directory `./docBin/xml`. Potential matches:

```
- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2,
          typename OutputIterator, typename StrictWeakCompare> __host__ __device__
          OutputIterator thrust::set_symmetric_difference(const thrust::detail::execution_
          policy_base< DerivedPolicy > &, InputIterator1, InputIterator1, InputIterator2,_
          InputIterator2, OutputIterator, StrictWeakCompare)
- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2,
          typename OutputIterator> __host__ __device__ OutputIterator thrust::set_symmetric_
          difference(const thrust::detail::execution_policy_base< DerivedPolicy > &,
          InputIterator1, InputIterator1, InputIterator2, InputIterator2, OutputIterator)
- template<typename InputIterator1, typename InputIterator2, typename_
          OutputIterator, typename StrictWeakCompare>
          OutputIterator thrust::set_symmetric_difference(InputIterator1, InputIterator1,_
          InputIterator2, InputIterator2, OutputIterator, StrictWeakCompare)
- template<typename InputIterator1, typename InputIterator2, typename_
          OutputIterator>
          OutputIterator thrust::set_symmetric_difference(InputIterator1, InputIterator1,_
          InputIterator2, InputIterator2, OutputIterator)
```

**Template Function `thrust::set_symmetric_difference(InputIterator1, InputIterator1, InputIterator2, InputIterator2, OutputIterator, StrictWeakCompare)`**

## Function Documentation

```
template<typename InputIterator1, typename InputIterator2, typename OutputIterator, typename StrictWeakCompare>
OutputIterator thrust::set_symmetric_difference(InputIterator1 first1, InputIterator1 last1, InputIterator2 first2, InputIterator2 last2, OutputIterator result, StrictWeakCompare comp)
```

`set_symmetric_difference` constructs a sorted range that is the set symmetric difference of the sorted ranges `[first1, last1]` and `[first2, last2]`. The return value is the end of the output range.

In the simplest case, `set_symmetric_difference` performs a set theoretic calculation: it constructs the union of the two sets  $A - B$  and  $B - A$ , where  $A$  and  $B$  are the two input ranges. That is, the output range contains a copy of every element that is contained in  $[first1, last1]$  but not  $[first2, last1]$ , and a copy of every element that is contained in  $[first2, last2]$  but not  $[first1, last1]$ . The general case is more complicated, because the input ranges may contain duplicate elements. The generalization is that if  $[first1, last1]$  contains  $m$  elements that are equivalent to each other and  $[first2, last1]$  contains  $n$  elements that are equivalent to them, then  $|m - n|$  of those elements shall be copied to the output range: the last  $m - n$  elements from  $[first1, last1]$  if  $m > n$ , and the last  $n - m$  of these elements from  $[first2, last2]$  if  $m < n$ .

This version of `set_union` compares elements using a function object `comp`.

The following code snippet demonstrates how to use `set_symmetric_difference` to compute the symmetric difference of two sets of integers sorted in descending order.

**Return** The end of the output range.

**Pre** The ranges [first1, last1) and [first2, last2) shall be sorted with respect to comp.

**Pre** The resulting range shall not overlap with either input range.

#### Parameters

- first1: The beginning of the first input range.
- last1: The end of the first input range.
- first2: The beginning of the second input range.
- last2: The end of the second input range.
- result: The beginning of the output range.
- comp: Comparison operator.

#### Template Parameters

- InputIterator1: is a model of [Input Iterator](#), InputIterator1 and InputIterator2 have the same value\_type, InputIterator1's value\_type is a model of [LessThan Comparable](#), the ordering on InputIterator1's value\_type is a strict weak ordering, as defined in the [LessThan Comparable](#) requirements, and InputIterator1's value\_type is convertible to a type in OutputIterator's set of value\_types.
- InputIterator2: is a model of [Input Iterator](#), InputIterator2 and InputIterator1 have the same value\_type, InputIterator2's value\_type is a model of [LessThan Comparable](#), the ordering on InputIterator2's value\_type is a strict weak ordering, as defined in the [LessThan Comparable](#) requirements, and InputIterator2's value\_type is convertible to a type in OutputIterator's set of value\_types.
- OutputIterator: is a model of [Output Iterator](#).

```
#include <thrust/set_operations.h>
...
int A1[6] = {7, 6, 4, 2, 2, 1, 0};
int A2[5] = {8, 5, 2, 1, 1};

int result[6];

int *result_end = thrust::set_symmetric_difference(A1, A1 + 6, A2, A2 + 5,
    ↵result);
// result = {8, 7, 6, 5, 4, 0}
```

**See** [http://www.sgi.com/tech/stl/set\\_symmetric\\_difference.html](http://www.sgi.com/tech/stl/set_symmetric_difference.html)

**See** [merge](#)

**See** [includes](#)

**See** [set\\_difference](#)

**See** [set\\_union](#)

**See** [set\\_intersection](#)

**See** [sort](#)

**See** [is\\_sorted](#)

**Template Function `thrust::set_symmetric_difference_by_key(const thrust::detail::execution_policy_base<DerivedPolicy>&, InputIterator1, InputIterator1, InputIterator2, InputIterator2, InputIterator3, InputIterator4, OutputIterator1, OutputIterator2)`**

- Defined in file `thrust_set_operations.h`

## Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::set_symmetric_difference_by_key`” with arguments (`const thrust::detail::execution_policy_base<DerivedPolicy>&, InputIterator1, InputIterator1, InputIterator2, InputIterator2, InputIterator3, InputIterator4, OutputIterator1, OutputIterator2`) in doxygen xml output for project “rocThrust” from directory: `./docBin/xml`. Potential matches:

```
- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2,
→ typename InputIterator3, typename InputIterator4, typename OutputIterator1,
→typename OutputIterator2, typename StrictWeakCompare>__host__ __device__
→thrust::pair<OutputIterator1,OutputIterator2> thrust::set_symmetric_difference_by_
→key(const thrust::detail::execution_policy_base< DerivedPolicy > &,
→InputIterator1, InputIterator1, InputIterator2, InputIterator2, InputIterator3,
→InputIterator4, OutputIterator1, OutputIterator2, StrictWeakCompare)
- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2,
→ typename InputIterator3, typename InputIterator4, typename OutputIterator1,
→typename OutputIterator2>__host__ __device__ thrust::pair<OutputIterator1,
→OutputIterator2> thrust::set_symmetric_difference_by_key(const
→thrust::detail::execution_policy_base< DerivedPolicy > &, InputIterator1,
→InputIterator1, InputIterator2, InputIterator2, InputIterator3, InputIterator4,
→OutputIterator1, OutputIterator2)
- template<typename InputIterator1, typename InputIterator2, typename
→InputIterator3, typename InputIterator4, typename OutputIterator1, typename
→OutputIterator2, typename StrictWeakCompare>
    thrust::pair<OutputIterator1, OutputIterator2> thrust::set_symmetric_difference_
→by_key(InputIterator1, InputIterator1, InputIterator2, InputIterator2,
→InputIterator3, InputIterator4, OutputIterator1, OutputIterator2,
→StrictWeakCompare)
- template<typename InputIterator1, typename InputIterator2, typename
→InputIterator3, typename InputIterator4, typename OutputIterator1, typename
→OutputIterator2>
    thrust::pair<OutputIterator1, OutputIterator2> thrust::set_symmetric_difference_
→by_key(InputIterator1, InputIterator1, InputIterator2, InputIterator2,
→InputIterator3, InputIterator4, OutputIterator1, OutputIterator2)
```

**Template Function `thrust::set_symmetric_difference_by_key(InputIterator1, InputIterator1, InputIterator2, InputIterator2, InputIterator3, InputIterator4, OutputIterator1, OutputIterator2)`**

## Function Documentation

```
template<typename InputIterator1, typename InputIterator2, typename InputIterator3, typename InputIterator4,
→ typename OutputIterator1, typename OutputIterator2>
```

```
thrust::pair<OutputIterator1, OutputIterator2> thrust::set_symmetric_difference_by_key(InputIterator1
    keys_first1,
    In-
    putIt-
    er-
    a-
    tor1
    keys_last1,
    In-
    putIt-
    er-
    a-
    tor2
    keys_first2,
    In-
    putIt-
    er-
    a-
    tor2
    keys_last2,
    In-
    putIt-
    er-
    a-
    tor3
    val-
    ues_first1,
    In-
    putIt-
    er-
    a-
    tor4
    val-
    ues_first2,
    Out-
    putIt-
    er-
    a-
    tor1
    keys_result,
    Out-
    putIt-
    er-
    a-
    tor2
    val-
    ues_result)
```

`set_symmetric_difference_by_key` performs a key-value symmetric difference operation from set theory. `set_difference_by_key` constructs a sorted range that is the symmetric difference of the sorted ranges `[keys_first1, keys_last1]` and `[keys_first2, keys_last2]`. Associated with each element from the input and output key ranges is a value element. The associated input value ranges need not be sorted.

In the simplest case, `set_symmetric_difference_by_key` performs a set theoretic calculation: it constructs the union of the two sets  $A - B$  and  $B - A$ , where  $A$  and  $B$  are the two input ranges. That is, the

output range contains a copy of every element that is contained in  $[\text{keys\_first1}, \text{keys\_last1}]$  but not  $[\text{keys\_first2}, \text{keys\_last1}]$ , and a copy of every element that is contained in  $[\text{keys\_first2}, \text{keys\_last2}]$  but not  $[\text{keys\_first1}, \text{keys\_last1}]$ . The general case is more complicated, because the input ranges may contain duplicate elements. The generalization is that if  $[\text{keys\_first1}, \text{keys\_last1}]$  contains  $m$  elements that are equivalent to each other and  $[\text{keys\_first2}, \text{keys\_last1}]$  contains  $n$  elements that are equivalent to them, then  $|m - n|$  of those elements shall be copied to the output range: the last  $m - n$  elements from  $[\text{keys\_first1}, \text{keys\_last1}]$  if  $m > n$ , and the last  $n - m$  of these elements from  $[\text{keys\_first2}, \text{keys\_last2}]$  if  $m < n$ .

Each time a key element is copied from  $[\text{keys\_first1}, \text{keys\_last1}]$  or  $[\text{keys\_first2}, \text{keys\_last2}]$  is copied to the keys output range, the corresponding value element is copied from the corresponding values input range (beginning at  $\text{values\_first1}$  or  $\text{values\_first2}$ ) to the values output range.

This version of `set_symmetric_difference_by_key` compares key elements using operator`<`.

The following code snippet demonstrates how to use `set_symmetric_difference_by_key` to compute the symmetric difference of two sets of integers sorted in ascending order with their values.

**Return** A pair  $p$  such that  $p.\text{first}$  is the end of the output range of keys, and such that  $p.\text{second}$  is the end of the output range of values.

**Pre** The ranges  $[\text{keys\_first1}, \text{keys\_last1}]$  and  $[\text{keys\_first2}, \text{keys\_last2}]$  shall be sorted with respect to operator`<`.

**Pre** The resulting ranges shall not overlap with any input range.

### Parameters

- `keys_first1`: The beginning of the first input range of keys.
- `keys_last1`: The end of the first input range of keys.
- `keys_first2`: The beginning of the second input range of keys.
- `keys_last2`: The end of the second input range of keys.
- `values_first1`: The beginning of the first input range of values.
- `values_first2`: The beginning of the first input range of values.
- `keys_result`: The beginning of the output range of keys.
- `values_result`: The beginning of the output range of values.

### Template Parameters

- `InputIterator1`: is a model of `Input Iterator`, `InputIterator1` and `InputIterator2` have the same `value_type`, `InputIterator1`'s `value_type` is a model of `LessThan Comparable`, the ordering on `InputIterator1`'s `value_type` is a strict weak ordering, as defined in the `LessThan Comparable` requirements, and `InputIterator1`'s `value_type` is convertible to a type in `OutputIterator`'s set of `value_types`.
- `InputIterator2`: is a model of `Input Iterator`, `InputIterator2` and `InputIterator1` have the same `value_type`, `InputIterator2`'s `value_type` is a model of `LessThan Comparable`, the ordering on `InputIterator2`'s `value_type` is a strict weak ordering, as defined in the `LessThan Comparable` requirements, and `InputIterator2`'s `value_type` is convertible to a type in `OutputIterator`'s set of `value_types`.
- `InputIterator3`: is a model of `Input Iterator`, and `InputIterator3`'s `value_type` is convertible to a type in `OutputIterator2`'s set of `value_types`.
- `InputIterator4`: is a model of `Input Iterator`, and `InputIterator4`'s `value_type` is convertible to a type in `OutputIterator2`'s set of `value_types`.

- `OutputIterator1`: is a model of Output Iterator.
- `OutputIterator2`: is a model of Output Iterator.

```
#include <thrust/set_operations.h>
...
int A_keys[6] = {0, 1, 2, 2, 4, 6, 7};
int A_vals[6] = {0, 0, 0, 0, 0, 0};

int B_keys[5] = {1, 1, 2, 5, 8};
int B_vals[5] = {1, 1, 1, 1, 1};

int keys_result[6];
int vals_result[6];

thrust::pair<int*,int*> end = thrust::set_symmetric_difference_by_key(A_keys, A_
→keys + 6, B_keys, B_keys + 5, A_vals, B_vals, keys_result, vals_result);
// keys_result is now {0, 4, 5, 6, 7, 8}
// vals_result is now {0, 0, 1, 0, 0, 1}
```

**See** `set_union_by_key`

**See** `set_intersection_by_key`

**See** `set_difference_by_key`

**See** `sort_by_key`

**See** `is_sorted`

**Template Function** `thrust::set_symmetric_difference_by_key(const thrust::detail::execution_policy_base<DerivedPolicy>&, InputIterator1, InputIterator1, InputIterator2, InputIterator2, InputIterator3, InputIterator4, OutputIterator1, OutputIterator2, StrictWeakCompare)`

## Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::set_symmetric_difference_by_key`” with arguments (`const thrust::detail::execution_policy_base<DerivedPolicy>&, InputIterator1, InputIterator1, InputIterator2, InputIterator2, InputIterator3, InputIterator4, OutputIterator1, OutputIterator2, StrictWeakCompare`) in doxygen xml output for project “rocThrust” from directory: ./docBin/xml. Potential matches:

```
- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2,
→ typename InputIterator3, typename InputIterator4, typename OutputIterator1,
→typename OutputIterator2, typename StrictWeakCompare> __host__ __device__
→thrust::pair<OutputIterator1,OutputIterator2> thrust::set_symmetric_difference_by_
→key(const thrust::detail::execution_policy_base< DerivedPolicy > &,
→InputIterator1, InputIterator1, InputIterator2, InputIterator2, InputIterator3,
→InputIterator4, OutputIterator2, StrictWeakCompare)
- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2,
→ typename InputIterator3, typename InputIterator4, typename OutputIterator1,
→typename OutputIterator2> __host__ __device__ thrust::pair<OutputIterator1,
→OutputIterator2> thrust::set_symmetric_difference_by_key(const
→thrust::detail::execution_policy_base< DerivedPolicy > &, InputIterator1,
→InputIterator1, InputIterator2, InputIterator2, InputIterator3, InputIterator4,
→OutputIterator1, OutputIterator2)
- template<typename InputIterator1, typename InputIterator2, typename
→InputIterators, typename InputIterator4, typename OutputIterator1, typename
→OutputIterator2, typename StrictWeakCompare>
```

**1.3. Full API** `pair<OutputIterator1, OutputIterator2> thrust::set_symmetric_difference_by_key(InputIterator1, InputIterator1, InputIterator2, InputIterator2, InputIterator3, InputIterator4, OutputIterator1, OutputIterator2, StrictWeakCompare)` **285**

```
- template<typename InputIterator1, typename InputIterator2, typename
```

**Template Function `thrust::set_symmetric_difference_by_key`(`InputIterator1`, `InputIterator1`, `InputIterator2`, `InputIterator2`, `InputIterator3`, `InputIterator4`, `OutputIterator1`, `OutputIterator2`, `StrictWeakCompare`)**

#### Function Documentation

template<typename **InputIterator1**, typename **InputIterator2**, typename **InputIterator3**, typename **InputIterator4**, typename **OutputIterator1**, typename **OutputIterator2**, typename **StrictWeakCompare**>

```
thrust::pair<OutputIterator1, OutputIterator2> thrust::set_symmetric_difference_by_key(InputIterator1
    keys_first1,
    In-
    putIt-
    er-
    a-
    tor1
    keys_last1,
    In-
    putIt-
    er-
    a-
    tor2
    keys_first2,
    In-
    putIt-
    er-
    a-
    tor2
    keys_last2,
    In-
    putIt-
    er-
    a-
    tor3
    val-
    ues_first1,
    In-
    putIt-
    er-
    a-
    tor4
    val-
    ues_first2,
    Out-
    putIt-
    er-
    a-
    tor1
    keys_result,
    Out-
    putIt-
    er-
    a-
    tor2
    val-
    ues_result,
    StrictWeak-
    Com-
    pare
    comp)
```

`set_symmetric_difference_by_key` performs a key-value symmetric difference operation from set theory. `set_difference_by_key` constructs a sorted range that is the symmetric difference of the sorted ranges `[keys_first1, keys_last1)` and `[keys_first2, keys_last2)`. Associated with each

element from the input and output key ranges is a value element. The associated input value ranges need not be sorted.

In the simplest case, `set_symmetric_difference_by_key` performs a set theoretic calculation: it constructs the union of the two sets  $A - B$  and  $B - A$ , where  $A$  and  $B$  are the two input ranges. That is, the output range contains a copy of every element that is contained in  $[keys\_first1, keys\_last1]$  but not  $[keys\_first2, keys\_last1]$ , and a copy of every element that is contained in  $[keys\_first2, keys\_last2]$  but not  $[keys\_first1, keys\_last1]$ . The general case is more complicated, because the input ranges may contain duplicate elements. The generalization is that if  $[keys\_first1, keys\_last1]$  contains  $m$  elements that are equivalent to each other and  $[keys\_first2, keys\_last1]$  contains  $n$  elements that are equivalent to them, then  $|m - n|$  of those elements shall be copied to the output range: the last  $m - n$  elements from  $[keys\_first1, keys\_last1]$  if  $m > n$ , and the last  $n - m$  of these elements from  $[keys\_first2, keys\_last2]$  if  $m < n$ .

Each time a key element is copied from  $[keys\_first1, keys\_last1]$  or  $[keys\_first2, keys\_last2]$  is copied to the keys output range, the corresponding value element is copied from the corresponding values input range (beginning at `values_first1` or `values_first2`) to the values output range.

This version of `set_symmetric_difference_by_key` compares key elements using a function object `comp`.

The following code snippet demonstrates how to use `set_symmetric_difference_by_key` to compute the symmetric difference of two sets of integers sorted in descending order with their values.

**Return** A pair  $p$  such that  $p.first$  is the end of the output range of keys, and such that  $p.second$  is the end of the output range of values.

**Pre** The ranges  $[keys\_first1, keys\_last1]$  and  $[keys\_first2, keys\_last2]$  shall be sorted with respect to `comp`.

**Pre** The resulting ranges shall not overlap with any input range.

### Parameters

- `keys_first1`: The beginning of the first input range of keys.
- `keys_last1`: The end of the first input range of keys.
- `keys_first2`: The beginning of the second input range of keys.
- `keys_last2`: The end of the second input range of keys.
- `values_first1`: The beginning of the first input range of values.
- `values_first2`: The beginning of the first input range of values.
- `keys_result`: The beginning of the output range of keys.
- `values_result`: The beginning of the output range of values.
- `comp`: Comparison operator.

### Template Parameters

- `InputIterator1`: is a model of `Input Iterator`, `InputIterator1` and `InputIterator2` have the same `value_type`, `InputIterator1`'s `value_type` is a model of `LessThan Comparable`, the ordering on `InputIterator1`'s `value_type` is a strict weak ordering, as defined in the `LessThan Comparable` requirements, and `InputIterator1`'s `value_type` is convertible to a type in `OutputIterator`'s set of `value_types`.
- `InputIterator2`: is a model of `Input Iterator`, `InputIterator2` and `InputIterator1` have the same `value_type`, `InputIterator2`'s `value_type` is a model of `LessThan Comparable`, the ordering on `InputIterator2`'s `value_type` is a strict weak ordering, as defined in the `LessThan Comparable` requirements, and `InputIterator2`'s `value_type` is convertible to a type in `OutputIterator`'s set of `value_types`.

in the `LessThan Comparable` requirements, and `InputIterator2`'s `value_type` is convertible to a type in `OutputIterator`'s set of `value_types`.

- `InputIterator3`: is a model of `Input Iterator`, and `InputIterator3`'s `value_type` is convertible to a type in `OutputIterator2`'s set of `value_types`.
- `InputIterator4`: is a model of `Input Iterator`, and `InputIterator4`'s `value_type` is convertible to a type in `OutputIterator2`'s set of `value_types`.
- `OutputIterator1`: is a model of `Output Iterator`.
- `OutputIterator2`: is a model of `Output Iterator`.
- `StrictWeakCompare`: is a model of `Strict Weak Ordering`.

```
#include <thrust/set_operations.h>
#include <thrust/functional.h>
...
int A_keys[6] = {7, 6, 4, 2, 2, 1, 0};
int A_vals[6] = {0, 0, 0, 0, 0, 0, 0};

int B_keys[5] = {8, 5, 2, 1, 1};
int B_vals[5] = {1, 1, 1, 1, 1};

int keys_result[6];
int vals_result[6];

thrust::pair<int*, int*> end = thrust::set_symmetric_difference_by_key(A_keys, A_
    ↪keys + 6, B_keys, B_keys + 5, A_vals, B_vals, keys_result, vals_result);
// keys_result is now {8, 7, 6, 5, 4, 0}
// vals_result is now {1, 0, 0, 1, 0, 0}
```

**See** `set_union_by_key`

**See** `set_intersection_by_key`

**See** `set_difference_by_key`

**See** `sort_by_key`

**See** `is_sorted`

**Template Function** `thrust::set_union(const thrust::detail::execution_policy_base<DerivedPolicy>&, InputIterator1, InputIterator1, InputIterator2, InputIterator2, OutputIterator)`

- Defined in file `thrust_set_operations.h`

## Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::set_union`” with arguments `(const thrust::detail::execution_policy_base<DerivedPolicy>&, InputIterator1, InputIterator1, InputIterator2, InputIterator2, OutputIterator)` in doxygen xml output for project “rocThrust” from directory: `./docBin/xml`. Potential matches:

```
- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2,
         typename OutputIterator, typename StrictWeakCompare> __host__ __device__
OutputIterator thrust::set_union(const thrust::detail::execution_policy_base<
    DerivedPolicy > &, InputIterator1, InputIterator1, InputIterator2, InputIterator2,
    OutputIterator, StrictWeakCompare)
- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2,
         typename OutputIterator> __host__ __device__ OutputIterator thrust::set_
union(const thrust::detail::execution_policy_base< DerivedPolicy > &,
InputIterator1, InputIterator1, InputIterator2, InputIterator2, OutputIterator)
- template<typename InputIterator1, typename InputIterator2, typename_
OutputIterator, typename StrictWeakCompare>
OutputIterator thrust::set_union(InputIterator1, InputIterator1, InputIterator2,
InputIterator2, OutputIterator, StrictWeakCompare)
- template<typename InputIterator1, typename InputIterator2, typename_
OutputIterator>
OutputIterator thrust::set_union(InputIterator1, InputIterator1, InputIterator2,
InputIterator2, OutputIterator)
```

## Template Function `thrust::set_union(InputIterator1, InputIterator1, InputIterator2, InputIterator2, OutputIterator)`

### Function Documentation

```
template<typename InputIterator1, typename InputIterator2, typename OutputIterator>
OutputIterator thrust::set_union(InputIterator1 first1, InputIterator1 last1, InputIterator2 first2, In-
putIterator2 last2, OutputIterator result)
set_union constructs a sorted range that is the union of the sorted ranges [first1, last1) and
[first2, last2). The return value is the end of the output range.
```

In the simplest case, `set_union` performs the “union” operation from set theory: the output range contains a copy of every element that is contained in  $[first_1, last_1]$ ,  $[first_2, last_1]$ , or both. The general case is more complicated, because the input ranges may contain duplicate elements. The generalization is that if  $[first_1, last_1]$  contains  $m$  elements that are equivalent to each other and if  $[first_2, last_2]$  contains  $n$  elements that are equivalent to them, then all  $m$  elements from the first range shall be copied to the output range, in order, and then  $\max(n - m, 0)$  elements from the second range shall be copied to the output, in order.

This version of `set_union` compares elements using operator`<`.

The following code snippet demonstrates how to use `set_union` to compute the union of two sets of integers sorted in ascending order.

**Return** The end of the output range.

**Pre** The ranges  $[first_1, last_1]$  and  $[first_2, last_2]$  shall be sorted with respect to operator`<`.

**Pre** The resulting range shall not overlap with either input range.

### Parameters

- `first1`: The beginning of the first input range.
- `last1`: The end of the first input range.
- `first2`: The beginning of the second input range.
- `last2`: The end of the second input range.

- **result:** The beginning of the output range.

### Template Parameters

- **InputIterator1:** is a model of [Input Iterator](#), **InputIterator1** and **InputIterator2** have the same **value\_type**, **InputIterator1**'s **value\_type** is a model of [LessThan Comparable](#), the ordering on **InputIterator1**'s **value\_type** is a strict weak ordering, as defined in the [LessThan Comparable requirements](#), and **InputIterator1**'s **value\_type** is convertible to a type in **OutputIterator**'s set of **value\_types**.
- **InputIterator2:** is a model of [Input Iterator](#), **InputIterator2** and **InputIterator1** have the same **value\_type**, **InputIterator2**'s **value\_type** is a model of [LessThan Comparable](#), the ordering on **InputIterator2**'s **value\_type** is a strict weak ordering, as defined in the [LessThan Comparable requirements](#), and **InputIterator2**'s **value\_type** is convertible to a type in **OutputIterator**'s set of **value\_types**.
- **OutputIterator:** is a model of [Output Iterator](#).

```
#include <thrust/set_operations.h>
...
int A1[7] = {0, 2, 4, 6, 8, 10, 12};
int A2[5] = {1, 3, 5, 7, 9};

int result[11];

int *result_end = thrust::set_union(A1, A1 + 7, A2, A2 + 5, result);
// result = {0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 12}
```

**See** [http://www.sgi.com/tech/stl/set\\_union.html](http://www.sgi.com/tech/stl/set_union.html)

**See** [merge](#)

**See** [includes](#)

**See** [set\\_union](#)

**See** [set\\_intersection](#)

**See** [set\\_symmetric\\_difference](#)

**See** [sort](#)

**See** [is\\_sorted](#)

**Template Function** `thrust::set_union(const thrust::detail::execution_policy_base<DerivedPolicy>&, InputIterator1, InputIterator1, InputIterator2, InputIterator2, OutputIterator, StrictWeakCompare)`

### Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::set_union`” with arguments (`const thrust::detail::execution_policy_base<DerivedPolicy>&`, `InputIterator1`, `InputIterator1`, `InputIterator2`, `InputIterator2`, `OutputIterator`, `StrictWeakCompare`) in doxygen xml output for project “rocThrust” from directory: `./docBin/xml`. Potential matches:

```
- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2,
         typename OutputIterator, typename StrictWeakCompare> __host__ __device__
         OutputIterator thrust::set_union(const thrust::detail::execution_policy_base<
         DerivedPolicy > &, InputIterator1, InputIterator1, InputIterator2, InputIterator2,
         OutputIterator, StrictWeakCompare)
- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2,
         typename OutputIterator> __host__ __device__ OutputIterator thrust::set_
         union(const thrust::detail::execution_policy_base< DerivedPolicy > &,
         InputIterator1, InputIterator1, InputIterator2, InputIterator2, OutputIterator)
- template<typename InputIterator1, typename InputIterator2, typename_
         OutputIterator, typename StrictWeakCompare>
         OutputIterator thrust::set_union(InputIterator1, InputIterator1, InputIterator2,
         InputIterator2, OutputIterator, StrictWeakCompare)
- template<typename InputIterator1, typename InputIterator2, typename_
         OutputIterator>
         OutputIterator thrust::set_union(InputIterator1, InputIterator1, InputIterator2,
         InputIterator2, OutputIterator)
```

## Template Function `thrust::set_union(InputIterator1, InputIterator1, InputIterator2, InputIterator2, OutputIterator, StrictWeakCompare)`

### Function Documentation

```
template<typename InputIterator1, typename InputIterator2, typename OutputIterator, typename StrictWeakCompare>
OutputIterator thrust::set_union(InputIterator1 first1, InputIterator1 last1, InputIterator2 first2, In-
```

```
putIterator2 last2, OutputIterator result, StrictWeakCompare comp)
set_union constructs a sorted range that is the union of the sorted ranges [first1, last1) and
[first2, last2). The return value is the end of the output range.
```

In the simplest case, set\_union performs the “union” operation from set theory: the output range contains a copy of every element that is contained in [first1, last1), [first2, last1), or both. The general case is more complicated, because the input ranges may contain duplicate elements. The generalization is that if [first1, last1) contains m elements that are equivalent to each other and if [first2, last2) contains n elements that are equivalent to them, then all m elements from the first range shall be copied to the output range, in order, and then max(n - m, 0) elements from the second range shall be copied to the output, in order.

This version of set\_union compares elements using a function object comp.

The following code snippet demonstrates how to use set\_union to compute the union of two sets of integers sorted in ascending order.

**Return** The end of the output range.

**Pre** The ranges [first1, last1) and [first2, last2) shall be sorted with respect to comp.

**Pre** The resulting range shall not overlap with either input range.

### Parameters

- first1: The beginning of the first input range.
- last1: The end of the first input range.
- first2: The beginning of the second input range.
- last2: The end of the second input range.

- **result:** The beginning of the output range.
- **comp:** Comparison operator.

### Template Parameters

- **InputIterator1:** is a model of [Input Iterator](#), **InputIterator1**'s `value_type` is convertible to [StrictWeakCompare](#)'s `first_argument_type`. and **InputIterator1**'s `value_type` is convertible to a type in [OutputIterator](#)'s set of `value_types`.
- **InputIterator2:** is a model of [Input Iterator](#), **InputIterator2**'s `value_type` is convertible to [StrictWeakCompare](#)'s `second_argument_type`. and **InputIterator2**'s `value_type` is convertible to a type in [OutputIterator](#)'s set of `value_types`.
- **OutputIterator:** is a model of [Output Iterator](#).
- **StrictWeakCompare:** is a model of [Strict Weak Ordering](#).

```
#include <thrust/set_operations.h>
#include <thrust/functional.h>
...
int A1[7] = {12, 10, 8, 6, 4, 2, 0};
int A2[5] = {9, 7, 5, 3, 1};

int result[11];

int *result_end = thrust::set_union(A1, A1 + 7, A2, A2 + 5, result,
                                     thrust::greater<int>());
// result = {12, 10, 9, 8, 7, 6, 5, 4, 3, 2, 1, 0}
```

**See** [http://www.sgi.com/tech/stl/set\\_union.html](http://www.sgi.com/tech/stl/set_union.html)

**See** [merge](#)

**See** [includes](#)

**See** [set\\_union](#)

**See** [set\\_intersection](#)

**See** [set\\_symmetric\\_difference](#)

**See** [sort](#)

**See** [is\\_sorted](#)

**Template Function** `thrust::set_union_by_key(const thrust::detail::execution_policy_base<DerivedPolicy>&, InputIterator1, InputIterator1, InputIterator2, InputIterator2, InputIterator3, InputIterator4, OutputIterator1, OutputIterator2)`

- Defined in file `thrust_set_operations.h`

### Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::set_union_by_key`” with arguments (`const thrust::detail::execution_policy_base<DerivedPolicy>&`, `InputIterator1`, `InputIterator1`, `InputIterator2`, `InputIterator2`, `InputIterator3`, `InputIterator4`, `OutputIterator1`, `OutputIterator2`) in doxygen xml output for project “rocThrust” from directory: `./docBin/xml`. Potential matches:

```

- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2,
  ~ typename InputIterator3, typename InputIterator4, typename OutputIterator1,
  ~typename OutputIterator2, typename StrictWeakCompare> __host__ __device__
  ~thrust::pair<OutputIterator1,OutputIterator2> thrust::set_union_by_key(const
  ~thrust::detail::execution_policy_base< DerivedPolicy > &, InputIterator1,
  ~InputIterator1, InputIterator2, InputIterator2, InputIterator3, InputIterator4,
  ~OutputIterator1, OutputIterator2, StrictWeakCompare)
- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2,
  ~typename InputIterator3, typename InputIterator4, typename OutputIterator1, typename
  ~OutputIterator2, typename StrictWeakCompare>
  thrust::pair<OutputIterator1, OutputIterator2> thrust::set_union_by_key(
  ~base< DerivedPolicy > &, InputIterator1, InputIterator1, InputIterator2,
  ~InputIterator2, InputIterator3, InputIterator4, OutputIterator1, OutputIterator2)
- template<typename InputIterator1, typename InputIterator2, typename
  ~InputIterator3, typename InputIterator4, typename OutputIterator1, typename
  ~OutputIterator2, typename StrictWeakCompare>
  thrust::pair<OutputIterator1, OutputIterator2> thrust::set_union_by_
  ~key(InputIterator1, InputIterator1, InputIterator2, InputIterator2,
  ~InputIterator3, InputIterator4, OutputIterator1, OutputIterator2,
  ~StrictWeakCompare)
- template<typename InputIterator1, typename InputIterator2, typename
  ~InputIterator3, typename InputIterator4, typename OutputIterator1, typename
  ~OutputIterator2>
  thrust::pair<OutputIterator1, OutputIterator2> thrust::set_union_by_
  ~key(InputIterator1, InputIterator1, InputIterator2, InputIterator2,
  ~InputIterator3, InputIterator4, OutputIterator1, OutputIterator2)

```

## Template Function `thrust::set_union_by_key(InputIterator1, InputIterator1, InputIterator2, InputIterator2, InputIterator3, InputIterator4, OutputIterator1, OutputIterator2)`

### Function Documentation

```

template<typename InputIterator1, typename InputIterator2, typename InputIterator3, typename InputIterator4,
thrust::pair<OutputIterator1, OutputIterator2> thrust::set_union_by_key(InputIterator1 keys_first1,
  InputIterator1 keys_last1,
  InputIterator2 keys_first2,
  InputIterator2 keys_last2,
  InputIterator3 values_first1, InputIterator4
  values_first2, OutputIterator1 keys_result,
  OutputIterator2 values_result)

```

`set_union_by_key` performs a key-value union operation from set theory. `set_union_by_key` constructs a sorted range that is the union of the sorted ranges  $[keys\_first1, keys\_last1]$  and  $[keys\_first2, keys\_last2]$ . Associated with each element from the input and output key ranges is a value element. The associated input value ranges need not be sorted.

In the simplest case, `set_union_by_key` performs the “union” operation from set theory: the output range contains a copy of every element that is contained in  $[keys\_first1, keys\_last1]$ ,  $[keys\_first2, keys\_last1]$ , or both. The general case is more complicated, because the input ranges may contain duplicate elements. The generalization is that if  $[keys\_first1, keys\_last1]$  contains  $m$  elements that are equivalent to each other and if  $[keys\_first2, keys\_last2]$  contains  $n$  elements that are equivalent to

them, then all  $m$  elements from the first range shall be copied to the output range, in order, and then  $\max(n - m, 0)$  elements from the second range shall be copied to the output, in order.

Each time a key element is copied from `[keys_first1, keys_last1]` or `[keys_first2, keys_last2]` is copied to the keys output range, the corresponding value element is copied from the corresponding values input range (beginning at `values_first1` or `values_first2`) to the values output range.

This version of `set_union_by_key` compares key elements using `operator<`.

The following code snippet demonstrates how to use `set_symmetric_difference_by_key` to compute the symmetric difference of two sets of integers sorted in ascending order with their values.

**Return** A pair `p` such that `p.first` is the end of the output range of keys, and such that `p.second` is the end of the output range of values.

**Pre** The ranges `[keys_first1, keys_last1]` and `[keys_first2, keys_last2]` shall be sorted with respect to `operator<`.

**Pre** The resulting ranges shall not overlap with any input range.

### Parameters

- `keys_first1`: The beginning of the first input range of keys.
- `keys_last1`: The end of the first input range of keys.
- `keys_first2`: The beginning of the second input range of keys.
- `keys_last2`: The end of the second input range of keys.
- `values_first1`: The beginning of the first input range of values.
- `values_first2`: The beginning of the first input range of values.
- `keys_result`: The beginning of the output range of keys.
- `values_result`: The beginning of the output range of values.

### Template Parameters

- `InputIterator1`: is a model of [Input Iterator](#), `InputIterator1` and `InputIterator2` have the same `value_type`, `InputIterator1`'s `value_type` is a model of [LessThan Comparable](#), the ordering on `InputIterator1`'s `value_type` is a strict weak ordering, as defined in the [LessThan Comparable](#) requirements, and `InputIterator1`'s `value_type` is convertible to a type in `OutputIterator`'s set of `value_types`.
- `InputIterator2`: is a model of [Input Iterator](#), `InputIterator2` and `InputIterator1` have the same `value_type`, `InputIterator2`'s `value_type` is a model of [LessThan Comparable](#), the ordering on `InputIterator2`'s `value_type` is a strict weak ordering, as defined in the [LessThan Comparable](#) requirements, and `InputIterator2`'s `value_type` is convertible to a type in `OutputIterator`'s set of `value_types`.
- `InputIterator3`: is a model of [Input Iterator](#), and `InputIterator3`'s `value_type` is convertible to a type in `OutputIterator2`'s set of `value_types`.
- `InputIterator4`: is a model of [Input Iterator](#), and `InputIterator4`'s `value_type` is convertible to a type in `OutputIterator2`'s set of `value_types`.
- `OutputIterator1`: is a model of [Output Iterator](#).
- `OutputIterator2`: is a model of [Output Iterator](#).

```
#include <thrust/set_operations.h>
...
int A_keys[6] = {0, 2, 4, 6, 8, 10, 12};
int A_vals[6] = {0, 0, 0, 0, 0, 0};

int B_keys[5] = {1, 3, 5, 7, 9};
int B_vals[5] = {1, 1, 1, 1, 1};

int keys_result[11];
int vals_result[11];

thrust::pair<int*, int*> end = thrust::set_symmetric_difference_by_key(A_keys, A_
→keys + 6, B_keys, B_keys + 5, A_vals, B_vals, keys_result, vals_result);
// keys_result is now {0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 12}
// vals_result is now {0, 1, 0, 1, 0, 1, 0, 1, 0, 1, 0}
```

**See** `set_symmetric_difference_by_key`

**See** `set_intersection_by_key`

**See** `set_difference_by_key`

**See** `sort_by_key`

**See** `is_sorted`

**Template Function** `thrust::set_union_by_key(const thrust::detail::execution_policy_base<DerivedPolicy>&, InputIterator1, InputIterator1, InputIterator2, InputIterator2, InputIterator3, InputIterator4, OutputIterator1, OutputIterator2, StrictWeakCompare)`

## Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::set_union_by_key`” with arguments (`const thrust::detail::execution_policy_base<DerivedPolicy>&`, `InputIterator1`, `InputIterator1`, `InputIterator2`, `InputIterator2`, `InputIterator3`, `InputIterator4`, `OutputIterator1`, `OutputIterator2`, `StrictWeakCompare`) in doxygen xml output for project “rocThrust” from directory: `./docBin/xml`. Potential matches:

```
- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2,
→ typename InputIterator3, typename InputIterator4, typename OutputIterator1,
→typename OutputIterator2, typename StrictWeakCompare> __host__ __device__ __
→thrust::pair<OutputIterator1,OutputIterator2> thrust::set_union_by_key(const
→thrust::detail::execution_policy_base< DerivedPolicy > &, InputIterator1,
→InputIterator1, InputIterator2, InputIterator2, InputIterator3, InputIterator4,
→OutputIterator1, OutputIterator2, StrictWeakCompare)
- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2,
→ typename InputIterator3, typename InputIterator4, typename OutputIterator1,
→typename OutputIterator2> __host__ __device__ thrust::pair<OutputIterator1,
→OutputIterator2> thrust::set_union_by_key(const thrust::detail::execution_policy_
→base< DerivedPolicy > &, InputIterator1, InputIterator1, InputIterator2,
→InputIterator2, InputIterator3, InputIterator4, OutputIterator1, OutputIterator2)
- template<typename InputIterator1, typename InputIterator2, typename_
→InputIterator3, typename InputIterator4, typename OutputIterator1, typename_
→OutputIterator2, typename StrictWeakCompare>
    thrust::pair<OutputIterator1, OutputIterator2> thrust::set_union_by_
→key(InputIterator1, InputIterator1, InputIterator2, InputIterator2,
→InputIterator3, InputIterator4, OutputIterator1, OutputIterator2,
→StrictWeakCompare)
- template<typename InputIterator1, typename InputIterator2, typename_
→InputIterator3, typename InputIterator4, typename OutputIterator1, typename_
→OutputIterator2>
    thrust::pair<OutputIterator1, OutputIterator2> thrust::set_union_by_
→key(InputIterator1, InputIterator1, InputIterator2, InputIterator2,
→InputIterator3, InputIterator4, OutputIterator1, OutputIterator2)
```

## Template Function `thrust::set_union_by_key(InputIterator1, InputIterator1, InputIterator2, InputIterator2, InputIterator3, InputIterator4, OutputIterator1, OutputIterator2, StrictWeakCompare)`

### Function Documentation

```
template<typename InputIterator1, typename InputIterator2, typename InputIterator3, typename InputIterator4, typename OutputIterator1, typename OutputIterator2OutputIterator1, OutputIterator2> thrust::set_union_by_key(InputIterator1 keys_first1,  
                                         InputIterator1 keys_last1,  
                                         InputIterator2 keys_first2,  
                                         InputIterator2 keys_last2,  
                                         InputIterator3      values_first1, InputIterator4  
                                         values_first2,   OutputIterator1      keys_result,  
                                         OutputIterator2      values_result,   StrictWeak-  
                                         Compare comp)
```

`set_union_by_key` performs a key-value union operation from set theory. `set_union_by_key` constructs a sorted range that is the union of the sorted ranges `[keys_first1, keys_last1]` and `[keys_first2, keys_last2]`. Associated with each element from the input and output key ranges is a value element. The associated input value ranges need not be sorted.

In the simplest case, `set_union_by_key` performs the “union” operation from set theory: the output range contains a copy of every element that is contained in `[keys_first1, keys_last1]`, `[keys_first2, keys_last1]`, or both. The general case is more complicated, because the input ranges may contain duplicate elements. The generalization is that if `[keys_first1, keys_last1]` contains  $m$  elements that are equivalent to each other and if `[keys_first2, keys_last2]` contains  $n$  elements that are equivalent to them, then all  $m$  elements from the first range shall be copied to the output range, in order, and then  $\max(n - m, 0)$  elements from the second range shall be copied to the output, in order.

Each time a key element is copied from `[keys_first1, keys_last1]` or `[keys_first2, keys_last2]` is copied to the keys output range, the corresponding value element is copied from the corresponding values input range (beginning at `values_first1` or `values_first2`) to the values output range.

This version of `set_union_by_key` compares key elements using a function object `comp`.

The following code snippet demonstrates how to use `set_symmetric_difference_by_key` to compute the symmetric difference of two sets of integers sorted in descending order with their values.

**Return** A pair `p` such that `p.first` is the end of the output range of keys, and such that `p.second` is the end of the output range of values.

**Pre** The ranges `[keys_first1, keys_last1]` and `[keys_first2, keys_last2]` shall be sorted with respect to `comp`.

**Pre** The resulting ranges shall not overlap with any input range.

### Parameters

- `keys_first1`: The beginning of the first input range of keys.
- `keys_last1`: The end of the first input range of keys.
- `keys_first2`: The beginning of the second input range of keys.

- `keys_last2`: The end of the second input range of keys.
- `values_first1`: The beginning of the first input range of values.
- `values_first2`: The beginning of the first input range of values.
- `keys_result`: The beginning of the output range of keys.
- `values_result`: The beginning of the output range of values.
- `comp`: Comparison operator.

### Template Parameters

- `InputIterator1`: is a model of [Input Iterator](#), `InputIterator1` and `InputIterator2` have the same `value_type`, `InputIterator1`'s `value_type` is a model of [LessThan Comparable](#), the ordering on `InputIterator1`'s `value_type` is a strict weak ordering, as defined in the [LessThan Comparable requirements](#), and `InputIterator1`'s `value_type` is convertible to a type in `OutputIterator`'s set of `value_types`.
- `InputIterator2`: is a model of [Input Iterator](#), `InputIterator2` and `InputIterator1` have the same `value_type`, `InputIterator2`'s `value_type` is a model of [LessThan Comparable](#), the ordering on `InputIterator2`'s `value_type` is a strict weak ordering, as defined in the [LessThan Comparable requirements](#), and `InputIterator2`'s `value_type` is convertible to a type in `OutputIterator`'s set of `value_types`.
- `InputIterator3`: is a model of [Input Iterator](#), and `InputIterator3`'s `value_type` is convertible to a type in `OutputIterator2`'s set of `value_types`.
- `InputIterator4`: is a model of [Input Iterator](#), and `InputIterator4`'s `value_type` is convertible to a type in `OutputIterator2`'s set of `value_types`.
- `OutputIterator1`: is a model of [Output Iterator](#).
- `OutputIterator2`: is a model of [Output Iterator](#).
- `StrictWeakCompare`: is a model of [Strict Weak Ordering](#).

```
#include <thrust/set_operations.h>
#include <thrust/functional.h>
...
int A_keys[6] = {12, 10, 8, 6, 4, 2, 0};
int A_vals[6] = { 0, 0, 0, 0, 0, 0, 0};

int B_keys[5] = {9, 7, 5, 3, 1};
int B_vals[5] = {1, 1, 1, 1, 1};

int keys_result[11];
int vals_result[11];

thrust::pair<int*,int*> end = thrust::set_symmetric_difference_by_key(A_keys, A_
    ↵keys + 6, B_keys, B_keys + 5, A_vals, B_vals, keys_result, vals_result, ↵
    ↵thrust::greater<int>());
// keys_result is now {12, 10, 9, 8, 7, 6, 5, 4, 3, 2, 1, 0}
// vals_result is now { 0, 1, 1, 0, 1, 0, 1, 0, 1, 0, 0}
```

**See** `set_symmetric_difference_by_key`

**See** `set_intersection_by_key`

**See** `set_difference_by_key`

**See** `sort_by_key`

See `is_sorted`

### Template Function `thrust::sin`

- Defined in file `thrust_complex.h`

#### Function Documentation

```
template<typename T> __host__ __device__ complex<T> thrust::sin(const complex < T > & z)
    Returns the complex sine of a complex number.
```

#### Parameters

- `z`: The complex argument.

### Template Function `thrust::sinh`

- Defined in file `thrust_complex.h`

#### Function Documentation

```
template<typename T> __host__ __device__ complex<T> thrust::sinh(const complex < T > & z)
    Returns the complex hyperbolic sine of a complex number.
```

#### Parameters

- `z`: The complex argument.

### Template Function `thrust::sort`(`const thrust::detail::execution_policy_base<DerivedPolicy>&, RandomAccessIterator, RandomAccessIterator`)

- Defined in file `thrust_sort.h`

#### Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::sort`” with arguments (`const thrust::detail::execution_policy_base<DerivedPolicy>&`, `RandomAccessIterator`, `RandomAccessIterator`) in doxygen xml output for project “rocThrust” from directory: `./docBin/xml`. Potential matches:

```
- template<typename DerivedPolicy, typename RandomAccessIterator, typename StrictWeakOrdering> __host__ __device__ void thrust::sort(const thrust::detail::execution_policy_base< DerivedPolicy > &, RandomAccessIterator, RandomAccessIterator, StrictWeakOrdering)
- template<typename DerivedPolicy, typename RandomAccessIterator> __host__ __device__ void thrust::sort(const thrust::detail::execution_policy_base< DerivedPolicy > &, RandomAccessIterator, RandomAccessIterator)
- template<typename RandomAccessIterator, typename StrictWeakOrdering> __host__ __device__ void thrust::sort(RandomAccessIterator, RandomAccessIterator, StrictWeakOrdering)
- template<typename RandomAccessIterator> void thrust::sort(RandomAccessIterator, RandomAccessIterator)
```

## Template Function `thrust::sort(RandomAccessIterator, RandomAccessIterator)`

### Function Documentation

```
template<typename RandomAccessIterator>
void thrust::sort (RandomAccessIterator first, RandomAccessIterator last)
    sort sorts the elements in [first, last) into ascending order, meaning that if i and j are any two
    valid iterators in [first, last) such that i precedes j, then *j is not less than *i. Note: sort is not
    guaranteed to be stable. That is, suppose that *i and *j are equivalent: neither one is less than the other. It is
    not guaranteed that the relative order of these two elements will be preserved by sort.
```

This version of `sort` compares objects using `operator<`.

The following code snippet demonstrates how to use `sort` to sort a sequence of integers.

#### Parameters

- `first`: The beginning of the sequence.
- `last`: The end of the sequence.

#### Template Parameters

- `RandomAccessIterator`: is a model of `Random Access Iterator`, `RandomAccessIterator` is mutable, and `RandomAccessIterator`'s `value_type` is a model of `LessThan Comparable`, and the ordering relation on `RandomAccessIterator`'s `value_type` is a *strict weak ordering*, as defined in the `LessThan Comparable` requirements.

```
#include <thrust/sort.h>
...
const int N = 6;
int A[N] = {1, 4, 2, 8, 5, 7};
thrust::sort(A, A + N);
// A is now {1, 2, 4, 5, 7, 8}
```

See <http://www.sgi.com/tech/stl/sort.html>

See `stable_sort`

See `sort_by_key`

## Template Function `thrust::sort(const thrust::detail::execution_policy_base<DerivedPolicy>&, RandomAccessIterator, RandomAccessIterator, StrictWeakOrdering)`

### Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::sort`” with arguments (`const thrust::detail::execution_policy_base<DerivedPolicy>&`, `RandomAccessIterator`, `RandomAccessIterator`, `StrictWeakOrdering`) in doxygen xml output for project “rocThrust” from directory: `./docBin/xml`. Potential matches:

```

- template<typename DerivedPolicy, typename RandomAccessIterator, typename
StrictWeakOrdering> __host__ __device__ void thrust::sort(const
thrust::detail::execution_policy_base< DerivedPolicy > &, RandomAccessIterator,
RandomAccessIterator, StrictWeakOrdering)
- template<typename DerivedPolicy, typename RandomAccessIterator> __host__ __device__
void thrust::sort(const thrust::detail::execution_policy_base< DerivedPolicy > &,
RandomAccessIterator, RandomAccessIterator)
- template<typename RandomAccessIterator, typename StrictWeakOrdering> __host__ __
device__ void thrust::sort(RandomAccessIterator, RandomAccessIterator,
StrictWeakOrdering)
- template<typename RandomAccessIterator>
void thrust::sort(RandomAccessIterator, RandomAccessIterator)

```

## Template Function `thrust::sort(RandomAccessIterator, RandomAccessIterator, StrictWeakOrdering)`

### Function Documentation

```
template<typename RandomAccessIterator, typename StrictWeakOrdering> __host__ __device__ void
```

sort sorts the elements in [first, last) into ascending order, meaning that if i and j are any two valid iterators in [first, last) such that i precedes j, then \*j is not less than \*i. Note: sort is not guaranteed to be stable. That is, suppose that \*i and \*j are equivalent: neither one is less than the other. It is not guaranteed that the relative order of these two elements will be preserved by sort.

This version of sort compares objects using a function object comp.

The following code demonstrates how to sort integers in descending order using the greater<int> comparison operator.

### Parameters

- first: The beginning of the sequence.
- last: The end of the sequence.
- comp: Comparison operator.

### Template Parameters

- RandomAccessIterator: is a model of Random Access Iterator, RandomAccessIterator is mutable, and RandomAccessIterator's value\_type is convertible to StrictWeakOrdering's first\_argument\_type and second\_argument\_type.
- StrictWeakOrdering: is a model of Strict Weak Ordering.

```
#include <thrust/sort.h>
#include <thrust/functional.h>
...
const int N = 6;
int A[N] = {1, 4, 2, 8, 5, 7};
thrust::sort(A, A + N, thrust::greater<int>());
// A is now {8, 7, 5, 4, 2, 1};
```

See <http://www.sgi.com/tech/stl/sort.html>

See `stable_sort`

See [sort\\_by\\_key](#)

**Template Function `thrust::sort_by_key(const thrust::detail::execution_policy_base<DerivedPolicy>&, RandomAccessIterator1, RandomAccessIterator1, RandomAccessIterator2)`**

- Defined in file `thrust_sort.h`

## Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::sort_by_key`” with arguments (`const thrust::detail::execution_policy_base<DerivedPolicy>&`, `RandomAccessIterator1`, `RandomAccessIterator1`, `RandomAccessIterator2`) in doxygen xml output for project “rocThrust” from directory: `./docBin/xml`. Potential matches:

```
- template<typename DerivedPolicy, typename RandomAccessIterator1, typename_
→RandomAccessIterator2, typename StrictWeakOrdering> __host__ __device__ void_
→thrust::sort_by_key(const thrust::detail::execution_policy_base< DerivedPolicy > &
→, RandomAccessIterator1, RandomAccessIterator1, RandomAccessIterator2,_
→StrictWeakOrdering)
- template<typename DerivedPolicy, typename RandomAccessIterator1, typename_
→RandomAccessIterator2> __host__ __device__ void thrust::sort_by_key(const_
→thrust::detail::execution_policy_base< DerivedPolicy > &, RandomAccessIterator1,_
→RandomAccessIterator1, RandomAccessIterator2)
- template<typename RandomAccessIterator1, typename RandomAccessIterator2, typename_
→StrictWeakOrdering>
  void thrust::sort_by_key(RandomAccessIterator1, RandomAccessIterator1,_
→RandomAccessIterator2, StrictWeakOrdering)
- template<typename RandomAccessIterator1, typename RandomAccessIterator2>
  void thrust::sort_by_key(RandomAccessIterator1, RandomAccessIterator1,_
→RandomAccessIterator2)
```

**Template Function `thrust::sort_by_key(RandomAccessIterator1, RandomAccessIterator1, RandomAccessIterator2)`**

## Function Documentation

```
template<typename RandomAccessIterator1, typename RandomAccessIterator2>
void thrust::sort_by_key(RandomAccessIterator1 keys_first, RandomAccessIterator1 keys_last, Ran-
domAccessIterator2 values_first)
```

`sort_by_key` performs a key-value sort. That is, `sort_by_key` sorts the elements in `[keys_first, keys_last)` and `[values_first, values_first + (keys_last - keys_first))` into ascending key order, meaning that if `i` and `j` are any two valid iterators in `[keys_first, keys_last)` such that `i` precedes `j`, and `p` and `q` are iterators in `[values_first, values_first + (keys_last - keys_first))` corresponding to `i` and `j` respectively, then  $*j$  is not less than  $*i$ .

Note: `sort_by_key` is not guaranteed to be stable. That is, suppose that  $*i$  and  $*j$  are equivalent: neither one is less than the other. It is not guaranteed that the relative order of these two keys or the relative order of their corresponding values will be preserved by `sort_by_key`.

This version of `sort_by_key` compares key objects using operator`<`.

The following code snippet demonstrates how to use `sort_by_key` to sort an array of character values using integers as sorting keys.

**Pre** The range `[keys_first, keys_last)` shall not overlap the range `[values_first, values_first + (keys_last - keys_first))`.

### Parameters

- `keys_first`: The beginning of the key sequence.
- `keys_last`: The end of the key sequence.
- `values_first`: The beginning of the value sequence.

### Template Parameters

- `RandomAccessIterator1`: is a model of Random Access Iterator, `RandomAccessIterator1` is mutable, and `RandomAccessIterator1`'s `value_type` is a model of `LessThan Comparable`, and the ordering relation on `RandomAccessIterator1`'s `value_type` is a *strict weak ordering*, as defined in the `LessThan Comparable` requirements.
- `RandomAccessIterator2`: is a model of Random Access Iterator, and `RandomAccessIterator2` is mutable.

```
#include <thrust/sort.h>
...
const int N = 6;
int keys[N] = { 1, 4, 2, 8, 5, 7};
char values[N] = {'a', 'b', 'c', 'd', 'e', 'f'};
thrust::sort_by_key(keys, keys + N, values);
// keys is now { 1, 2, 4, 5, 7, 8}
// values is now { 'a', 'c', 'b', 'e', 'f', 'd'}
```

See <http://www.sgi.com/tech/stl/sort.html>

See `stable_sort_by_key`

See `sort`

**Template Function** `thrust::sort_by_key(const thrust::detail::execution_policy_base<DerivedPolicy>&, RandomAccessIterator1, RandomAccessIterator1, RandomAccessIterator2, StrictWeakOrdering)`

### Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::sort_by_key`” with arguments (`const thrust::detail::execution_policy_base<DerivedPolicy>&`, `RandomAccessIterator1`, `RandomAccessIterator1`, `RandomAccessIterator2`, `StrictWeakOrdering`) in doxygen xml output for project “rocThrust” from directory: `./docBin/xml`. Potential matches:

```
- template<typename DerivedPolicy, typename RandomAccessIterator1, typename _RandomAccessIterator2, typename StrictWeakOrdering> __host__ __device__ void __thrust::sort_by_key(const thrust::detail::execution_policy_base< DerivedPolicy > &, RandomAccessIterator1, RandomAccessIterator1, RandomAccessIterator2, __StrictWeakOrdering)
- template<typename DerivedPolicy, typename RandomAccessIterator1, typename _RandomAccessIterator2> __host__ __device__ void __thrust::sort_by_key(const __thrust::detail::execution_policy_base< DerivedPolicy > &, RandomAccessIterator1, RandomAccessIterator2)
- template<typename RandomAccessIterator1, typename RandomAccessIterator2, typename __StrictWeakOrdering> void __thrust::sort_by_key(RandomAccessIterator1, RandomAccessIterator1, RandomAccessIterator2, StrictWeakOrdering)
- template<typename RandomAccessIterator1, typename RandomAccessIterator2> __host__ __device__ void __thrust::sort_by_key(RandomAccessIterator1, RandomAccessIterator1, RandomAccessIterator2)
```

## Template Function `thrust::sort_by_key(RandomAccessIterator1, RandomAccessIterator1, RandomAccessIterator2, StrictWeakOrdering)`

### Function Documentation

```
template<typename RandomAccessIterator1, typename RandomAccessIterator2, typename StrictWeakOrdering>
void thrust::sort_by_key(RandomAccessIterator1 keys_first, RandomAccessIterator1 keys_last, RandomAccessIterator2 values_first, StrictWeakOrdering comp)
```

`sort_by_key` performs a key-value sort. That is, `sort_by_key` sorts the elements in  $[\text{keys\_first}, \text{keys\_last})$  and  $[\text{values\_first}, \text{values\_first} + (\text{keys\_last} - \text{keys\_first}))$  into ascending key order, meaning that if  $i$  and  $j$  are any two valid iterators in  $[\text{keys\_first}, \text{keys\_last})$  such that  $i$  precedes  $j$ , and  $p$  and  $q$  are iterators in  $[\text{values\_first}, \text{values\_first} + (\text{keys\_last} - \text{keys\_first}))$  corresponding to  $i$  and  $j$  respectively, then  $*j$  is not less than  $*i$ .

Note: `sort_by_key` is not guaranteed to be stable. That is, suppose that  $*i$  and  $*j$  are equivalent: neither one is less than the other. It is not guaranteed that the relative order of these two keys or the relative order of their corresponding values will be preserved by `sort_by_key`.

This version of `sort_by_key` compares key objects using a function object `comp`.

The following code snippet demonstrates how to use `sort_by_key` to sort an array of character values using integers as sorting keys. The keys are sorted in descending order using the `greater<int>` comparison operator.

**Pre** The range  $[\text{keys\_first}, \text{keys\_last})$  shall not overlap the range  $[\text{values\_first}, \text{values\_first} + (\text{keys\_last} - \text{keys\_first}))$ .

### Parameters

- `keys_first`: The beginning of the key sequence.
- `keys_last`: The end of the key sequence.
- `values_first`: The beginning of the value sequence.
- `comp`: Comparison operator.

### Template Parameters

- `RandomAccessIterator1`: is a model of `Random Access Iterator`, `RandomAccessIterator1` is mutable, and `RandomAccessIterator1`'s `value_type` is convertible to `StrictWeakOrdering`'s `first_argument_type` and `second_argument_type`.
- `RandomAccessIterator2`: is a model of `Random Access Iterator`, and `RandomAccessIterator2` is mutable.
- `StrictWeakOrdering`: is a model of `Strict Weak Ordering`.

```
#include <thrust/sort.h>
...
const int N = 6;
int keys[N] = { 1, 4, 2, 8, 5, 7};
char values[N] = {'a', 'b', 'c', 'd', 'e', 'f'};
thrust::sort_by_key(keys, keys + N, values, thrust::greater<int>());
// keys is now { 8, 7, 5, 4, 2, 1}
// values is now { 'd', 'f', 'e', 'b', 'c', 'a'}
```

**See** <http://www.sgi.com/tech/stl/sort.html>

**See** `stable_sort_by_key`

**See** `sort`

## Template Function `thrust::sqrt`

- Defined in file `thrust_complex.h`

### Function Documentation

```
template<typename T> __host__ __device__ complex<T> thrust::sqrt(const complex < T > & z)
```

Returns the complex square root of a complex number.

#### Parameters

- `z`: The complex argument.

## Template Function `thrust::stable_partition`(`const thrust::detail::execution_policy_base<DerivedPolicy>&, ForwardIterator, ForwardIterator, Predicate)`

- Defined in file `thrust_partition.h`

### Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::stable_partition`” with arguments (`const thrust::detail::execution_policy_base<DerivedPolicy>&`, `ForwardIterator`, `ForwardIterator`, `Predicate`) in doxygen xml output for project “rocThrust” from directory: `./docBin/xml`. Potential matches:

```
- template<typename DerivedPolicy, typename ForwardIterator, typename InputIterator,
  ↵ typename Predicate> __host__ __device__ ForwardIterator thrust::stable_
  ↵ partition(const thrust::detail::execution_policy_base< DerivedPolicy > &, ↵
  ↵ ForwardIterator, ForwardIterator, InputIterator, Predicate)
- template<typename DerivedPolicy, typename ForwardIterator, typename Predicate> __
  ↵ host__ __device__ ForwardIterator thrust::stable_partition(const_
  ↵ thrust::detail::execution_policy_base< DerivedPolicy > &, ForwardIterator, ↵
  ↵ ForwardIterator, Predicate)
- template<typename ForwardIterator, typename InputIterator, typename Predicate>
  ForwardIterator thrust::stable_partition(ForwardIterator, ForwardIterator, ↵
  ↵ InputIterator, Predicate)
- template<typename ForwardIterator, typename Predicate>
  ForwardIterator thrust::stable_partition(ForwardIterator, ForwardIterator, ↵
  ↵ Predicate)
```

## Template Function `thrust::stable_partition(ForwardIterator, ForwardIterator, Predicate)`

### Function Documentation

```
template<typename ForwardIterator, typename Predicate>
```

*ForwardIterator* `thrust::stable_partition(ForwardIterator first, ForwardIterator last, Predicate pred)`

`stable_partition` is much like `partition`: it reorders the elements in the range `[first, last]` based on the function object `pred`, such that all of the elements that satisfy `pred` precede all of the elements that fail to satisfy it. The postcondition is that, for some iterator `middle` in the range `[first, last]`, `pred(*i)` is true for every iterator `i` in the range `[first, middle)` and false for every iterator `i` in the range `[middle, last)`. The return value of `stable_partition` is `middle`.

`stable_partition` differs from `partition` in that `stable_partition` is guaranteed to preserve relative order. That is, if `x` and `y` are elements in `[first, last)`, and `stencil_x` and `stencil_y` are the stencil elements in corresponding positions within `[stencil, stencil + (last - first))`, and `pred(stencil_x) == pred(stencil_y)`, and if `x` precedes `y`, then it will still be true after `stable_partition` that `x` precedes `y`.

The following code snippet demonstrates how to use `stable_partition` to reorder a sequence so that even numbers precede odd numbers.

**Return** An iterator referring to the first element of the second partition, that is, the sequence of the elements which do not satisfy `pred`.

#### Parameters

- `first`: The first element of the sequence to reorder.
- `last`: One position past the last element of the sequence to reorder.
- `pred`: A function object which decides to which partition each element of the sequence `[first, last)` belongs.

#### Template Parameters

- `ForwardIterator`: is a model of `Forward Iterator`, and `ForwardIterator`'s `value_type` is convertible to `Predicate`'s `argument_type`, and `ForwardIterator` is mutable.
- `Predicate`: is a model of `Predicate`.

```
#include <thrust/partition.h>
...
struct is_even
{
    __host__ __device__
    bool operator() (const int &x)
    {
        return (x % 2) == 0;
    }
};

int A[] = {1, 2, 3, 4, 5, 6, 7, 8, 9, 10};
const int N = sizeof(A)/sizeof(int);
thrust::stable_partition(A, A + N,
                        is_even());
// A is now {2, 4, 6, 8, 10, 1, 3, 5, 7, 9}
```

See [http://www.sgi.com/tech/stl/stable\\_partition.html](http://www.sgi.com/tech/stl/stable_partition.html)

See `partition`

See `stable_partition_copy`

**Template Function `thrust::stable_partition(const thrust::detail::execution_policy_base<DerivedPolicy>&, ForwardIterator, ForwardIterator, InputIterator, Predicate)`**

## Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::stable_partition`” with arguments (`const thrust::detail::execution_policy_base<DerivedPolicy>&`, `ForwardIterator`, `ForwardIterator`, `InputIterator`, `Predicate`) in doxygen xml output for project “rocThrust” from directory: `./docBin/xml`. Potential matches:

```
- template<typename DerivedPolicy, typename ForwardIterator, typename InputIterator,
→ typename Predicate> __host__ __device__ ForwardIterator thrust::stable_
→partition(const thrust::detail::execution_policy_base< DerivedPolicy > &, ↵
→ForwardIterator, ForwardIterator, InputIterator, Predicate)
- template<typename DerivedPolicy, typename ForwardIterator, typename Predicate> __
→host__ __device__ ForwardIterator thrust::stable_partition(const ↵
→thrust::detail::execution_policy_base< DerivedPolicy > &, ForwardIterator, ↵
→ForwardIterator, Predicate)
- template<typename ForwardIterator, typename InputIterator, typename Predicate>
  ForwardIterator thrust::stable_partition(ForwardIterator, ForwardIterator, ↵
→InputIterator, Predicate)
- template<typename ForwardIterator, typename Predicate>
  ForwardIterator thrust::stable_partition(ForwardIterator, ForwardIterator, ↵
→Predicate)
```

**Template Function `thrust::stable_partition(ForwardIterator, ForwardIterator, InputIterator, Predicate)`**

## Function Documentation

```
template<typename ForwardIterator, typename InputIterator, typename PredicateForwardIterator thrust::stable_partition(ForwardIterator first, ForwardIterator last, InputIterator
stencil, Predicate pred)
```

`stable_partition` is much like `partition`: it reorders the elements in the range `[first, last)` based on the function object `pred` applied to a stencil range `[stencil, stencil + (last - first))`, such that all of the elements whose corresponding stencil element satisfies `pred` precede all of the elements whose corresponding stencil element fails to satisfy it. The postcondition is that, for some iterator `middle` in the range `[first, last)`, `pred(*stencil_i)` is true for every iterator `stencil_i` in the range `[stencil, stencil + (middle - first))` and false for every iterator `stencil_i` in the range `[stencil + (middle - first), stencil + (last - first))`. The return value of `stable_partition` is `middle`.

`stable_partition` differs from `partition` in that `stable_partition` is guaranteed to preserve relative order. That is, if `x` and `y` are elements in `[first, last)`, such that `pred(x) == pred(y)`, and if `x` precedes `y`, then it will still be true after `stable_partition` that `x` precedes `y`.

The following code snippet demonstrates how to use `stable_partition` to reorder a sequence so that even numbers precede odd numbers.

**Return** An iterator referring to the first element of the second partition, that is, the sequence of the elements whose stencil elements do not satisfy `pred`.

**Pre** The range `[first, last)` shall not overlap with the range `[stencil, stencil + (last - first))`.

## Parameters

- `first`: The first element of the sequence to reorder.
- `last`: One position past the last element of the sequence to reorder.
- `stencil`: The beginning of the stencil sequence.
- `pred`: A function object which decides to which partition each element of the sequence [`first`, `last`) belongs.

### Template Parameters

- `ForwardIterator`: is a model of [Forward Iterator](#), and `ForwardIterator` is mutable.
- `InputIterator`: is a model of [Input Iterator](#), and `InputIterator`'s `value_type` is convertible to `Predicate`'s `argument_type`.
- `Predicate`: is a model of [Predicate](#).

```
#include <thrust/partition.h>
...
struct is_even
{
    __host__ __device__
    bool operator() (const int &x)
    {
        return (x % 2) == 0;
    }
};
...
int A[] = {0, 1, 0, 1, 0, 1, 0, 1, 0, 1};
int S[] = {1, 2, 3, 4, 5, 6, 7, 8, 9, 10};
const int N = sizeof(A)/sizeof(int);
thrust::stable_partition(A, A + N, S, is_even());
// A is now {1, 1, 1, 1, 0, 0, 0, 0, 0}
// S is unmodified
```

**See** [http://www.sgi.com/tech/stl/stable\\_partition.html](http://www.sgi.com/tech/stl/stable_partition.html)

**See** `partition`

**See** `stable_partition_copy`

**Template Function** `thrust::stable_partition_copy(const thrust::detail::execution_policy_base<DerivedPolicy>&, InputIterator, InputIterator, OutputIterator1, OutputIterator2, Predicate)`

- Defined in `file_thrust_partition.h`

### Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::stable_partition_copy`” with arguments (`const thrust::detail::execution_policy_base<DerivedPolicy>&`, `InputIterator`, `InputIterator`, `OutputIterator1`, `OutputIterator2`, `Predicate`) in doxygen xml output for project “rocThrust” from directory: `./docBin/xml`. Potential matches:

```

- template<typename DerivedPolicy, typename InputIterator, typename OutputIterator1,
  ↵ typename OutputIterator2, typename Predicate> __host__ __device__ thrust::pair<
  ↵<OutputIterator1,OutputIterator2> thrust::stable_partition_copy(const_
  ↵thrust::detail::execution_policy_base< DerivedPolicy > &, InputIterator,_
  ↵InputIterator, OutputIterator1, OutputIterator2, Predicate)
- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2,
  ↵ typename OutputIterator1, typename OutputIterator2, typename Predicate> __host__ __
  ↵_device__ thrust::pair<OutputIterator1,OutputIterator2> thrust::stable_partition_
  ↵copy(const thrust::detail::execution_policy_base< DerivedPolicy > &,_
  ↵InputIterator1, InputIterator1, InputIterator2, OutputIterator1, OutputIterator2,_
  ↵Predicate)
- template<typename InputIterator, typename OutputIterator1, typename_
  ↵OutputIterator2, typename Predicate>
  thrust::pair<OutputIterator1, OutputIterator2> thrust::stable_partition_
  ↵copy(InputIterator, InputIterator, OutputIterator1, OutputIterator2, Predicate)
- template<typename InputIterator1, typename InputIterator2, typename_
  ↵OutputIterator1, typename OutputIterator2, typename Predicate>
  thrust::pair<OutputIterator1, OutputIterator2> thrust::stable_partition_
  ↵copy(InputIterator1, InputIterator1, InputIterator2, OutputIterator1,_
  ↵OutputIterator2, Predicate)

```

## Template Function `thrust::stable_partition_copy(InputIterator, InputIterator, OutputIterator1, OutputIterator2, Predicate)`

### Function Documentation

```

template<typename InputIterator, typename OutputIterator1, typename OutputIterator2, typename Predicate>
thrust::pair<OutputIterator1, OutputIterator2> thrust::stable_partition_copy (InputIterator
  ↵ first, InputIterator
  ↵ last, OutputIter-
  ↵ ator1 out_true,
  ↵ OutputItera-
  ↵ tor2 out_false,
  ↵ Predicate pred)

```

`stable_partition_copy` differs from `stable_partition` only in that the reordered sequence is written to different output sequences, rather than in place.

`stable_partition_copy` copies the elements  $[first, last]$  based on the function object `pred`. All of the elements that satisfy `pred` are copied to the range beginning at `out_true` and all the elements that fail to satisfy it are copied to the range beginning at `out_false`.

`stable_partition_copy` differs from `partition_copy` in that `stable_partition_copy` is guaranteed to preserve relative order. That is, if  $x$  and  $y$  are elements in  $[first, last]$ , such that  $pred(x) == pred(y)$ , and if  $x$  precedes  $y$ , then it will still be true after `stable_partition_copy` that  $x$  precedes  $y$  in the output.

The following code snippet demonstrates how to use `stable_partition_copy` to reorder a sequence so that even numbers precede odd numbers.

**Return** A pair  $p$  such that  $p.first$  is the end of the output range beginning at `out_true` and  $p.second$  is the end of the output range beginning at `out_false`.

**Pre** The input ranges shall not overlap with either output range.

### Parameters

- `first`: The first element of the sequence to reorder.
- `last`: One position past the last element of the sequence to reorder.
- `out_true`: The destination of the resulting sequence of elements which satisfy `pred`.
- `out_false`: The destination of the resulting sequence of elements which fail to satisfy `pred`.
- `pred`: A function object which decides to which partition each element of the sequence [`first`, `last`) belongs.

### Template Parameters

- `InputIterator`: is a model of `Input Iterator`, and `InputIterator`'s `value_type` is convertible to `Predicate`'s `argument_type` and `InputIterator`'s `value_type` is convertible to `OutputIterator1` and `OutputIterator2`'s `value_types`.
- `OutputIterator1`: is a model of `Output Iterator`.
- `OutputIterator2`: is a model of `Output Iterator`.
- `Predicate`: is a model of `Predicate`.

```
#include <thrust/partition.h>
...
struct is_even
{
    __host__ __device__
    bool operator() (const int &x)
    {
        return (x % 2) == 0;
    }
};

int A[] = {1, 2, 3, 4, 5, 6, 7, 8, 9, 10};
int result[10];
const int N = sizeof(A) / sizeof(int);
int *evens = result;
int *odds = result + 5;
thrust::stable_partition_copy(A, A + N, evens, odds, is_even());
// A remains {1, 2, 3, 4, 5, 6, 7, 8, 9, 10}
// result is now {2, 4, 6, 8, 10, 1, 3, 5, 7, 9}
// evens points to {2, 4, 6, 8, 10}
// odds points to {1, 3, 5, 7, 9}
```

See <http://www.open-std.org/jtc1/sc22/wg21/docs/papers/2008/n2569.pdf>

See `partition_copy`

See `stable_partition`

**Template Function** `thrust::stable_partition_copy(const thrust::detail::execution_policy_base<DerivedPolicy>&, InputIterator1, InputIterator1, InputIterator2, OutputIterator1, OutputIterator2, Predicate)`

### Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “thrust::stable\_partition\_copy” with arguments (const thrust::detail::execution\_policy\_base<DerivedPolicy>&, InputIterator1, InputIterator1, InputIterator2, OutputIterator1, OutputIterator2, Predicate) in doxygen xml output for project “rocThrust” from directory: ./docBin/xml. Potential matches:

```
- template<typename DerivedPolicy, typename InputIterator, typename OutputIterator1,
→ typename OutputIterator2, typename Predicate> __host__ __device__ thrust::pair
→<OutputIterator1,OutputIterator2> thrust::stable_partition_copy(const_
→thrust::detail::execution_policy_base< DerivedPolicy > &, InputIterator,_
→InputIterator, OutputIterator1, OutputIterator2, Predicate)
- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2,
→ typename OutputIterator1, typename OutputIterator2, typename Predicate> __host__ __
→_device__ thrust::pair<OutputIterator1,OutputIterator2> thrust::stable_partition_
→copy(const thrust::detail::execution_policy_base< DerivedPolicy > &,_
→InputIterator1, InputIterator1, InputIterator2, OutputIterator1, OutputIterator2,_
→Predicate)
- template<typename InputIterator, typename OutputIterator1, typename_
→OutputIterator2, typename Predicate>
  thrust::pair<OutputIterator1, OutputIterator2> thrust::stable_partition_
→copy(InputIterator, InputIterator, OutputIterator1, OutputIterator2, Predicate)
- template<typename InputIterator1, typename InputIterator2, typename_
→OutputIterator1, typename OutputIterator2, typename Predicate>
  thrust::pair<OutputIterator1, OutputIterator2> thrust::stable_partition_
→copy(InputIterator1, InputIterator1, InputIterator2, OutputIterator1,_
→OutputIterator2, Predicate)
```

## Template Function `thrust::stable_partition_copy(InputIterator1, InputIterator1, InputIterator2, OutputIterator1, OutputIterator2, Predicate)`

### Function Documentation

```
template<typename InputIterator1, typename InputIterator2, typename OutputIterator1, typename OutputIterator2>
thrust::pair<OutputIterator1, OutputIterator2> thrust::stable_partition_copy(InputIterator1
first,           InputIter-
→er1 last,
InputIterator2
stencil,          OutputIter-
→er1 out_true,
OutputItera-
tor2 out_false,
Predicate pred)
```

`stable_partition_copy` differs from `stable_partition` only in that the reordered sequence is written to different output sequences, rather than in place.

`stable_partition_copy` copies the elements `[first, last)` based on the function object `pred` which is applied to a range of stencil elements. All of the elements whose corresponding stencil element satisfies `pred` are copied to the range beginning at `out_true` and all the elements whose stencil element fails to satisfy it are copied to the range beginning at `out_false`.

`stable_partition_copy` differs from `partition_copy` in that `stable_partition_copy` is guaranteed to preserve relative order. That is, if `x` and `y` are elements in `[first, last)`, such that `pred(x) == pred(y)`, and if `x` precedes `y`, then it will still be true after `stable_partition_copy` that `x` precedes `y` in the output.

The following code snippet demonstrates how to use `stable_partition_copy` to reorder a sequence so

that even numbers precede odd numbers.

**Return** A pair  $p$  such that  $p.\text{first}$  is the end of the output range beginning at  $\text{out\_true}$  and  $p.\text{second}$  is the end of the output range beginning at  $\text{out\_false}$ .

**Pre** The input ranges shall not overlap with either output range.

#### Parameters

- $\text{first}$ : The first element of the sequence to reorder.
- $\text{last}$ : One position past the last element of the sequence to reorder.
- $\text{stencil}$ : The beginning of the stencil sequence.
- $\text{out\_true}$ : The destination of the resulting sequence of elements which satisfy  $\text{pred}$ .
- $\text{out\_false}$ : The destination of the resulting sequence of elements which fail to satisfy  $\text{pred}$ .
- $\text{pred}$ : A function object which decides to which partition each element of the sequence  $[\text{first}, \text{last})$  belongs.

#### Template Parameters

- $\text{InputIterator1}$ : is a model of [Input Iterator](#), and  $\text{InputIterator1}'\text{s value\_type}$  is convertible to  $\text{OutputIterator1}$  and  $\text{OutputIterator2}'\text{s value\_types}$ .
- $\text{InputIterator2}$ : is a model of [Input Iterator](#), and  $\text{InputIterator2}'\text{s value\_type}$  is convertible to [Predicate](#)'s argument\_type.
- $\text{OutputIterator1}$ : is a model of [Output Iterator](#).
- $\text{OutputIterator2}$ : is a model of [Output Iterator](#).
- $\text{Predicate}$ : is a model of [Predicate](#).

```
#include <thrust/partition.h>
#include <thrust/functional.h>
...
int A[] = {1, 2, 3, 4, 5, 6, 7, 8, 9, 10};
int S[] = {0, 1, 0, 1, 0, 1, 0, 1, 0, 1};
int result[10];
const int N = sizeof(A)/sizeof(int);
int *evens = result;
int *odds = result + 5;
thrust::stable_partition_copy(A, A + N, S, evens, odds, thrust::identity<int>());
// A remains {1, 2, 3, 4, 5, 6, 7, 8, 9, 10}
// S remains {0, 1, 0, 1, 0, 1, 0, 1, 0, 1}
// result is now {2, 4, 6, 8, 10, 1, 3, 5, 7, 9}
// evens points to {2, 4, 6, 8, 10}
// odds points to {1, 3, 5, 7, 9}
```

**See** <http://www.open-std.org/jtc1/sc22/wg21/docs/papers/2008/n2569.pdf>

**See** [partition\\_copy](#)

**See** [stable\\_partition](#)

### Template Function `thrust::stable_sort(const thrust::detail::execution_policy_base<DerivedPolicy>&, RandomAccessIterator, RandomAccessIterator)`

- Defined in file `thrust_sort.h`

## Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “thrust::stable\_sort” with arguments (const thrust::detail::execution\_policy\_base<DerivedPolicy>&, RandomAccessIterator, RandomAccessIterator) in doxygen xml output for project “rocThrust” from directory: ./docBin/xml. Potential matches:

```
- template<typename DerivedPolicy, typename RandomAccessIterator, typename StrictWeakOrdering>_host_ _device_ void thrust::stable_sort(const
_host_ _device_ void thrust::stable_sort(const thrust::detail::execution_policy_base< DerivedPolicy > &, RandomAccessIterator,
_host_ _device_ void thrust::stable_sort(const thrust::detail::execution_policy_base<
_host_ _device_ void thrust::stable_sort(RandomAccessIterator, RandomAccessIterator,
_host_ _device_ void thrust::stable_sort(RandomAccessIterator, RandomAccessIterator,
_host_ _device_ void thrust::stable_sort(RandomAccessIterator, RandomAccessIterator)
```

## Template Function `thrust::stable_sort(RandomAccessIterator, RandomAccessIterator)`

### Function Documentation

```
template<typename RandomAccessIterator>
void thrust::stable_sort(RandomAccessIterator first, RandomAccessIterator last)
    stable_sort is much like sort: it sorts the elements in [first, last) into ascending order, meaning
    that if i and j are any two valid iterators in [first, last) such that i precedes j, then *j is not less than
    *i.
```

As the name suggests, stable\_sort is stable: it preserves the relative ordering of equivalent elements. That is, if x and y are elements in [first, last) such that x precedes y, and if the two elements are equivalent (neither  $x < y$  nor  $y < x$ ) then a postcondition of stable\_sort is that x still precedes y.

This version of stable\_sort compares objects using operator<.

The following code snippet demonstrates how to use sort to sort a sequence of integers.

### Parameters

- `first`: The beginning of the sequence.
- `last`: The end of the sequence.

### Template Parameters

- `RandomAccessIterator`: is a model of `Random Access Iterator`, `RandomAccessIterator` is mutable, and `RandomAccessIterator`'s `value_type` is a model of `LessThan Comparable`, and the ordering relation on `RandomAccessIterator`'s `value_type` is a *strict weak ordering*, as defined in the `LessThan Comparable` requirements.

```
#include <thrust/sort.h>
...
const int N = 6;
int A[N] = {1, 4, 2, 8, 5, 7};
thrust::stable_sort(A, A + N);
// A is now {1, 2, 4, 5, 7, 8}
```

See [http://www.sgi.com/tech/stl/stable\\_sort.html](http://www.sgi.com/tech/stl/stable_sort.html)

See sort

See stable\_sort\_by\_key

**Template Function thrust::stable\_sort(const thrust::detail::execution\_policy\_base<DerivedPolicy>&, RandomAccessIterator, RandomAccessIterator, StrictWeakOrdering)**

## Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “thrust::stable\_sort” with arguments (const thrust::detail::execution\_policy\_base<DerivedPolicy>&, RandomAccessIterator, RandomAccessIterator, StrictWeakOrdering) in doxygen xml output for project “rocThrust” from directory: ./docBin/xml. Potential matches:

```
- template<typename DerivedPolicy, typename RandomAccessIterator, typename_
  ↵ StrictWeakOrdering> __host__ __device__ void thrust::stable_sort(const_
  ↵ thrust::detail::execution_policy_base< DerivedPolicy > &, RandomAccessIterator,_
  ↵ RandomAccessIterator, StrictWeakOrdering)
- template<typename DerivedPolicy, typename RandomAccessIterator> __host__ __device__
  ↵ void thrust::stable_sort(const thrust::detail::execution_policy_base<_
  ↵ DerivedPolicy > &, RandomAccessIterator, RandomAccessIterator)
- template<typename RandomAccessIterator, typename StrictWeakOrdering>
  ↵ void thrust::stable_sort(RandomAccessIterator, RandomAccessIterator,_
  ↵ StrictWeakOrdering)
- template<typename RandomAccessIterator>
  ↵ void thrust::stable_sort(RandomAccessIterator, RandomAccessIterator)
```

**Template Function      thrust::stable\_sort(RandomAccessIterator, RandomAccessIterator, StrictWeakOrdering)**

## Function Documentation

```
template<typename RandomAccessIterator, typename StrictWeakOrdering>
void thrust::stable_sort(RandomAccessIterator first, RandomAccessIterator last, StrictWeakOrder-
  ↵ ing comp)
```

stable\_sort is much like sort: it sorts the elements in [first, last) into ascending order, meaning that if i and j are any two valid iterators in [first, last) such that i precedes j, then \*j is not less than \*i.

As the name suggests, stable\_sort is stable: it preserves the relative ordering of equivalent elements. That is, if x and y are elements in [first, last) such that x precedes y, and if the two elements are equivalent (neither x < y nor y < x) then a postcondition of stable\_sort is that x still precedes y.

This version of stable\_sort compares objects using a function object comp.

The following code demonstrates how to sort integers in descending order using the greater<int> comparison operator.

### Parameters

- first: The beginning of the sequence.
- last: The end of the sequence.

- `comp`: Comparison operator.

### Template Parameters

- `RandomAccessIterator`: is a model of Random Access Iterator, `RandomAccessIterator` is mutable, and `RandomAccessIterator`'s `value_type` is convertible to `StrictWeakOrdering`'s `first_argument_type` and `second_argument_type`.
- `StrictWeakOrdering`: is a model of Strict Weak Ordering.

```
#include <thrust/sort.h>
#include <thrust/functional.h>
...
const int N = 6;
int A[N] = {1, 4, 2, 8, 5, 7};
thrust::sort(A, A + N, thrust::greater<int>());
// A is now {8, 7, 5, 4, 2, 1};
```

See [http://www.sgi.com/tech/stl/stable\\_sort.html](http://www.sgi.com/tech/stl/stable_sort.html)

See `sort`

See `stable_sort_by_key`

### Template Function `thrust::stable_sort_by_key(const thrust::detail::execution_policy_base<DerivedPolicy>&, RandomAccessIterator1, RandomAccessIterator1, RandomAccessIterator2)`

- Defined in file `_thrust_sort.h`

### Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::stable_sort_by_key`” with arguments (`const thrust::detail::execution_policy_base<DerivedPolicy>&`, `RandomAccessIterator1`, `RandomAccessIterator1`, `RandomAccessIterator2`) in doxygen xml output for project “rocThrust” from directory: `./docBin/xml`. Potential matches:

```
- template<typename DerivedPolicy, typename RandomAccessIterator1, typename
→RandomAccessIterator2, typename StrictWeakOrdering>__host__ __device__ void
→thrust::stable_sort_by_key(const thrust::detail::execution_policy_base<
→DerivedPolicy > &, RandomAccessIterator1, RandomAccessIterator1,
→RandomAccessIterator2, StrictWeakOrdering)
- template<typename DerivedPolicy, typename RandomAccessIterator1, typename
→RandomAccessIterator2>__host__ __device__ void thrust::stable_sort_by_key(const_
→thrust::detail::execution_policy_base< DerivedPolicy > &, RandomAccessIterator1,
→RandomAccessIterator1, RandomAccessIterator2)
- template<typename RandomAccessIterator1, typename RandomAccessIterator2, typename
→StrictWeakOrdering>
→void thrust::stable_sort_by_key(RandomAccessIterator1, RandomAccessIterator1,
→RandomAccessIterator2, StrictWeakOrdering)
- template<typename RandomAccessIterator1, typename RandomAccessIterator2>
→void thrust::stable_sort_by_key(RandomAccessIterator1, RandomAccessIterator1,
→RandomAccessIterator2)
```

**Template Function `thrust::stable_sort_by_key(RandomAccessIterator1, RandomAccessIterator1, RandomAccessIterator2)`**

## Function Documentation

```
template<typename RandomAccessIterator1, typename RandomAccessIterator2>
void thrust::stable_sort_by_key(RandomAccessIterator1 keys_first, RandomAccessIterator1
                               keys_last, RandomAccessIterator2 values_first)
    stable_sort_by_key performs a key-value sort. That is, stable_sort_by_key sorts the elements in [keys_first, keys_last) and [values_first, values_first + (keys_last - keys_first)) into ascending key order, meaning that if i and j are any two valid iterators in [keys_first, keys_last) such that i precedes j, and p and q are iterators in [values_first, values_first + (keys_last - keys_first)) corresponding to i and j respectively, then *j is not less than *i.
```

As the name suggests, `stable_sort_by_key` is stable: it preserves the relative ordering of equivalent elements. That is, if  $x$  and  $y$  are elements in  $[keys\_first, keys\_last)$  such that  $x$  precedes  $y$ , and if the two elements are equivalent (neither  $x < y$  nor  $y < x$ ) then a postcondition of `stable_sort_by_key` is that  $x$  still precedes  $y$ .

This version of `stable_sort_by_key` compares key objects using operator`<`.

The following code snippet demonstrates how to use `stable_sort_by_key` to sort an array of characters using integers as sorting keys.

**Pre** The range  $[keys\_first, keys\_last)$  shall not overlap the range  $[values\_first, values\_first + (keys\_last - keys\_first))$ .

### Parameters

- `keys_first`: The beginning of the key sequence.
- `keys_last`: The end of the key sequence.
- `values_first`: The beginning of the value sequence.

### Template Parameters

- `RandomAccessIterator1`: is a model of `Random Access Iterator`, `RandomAccessIterator1` is mutable, and `RandomAccessIterator1`'s `value_type` is a model of `LessThan Comparable`, and the ordering relation on `RandomAccessIterator1`'s `value_type` is a *strict weak ordering*, as defined in the `LessThan Comparable` requirements.
- `RandomAccessIterator2`: is a model of `Random Access Iterator`, and `RandomAccessIterator2` is mutable.

```
#include <thrust/sort.h>
...
const int N = 6;
int keys[N] = { 1, 4, 2, 8, 5, 7};
char values[N] = {'a', 'b', 'c', 'd', 'e', 'f'};
thrust::stable_sort_by_key(keys, keys + N, values);
// keys is now { 1, 2, 4, 5, 7, 8}
// values is now {'a', 'c', 'b', 'e', 'f', 'd'}
```

See <http://www.sgi.com/tech/stl/sort.html>

See `sort_by_key`

See `stable_sort`

**Template Function `thrust::stable_sort_by_key(const thrust::detail::execution_policy_base<DerivedPolicy>&, RandomAccessIterator1, RandomAccessIterator1, RandomAccessIterator2, StrictWeakOrdering)`**

## Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::stable_sort_by_key`” with arguments (`const thrust::detail::execution_policy_base<DerivedPolicy>&`, `RandomAccessIterator1`, `RandomAccessIterator1`, `RandomAccessIterator2`, `StrictWeakOrdering`) in doxygen xml output for project “rocThrust” from directory: `./docBin/xml`. Potential matches:

```
- template<typename DerivedPolicy, typename RandomAccessIterator1, typename
→RandomAccessIterator2, typename StrictWeakOrdering> __host__ __device__ void
→thrust::stable_sort_by_key(const thrust::detail::execution_policy_base<
→DerivedPolicy > &, RandomAccessIterator1, RandomAccessIterator1,
→RandomAccessIterator2, StrictWeakOrdering)
- template<typename DerivedPolicy, typename RandomAccessIterator1, typename
→RandomAccessIterator2> __host__ __device__ void thrust::stable_sort_by_key(const
→thrust::detail::execution_policy_base< DerivedPolicy > &, RandomAccessIterator1,
→RandomAccessIterator1, RandomAccessIterator2)
- template<typename RandomAccessIterator1, typename RandomAccessIterator2, typename
→StrictWeakOrdering>
  void thrust::stable_sort_by_key(RandomAccessIterator1, RandomAccessIterator1,
→RandomAccessIterator2, StrictWeakOrdering)
- template<typename RandomAccessIterator1, typename RandomAccessIterator2>
  void thrust::stable_sort_by_key(RandomAccessIterator1, RandomAccessIterator1,
→RandomAccessIterator2)
```

**Template Function `thrust::stable_sort_by_key(RandomAccessIterator1, RandomAccessIterator1, RandomAccessIterator2, StrictWeakOrdering)`**

## Function Documentation

```
template<typename RandomAccessIterator1, typename RandomAccessIterator2, typename StrictWeakOrdering>
void thrust::stable_sort_by_key(RandomAccessIterator1 keys_first, RandomAccessIterator1
                               keys_last, RandomAccessIterator2 values_first, StrictWeakOrder
                               ing comp)
```

`stable_sort_by_key` performs a key-value sort. That is, `stable_sort_by_key` sorts the elements in  $[keys\_first, keys\_last]$  and  $[values\_first, values\_first + (keys\_last - keys\_first)]$  into ascending key order, meaning that if  $i$  and  $j$  are any two valid iterators in  $[keys\_first, keys\_last]$  such that  $i$  precedes  $j$ , and  $p$  and  $q$  are iterators in  $[values\_first, values\_first + (keys\_last - keys\_first)]$  corresponding to  $i$  and  $j$  respectively, then  $*j$  is not less than  $*i$ .

As the name suggests, `stable_sort_by_key` is stable: it preserves the relative ordering of equivalent elements. That is, if  $x$  and  $y$  are elements in  $[keys\_first, keys\_last]$  such that  $x$  precedes  $y$ , and if the two elements are equivalent (neither  $x < y$  nor  $y < x$ ) then a postcondition of `stable_sort_by_key` is that  $x$  still precedes  $y$ .

This version of `stable_sort_by_key` compares key objects using the function object `comp`.

The following code snippet demonstrates how to use `sort_by_key` to sort an array of character values using integers as sorting keys. The keys are sorted in descending order using the greater<int> comparison operator.

**Pre** The range `[keys_first, keys_last)` shall not overlap the range `[values_first, values_first + (keys_last - keys_first))`.

### Parameters

- `keys_first`: The beginning of the key sequence.
- `keys_last`: The end of the key sequence.
- `values_first`: The beginning of the value sequence.
- `comp`: Comparison operator.

### Template Parameters

- `RandomAccessIterator1`: is a model of Random Access Iterator, `RandomAccessIterator1` is mutable, and `RandomAccessIterator1`'s `value_type` is convertible to `StrictWeakOrdering`'s `first_argument_type` and `second_argument_type`.
- `RandomAccessIterator2`: is a model of Random Access Iterator, and `RandomAccessIterator2` is mutable.
- `StrictWeakOrdering`: is a model of Strict Weak Ordering.

```
#include <thrust/sort.h>
...
const int N = 6;
int keys[N] = { 1, 4, 2, 8, 5, 7};
char values[N] = {'a', 'b', 'c', 'd', 'e', 'f'};
thrust::stable_sort_by_key(keys, keys + N, values, thrust::greater<int>());
// keys is now { 8, 7, 5, 4, 2, 1}
// values is now { 'd', 'f', 'e', 'b', 'c', 'a'}
```

See <http://www.sgi.com/tech/stl/sort.html>

See `sort_by_key`

See `stable_sort`

## Template Function `thrust::swap(device_reference<T>&, device_reference<T>&)`

### Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::swap`” with arguments `(device_reference<T>&, device_reference<T>&)` in doxygen xml output for project “rocThrust” from directory: `./docBin/xml`. Potential matches:

```
- template<typename Assignable1, typename Assignable2>__host__ __device__ void
→thrust::swap(Assignable1 &, Assignable2 &)
- template<typename T0, typename T1, typename T2, typename T3, typename T4, typename T5, typename T6, typename T7, typename T8, typename T9, typename U0, typename U1, typename U2, typename U3, typename U4, typename U5, typename U6, typename U7, typename U8, typename U9>__host__ __device__ void thrust::swap(tuple < T0, T1, T2, T3, T4, T5, T6, T7, T8, T9 > &, tuple < U0, U1, U2, U3, U4, U5, U6, U7, U8, U9 > &)
- template<typename T1, typename T2>__host__ __device__ void thrust::swap(pair < T1, T2 > &, pair < T1, T2 > &)
- template<typename T>__host__ __device__ void thrust::swap(device_reference < T > &, device_reference < T > &)
```

## Template Function `thrust::swap(pair<T1, T2>&, pair<T1, T2>&)`

### Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “thrust::swap” with arguments (`pair<T1, T2>&`, `pair<T1, T2>&`) in doxygen xml output for project “rocThrust” from directory: ./docBin/xml. Potential matches:

```
- template<typename Assignable1, typename Assignable2>__host__ __device__ void
→thrust::swap(Assignable1 &, Assignable2 &)
- template<typename T0, typename T1, typename T2, typename T3, typename T4,
→typename T5, typename T6, typename T7, typename T8, typename T9, typename U0,
→typename U1, typename U2, typename U3, typename U4, typename U5, typename U6,
→typename U7, typename U8, typename U9>__host__ __device__ void thrust::swap(tuple
→< T0, T1, T2, T3, T4, T5, T6, T7, T8, T9 > &, tuple < U0, U1, U2, U3, U4, U5, U6,
→U7, U8, U9 > &)
- template<typename T1, typename T2>__host__ __device__ void thrust::swap(pair < T1,
→ T2 > &, pair < T1, T2 > &)
- template<typename T>__host__ __device__ void thrust::swap(device_reference < T > &
→, device_reference < T > &)
```

## Template Function `thrust::swap(Assignable1&, Assignable2&)`

### Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “thrust::swap” with arguments (`Assignable1&`, `Assignable2&`) in doxygen xml output for project “rocThrust” from directory: ./docBin/xml. Potential matches:

```
- template<typename Assignable1, typename Assignable2>__host__ __device__ void
→thrust::swap(Assignable1 &, Assignable2 &)
- template<typename T0, typename T1, typename T2, typename T3, typename T4,
→typename T5, typename T6, typename T7, typename T8, typename T9, typename U0,
→typename U1, typename U2, typename U3, typename U4, typename U5, typename U6,
→typename U7, typename U8, typename U9>__host__ __device__ void thrust::swap(tuple
→< T0, T1, T2, T3, T4, T5, T6, T7, T8, T9 > &, tuple < U0, U1, U2, U3, U4, U5, U6,
→U7, U8, U9 > &)
- template<typename T1, typename T2>__host__ __device__ void thrust::swap(pair < T1,
→ T2 > &, pair < T1, T2 > &)
- template<typename T>__host__ __device__ void thrust::swap(device_reference < T > &
→, device_reference < T > &)
```

## Template Function `thrust::swap(tuple<T0, T1, T2, T3, T4, T5, T6, T7, T8, T9>&, tuple<U0, U1, U2, U3, U4, U5, U6, U7, U8, U9>&)`

- Defined in file\_thrust\_tuple.h

## Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “thrust::swap” with arguments (tuple<T0, T1, T2, T3, T4, T5, T6, T7, T8, T9>&, tuple<U0, U1, U2, U3, U4, U5, U6, U7, U8, U9>&) in doxygen xml output for project “rocThrust” from directory: ./docBin/xml. Potential matches:

```
- template<typename Assignable1, typename Assignable2>__host__ __device__ void
→thrust::swap(Assignable1 &, Assignable2 &)
- template<typename T0, typename T1, typename T2, typename T3, typename T4,
→typename T5, typename T6, typename T7, typename T8, typename T9, typename U0,
→typename U1, typename U2, typename U3, typename U4, typename U5, typename U6,
→typename U7, typename U8, typename U9>__host__ __device__ void thrust::swap(tuple
→< T0, T1, T2, T3, T4, T5, T6, T7, T8, T9 > &, tuple < U0, U1, U2, U3, U4, U5, U6,
→U7, U8, U9 > &)
- template<typename T1, typename T2>__host__ __device__ void thrust::swap(pair < T1,
→ T2 > &, pair < T1, T2 > &)
- template<typename T>__host__ __device__ void thrust::swap(device_reference < T > &
→, device_reference < T > &)
```

**Template Function** `thrust::swap_ranges(const thrust::detail::execution_policy_base<DerivedPolicy>&, ForwardIterator1, ForwardIterator1, ForwardIterator2)`

- Defined in file `thrust_swap.h`

## Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “thrust::swap\_ranges” with arguments (const thrust::detail::execution\_policy\_base<DerivedPolicy>&, ForwardIterator1, ForwardIterator1, ForwardIterator2) in doxygen xml output for project “rocThrust” from directory: ./docBin/xml. Potential matches:

```
- template<typename DerivedPolicy, typename ForwardIterator1, typename
→ForwardIterator2>__host__ __device__ ForwardIterator2 thrust::swap_ranges(const
→thrust::detail::execution_policy_base< DerivedPolicy > &, ForwardIterator1,
→ForwardIterator1, ForwardIterator2)
- template<typename ForwardIterator1, typename ForwardIterator2>
  ForwardIterator2 thrust::swap_ranges(ForwardIterator1, ForwardIterator1,
→ForwardIterator2)
```

**Template Function** `thrust::swap_ranges(ForwardIterator1, ForwardIterator1, ForwardIterator2)`

## Function Documentation

```
template<typename ForwardIterator1, typename ForwardIterator2>
ForwardIterator2 thrust::swap_ranges(ForwardIterator1 first1, ForwardIterator1 last1, ForwardItera-
tor2 first2)
```

`swap_ranges` swaps each of the elements in the range  $[first1, \ last1]$  with the corresponding element in the range  $[first2, \ first2 + (last1 - first1)]$ . That is, for each integer  $n$  such that  $0 \leq n < (last1 - first1)$ , it swaps  $*(first1 + n)$  and  $*(first2 + n)$ . The return value is  $first2 + (last1 - first1)$ .

The following code snippet demonstrates how to use `swap_ranges` to swap the contents of two `thrust::device_vectors`.

**Return** An iterator pointing to one position past the last element of the second sequence to swap.

**Pre** `first1` may equal `first2`, but the range  $[first1, \text{last1})$  shall not overlap the range  $[first2, first2 + (\text{last1} - \text{first1}))$  otherwise.

### Parameters

- `first1`: The beginning of the first sequence to swap.
- `last1`: One position past the last element of the first sequence to swap.
- `first2`: The beginning of the second sequence to swap.

### Template Parameters

- `ForwardIterator1`: is a model of `Forward Iterator`, and `ForwardIterator1`'s `value_type` must be convertible to `ForwardIterator2`'s `value_type`.
- `ForwardIterator2`: is a model of `Forward Iterator`, and `ForwardIterator2`'s `value_type` must be convertible to `ForwardIterator1`'s `value_type`.

```
#include <thrust/swap.h>
#include <thrust/device_vector.h>
...
thrust::device_vector<int> v1(2), v2(2);
v1[0] = 1;
v1[1] = 2;
v2[0] = 3;
v2[1] = 4;

thrust::swap_ranges(v1.begin(), v1.end(), v2.begin());
// v1[0] == 3, v1[1] == 4, v2[0] == 1, v2[1] == 2
```

**See** [http://www.sgi.com/tech/stl/swap\\_ranges.html](http://www.sgi.com/tech/stl/swap_ranges.html)

**See** `swap`

## Template Function `thrust::tabulate(const thrust::detail::execution_policy_base<DerivedPolicy>&, ForwardIterator, ForwardIterator, UnaryOperation)`

- Defined in file `thrust_tabulate.h`

### Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::tabulate`” with arguments (`const thrust::detail::execution_policy_base<DerivedPolicy>&`, `ForwardIterator`, `ForwardIterator`, `UnaryOperation`) in doxygen xml output for project “rocThrust” from directory: `./docBin/xml`. Potential matches:

```
- template<typename DerivedPolicy, typename ForwardIterator, typename_
→UnaryOperation> __host__ __device__ void thrust::tabulate(const_
→thrust::detail::execution_policy_base< DerivedPolicy > &, ForwardIterator,_
→ForwardIterator, UnaryOperation)
- template<typename ForwardIterator, typename UnaryOperation>
  void thrust::tabulate(ForwardIterator, ForwardIterator, UnaryOperation)
```

## Template Function `thrust::tabulate(ForwardIterator, ForwardIterator, UnaryOperation)`

### Function Documentation

```
template<typename ForwardIterator, typename UnaryOperation>
void thrust::tabulate(ForwardIterator first, ForwardIterator last, UnaryOperation unary_op)
    tabulate fills the range [first, last) with the value of a function applied to each element's index.
```

For each iterator `i` in the range `[first, last)`, `tabulate` performs the assignment `*i = unary_op(i - first)`.

The following code snippet demonstrates how to use `tabulate` to generate the first `n` non-positive integers:

#### Parameters

- `first`: The beginning of the range.
- `last`: The end of the range.
- `unary_op`: The unary operation to apply.

#### Template Parameters

- `ForwardIterator`: is a model of `Forward Iterator`, and `ForwardIterator` is mutable, and if `x` and `y` are objects of `ForwardIterator`'s `value_type`, then `x + y` is defined, and if `T` is `ForwardIterator`'s `value_type`, then `T(0)` is defined.
- `UnaryOperation`: is a model of `Unary Function` and `UnaryFunction`'s `result_type` is convertible to `OutputIterator`'s `value_type`.

```
#include <thrust/tabulate.h>
#include <thrust/functional.h>
...
const int N = 10;
int A[N];
thrust::tabulate(A, A + 10, thrust::negate<int>());
// A is now {0, -1, -2, -3, -4, -5, -6, -7, -8, -9}
```

See `thrust::fill`

See `thrust::generate`

See `thrust::sequence`

## Template Function `thrust::tan`

- Defined in file `thrust_complex.h`

### Function Documentation

```
template<typename T> __host__ __device__ complex<T> thrust::tan(const complex < T > & z)
    Returns the complex tangent of a complex number.
```

#### Parameters

- z: The complex argument.

### Template Function thrust::tanh

- Defined in file\_thrust\_complex.h

### Function Documentation

```
template<typename T> __host__ __device__ complex<T> thrust::tanh(const complex < T > & z)
    Returns the complex hyperbolic tangent of a complex number.
```

#### Parameters

- z: The complex argument.

### Template Function thrust::THRUST\_PREVENT\_MACRO\_SUBSTITUTION(const T&, const T&, BinaryPredicate)

### Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “thrust::THRUST\_PREVENT\_MACRO\_SUBSTITUTION” with arguments (const T&, const T&, BinaryPredicate) in doxygen xml output for project “rocThrust” from directory: ./docBin/xml. Potential matches:

```
- template<typename T, typename BinaryPredicate> __host__ __device__ T max_
  ↵thrust::THRUST_PREVENT_MACRO_SUBSTITUTION(const T &, const T &, BinaryPredicate)
- template<typename T, typename BinaryPredicate> __host__ __device__ T min_
  ↵thrust::THRUST_PREVENT_MACRO_SUBSTITUTION(const T &, const T &, BinaryPredicate)
- template<typename T> __host__ __device__ T max thrust::THRUST_PREVENT_MACRO_
  ↵SUBSTITUTION(const T &, const T &)
- template<typename T> __host__ __device__ T min thrust::THRUST_PREVENT_MACRO_
  ↵SUBSTITUTION(const T &, const T &)
```

### Template Function thrust::THRUST\_PREVENT\_MACRO\_SUBSTITUTION(const T&, const T&)

### Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “thrust::THRUST\_PREVENT\_MACRO\_SUBSTITUTION” with arguments (const T&, const T&) in doxygen xml output for project “rocThrust” from directory: ./docBin/xml. Potential matches:

```
- template<typename T, typename BinaryPredicate> __host__ __device__ T max_
  ↵thrust::THRUST_PREVENT_MACRO_SUBSTITUTION(const T &, const T &, BinaryPredicate)
- template<typename T, typename BinaryPredicate> __host__ __device__ T min_
  ↵thrust::THRUST_PREVENT_MACRO_SUBSTITUTION(const T &, const T &, BinaryPredicate)
- template<typename T> __host__ __device__ T max thrust::THRUST_PREVENT_MACRO_
  ↵SUBSTITUTION(const T &, const T &)
- template<typename T> __host__ __device__ T min thrust::THRUST_PREVENT_MACRO_
  ↵SUBSTITUTION(const T &, const T &)
```

**Template Function `thrust::THRUST_PREVENT_MACRO_SUBSTITUTION(const T&, const T&, BinaryPredicate)`****Function Documentation**

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::THRUST_PREVENT_MACRO_SUBSTITUTION`” with arguments (`const T&`, `const T&`, `BinaryPredicate`) in doxygen xml output for project “rocThrust” from directory: ./docBin/xml. Potential matches:

```
- template<typename T, typename BinaryPredicate> __host__ __device__ T max_
  ↵thrust::THRUST_PREVENT_MACRO_SUBSTITUTION(const T &, const T &, BinaryPredicate)
- template<typename T, typename BinaryPredicate> __host__ __device__ T min_
  ↵thrust::THRUST_PREVENT_MACRO_SUBSTITUTION(const T &, const T &, BinaryPredicate)
- template<typename T> __host__ __device__ T max thrust::THRUST_PREVENT_MACRO_
  ↵SUBSTITUTION(const T &, const T &)
- template<typename T> __host__ __device__ T min thrust::THRUST_PREVENT_MACRO_
  ↵SUBSTITUTION(const T &, const T &)
```

**Template Function `thrust::THRUST_PREVENT_MACRO_SUBSTITUTION(const T&, const T&)`****Function Documentation**

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::THRUST_PREVENT_MACRO_SUBSTITUTION`” with arguments (`const T&`, `const T&`) in doxygen xml output for project “rocThrust” from directory: ./docBin/xml. Potential matches:

```
- template<typename T, typename BinaryPredicate> __host__ __device__ T max_
  ↵thrust::THRUST_PREVENT_MACRO_SUBSTITUTION(const T &, const T &, BinaryPredicate)
- template<typename T, typename BinaryPredicate> __host__ __device__ T min_
  ↵thrust::THRUST_PREVENT_MACRO_SUBSTITUTION(const T &, const T &, BinaryPredicate)
- template<typename T> __host__ __device__ T max thrust::THRUST_PREVENT_MACRO_
  ↵SUBSTITUTION(const T &, const T &)
- template<typename T> __host__ __device__ T min thrust::THRUST_PREVENT_MACRO_
  ↵SUBSTITUTION(const T &, const T &)
```

**Template Function `thrust::tie(T0&)`**

- Defined in file `thrust_tuple.h`

**Function Documentation**

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::tie`” with arguments (`T0&`) in doxygen xml output for project “rocThrust” from directory: ./docBin/xml. Potential matches:

```
- template<typename T0, typename T1> __host__ __device__ tuple<T0&, T1&>_
  ↵thrust::tie(T0 &, T1 &)
- template<typename T0> __host__ __device__ tuple<T0&> thrust::tie(T0 &)
```

## Template Function `thrust::tie(T0&, T1&)`

### Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::tie`” with arguments `(T0&, T1&)` in doxygen xml output for project “rocThrust” from directory: `./docBin/xml`. Potential matches:

```
- template<typename T0, typename T1>__host__ __device__ tuple<T0&, T1&>_
  ↪thrust::tie(T0 &, T1 &)
- template<typename T0>__host__ __device__ tuple<T0&> thrust::tie(T0 &)
```

## Template Function `thrust::transform(const thrust::detail::execution_policy_base<DerivedPolicy>&, InputIterator, InputIterator, OutputIterator, UnaryFunction)`

- Defined in file `thrust_transform.h`

### Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::transform`” with arguments `(const thrust::detail::execution_policy_base<DerivedPolicy>&, InputIterator, InputIterator, OutputIterator, UnaryFunction)` in doxygen xml output for project “rocThrust” from directory: `./docBin/xml`. Potential matches:

```
- template<typename DerivedPolicy, typename InputIterator, typename OutputIterator,_
  ↪typename UnaryFunction>__host__ __device__ OutputIterator thrust::transform(const_
  ↪thrust::detail::execution_policy_base< DerivedPolicy > &, InputIterator,_
  ↪InputIterator, OutputIterator, UnaryFunction)
- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2,_
  ↪typename OutputIterator, typename BinaryFunction>__host__ __device___
  ↪OutputIterator thrust::transform(const thrust::detail::execution_policy_base<_
  ↪DerivedPolicy > &, InputIterator1, InputIterator1, InputIterator2, OutputIterator,_
  ↪BinaryFunction)
- template<typename InputIterator, typename OutputIterator, typename UnaryFunction>
  OutputIterator thrust::transform(InputIterator, InputIterator, OutputIterator,_
  ↪UnaryFunction)
- template<typename InputIterator1, typename InputIterator2, typename_
  ↪OutputIterator, typename BinaryFunction>
  OutputIterator thrust::transform(InputIterator1, InputIterator1, InputIterator2,_
  ↪OutputIterator, BinaryFunction)
```

## Template Function `thrust::transform(InputIterator, InputIterator, OutputIterator, UnaryFunction)`

### Function Documentation

```
template<typename InputIterator, typename OutputIterator, typename UnaryFunction>
OutputIterator thrust::transform(InputIterator first, InputIterator last, OutputIterator result, Unary-
Function op)
```

This version of `transform` applies a unary function to each element of an input sequence and stores the result in the corresponding position in an output sequence. Specifically, for each iterator `i` in the range `[first, last)` the operation `op(*i)` is performed and the result is assigned to `*o`, where `o` is the corresponding output

iterator in the range [result, result + (last - first) ). The input and output sequences may coincide, resulting in an in-place transformation.

The following code snippet demonstrates how to use `transform`

**Return** The end of the output sequence.

**Pre** `first` may equal `result`, but the range `[first, last)` shall not overlap the range `[result, result + (last - first))` otherwise.

#### Parameters

- `first`: The beginning of the input sequence.
- `last`: The end of the input sequence.
- `result`: The beginning of the output sequence.
- `op`: The transformation operation.

#### Template Parameters

- `InputIterator`: is a model of `Input Iterator` and `InputIterator`'s `value_type` is convertible to `UnaryFunction`'s `argument_type`.
- `OutputIterator`: is a model of `Output Iterator`.
- `UnaryFunction`: is a model of `Unary Function` and `UnaryFunction`'s `result_type` is convertible to `OutputIterator`'s `value_type`.

```
#include <thrust/transform.h>
#include <thrust/functional.h>

int data[10] = {-5, 0, 2, -3, 2, 4, 0, -1, 2, 8};

thrust::negate<int> op;

thrust::transform(data, data + 10, data, op); // in-place transformation

// data is now {5, 0, -2, 3, -2, -4, 0, 1, -2, -8};
```

See <http://www.sgi.com/tech/stl/transform.html>

**Template Function** `thrust::transform(const thrust::detail::execution_policy_base<DerivedPolicy>&, InputIterator1, InputIterator1, InputIterator2, OutputIterator, BinaryFunction)`

#### Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::transform`” with arguments `(const thrust::detail::execution_policy_base<DerivedPolicy>&, InputIterator1, InputIterator1, InputIterator2, OutputIterator, BinaryFunction)` in doxygen xml output for project “rocThrust” from directory: ./docBin/xml. Potential matches:

```

- template<typename DerivedPolicy, typename InputIterator, typename OutputIterator,
        typename UnaryFunction> __host__ __device__ OutputIterator thrust::transform(const
        thrust::detail::execution_policy_base< DerivedPolicy > &, InputIterator,
        InputIterator, OutputIterator, UnaryFunction)
- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2,
        typename OutputIterator, typename BinaryFunction> __host__ __device__
        OutputIterator thrust::transform(const thrust::detail::execution_policy_base<
```

$$\begin{aligned} &\text{DerivedPolicy} && \text{InputIterator1, InputIterator2, OutputIterator,} \\ &\text{BinaryFunction)} && \text{OutputIterator thrust::transform(InputIterator1, InputIterator1, InputIterator2, OutputIterator,} \\ &\text{BinaryFunction)} && \text{OutputIterator, BinaryFunction)} \end{aligned}$$

## Template Function `thrust::transform(InputIterator1, InputIterator1, InputIterator2, OutputIterator, BinaryFunction)`

### Function Documentation

```
template<typename InputIterator1, typename InputIterator2, typename OutputIterator, typename BinaryFunction,
OutputIterator thrust::transform(InputIterator1 first1, InputIterator1 last1, InputIterator2 first2, Out-
putIterator result, BinaryFunction op)
```

This version of transform applies a binary function to each pair of elements from two input sequences and stores the result in the corresponding position in an output sequence. Specifically, for each iterator  $i$  in the range  $[first1, last1]$  and  $j = first + (i - first1)$  in the range  $[first2, last2]$  the operation  $op(*i, *j)$  is performed and the result is assigned to  $*o$ , where  $o$  is the corresponding output iterator in the range  $[result, result + (last - first)]$ . The input and output sequences may coincide, resulting in an in-place transformation.

The following code snippet demonstrates how to use transform

**Return** The end of the output sequence.

**Pre**  $first1$  may equal  $result$ , but the range  $[first1, last1]$  shall not overlap the range  $[result, result + (last1 - first1)]$  otherwise.

**Pre**  $first2$  may equal  $result$ , but the range  $[first2, first2 + (last1 - first1)]$  shall not overlap the range  $[result, result + (last1 - first1)]$  otherwise.

### Parameters

- $first1$ : The beginning of the first input sequence.
- $last1$ : The end of the first input sequence.
- $first2$ : The beginning of the second input sequence.
- $result$ : The beginning of the output sequence.
- $op$ : The transformation operation.

### Template Parameters

- $InputIterator1$ : is a model of `Input Iterator` and  $InputIterator1$ 's `value_type` is convertible to  $BinaryFunction$ 's `first_argument_type`.

- `InputIterator2`: is a model of `Input Iterator` and `InputIterator2`'s `value_type` is convertible to `BinaryFunction`'s `second_argument_type`.
- `OutputIterator`: is a model of `Output Iterator`.
- `BinaryFunction`: is a model of `Binary Function` and `BinaryFunction`'s `result_type` is convertible to `OutputIterator`'s `value_type`.

```
#include <thrust/transform.h>
#include <thrust/functional.h>

int input1[6] = {-5, 0, 2, 3, 2, 4};
int input2[6] = { 3, 6, -2, 1, 2, 3};
int output[6];

thrust::plus<int> op;

thrust::transform(input1, input1 + 6, input2, output, op);

// output is now {-2, 6, 0, 4, 4, 7};
```

See <http://www.sgi.com/tech/stl/transform.html>

### Template Function `thrust::transform_exclusive_scan(const thrust::detail::execution_policy_base<DerivedPolicy>&, InputIterator, InputIterator, OutputIterator, UnaryFunction, T, AssociativeOperator)`

- Defined in file `_thrust_transform_scan.h`

#### Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::transform_exclusive_scan`” with arguments (`const thrust::detail::execution_policy_base<DerivedPolicy>&`, `InputIterator`, `InputIterator`, `OutputIterator`, `UnaryFunction`, `T`, `AssociativeOperator`) in doxygen xml output for project “rocThrust” from directory: `./docBin/xml`. Potential matches:

```
- template<typename DerivedPolicy, typename InputIterator, typename OutputIterator, typename UnaryFunction, typename T, typename AssociativeOperator> __host__ __device__ OutputIterator thrust::transform_exclusive_scan(const thrust::detail::execution_policy_base< DerivedPolicy > &, InputIterator, InputIterator, OutputIterator, UnaryFunction, T, AssociativeOperator)
- template<typename InputIterator, typename OutputIterator, typename UnaryFunction, typename T, typename AssociativeOperator>
  OutputIterator thrust::transform_exclusive_scan(InputIterator, InputIterator, OutputIterator, UnaryFunction, T, AssociativeOperator)
```

### Template Function `thrust::transform_exclusive_scan(InputIterator, InputIterator, OutputIterator, UnaryFunction, T, AssociativeOperator)`

#### Function Documentation

```
template<typename InputIterator, typename OutputIterator, typename UnaryFunction, typename T, typename AssociativeOperator>
```

---

`OutputIterator thrust::transform_exclusive_scan (InputIterator first, InputIterator last, OutputIterator result, UnaryFunction unary_op, T init, AssociativeOperator binary_op)`

`transform_exclusive_scan` fuses the `transform` and `exclusive_scan` operations. `transform_exclusive_scan` is equivalent to performing a transformation defined by `unary_op` into a temporary sequence and then performing an `exclusive_scan` on the transformed sequence. In most cases, fusing these two operations together is more efficient, since fewer memory reads and writes are required. In `transform_exclusive_scan`, `init` is assigned to `*result` and the result of `binary_op`(`init`, `unary_op(*first)`) is assigned to `*(result + 1)`, and so on. The transform scan operation is permitted to be in-place.

The following code snippet demonstrates how to use `transform_exclusive_scan`

**Return** The end of the output sequence.

**Pre** `first` may equal `result`, but the range `[first, last)` and the range `[result, result + (last - first))` shall not overlap otherwise.

### Parameters

- `first`: The beginning of the input sequence.
- `last`: The end of the input sequence.
- `result`: The beginning of the output sequence.
- `unary_op`: The function used to transform the input sequence.
- `init`: The initial value of the `exclusive_scan`
- `binary_op`: The associative operator used to ‘sum’ transformed values.

### Template Parameters

- `InputIterator`: is a model of `Input Iterator` and `InputIterator`'s `value_type` is convertible to `unary_op`'s input type.
- `OutputIterator`: is a model of `Output Iterator`.
- `UnaryFunction`: is a model of `Unary Function` and accepts inputs of `InputIterator`'s `value_type`. `UnaryFunction`'s `result_type` is convertible to `OutputIterator`'s `value_type`.
- `T`: is convertible to `OutputIterator`'s `value_type`.
- `AssociativeOperator`: is a model of `Binary Function` and `AssociativeOperator`'s `result_type` is convertible to `OutputIterator`'s `value_type`.

```
#include <thrust/transform_scan.h>

int data[6] = {1, 0, 2, 2, 1, 3};

thrust::negate<int> unary_op;
thrust::plus<int> binary_op;

thrust::transform_exclusive_scan(data, data + 6, data, unary_op, 4, binary_op); // 
    ↳ in-place scan

// data is now {4, 3, 3, 1, -1, -2}
```

**See** `transform`

**See** `exclusive_scan`

**Template Function `thrust::transform_if(const thrust::detail::execution_policy_base<DerivedPolicy>&, InputIterator, InputIterator, ForwardIterator, UnaryFunction, Predicate)`**

- Defined in file `thrust_transform.h`

**Function Documentation**

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::transform_if`” with arguments (`const thrust::detail::execution_policy_base<DerivedPolicy>&`, `InputIterator`, `InputIterator`, `ForwardIterator`, `UnaryFunction`, `Predicate`) in doxygen xml output for project “rocThrust” from directory: `./docBin/xml`. Potential matches:

```
- template<typename DerivedPolicy, typename InputIterator, typename ForwardIterator,
→ typename UnaryFunction, typename Predicate> __host__ __device__ ForwardIterator
→ thrust::transform_if(const thrust::detail::execution_policy_base< DerivedPolicy >_
→ &, InputIterator, InputIterator, ForwardIterator, UnaryFunction, Predicate)
- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2,
→ typename ForwardIterator, typename UnaryFunction, typename Predicate> __host__ __
→ device__ ForwardIterator thrust::transform_if(const thrust::detail::execution_
→ policy_base< DerivedPolicy > &, InputIterator1, InputIterator1, InputIterator2,_
→ ForwardIterator, UnaryFunction, Predicate)
- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2,
→ typename InputIterator3, typename ForwardIterator, typename BinaryFunction,_
→ typename Predicate> __host__ __device__ ForwardIterator thrust::transform_if(const_
→ thrust::detail::execution_policy_base< DerivedPolicy > &, InputIterator1,_
→ InputIterator1, InputIterator2, InputIterator3, ForwardIterator, BinaryFunction,_
→ Predicate)
- template<typename InputIterator, typename ForwardIterator, typename UnaryFunction,
→ typename Predicate>
→ ForwardIterator thrust::transform_if(InputIterator, InputIterator,_
→ ForwardIterator, UnaryFunction, Predicate)
- template<typename InputIterator1, typename InputIterator2, typename_
→ ForwardIterator, typename UnaryFunction, typename Predicate>
→ ForwardIterator thrust::transform_if(InputIterator1, InputIterator1,_
→ InputIterator2, ForwardIterator, UnaryFunction, Predicate)
- template<typename InputIterator1, typename InputIterator2, typename_
→ InputIterator3, typename ForwardIterator, typename BinaryFunction, typename_
→ Predicate>
→ ForwardIterator thrust::transform_if(InputIterator1, InputIterator1,_
→ InputIterator2, InputIterator3, ForwardIterator, BinaryFunction, Predicate)
```

**Template Function `thrust::transform_if(InputIterator, InputIterator, ForwardIterator, UnaryFunction, Predicate)`****Function Documentation**

```
template<typename InputIterator, typename ForwardIterator, typename UnaryFunction, typename Predicate>
ForwardIterator thrust::transform_if(InputIterator first, InputIterator last, ForwardIterator result,
→ UnaryFunction op, Predicate pred)
```

This version of `transform_if` conditionally applies a unary function to each element of an input sequence and stores the result in the corresponding position in an output sequence if the corresponding position in the input sequence satisfies a predicate. Otherwise, the corresponding position in the output sequence is not modified.

Specifically, for each iterator `i` in the range `[first, last)` the predicate `pred(*i)` is evaluated. If this predicate evaluates to `true`, the result of `op(*i)` is assigned to `*o`, where `o` is the corresponding output iterator in the range `[result, result + (last - first))`. Otherwise, `op(*i)` is not evaluated and no assignment occurs. The input and output sequences may coincide, resulting in an in-place transformation.

The following code snippet demonstrates how to use `transform_if`:

**Return** The end of the output sequence.

**Pre** `first` may equal `result`, but the range `[first, last)` shall not overlap the range `[result, result + (last - first))` otherwise.

### Parameters

- `first`: The beginning of the input sequence.
- `last`: The end of the input sequence.
- `result`: The beginning of the output sequence.
- `op`: The transformation operation.
- `pred`: The predicate operation.

### Template Parameters

- `InputIterator`: is a model of [Input Iterator](#), and `InputIterator`'s `value_type` is convertible to `Predicate`'s `argument_type`, and `InputIterator`'s `value_type` is convertible to `UnaryFunction`'s `argument_type`.
- `ForwardIterator`: is a model of [Forward Iterator](#).
- `UnaryFunction`: is a model of [Unary Function](#) and `UnaryFunction`'s `result_type` is convertible to `OutputIterator`'s `value_type`.
- `Predicate`: is a model of [Predicate](#).

```
#include <thrust/transform.h>
#include <thrust/functional.h>

int data[10] = {-5, 0, 2, -3, 2, 4, 0, -1, 2, 8};

struct is_odd
{
    __host__ __device__
    bool operator()(int x)
    {
        return x % 2;
    }
};

thrust::negate<int> op;
thrust::identity<int> identity;

// negate odd elements
thrust::transform_if(data, data + 10, data, op, is_odd()); // in-place
// transformation

// data is now {5, 0, 2, 3, 2, 4, 0, 1, 2, 8};
```

See `thrust::transform`

**Template Function `thrust::transform_if(const thrust::detail::execution_policy_base<DerivedPolicy>&, InputIterator1, InputIterator1, InputIterator2, ForwardIterator, UnaryFunction, Predicate)`**

## Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::transform_if`” with arguments (`const thrust::detail::execution_policy_base<DerivedPolicy>&`, `InputIterator1`, `InputIterator1`, `InputIterator2`, `ForwardIterator`, `UnaryFunction`, `Predicate`) in doxygen xml output for project “rocThrust” from directory: `./docBin/xml`. Potential matches:

```
- template<typename DerivedPolicy, typename InputIterator, typename ForwardIterator,
→ typename UnaryFunction, typename Predicate> __host__ __device__ ForwardIterator
→ thrust::transform_if(const thrust::detail::execution_policy_base< DerivedPolicy >_
→ &, InputIterator, InputIterator, ForwardIterator, UnaryFunction, Predicate)
- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2,
→ typename ForwardIterator, typename UnaryFunction, typename Predicate> __host__ __
→ device__ ForwardIterator thrust::transform_if(const thrust::detail::execution_
→ policy_base< DerivedPolicy > &, InputIterator1, InputIterator1, InputIterator2,_
→ ForwardIterator, UnaryFunction, Predicate)
- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2,
→ typename InputIterator3, typename ForwardIterator, typename BinaryFunction,&_
→ typename Predicate> __host__ __device__ ForwardIterator thrust::transform_if(const_
→ thrust::detail::execution_policy_base< DerivedPolicy > &, InputIterator1,_
→ InputIterator1, InputIterator2, InputIterator3, ForwardIterator, BinaryFunction,&_
→ Predicate)
- template<typename InputIterator, typename ForwardIterator, typename UnaryFunction,
→ typename Predicate>
  ForwardIterator thrust::transform_if(InputIterator, InputIterator,_
→ ForwardIterator, UnaryFunction, Predicate)
- template<typename InputIterator1, typename InputIterator2, typename_
→ ForwardIterator, typename UnaryFunction, typename Predicate>
  ForwardIterator thrust::transform_if(InputIterator1, InputIterator1,_
→ InputIterator2, ForwardIterator, UnaryFunction, Predicate)
- template<typename InputIterator1, typename InputIterator2, typename_
→ InputIterator3, typename ForwardIterator, typename BinaryFunction, typename_
→ Predicate>
  ForwardIterator thrust::transform_if(InputIterator1, InputIterator1,_
→ InputIterator2, InputIterator3, ForwardIterator, BinaryFunction, Predicate)
```

**Template Function `thrust::transform_if(InputIterator1, InputIterator1, InputIterator2, ForwardIterator, UnaryFunction, Predicate)`**

## Function Documentation

```
template<typename InputIterator1, typename InputIterator2, typename ForwardIterator, typename UnaryFunction>
ForwardIterator thrust::transform_if(InputIterator1 first, InputIterator1 last, InputIterator2 stencil,
→ ForwardIterator result, UnaryFunction op, Predicate pred)
```

This version of `transform_if` conditionally applies a unary function to each element of an input sequence and stores the result in the corresponding position in an output sequence if the corresponding position in a stencil sequence satisfies a predicate. Otherwise, the corresponding position in the output sequence is not modified.

Specifically, for each iterator `i` in the range `[first, last)` the predicate `pred(*s)` is evaluated, where `s` is the corresponding input iterator in the range `[stencil, stencil + (last - first) )`. If this predicate evaluates to `true`, the result of `op(*i)` is assigned to `*o`, where `o` is the corresponding output

iterator in the range [result, result + (last - first) ]. Otherwise, `op(*i)` is not evaluated and no assignment occurs. The input and output sequences may coincide, resulting in an in-place transformation.

The following code snippet demonstrates how to use `transform_if`:

**Return** The end of the output sequence.

**Pre** `first` may equal `result`, but the range [`first`, `last`] shall not overlap the range [`result`, `result + (last - first)`) otherwise.

**Pre** `stencil` may equal `result`, but the range [`stencil`, `stencil + (last - first)`) shall not overlap the range [`result`, `result + (last - first)`) otherwise.

### Parameters

- `first`: The beginning of the input sequence.
- `last`: The end of the input sequence.
- `stencil`: The beginning of the stencil sequence.
- `result`: The beginning of the output sequence.
- `op`: The transformation operation.
- `pred`: The predicate operation.

### Template Parameters

- `InputIterator1`: is a model of `Input Iterator` and `InputIterator1`'s `value_type` is convertible to `UnaryFunction`'s `argument_type`.
- `InputIterator2`: is a model of `Input Iterator` and `InputIterator2`'s `value_type` is convertible to `Predicate`'s `argument_type`.
- `ForwardIterator`: is a model of `Forward Iterator`.
- `UnaryFunction`: is a model of `Unary Function` and `UnaryFunction`'s `result_type` is convertible to `OutputIterator`'s `value_type`.
- `Predicate`: is a model of `Predicate`.

```
#include <thrust/transform.h>
#include <thrust/functional.h>

int data[10]    = {-5, 0, 2, -3, 2, 4, 0, -1, 2, 8};
int stencil[10] = { 1, 0, 1, 0, 1, 0, 1, 0, 1, 0};

thrust::negate<int> op;
thrust::identity<int> identity;

thrust::transform_if(data, data + 10, stencil, data, op, identity); // in-place
//transformation

// data is now {5, 0, -2, -3, -2, 4, 0, -1, -2, 8};
```

See `thrust::transform`

**Template Function** `thrust::transform_if(const thrust::detail::execution_policy_base<DerivedPolicy>&, InputIterator1, InputIterator1, InputIterator2, InputIterator3, ForwardIterator, BinaryFunction, Predicate)`

## Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “thrust::transform\_if” with arguments (const thrust::detail::execution\_policy\_base<DerivedPolicy>&, InputIterator1, InputIterator1, InputIterator2, InputIterator3, ForwardIterator, BinaryFunction, Predicate) in doxygen xml output for project “rocThrust” from directory: ./docBin/xml. Potential matches:

```
- template<typename DerivedPolicy, typename InputIterator, typename ForwardIterator,
→ typename UnaryFunction, typename Predicate>__host__ __device__ ForwardIterator
→thrust::transform_if(const thrust::detail::execution_policy_base< DerivedPolicy >
→&, InputIterator, InputIterator, ForwardIterator, UnaryFunction, Predicate)
- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2,
→ typename ForwardIterator, typename UnaryFunction, typename Predicate>__host__ __
→device__ ForwardIterator thrust::transform_if(const thrust::detail::execution_
→policy_base< DerivedPolicy > &, InputIterator1, InputIterator1, InputIterator2,
→ForwardIterator, UnaryFunction, Predicate)
- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2,
→ typename InputIterator3, typename ForwardIterator, typename BinaryFunction,
→typename Predicate>__host__ __device__ ForwardIterator thrust::transform_if(const
→thrust::detail::execution_policy_base< DerivedPolicy > &, InputIterator1,
→InputIterator1, InputIterator2, InputIterator3, ForwardIterator, BinaryFunction,
→Predicate)
- template<typename InputIterator, typename ForwardIterator, typename UnaryFunction,
→ typename Predicate>
→ ForwardIterator thrust::transform_if(InputIterator, InputIterator,
→ForwardIterator, UnaryFunction, Predicate)
- template<typename InputIterator1, typename InputIterator2, typename_
→ForwardIterator, typename UnaryFunction, typename Predicate>
→ ForwardIterator thrust::transform_if(InputIterator1, InputIterator1,
→InputIterator2, ForwardIterator, UnaryFunction, Predicate)
- template<typename InputIterator1, typename InputIterator2, typename_
→InputIterator3, typename ForwardIterator, typename BinaryFunction, typename_
→Predicate>
→ ForwardIterator thrust::transform_if(InputIterator1, InputIterator1,
→InputIterator2, InputIterator3, ForwardIterator, BinaryFunction, Predicate)
```

### Template Function thrust::transform\_if(InputIterator1, InputIterator1, InputIterator2, InputIterator3, ForwardIterator, BinaryFunction, Predicate)

#### Function Documentation

```
template<typename InputIterator1, typename InputIterator2, typename InputIterator3, typename ForwardIterator
ForwardIterator thrust::transform_if(InputIterator1 first1, InputIterator1 last1, InputIterator2 first2,
→ InputIterator3 stencil, ForwardIterator result, BinaryFunction
→ binary_op, Predicate pred)
```

This version of transform\_if conditionally applies a binary function to each pair of elements from two input sequences and stores the result in the corresponding position in an output sequence if the corresponding position in a stencil sequence satisfies a predicate. Otherwise, the corresponding position in the output sequence is not modified.

Specifically, for each iterator  $i$  in the range  $[first1, last1]$  and  $j = first2 + (i - first1)$  in the range  $[first2, first2 + (last1 - first1)]$ , the predicate  $pred(*s)$  is evaluated, where  $s$  is the corresponding input iterator in the range  $[stencil, stencil + (last1 - first1)]$ . If this predicate evaluates to true, the result of  $binary\_op(*i, *j)$  is assigned to  $*o$ , where  $o$  is the

corresponding output iterator in the range `[result, result + (last1 - first1)]`. Otherwise, `binary_op(*i,*j)` is not evaluated and no assignment occurs. The input and output sequences may coincide, resulting in an in-place transformation.

The following code snippet demonstrates how to use `transform_if`:

**Return** The end of the output sequence.

**Pre** `first1` may equal `result`, but the range `[first1, last1]` shall not overlap the range `[result, result + (last1 - first1)]` otherwise.

**Pre** `first2` may equal `result`, but the range `[first2, first2 + (last1 - first1)]` shall not overlap the range `[result, result + (last1 - first1)]` otherwise.

**Pre** `stencil` may equal `result`, but the range `[stencil, stencil + (last1 - first1)]` shall not overlap the range `[result, result + (last1 - first1)]` otherwise.

### Parameters

- `first1`: The beginning of the first input sequence.
- `last1`: The end of the first input sequence.
- `first2`: The beginning of the second input sequence.
- `stencil`: The beginning of the stencil sequence.
- `result`: The beginning of the output sequence.
- `binary_op`: The transformation operation.
- `pred`: The predicate operation.

### Template Parameters

- `InputIterator1`: is a model of `Input Iterator` and `InputIterator1`'s `value_type` is convertible to `BinaryFunction`'s `first_argument_type`.
- `InputIterator2`: is a model of `Input Iterator` and `InputIterator2`'s `value_type` is convertible to `BinaryFunction`'s `second_argument_type`.
- `ForwardIterator`: is a model of `Forward Iterator`.
- `BinaryFunction`: is a model of `Binary Function` and `BinaryFunction`'s `result_type` is convertible to `OutputIterator`'s `value_type`.
- `Predicate`: is a model of `Predicate`.

```
#include <thrust/transform.h>
#include <thrust/functional.h>

int input1[6] = {-5, 0, 2, 3, 2, 4};
int input2[6] = { 3, 6, -2, 1, 2, 3};
int stencil[8] = { 1, 0, 1, 0, 1, 0};
int output[6];

thrust::plus<int> op;
thrust::identity<int> identity;

thrust::transform_if(input1, input1 + 6, input2, stencil, output, op, identity);

// output is now {-2, 0, 0, 3, 4, 4};
```

**See** `thrust::transform`

**Template Function `thrust::transform_inclusive_scan(const thrust::detail::execution_policy_base<DerivedPolicy>&, InputIterator, InputIterator, OutputIterator, UnaryFunction, AssociativeOperator)`**

- Defined in file `thrust_transform_scan.h`

**Function Documentation**

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::transform_inclusive_scan`” with arguments (`const thrust::detail::execution_policy_base<DerivedPolicy>&`, `InputIterator`, `InputIterator`, `OutputIterator`, `UnaryFunction`, `AssociativeOperator`) in doxygen xml output for project “rocThrust” from directory: `./docBin/xml`. Potential matches:

```
- template<typename DerivedPolicy, typename InputIterator, typename OutputIterator,
         typename UnaryFunction, typename AssociativeOperator> __host__ __device__
         OutputIterator thrust::transform_inclusive_scan(const thrust::detail::execution_
         policy_base< DerivedPolicy > &, InputIterator, InputIterator, OutputIterator,
         UnaryFunction, AssociativeOperator)
- template<typename InputIterator, typename OutputIterator, typename UnaryFunction,
         typename AssociativeOperator>
         OutputIterator thrust::transform_inclusive_scan(InputIterator, InputIterator,
         OutputIterator, UnaryFunction, AssociativeOperator)
```

**Template Function `thrust::transform_inclusive_scan(InputIterator, InputIterator, OutputIterator, UnaryFunction, AssociativeOperator)`****Function Documentation**

```
template<typename InputIterator, typename OutputIterator, typename UnaryFunction, typename AssociativeOperator>
OutputIterator thrust::transform_inclusive_scan(InputIterator first, InputIterator last, OutputIterator result, UnaryFunction unary_op, AssociativeOperator binary_op)
```

`transform_inclusive_scan` fuses the `transform` and `inclusive_scan` operations. `transform_inclusive_scan` is equivalent to performing a transformation defined by `unary_op` into a temporary sequence and then performing an `inclusive_scan` on the transformed sequence. In most cases, fusing these two operations together is more efficient, since fewer memory reads and writes are required. In `transform_inclusive_scan`, `unary_op(*first)` is assigned to `*result` and the result of `binary_op(unary_op(*first), unary_op(*(first + 1)))` is assigned to `*(result + 1)`, and so on. The transform scan operation is permitted to be in-place.

The following code snippet demonstrates how to use `transform_inclusive_scan`

**Return** The end of the output sequence.

**Pre** `first` may equal `result`, but the range `[first, last)` and the range `[result, result + (last - first))` shall not overlap otherwise.

**Parameters**

- `first`: The beginning of the input sequence.
- `last`: The end of the input sequence.
- `result`: The beginning of the output sequence.
- `unary_op`: The function used to transform the input sequence.

- `binary_op`: The associative operator used to ‘sum’ transformed values.

### Template Parameters

- `InputIterator`: is a model of `Input Iterator` and `InputIterator`'s `value_type` is convertible to `unary_op`'s input type.
- `OutputIterator`: is a model of `Output Iterator`.
- `UnaryFunction`: is a model of `Unary Function` and accepts inputs of `InputIterator`'s `value_type`. `UnaryFunction`'s `result_type` is convertible to `OutputIterator`'s `value_type`.
- `AssociativeOperator`: is a model of `Binary Function` and `AssociativeOperator`'s `result_type` is convertible to `OutputIterator`'s `value_type`.

```
#include <thrust/transform_scan.h>

int data[6] = {1, 0, 2, 2, 1, 3};

thrust::negate<int> unary_op;
thrust::plus<int> binary_op;

thrust::transform_inclusive_scan(data, data + 6, data, unary_op, binary_op); // ↵
// in-place scan

// data is now {-1, -1, -3, -5, -6, -9}
```

**See** `transform`

**See** `inclusive_scan`

## Template Function `thrust::transform_reduce(const thrust::detail::execution_policy_base<DerivedPolicy>&, InputIterator, InputIterator, UnaryFunction, OutputType, BinaryFunction)`

- Defined in file `_thrust_transform_reduce.h`

## Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::transform_reduce`” with arguments (`const thrust::detail::execution_policy_base<DerivedPolicy>&`, `InputIterator`, `InputIterator`, `UnaryFunction`, `OutputType`, `BinaryFunction`) in doxygen xml output for project “rocThrust” from directory: `./docBin/xml`. Potential matches:

```
- template<typename DerivedPolicy, typename InputIterator, typename UnaryFunction, ↵
→ typename OutputType, typename BinaryFunction> __host__ __device__ OutputType ↵
→ thrust::transform_reduce(const thrust::detail::execution_policy_base< ↵
→ DerivedPolicy > &, InputIterator, InputIterator, UnaryFunction, OutputType, ↵
→ BinaryFunction)
- template<typename InputIterator, typename UnaryFunction, typename OutputType, ↵
→ typename BinaryFunction> ↵
→ OutputType thrust::transform_reduce(InputIterator, InputIterator, UnaryFunction, ↵
→ OutputType, BinaryFunction)
```

## Template Function `thrust::transform_reduce(InputIterator, InputIterator, UnaryFunction, OutputType, BinaryFunction)`

### Function Documentation

```
template<typename InputIterator, typename UnaryFunction, typename OutputType, typename BinaryFunction>
OutputType thrust::transform_reduce(InputIterator first, InputIterator last, UnaryFunction
                                  unary_op, OutputType init, BinaryFunction binary_op)
```

`transform_reduce` fuses the `transform` and `reduce` operations. `transform_reduce` is equivalent to performing a transformation defined by `unary_op` into a temporary sequence and then performing `reduce` on the transformed sequence. In most cases, fusing these two operations together is more efficient, since fewer memory reads and writes are required.

`transform_reduce` performs a reduction on the transformation of the sequence `[first, last)` according to `unary_op`. Specifically, `unary_op` is applied to each element of the sequence and then the result is reduced to a single value with `binary_op` using the initial value `init`. Note that the transformation `unary_op` is not applied to the initial value `init`. The order of reduction is not specified, so `binary_op` must be both commutative and associative.

The following code snippet demonstrates how to use `transform_reduce` to compute the maximum value of the absolute value of the elements of a range.

**Return** The result of the transformed reduction.

#### Parameters

- `first`: The beginning of the sequence.
- `last`: The end of the sequence.
- `unary_op`: The function to apply to each element of the input sequence.
- `init`: The result is initialized to this value.
- `binary_op`: The reduction operation.

#### Template Parameters

- `InputIterator`: is a model of `Input Iterator`, and `InputIterator`'s `value_type` is convertible to `UnaryFunction`'s `argument_type`.
- `UnaryFunction`: is a model of `Unary Function`, and `UnaryFunction`'s `result_type` is convertible to `OutputType`.
- `OutputType`: is a model of `Assignable`, and is convertible to `BinaryFunction`'s `first_argument_type` and `second_argument_type`.
- `BinaryFunction`: is a model of `Binary Function`, and `BinaryFunction`'s `result_type` is convertible to `OutputType`.

```
#include <thrust/transform_reduce.h>
#include <thrust/functional.h>

template<typename T>
struct absolute_value : public unary_function<T, T>
{
    __host__ __device__ T operator()(const T &x) const
    {
        return x < T(0) ? -x : x;
    }
};
```

(continues on next page)

(continued from previous page)

```

...
int data[6] = {-1, 0, -2, -2, 1, -3};
int result = thrust::transform_reduce(data, data + 6,
                                      absolute_value<int>(),
                                      0,
                                      thrust::maximum<int>());
// result == 3

```

**See** transform**See** reduce**Template Function `thrust::uninitialized_copy(const thrust::detail::execution_policy_base<DerivedPolicy>&, InputIterator, InputIterator, ForwardIterator)`**

- Defined in file `_thrust_uninitialized_copy.h`

**Function Documentation**

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::uninitialized_copy`” with arguments (`const thrust::detail::execution_policy_base<DerivedPolicy>&`, `InputIterator`, `InputIterator`, `ForwardIterator`) in doxygen xml output for project “rocThrust” from directory: `./docBin/xml`. Potential matches:

```

- template<typename DerivedPolicy, typename InputIterator, typename ForwardIterator>
  __host__ __device__ ForwardIterator thrust::uninitialized_copy(const_
  thrust::detail::execution_policy_base< DerivedPolicy > &, InputIterator,
  InputIterator, ForwardIterator)
- template<typename InputIterator, typename ForwardIterator>
  ForwardIterator thrust::uninitialized_copy(InputIterator, InputIterator,
  ForwardIterator)

```

**Template Function `thrust::uninitialized_copy(InputIterator, InputIterator, ForwardIterator)`****Function Documentation**

```
template<typename InputIterator, typename ForwardIterator>
ForwardIterator thrust::uninitialized_copy (InputIterator first, InputIterator last, ForwardIterator
result)
```

In `thrust`, the function `thrust::device_new` allocates memory for an object and then creates an object at that location by calling a constructor. Occasionally, however, it is useful to separate those two operations. If each iterator in the range `[result, result + (last - first)]` points to uninitialized memory, then `uninitialized_copy` creates a copy of `[first, last]` in that range. That is, for each iterator `i` in the input, `uninitialized_copy` creates a copy of `*i` in the location pointed to by the corresponding iterator in the output range by `ForwardIterator`'s `value_type`'s `copy` constructor with `*i` as its argument.

The following code snippet demonstrates how to use `uninitialized_copy` to initialize a range of uninitialized memory.

**Return** An iterator pointing to the last element of the output range.

**Pre** `first` may equal `result`, but the range `[first, last)` and the range `[result, result + (last - first))` shall not overlap otherwise.

### Parameters

- `first`: The first element of the input range to copy from.
- `last`: The last element of the input range to copy from.
- `result`: The first element of the output range to copy to.

### Template Parameters

- `InputIterator`: is a model of [Input Iterator](#).
- `ForwardIterator`: is a model of [Forward Iterator](#), `ForwardIterator` is mutable, and `ForwardIterator`'s `value_type` has a constructor that takes a single argument whose type is `InputIterator`'s `value_type`.

```
#include <thrust/uninitialized_copy.h>
#include <thrust/device_malloc.h>
#include <thrust/device_vector.h>

struct Int
{
    __host__ __device__
    Int(int x) : val(x) {}
    int val;
};

const int N = 137;

Int val(46);
thrust::device_vector<Int> input(N, val);
thrust::device_ptr<Int> array = thrust::device_malloc<Int>(N);
thrust::uninitialized_copy(input.begin(), input.end(), array);

// Int x = array[i];
// x.val == 46 for all 0 <= i < N
```

See [http://www.sgi.com/tech/stl/uninitialized\\_copy.html](http://www.sgi.com/tech/stl/uninitialized_copy.html)

See `copy`

See `uninitialized_fill`

See `device_new`

See `device_malloc`

## Template Function `thrust::uninitialized_copy_n(const thrust::detail::execution_policy_base<DerivedPolicy>&, InputIterator, Size, ForwardIterator)`

- Defined in file `thrust/uninitialized_copy.h`

## Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “thrust::uninitialized\_copy\_n” with arguments (const thrust::detail::execution\_policy\_base<DerivedPolicy>&, InputIterator, Size, ForwardIterator) in doxygen xml output for project “rocThrust” from directory: ./docBin/xml. Potential matches:

```
- template<typename DerivedPolicy, typename InputIterator, typename Size, typename _host_ _device_ ForwardIterator thrust::uninitialized_copy_n(const thrust::detail::execution_policy_base< DerivedPolicy > &, InputIterator, _Size, ForwardIterator)
- template<typename InputIterator, typename Size, typename ForwardIterator>
  ForwardIterator thrust::uninitialized_copy_n(InputIterator, Size, ForwardIterator)
```

## Template Function `thrust::uninitialized_copy_n(InputIterator, Size, ForwardIterator)`

### Function Documentation

`template<typename InputIterator, typename Size, typename ForwardIterator>`  
`ForwardIterator thrust::uninitialized_copy_n(InputIterator first, Size n, ForwardIterator result)`

In thrust, the function `thrust::device_new` allocates memory for an object and then creates an object at that location by calling a constructor. Occasionally, however, it is useful to separate those two operations. If each iterator in the range `[result, result + n)` points to uninitialized memory, then `uninitialized_copy_n` creates a copy of `[first, first + n)` in that range. That is, for each iterator `i` in the input, `uninitialized_copy_n` creates a copy of `*i` in the location pointed to by the corresponding iterator in the output range by `InputIterator`'s `value_type`'s copy constructor with `*i` as its argument.

The following code snippet demonstrates how to use `uninitialized_copy` to initialize a range of uninitialized memory.

**Return** An iterator pointing to the last element of the output range.

**Pre** `first` may equal `result`, but the range `[first, first + n)` and the range `[result, result + n)` shall not overlap otherwise.

### Parameters

- `first`: The first element of the input range to copy from.
- `n`: The number of elements to copy.
- `result`: The first element of the output range to copy to.

### Template Parameters

- `InputIterator`: is a model of `Input Iterator`.
- `Size`: is an integral type.
- `ForwardIterator`: is a model of `Forward Iterator`, `ForwardIterator` is mutable, and `ForwardIterator`'s `value_type` has a constructor that takes a single argument whose type is `InputIterator`'s `value_type`.

```
#include <thrust/uninitialized_copy.h>
#include <thrust/device_malloc.h>
#include <thrust/device_vector.h>
```

(continues on next page)

(continued from previous page)

```

struct Int
{
    __host__ __device__
    Int(int x) : val(x) {}
    int val;
};

...
const int N = 137;

Int val(46);
thrust::device_vector<Int> input(N, val);
thrust::device_ptr<Int> array = thrust::device_malloc<Int>(N);
thrust::uninitialized_copy_n(input.begin(), N, array);

// Int x = array[i];
// x.val == 46 for all 0 <= i < N

```

**See** [http://www.sgi.com/tech/stl/uninitialized\\_copy.html](http://www.sgi.com/tech/stl/uninitialized_copy.html)

**See** `uninitialized_copy`

**See** `copy`

**See** `uninitialized_fill`

**See** `device_new`

**See** `device_malloc`

### Template Function `thrust::uninitialized_fill(const thrust::detail::execution_policy_base<DerivedPolicy>&, ForwardIterator, ForwardIterator, const T&)`

- Defined in file `thrust_uninitialized_fill.h`

#### Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::uninitialized_fill`” with arguments (`const thrust::detail::execution_policy_base<DerivedPolicy>&`, `ForwardIterator`, `ForwardIterator`, `const T&`) in doxygen xml output for project “rocThrust” from directory: `./docBin/xml`. Potential matches:

```

- template<typename DerivedPolicy, typename ForwardIterator, typename T> __host__ __device__ void thrust::uninitialized_fill(const thrust::detail::execution_policy_base<DerivedPolicy> &, ForwardIterator, ForwardIterator, const T &)
- template<typename ForwardIterator, typename T> void thrust::uninitialized_fill(ForwardIterator, ForwardIterator, const T &)

```

### Template Function `thrust::uninitialized_fill(ForwardIterator, ForwardIterator, const T&)`

#### Function Documentation

`template<typename ForwardIterator, typename T>`

```
void thrust::uninitialized_fill(ForwardIterator first, ForwardIterator last, const T &x)
```

In `thrust`, the function `thrust::device_new` allocates memory for an object and then creates an object at that location by calling a constructor. Occasionally, however, it is useful to separate those two operations. If each iterator in the range `[first, last)` points to uninitialized memory, then `uninitialized_fill` creates copies of `x` in that range. That is, for each iterator `i` in the range `[first, last)`, `uninitialized_fill` creates a copy of `x` in the location pointed to `i` by calling `ForwardIterator`'s `value_type`'s `copy` constructor.

The following code snippet demonstrates how to use `uninitialized_fill` to initialize a range of uninitialized memory.

### Parameters

- `first`: The first element of the range of interest.
- `last`: The last element of the range of interest.
- `x`: The value to use as the exemplar of the copy constructor.

### Template Parameters

- `ForwardIterator`: is a model of `Forward Iterator`, `ForwardIterator` is `mutable`, and `ForwardIterator`'s `value_type` has a constructor that takes a single argument of type `T`.

```
#include <thrust/uninitialized_fill.h>
#include <thrust/device_malloc.h>

struct Int
{
    __host__ __device__
    Int(int x) : val(x) {}
    int val;
};

const int N = 137;

Int val(46);
thrust::device_ptr<Int> array = thrust::device_malloc<Int>(N);
thrust::uninitialized_fill(array, array + N, val);

// Int x = array[i];
// x.val == 46 for all 0 <= i < N
```

**See** [http://www.sgi.com/tech/stl/uninitialized\\_fill.html](http://www.sgi.com/tech/stl/uninitialized_fill.html)

**See** `uninitialized_fill_n`

**See** `fill`

**See** `uninitialized_copy`

**See** `device_new`

**See** `device_malloc`

**Template Function** `thrust::uninitialized_fill_n(const thrust::detail::execution_policy_base<DerivedPolicy>&, ForwardIterator, Size, const T&)`

- Defined in file `thrust_uninitialized_fill.h`

## Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “thrust::uninitialized\_fill\_n” with arguments (const thrust::detail::execution\_policy\_base<DerivedPolicy>&, ForwardIterator, Size, const T&) in doxygen xml output for project “rocThrust” from directory: ./docBin/xml. Potential matches:

```
- template<typename DerivedPolicy, typename ForwardIterator, typename Size, 
→typename T> __host__ __device__ ForwardIterator thrust::uninitialized_fill_n(const 
→thrust::detail::execution_policy_base< DerivedPolicy > &, ForwardIterator, Size, 
→const T &)
- template<typename ForwardIterator, typename Size, typename T>
  ForwardIterator thrust::uninitialized_fill_n(ForwardIterator, Size, const T&)
```

## Template Function `thrust::uninitialized_fill_n(ForwardIterator, Size, const T&)`

### Function Documentation

```
template<typename ForwardIterator, typename Size, typename T>
ForwardIterator thrust::uninitialized_fill_n(ForwardIterator first, Size n, const T &x)
```

In thrust, the function `thrust::device_new` allocates memory for an object and then creates an object at that location by calling a constructor. Occasionally, however, it is useful to separate those two operations. If each iterator in the range `[first, first+n]` points to uninitialized memory, then `uninitialized_fill` creates copies of `x` in that range. That is, for each iterator `i` in the range `[first, first+n]`, `uninitialized_fill` creates a copy of `x` in the location pointed to `i` by calling `ForwardIterator`'s `value_type`'s `copy` constructor.

The following code snippet demonstrates how to use `uninitialized_fill` to initialize a range of uninitialized memory.

**Return** `first+n`

### Parameters

- `first`: The first element of the range of interest.
- `n`: The size of the range of interest.
- `x`: The value to use as the exemplar of the copy constructor.

### Template Parameters

- `ForwardIterator`: is a model of `Forward Iterator`, `ForwardIterator` is mutable, and `ForwardIterator`'s `value_type` has a constructor that takes a single argument of type `T`.

```
#include <thrust/uninitialized_fill.h>
#include <thrust/device_malloc.h>

struct Int
{
    __host__ __device__
    Int(int x) : val(x) {}
    int val;
};

...
const int N = 137;
```

(continues on next page)

(continued from previous page)

```
Int val(46);
thrust::device_ptr<Int> array = thrust::device_malloc<Int>(N);
thrust::uninitialized_fill_n(array, N, val);

// Int x = array[i];
// x.val == 46 for all 0 <= i < N
```

**See** [http://www.sgi.com/tech/stl/uninitialized\\_fill.html](http://www.sgi.com/tech/stl/uninitialized_fill.html)

**See** [uninitialized\\_fill](#)

**See** [fill](#)

**See** [uninitialized\\_copy\\_n](#)

**See** [device\\_new](#)

**See** [device\\_malloc](#)

## Template Function `thrust::unique(const thrust::detail::execution_policy_base<DerivedPolicy>&, ForwardIterator, ForwardIterator)`

- Defined in file `thrust_unique.h`

### Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::unique`” with arguments (`const thrust::detail::execution_policy_base<DerivedPolicy>&`, `ForwardIterator`, `ForwardIterator`) in doxygen xml output for project “rocThrust” from directory: `./docBin/xml`. Potential matches:

```
- template<typename DerivedPolicy, typename ForwardIterator, typename BinaryPredicate> __host__ __device__ ForwardIterator thrust::unique(const thrust::detail::execution_policy_base< DerivedPolicy > &, ForwardIterator, const BinaryPredicate)
- template<typename DerivedPolicy, typename ForwardIterator> __host__ __device__ ForwardIterator thrust::unique(const thrust::detail::execution_policy_base< DerivedPolicy > &, ForwardIterator, ForwardIterator)
- template<typename ForwardIterator, typename BinaryPredicate> ForwardIterator thrust::unique(ForwardIterator, ForwardIterator, BinaryPredicate)
- template<typename ForwardIterator> ForwardIterator thrust::unique(ForwardIterator, ForwardIterator)
```

## Template Function `thrust::unique(ForwardIterator, ForwardIterator)`

### Function Documentation

`template<typename ForwardIterator>`

`ForwardIterator thrust::unique(ForwardIterator first, ForwardIterator last)`

For each group of consecutive elements in the range `[first, last]` with the same value, `unique` removes all but the first element of the group. The return value is an iterator `new_last` such that no two consecutive elements in the range `[first, new_last]` are equal. The iterators in the range `[new_last, last]` are

all still dereferenceable, but the elements that they point to are unspecified. `unique` is stable, meaning that the relative order of elements that are not removed is unchanged.

This version of `unique` uses `operator==` to test for equality.

The following code snippet demonstrates how to use `unique` to compact a sequence of numbers to remove consecutive duplicates.

**Return** The end of the unique range `[first, new_last)`.

#### Parameters

- `first`: The beginning of the input range.
- `last`: The end of the input range.

#### Template Parameters

- `ForwardIterator`: is a model of `Forward Iterator`, and `ForwardIterator` is `mutable`, and `ForwardIterator`'s `value_type` is a model of `Equality Comparable`.

```
#include <thrust/unique.h>
...
const int N = 7;
int A[N] = {1, 3, 3, 3, 2, 2, 1};
int *new_end = thrust::unique(A, A + N);
// The first four values of A are now {1, 3, 2, 1}
// Values beyond new_end are unspecified.
```

See <http://www.sgi.com/tech/stl/unique.html>

See `unique_copy`

**Template Function `thrust::unique(const thrust::detail::execution_policy_base<DerivedPolicy>&, ForwardIterator, ForwardIterator, BinaryPredicate)`**

#### Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::unique`” with arguments (`const thrust::detail::execution_policy_base<DerivedPolicy>&`, `ForwardIterator`, `ForwardIterator`, `BinaryPredicate`) in doxygen xml output for project “rocThrust” from directory: `./docBin/xml`. Potential matches:

```
- template<typename DerivedPolicy, typename ForwardIterator, typename
→BinaryPredicate>__host__ __device__ ForwardIterator thrust::unique(const_
→thrust::detail::execution_policy_base< DerivedPolicy > &, ForwardIterator,_
→ForwardIterator, BinaryPredicate)
- template<typename DerivedPolicy, typename ForwardIterator>__host__ __device__
→ForwardIterator thrust::unique(const thrust::detail::execution_policy_base<_
→DerivedPolicy > &, ForwardIterator, ForwardIterator)
- template<typename ForwardIterator, typename BinaryPredicate>
ForwardIterator thrust::unique(ForwardIterator, ForwardIterator, BinaryPredicate)
- template<typename ForwardIterator>
ForwardIterator thrust::unique(ForwardIterator, ForwardIterator)
```

**Template Function `thrust::unique(ForwardIterator, ForwardIterator, BinaryPredicate)`**

## Function Documentation

```
template<typename ForwardIterator, typename BinaryPredicate>
ForwardIterator thrust::unique(ForwardIterator first, ForwardIterator last, BinaryPredicate binary_pred)
```

For each group of consecutive elements in the range [first, last) with the same value, unique removes all but the first element of the group. The return value is an iterator new\_last such that no two consecutive elements in the range [first, new\_last) are equal. The iterators in the range [new\_last, last) are all still dereferenceable, but the elements that they point to are unspecified. unique is stable, meaning that the relative order of elements that are not removed is unchanged.

This version of unique uses the function object binary\_pred to test for equality.

The following code snippet demonstrates how to use unique to compact a sequence of numbers to remove consecutive duplicates.

**Return** The end of the unique range [first, new\_last)

### Parameters

- first: The beginning of the input range.
- last: The end of the input range.
- binary\_pred: The binary predicate used to determine equality.

### Template Parameters

- ForwardIterator: is a model of `Forward Iterator`, and `ForwardIterator` is mutable, and `ForwardIterator`'s `value_type` is convertible to `BinaryPredicate`'s `first_argument_type` and to `BinaryPredicate`'s `second_argument_type`.
- BinaryPredicate: is a model of `Binary Predicate`.

```
#include <thrust/unique.h>
...
const int N = 7;
int A[N] = {1, 3, 3, 3, 2, 2, 1};
int *new_end = thrust::unique(A, A + N, thrust::equal_to<int>());
// The first four values of A are now {1, 3, 2, 1}
// Values beyond new_end are unspecified.
```

See <http://www.sgi.com/tech/stl/unique.html>

See `unique_copy`

**Template Function** `thrust::unique_by_key(const thrust::detail::execution_policy_base<DerivedPolicy>&, ForwardIterator1, ForwardIterator1, ForwardIterator2)`

- Defined in file `thrust_unique.h`

## Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::unique_by_key`” with arguments (`const thrust::detail::execution_policy_base<DerivedPolicy>&`, `ForwardIterator1`, `ForwardIterator1`, `ForwardIterator2`) in doxygen xml output for project “rocThrust” from directory: `./docBin/xml`. Potential matches:

```
- template<typename DerivedPolicy, typename ForwardIterator1, typename_
→ForwardIterator2, typename BinaryPredicate> __host__ __device__ thrust::pair
→<ForwardIterator1,ForwardIterator2> thrust::unique_by_key(const_
→thrust::detail::execution_policy_base< DerivedPolicy > &, ForwardIterator1,
→ForwardIterator1, ForwardIterator2, BinaryPredicate)
- template<typename DerivedPolicy, typename ForwardIterator1, typename_
→ForwardIterator2> __host__ __device__ thrust::pair<ForwardIterator1,
→ForwardIterator2> thrust::unique_by_key(const thrust::detail::execution_policy_
→base< DerivedPolicy > &, ForwardIterator1, ForwardIterator1, ForwardIterator2)
- template<typename ForwardIterator1, typename ForwardIterator2, typename_
→BinaryPredicate>
    thrust::pair<ForwardIterator1, ForwardIterator2> thrust::unique_by_
→key(ForwardIterator1, ForwardIterator1, ForwardIterator2, BinaryPredicate)
- template<typename ForwardIterator1, typename ForwardIterator2>
    thrust::pair<ForwardIterator1, ForwardIterator2> thrust::unique_by_
→key(ForwardIterator1, ForwardIterator1, ForwardIterator2)
```

## Template Function `thrust::unique_by_key(ForwardIterator1, ForwardIterator1, ForwardIterator2)`

### Function Documentation

```
template<typename ForwardIterator1, typename ForwardIterator2>
thrust::pair<ForwardIterator1, ForwardIterator2> thrust::unique_by_key(ForwardIterator1
                                                               keys_first, ForwardItera-
                                                               tor1 keys_last, ForwardItera-
                                                               tor2 values_first)
```

`unique_by_key` is a generalization of `unique` to key-value pairs. For each group of consecutive keys in the range `[keys_first, keys_last]` that are equal, `unique_by_key` removes all but the first element of the group. Similarly, the corresponding values in the range `[values_first, values_first + (keys_last - keys_first)]` are also removed.

The return value is a pair of iterators `(new_keys_last, new_values_last)` such that no two consecutive elements in the range `[keys_first, new_keys_last]` are equal.

This version of `unique_by_key` uses `operator==` to test for equality and `project1st` to reduce values with equal keys.

The following code snippet demonstrates how to use `unique_by_key` to compact a sequence of key/value pairs to remove consecutive duplicates.

**Return** A pair of iterators at end of the ranges `[key_first, keys_new_last]` and `[values_first, values_new_last]`.

**Pre** The range `[keys_first, keys_last]` and the range `[values_first, values_first + (keys_last - keys_first)]` shall not overlap.

### Parameters

- `keys_first`: The beginning of the key range.
- `keys_last`: The end of the key range.
- `values_first`: The beginning of the value range.

### Template Parameters

- `ForwardIterator1`: is a model of `Forward Iterator`, and `ForwardIterator1` is mutable, and `ForwardIterator1`'s `value_type` is a model of `Equality Comparable`.

- `ForwardIterator2`: is a model of `Forward Iterator`, and `ForwardIterator2` is mutable.

```
#include <thrust/unique.h>
...
const int N = 7;
int A[N] = {1, 3, 3, 3, 2, 2, 1}; // keys
int B[N] = {9, 8, 7, 6, 5, 4, 3}; // values

thrust::pair<int*, int*> new_end;
new_end = thrust::unique_by_key(A, A + N, B);

// The first four keys in A are now {1, 3, 2, 1} and new_end.first - A is 4.
// The first four values in B are now {9, 8, 5, 3} and new_end.second - B is 4.
```

**See** `unique`

**See** `unique_by_key_copy`

**See** `reduce_by_key`

**Template Function** `thrust::unique_by_key(const thrust::detail::execution_policy_base<DerivedPolicy>&, ForwardIterator1, ForwardIterator1, ForwardIterator2, BinaryPredicate)`

## Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::unique_by_key`” with arguments (`const thrust::detail::execution_policy_base<DerivedPolicy>&`, `ForwardIterator1`, `ForwardIterator1`, `ForwardIterator2`, `BinaryPredicate`) in doxygen xml output for project “rocThrust” from directory: ./docBin/xml. Potential matches:

```
- template<typename DerivedPolicy, typename ForwardIterator1, typename ForwardIterator2, typename BinaryPredicate> __host__ __device__ thrust::pair<ForwardIterator1, ForwardIterator2> thrust::unique_by_key(const thrust::detail::execution_policy_base< DerivedPolicy > &, ForwardIterator1, ForwardIterator1, ForwardIterator2, BinaryPredicate)
- template<typename DerivedPolicy, typename ForwardIterator1, typename ForwardIterator2> __host__ __device__ thrust::pair<ForwardIterator1, ForwardIterator2> thrust::unique_by_key(const thrust::detail::execution_policy_base< DerivedPolicy > &, ForwardIterator1, ForwardIterator1, ForwardIterator2)
- template<typename ForwardIterator1, typename ForwardIterator2, typename BinaryPredicate>
  thrust::pair<ForwardIterator1, ForwardIterator2> thrust::unique_by_key(ForwardIterator1, ForwardIterator1, ForwardIterator2, BinaryPredicate)
- template<typename ForwardIterator1, typename ForwardIterator2>
  thrust::pair<ForwardIterator1, ForwardIterator2> thrust::unique_by_key(ForwardIterator1, ForwardIterator1, ForwardIterator2)
```

**Template Function** `thrust::unique_by_key(ForwardIterator1, ForwardIterator1, ForwardIterator2, BinaryPredicate)`

## Function Documentation

`template<typename ForwardIterator1, typename ForwardIterator2, typename BinaryPredicate>`

```
thrust::pair<ForwardIterator1, ForwardIterator2> thrust::unique_by_key(ForwardIterator1
    keys_first,           ForwardIterator1 keys_last,   ForwardIterator2 values_first,
    BinaryPredicate        binary_pred)
```

`unique_by_key` is a generalization of `unique` to key-value pairs. For each group of consecutive keys in the range `[keys_first, keys_last]` that are equal, `unique_by_key` removes all but the first element of the group. Similarly, the corresponding values in the range `[values_first, values_first + (keys_last - keys_first)]` are also removed.

This version of `unique_by_key` uses the function object `binary_pred` to test for equality and `project1st` to reduce values with equal keys.

The following code snippet demonstrates how to use `unique_by_key` to compact a sequence of key/value pairs to remove consecutive duplicates.

**Return** The end of the unique range `[first, new_end]`.

**Pre** The range `[keys_first, keys_last]` and the range `[values_first, values_first + (keys_last - keys_first)]` shall not overlap.

### Parameters

- `keys_first`: The beginning of the key range.
- `keys_last`: The end of the key range.
- `values_first`: The beginning of the value range.
- `binary_pred`: The binary predicate used to determine equality.

### Template Parameters

- `ForwardIterator1`: is a model of `Forward Iterator`, and `ForwardIterator1` is mutable, and `ForwardIterator1`'s `value_type` is a model of `Equality Comparable`.
- `ForwardIterator2`: is a model of `Forward Iterator`, and `ForwardIterator2` is mutable.
- `BinaryPredicate`: is a model of `Binary Predicate`.

```
#include <thrust/unique.h>
...
const int N = 7;
int A[N] = {1, 3, 3, 3, 2, 2, 1}; // keys
int B[N] = {9, 8, 7, 6, 5, 4, 3}; // values

thrust::pair<int*, int*> new_end;
thrust::equal_to<int> binary_pred;
new_end = thrust::unique_by_key(keys, keys + N, values, binary_pred);

// The first four keys in A are now {1, 3, 2, 1} and new_end.first - A is 4.
// The first four values in B are now {9, 8, 5, 3} and new_end.second - B is 4.
```

**See** `unique`

**See** `unique_by_key_copy`

**See** `reduce_by_key`

## Template Function `thrust::unique_by_key_copy(const thrust::detail::execution_policy_base<DerivedPolicy>&, InputIterator1, InputIterator1, InputIterator2, OutputIterator1, OutputIterator2)`

- Defined in file `thrust_unique.h`

### Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::unique_by_key_copy`” with arguments (`const thrust::detail::execution_policy_base<DerivedPolicy>&`, `InputIterator1`, `InputIterator1`, `InputIterator2`, `OutputIterator1`, `OutputIterator2`) in doxygen xml output for project “rocThrust” from directory: `./docBin/xml`. Potential matches:

```
- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2,
→ typename OutputIterator1, typename OutputIterator2, typename BinaryPredicate> __
→ host__ __device__ thrust::pair<OutputIterator1,OutputIterator2> thrust::unique_by_
→ key_copy(const thrust::detail::execution_policy_base< DerivedPolicy > &, __
→ InputIterator1, InputIterator1, InputIterator2, OutputIterator1, OutputIterator2, __
→ BinaryPredicate)
- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2,
→ typename OutputIterator1, typename OutputIterator2> __host__ __device__ __
→ thrust::pair<OutputIterator1,OutputIterator2> thrust::unique_by_key_copy(const __
→ thrust::detail::execution_policy_base< DerivedPolicy > &, InputIterator1, __
→ InputIterator1, InputIterator2, OutputIterator1, OutputIterator2)
- template<typename InputIterator1, typename InputIterator2, typename __
→ OutputIterator1, typename OutputIterator2, typename BinaryPredicate>
→ thrust::pair<OutputIterator1, OutputIterator2> thrust::unique_by_key_
→ copy(InputIterator1, InputIterator1, InputIterator2, OutputIterator1, __
→ OutputIterator2, BinaryPredicate)
- template<typename InputIterator1, typename InputIterator2, typename __
→ OutputIterator1, typename OutputIterator2>
→ thrust::pair<OutputIterator1, OutputIterator2> thrust::unique_by_key_
→ copy(InputIterator1, InputIterator1, InputIterator2, OutputIterator1, __
→ OutputIterator2)
```

## Template Function `thrust::unique_by_key_copy(InputIterator1, InputIterator1, InputIterator2, OutputIterator1, OutputIterator2)`

### Function Documentation

```
template<typename InputIterator1, typename InputIterator2, typename OutputIterator1, typename OutputIterator2
thrust::pair<OutputIterator1, OutputIterator2> thrust::unique_by_key_copy(InputIterator1
→ keys_first, InputIt-
→ erator1 keys_last,
→ InputIterator2 val-
→ ues_first, OutputIt-
→ erator1 keys_result,
→ OutputIterator2 val-
→ ues_result)
```

`unique_by_key_copy` is a generalization of `unique_copy` to key-value pairs. For each group of consecutive keys in the range [`keys_first`, `keys_last`) that are equal, `unique_by_key_copy` copies the first element of the group to a range beginning with `keys_result` and the corresponding values from the

range [values\_first, values\_first + (keys\_last - keys\_first)) are copied to a range beginning with values\_result.

This version of unique\_by\_key\_copy uses operator== to test for equality and *project1st* to reduce values with equal keys.

The following code snippet demonstrates how to use unique\_by\_key\_copy to compact a sequence of key/value pairs and with equal keys.

**Return** A pair of iterators at end of the ranges [keys\_result, keys\_result\_last) and [values\_result, values\_result\_last).

**Pre** The input ranges shall not overlap either output range.

#### Parameters

- keys\_first: The beginning of the input key range.
- keys\_last: The end of the input key range.
- values\_first: The beginning of the input value range.
- keys\_result: The beginning of the output key range.
- values\_result: The beginning of the output value range.

#### Template Parameters

- InputIterator1: is a model of [Input Iterator](#),
- InputIterator2: is a model of [Input Iterator](#),
- OutputIterator1: is a model of [Output Iterator](#) and and InputIterator1's value\_type is convertible to OutputIterator1's value\_type.
- OutputIterator2: is a model of [Output Iterator](#) and and InputIterator2's value\_type is convertible to OutputIterator2's value\_type.

```
#include <thrust/unique.h>
...
const int N = 7;
int A[N] = {1, 3, 3, 3, 2, 2, 1}; // input keys
int B[N] = {9, 8, 7, 6, 5, 4, 3}; // input values
int C[N]; // output keys
int D[N]; // output values

thrust::pair<int*,int*> new_end;
new_end = thrust::unique_by_key_copy(A, A + N, B, C, D);

// The first four keys in C are now {1, 3, 2, 1} and new_end.first - C is 4.
// The first four values in D are now {9, 8, 5, 3} and new_end.second - D is 4.
```

**See** [unique\\_copy](#)

**See** [unique\\_by\\_key](#)

**See** [reduce\\_by\\_key](#)

**Template Function** `thrust::unique_by_key_copy(const thrust::detail::execution_policy_base<DerivedPolicy>&, InputIterator1, InputIterator1, InputIterator2, OutputIterator1, OutputIterator2, BinaryPredicate)`

## Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “thrust::unique\_by\_key\_copy” with arguments (const thrust::detail::execution\_policy\_base<DerivedPolicy>&, InputIterator1, InputIterator1, InputIterator2, OutputIterator1, OutputIterator2, BinaryPredicate) in doxygen xml output for project “rocThrust” from directory: ./docBin/xml. Potential matches:

```
- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2,
→ typename OutputIterator1, typename OutputIterator2, typename BinaryPredicate> __
→ host__ __device__ thrust::pair<OutputIterator1,OutputIterator2> thrust::unique_by_
→ key_copy(const thrust::detail::execution_policy_base< DerivedPolicy > &,
→ InputIterator1, InputIterator1, InputIterator2, OutputIterator1, OutputIterator2, __
→ BinaryPredicate)
- template<typename DerivedPolicy, typename InputIterator1, typename InputIterator2,
→ typename OutputIterator1, typename OutputIterator2> __host__ __device__ __
→ thrust::pair<OutputIterator1,OutputIterator2> thrust::unique_by_key_copy(const __
→ thrust::detail::execution_policy_base< DerivedPolicy > &, InputIterator1, __
→ InputIterator1, InputIterator2, OutputIterator1, OutputIterator2)
- template<typename InputIterator1, typename InputIterator2, typename __
→ OutputIterator1, typename OutputIterator2, typename BinaryPredicate>
→ thrust::pair<OutputIterator1, OutputIterator2> thrust::unique_by_key_
→ copy(InputIterator1, InputIterator1, InputIterator2, OutputIterator1, __
→ OutputIterator2, BinaryPredicate)
- template<typename InputIterator1, typename InputIterator2, typename __
→ OutputIterator1, typename OutputIterator2>
→ thrust::pair<OutputIterator1, OutputIterator2> thrust::unique_by_key_
→ copy(InputIterator1, InputIterator1, InputIterator2, OutputIterator1, __
→ OutputIterator2)
```

### Template Function `thrust::unique_by_key_copy(InputIterator1, InputIterator1, InputIterator2, OutputIterator1, OutputIterator2, BinaryPredicate)`

#### Function Documentation

```
template<typename InputIterator1, typename InputIterator2, typename OutputIterator1, typename OutputIterator2,
thrust::pair<OutputIterator1, OutputIterator2> thrust::unique_by_key_copy (InputIterator1
→ keys_first, InputIterator1 keys_last, InputIterator2 values_first,
→ OutputIterator1
→ keys_result, OutputIterator2 values_result,
→ BinaryPredicate
→ binary_pred)
```

`unique_by_key_copy` is a generalization of `unique_copy` to key-value pairs. For each group of consecutive keys in the range `[keys_first, keys_last]` that are equal, `unique_by_key_copy` copies the first element of the group to a range beginning with `keys_result` and the corresponding values from the range `[values_first, values_first + (keys_last - keys_first)]` are copied to a range beginning with `values_result`.

This version of `unique_by_key_copy` uses the function object `binary_pred` to test for equality and `project1st` to reduce values with equal keys.

The following code snippet demonstrates how to use `unique_by_key_copy` to compact a sequence of key/value pairs and with equal keys.

**Return** A pair of iterators at end of the ranges `[keys_result, keys_result_last)` and `[values_result, values_result_last)`.

**Pre** The input ranges shall not overlap either output range.

### Parameters

- `keys_first`: The beginning of the input key range.
- `keys_last`: The end of the input key range.
- `values_first`: The beginning of the input value range.
- `keys_result`: The beginning of the output key range.
- `values_result`: The beginning of the output value range.
- `binary_pred`: The binary predicate used to determine equality.

### Template Parameters

- `InputIterator1`: is a model of `Input Iterator`,
- `InputIterator2`: is a model of `Input Iterator`,
- `OutputIterator1`: is a model of `Output Iterator` and `and InputIterator1's value_type` is convertible to `OutputIterator1's value_type`.
- `OutputIterator2`: is a model of `Output Iterator` and `and InputIterator2's value_type` is convertible to `OutputIterator2's value_type`.
- `BinaryPredicate`: is a model of `Binary Predicate`.

```
#include <thrust/unique.h>
...
const int N = 7;
int A[N] = {1, 3, 3, 3, 2, 2, 1}; // input keys
int B[N] = {9, 8, 7, 6, 5, 4, 3}; // input values
int C[N]; // output keys
int D[N]; // output values

thrust::pair<int*,int*> new_end;
thrust::equal_to<int> binary_pred;
new_end = thrust::unique_by_key_copy(A, A + N, B, C, D, binary_pred);

// The first four keys in C are now {1, 3, 2, 1} and new_end.first - C is 4.
// The first four values in D are now {9, 8, 5, 3} and new_end.second - D is 4.
```

**See** `unique_copy`

**See** `unique_by_key`

**See** `reduce_by_key`

**Template Function** `thrust::unique_copy(const thrust::detail::execution_policy_base<DerivedPolicy>&, InputIterator, InputIterator, OutputIterator)`

- Defined in file `_thrust_unique.h`

## Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “thrust::unique\_copy” with arguments (const thrust::detail::execution\_policy\_base<DerivedPolicy>&, InputIterator, InputIterator, OutputIterator) in doxygen xml output for project “rocThrust” from directory: ./docBin/xml. Potential matches:

```
- template<typename DerivedPolicy, typename InputIterator, typename OutputIterator,
          typename BinaryPredicate> __host__ __device__ OutputIterator thrust::unique_
          copy(const thrust::detail::execution_policy_base< DerivedPolicy > &,_
          InputIterator, InputIterator, OutputIterator, BinaryPredicate)
- template<typename DerivedPolicy, typename InputIterator, typename OutputIterator>_
          __host__ __device__ OutputIterator thrust::unique_copy(const_
          thrust::detail::execution_policy_base< DerivedPolicy > &, InputIterator,_
          InputIterator, OutputIterator)
- template<typename InputIterator, typename OutputIterator, typename_
          BinaryPredicate>
          OutputIterator thrust::unique_copy(InputIterator, InputIterator, OutputIterator,_
          BinaryPredicate)
- template<typename InputIterator, typename OutputIterator>
          OutputIterator thrust::unique_copy(InputIterator, InputIterator, OutputIterator)
```

## Template Function thrust::unique\_copy(InputIterator, InputIterator, OutputIterator)

### Function Documentation

template<typename **InputIterator**, typename **OutputIterator**>  
*OutputIterator thrust::unique\_copy (InputIterator first, InputIterator last, OutputIterator result)*  
 unique\_copy copies elements from the range [first, last) to a range beginning with result, except that in a consecutive group of duplicate elements only the first one is copied. The return value is the end of the range to which the elements are copied.

The reason there are two different versions of unique\_copy is that there are two different definitions of what it means for a consecutive group of elements to be duplicates. In the first version, the test is simple equality: the elements in a range [f, l) are duplicates if, for every iterator i in the range, either  $i == f$  or else  $*i == *(i-1)$ . In the second, the test is an arbitrary BinaryPredicate binary\_pred: the elements in [f, l) are duplicates if, for every iterator i in the range, either  $i == f$  or else  $\text{binary\_pred}(*i, *(i-1))$  is true.

This version of unique\_copy uses operator== to test for equality.

The following code snippet demonstrates how to use unique\_copy to compact a sequence of numbers to remove consecutive duplicates.

**Return** The end of the unique range [result, result\_end).

**Pre** The range [first, last) and the range [result, result + (last - first)) shall not overlap.

### Parameters

- **first**: The beginning of the input range.
- **last**: The end of the input range.
- **result**: The beginning of the output range.

### Template Parameters

- `InputIterator`: is a model of `Input Iterator`, and `InputIterator`'s `value_type` is a model of `Equality Comparable`.
- `OutputIterator`: is a model of `Output Iterator` and `InputIterator`'s `value_type` is convertible to `OutputIterator`'s `value_type`.

```
#include <thrust/unique.h>
...
const int N = 7;
int A[N] = {1, 3, 3, 3, 2, 2, 1};
int B[N];
int *result_end = thrust::unique_copy(A, A + N, B);
// The first four values of B are now {1, 3, 2, 1} and (result_end - B) is 4
// Values beyond result_end are unspecified
```

See `unique`

See [http://www.sgi.com/tech/stl/unique\\_copy.html](http://www.sgi.com/tech/stl/unique_copy.html)

**Template Function `thrust::unique_copy(const thrust::detail::execution_policy_base<DerivedPolicy>&, InputIterator, InputIterator, OutputIterator, BinaryPredicate)`**

#### Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::unique_copy`” with arguments (`const thrust::detail::execution_policy_base<DerivedPolicy>&`, `InputIterator`, `InputIterator`, `OutputIterator`, `BinaryPredicate`) in doxygen xml output for project “rocThrust” from directory: ./docBin/xml. Potential matches:

```
- template<typename DerivedPolicy, typename InputIterator, typename OutputIterator,  
→typename BinaryPredicate> __host__ __device__ OutputIterator thrust::unique_  
→copy(const thrust::detail::execution_policy_base< DerivedPolicy > &,  
→InputIterator, InputIterator, OutputIterator, BinaryPredicate)  
- template<typename DerivedPolicy, typename InputIterator, typename OutputIterator>_  
→__host__ __device__ OutputIterator thrust::unique_copy(const  
→thrust::detail::execution_policy_base< DerivedPolicy > &, InputIterator,  
→InputIterator, OutputIterator)  
- template<typename InputIterator, typename OutputIterator, typename  
→BinaryPredicate  
→OutputIterator thrust::unique_copy(InputIterator, InputIterator, OutputIterator,  
→BinaryPredicate)  
- template<typename InputIterator, typename OutputIterator>  
→OutputIterator thrust::unique_copy(InputIterator, InputIterator, OutputIterator)
```

**Template Function `thrust::unique_copy(InputIterator, InputIterator, OutputIterator, BinaryPredicate)`**

#### Function Documentation

```
template<typename InputIterator, typename OutputIterator, typename BinaryPredicate>  
OutputIterator thrust::unique_copy(InputIterator first, InputIterator last, OutputIterator result, Bi-  
→naryPredicate binary_pred)
```

`unique_copy` copies elements from the range `[first, last)` to a range beginning with `result`, except that in a consecutive group of duplicate elements only the first one is copied. The return value is the end of the range to which the elements are copied.

This version of `unique_copy` uses the function object `binary_pred` to test for equality.

The following code snippet demonstrates how to use `unique_copy` to compact a sequence of numbers to remove consecutive duplicates.

**Return** The end of the unique range `[result, result_end)`.

**Pre** The range `[first, last)` and the range `[result, result + (last - first))` shall not overlap.

### Parameters

- `first`: The beginning of the input range.
- `last`: The end of the input range.
- `result`: The beginning of the output range.
- `binary_pred`: The binary predicate used to determine equality.

### Template Parameters

- `InputIterator`: is a model of `Input Iterator`, and `InputIterator`'s `value_type` is a model of `Equality Comparable`.
- `OutputIterator`: is a model of `Output Iterator` and `InputIterator`'s `value_type` is convertible to `OutputIterator`'s `value_type`.
- `BinaryPredicate`: is a model of `Binary Predicate`.

```
#include <thrust/unique.h>
...
const int N = 7;
int A[N] = {1, 3, 3, 3, 2, 2, 1};
int B[N];
int *result_end = thrust::unique_copy(A, A + N, B, thrust::equal_to<int>());
// The first four values of B are now {1, 3, 2, 1} and (result_end - B) is 4
// Values beyond result_end are unspecified.
```

See `unique`

See [http://www.sgi.com/tech/stl/unique\\_copy.html](http://www.sgi.com/tech/stl/unique_copy.html)

**Template Function** `thrust::upper_bound(const thrust::detail::execution_policy_base<DerivedPolicy>&, ForwardIterator, ForwardIterator, const LessThanComparable&)`

- Defined in file `thrust_binary_search.h`

### Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::upper_bound`” with arguments (`const thrust::detail::execution_policy_base<DerivedPolicy>&`, `ForwardIterator`, `ForwardIterator`, `const LessThanComparable&`) in doxygen xml output for project “rocThrust” from directory: `./docBin/xml`. Potential matches:

```

- template<class ForwardIterator, class InputIterator, class OutputIterator, class_
→StrictWeakOrdering>
    OutputIterator thrust::upper_bound(ForwardIterator, ForwardIterator,_
→InputIterator, InputIterator, OutputIterator, StrictWeakOrdering)
- template<class ForwardIterator, class InputIterator, class OutputIterator>
    OutputIterator thrust::upper_bound(ForwardIterator, ForwardIterator,_
→InputIterator, InputIterator, OutputIterator)
- template<class ForwardIterator, class LessThanComparable>
    ForwardIterator thrust::upper_bound(ForwardIterator, ForwardIterator, const_
→LessThanComparable&)
- template<class ForwardIterator, class T, class StrictWeakOrdering>
    ForwardIterator thrust::upper_bound(ForwardIterator, ForwardIterator, const T&,_
→StrictWeakOrdering)
- template<typename DerivedPolicy, typename ForwardIterator, typename InputIterator,
→ typename OutputIterator, typename StrictWeakOrdering>__host__ __device__
→OutputIterator thrust::upper_bound(const thrust::detail::execution_policy_base<_>,
→DerivedPolicy > &, ForwardIterator, ForwardIterator, InputIterator, InputIterator,
→OutputIterator, StrictWeakOrdering)
- template<typename DerivedPolicy, typename ForwardIterator, typename InputIterator,
→ typename OutputIterator>__host__ __device__ OutputIterator thrust::upper_
→bound(const thrust::detail::execution_policy_base< DerivedPolicy > &,_
→ForwardIterator, ForwardIterator, InputIterator, InputIterator, OutputIterator)
- template<typename DerivedPolicy, typename ForwardIterator, typename_
→LessThanComparable>__host__ __device__ ForwardIterator thrust::upper_bound(const_
→thrust::detail::execution_policy_base< DerivedPolicy > &, ForwardIterator,_
→ForwardIterator, const LessThanComparable &)
- template<typename DerivedPolicy, typename ForwardIterator, typename T, typename_
→StrictWeakOrdering>__host__ __device__ ForwardIterator thrust::upper_bound(const_
→thrust::detail::execution_policy_base< DerivedPolicy > &, ForwardIterator,_
→ForwardIterator, const T &, StrictWeakOrdering)

```

## Template Function `thrust::upper_bound(ForwardIterator, ForwardIterator, const LessThanComparable&)`

### Function Documentation

```
template<class ForwardIterator, class LessThanComparable>
ForwardIterator thrust::upper_bound(ForwardIterator first, ForwardIterator last, const
LessThanComparable &value)
upper_bound is a version of binary search: it attempts to find the element value in an ordered range [first, last). Specifically, it returns the last position where value could be inserted without violating the ordering. This version of upper_bound uses operator< for comparison and returns the furthermost iterator i in [first, last) such that, for every iterator j in [first, i), value < *j is false.
```

The following code snippet demonstrates how to use `upper_bound` to search for values in a ordered range.

**Return** The furthermost iterator i, such that `value < *i` is false.

#### Parameters

- `first`: The beginning of the ordered sequence.
- `last`: The end of the ordered sequence.
- `value`: The value to be searched.

#### Template Parameters

- `ForwardIterator`: is a model of `Forward Iterator`.
- `LessThanComparable`: is a model of `LessThanComparable`.

```
#include <thrust/binary_search.h>
#include <thrust/device_vector.h>
...
thrust::device_vector<int> input(5);

input[0] = 0;
input[1] = 2;
input[2] = 5;
input[3] = 7;
input[4] = 8;

thrust::upper_bound(input.begin(), input.end(), 0); // returns input.begin() + 1
thrust::upper_bound(input.begin(), input.end(), 1); // returns input.begin() + 1
thrust::upper_bound(input.begin(), input.end(), 2); // returns input.begin() + 2
thrust::upper_bound(input.begin(), input.end(), 3); // returns input.begin() + 2
thrust::upper_bound(input.begin(), input.end(), 8); // returns input.end()
thrust::upper_bound(input.begin(), input.end(), 9); // returns input.end()
```

**See** [http://www.sgi.com/tech/stl/upper\\_bound.html](http://www.sgi.com/tech/stl/upper_bound.html)

**See** `lower_bound`

**See** `equal_range`

**See** `binary_search`

**Template Function** `thrust::upper_bound(const thrust::detail::execution_policy_base<DerivedPolicy>&, ForwardIterator, ForwardIterator, const T&, StrictWeakOrdering)`

## Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “`thrust::upper_bound`” with arguments (`const thrust::detail::execution_policy_base<DerivedPolicy>&`, `ForwardIterator`, `ForwardIterator`, `const T&`, `StrictWeakOrdering`) in doxygen xml output for project “rocThrust” from directory: ./docBin/xml. Potential matches:

```
- template<class ForwardIterator, class InputIterator, class OutputIterator, class LessThanComparable>
  OutputIterator thrust::upper_bound(ForwardIterator, ForwardIterator, InputIterator, InputIterator, OutputIterator, StrictWeakOrdering)
- template<class ForwardIterator, class InputIterator, class OutputIterator>
  OutputIterator thrust::upper_bound(ForwardIterator, ForwardIterator, InputIterator, InputIterator, OutputIterator)
- template<class ForwardIterator, class LessThanComparable>
  ForwardIterator thrust::upper_bound(ForwardIterator, ForwardIterator, const LessThanComparable&)
- template<class ForwardIterator, class T, class StrictWeakOrdering>
  ForwardIterator thrust::upper_bound(ForwardIterator, ForwardIterator, const T&, StrictWeakOrdering)
- template<typename DerivedPolicy, typename ForwardIterator, typename InputIterator, typename OutputIterator, typename StrictWeakOrdering> __host__ __device__
  OutputIterator thrust::upper_bound(const thrust::detail::execution_policy_base<DerivedPolicy> &, ForwardIterator, ForwardIterator, InputIterator, InputIterator, OutputIterator, StrictWeakOrdering)
- template<typename DerivedPolicy, typename ForwardIterator, typename InputIterator, typename OutputIterator> __host__ __device__
  OutputIterator thrust::upper_bound(const thrust::detail::execution_policy_base<DerivedPolicy> &, ForwardIterator, ForwardIterator, InputIterator, InputIterator, OutputIterator, StrictWeakOrdering)
1.3. Future API OutputIterator> __host__ __device__ OutputIterator thrust::upper_bound(const thrust::detail::execution_policy_base<DerivedPolicy> &, ForwardIterator, ForwardIterator, InputIterator, InputIterator, OutputIterator)
- template<typename DerivedPolicy, typename ForwardIterator, typename LessThanComparable> __host__ __device__ ForwardIterator thrust::upper_bound(const LessThanComparable&, ForwardIterator, ForwardIterator, InputIterator, InputIterator, OutputIterator)
```

## Template Function `thrust::upper_bound(ForwardIterator, ForwardIterator, const T&, StrictWeakOrdering)`

### Function Documentation

```
template<class ForwardIterator, class T, class StrictWeakOrderingForwardIterator thrust::upper_bound(ForwardIterator first, ForwardIterator last, const T & value,
StrictWeakOrdering comp)
```

`upper_bound` is a version of binary search: it attempts to find the element value in an ordered range  $[first, last]$ . Specifically, it returns the last position where `value` could be inserted without violating the ordering. This version of `upper_bound` uses function object `comp` for comparison and returns the furthermost iterator `i` in  $[first, last]$  such that, for every iterator `j` in  $[first, i]$ , `comp(value, *j)` is false.

The following code snippet demonstrates how to use `upper_bound` to search for values in a ordered range.

**Return** The furthermost iterator `i`, such that `comp(value, *i)` is false.

#### Parameters

- `first`: The beginning of the ordered sequence.
- `last`: The end of the ordered sequence.
- `value`: The value to be searched.
- `comp`: The comparison operator.

#### Template Parameters

- `ForwardIterator`: is a model of `Forward Iterator`.
- `T`: is comparable to `ForwardIterator`'s `value_type`.
- `StrictWeakOrdering`: is a model of `Strict Weak Ordering`.

```
#include <thrust/binary_search.h>
#include <thrust/device_vector.h>
#include <thrust/functional.h>
...
thrust::device_vector<int> input(5);

input[0] = 0;
input[1] = 2;
input[2] = 5;
input[3] = 7;
input[4] = 8;

thrust::upper_bound(input.begin(), input.end(), 0, thrust::less<int>()); // ↵
// returns input.begin() + 1
thrust::upper_bound(input.begin(), input.end(), 1, thrust::less<int>()); // ↵
// returns input.begin() + 1
thrust::upper_bound(input.begin(), input.end(), 2, thrust::less<int>()); // ↵
// returns input.begin() + 2
thrust::upper_bound(input.begin(), input.end(), 3, thrust::less<int>()); // ↵
// returns input.begin() + 2
```

(continues on next page)

(continued from previous page)

```
thrust::upper_bound(input.begin(), input.end(), 8, thrust::less<int>()); //_
↳ returns input.end()
thrust::upper_bound(input.begin(), input.end(), 9, thrust::less<int>()); //_
↳ returns input.end()
```

**See** [http://www.sgi.com/tech/stl/upper\\_bound.html](http://www.sgi.com/tech/stl/upper_bound.html)

**See** [lower\\_bound](#)

**See** [equal\\_range](#)

**See** [binary\\_search](#)

**Template Function** `thrust::upper_bound(const thrust::detail::execution_policy_base<DerivedPolicy>&, ForwardIterator, ForwardIterator, InputIterator, InputIterator, OutputIterator)`

## Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “thrust::upper\_bound” with arguments (const thrust::detail::execution\_policy\_base<DerivedPolicy>&, ForwardIterator, ForwardIterator, InputIterator, InputIterator, OutputIterator) in doxygen xml output for project “rocThrust” from directory: ./docBin/xml. Potential matches:

```
- template<class ForwardIterator, class InputIterator, class OutputIterator, class_
→ StrictWeakOrdering>
    OutputIterator thrust::upper_bound(ForwardIterator, ForwardIterator,_
→ InputIterator, InputIterator, OutputIterator, StrictWeakOrdering)
- template<class ForwardIterator, class InputIterator, class OutputIterator>
    OutputIterator thrust::upper_bound(ForwardIterator, ForwardIterator,_
→ InputIterator, InputIterator, OutputIterator)
- template<class ForwardIterator, class LessThanComparable>
    ForwardIterator thrust::upper_bound(ForwardIterator, ForwardIterator, const_
→ LessThanComparable&)
- template<class ForwardIterator, class T, class StrictWeakOrdering>
    ForwardIterator thrust::upper_bound(ForwardIterator, ForwardIterator, const T&,_
→ StrictWeakOrdering)
- template<typename DerivedPolicy, typename ForwardIterator, typename InputIterator,
→ typename OutputIterator, typename StrictWeakOrdering>__host__ __device__
→ OutputIterator thrust::upper_bound(const thrust::detail::execution_policy_base<_
→ DerivedPolicy > &, ForwardIterator, ForwardIterator, InputIterator, InputIterator,
→ OutputIterator, StrictWeakOrdering)
- template<typename DerivedPolicy, typename ForwardIterator, typename InputIterator,
→ typename OutputIterator>__host__ __device__ OutputIterator thrust::upper_
→ bound(const thrust::detail::execution_policy_base< DerivedPolicy > &,_
→ ForwardIterator, ForwardIterator, InputIterator, InputIterator, OutputIterator)
- template<typename DerivedPolicy, typename ForwardIterator, typename_
→ LessThanComparable>__host__ __device__ ForwardIterator thrust::upper_bound(const_
→ thrust::detail::execution_policy_base< DerivedPolicy > &, ForwardIterator,_
→ ForwardIterator, const LessThanComparable &)
- template<typename DerivedPolicy, typename ForwardIterator, typename T, typename_
→ StrictWeakOrdering>__host__ __device__ ForwardIterator thrust::upper_bound(const_
→ thrust::detail::execution_policy_base< DerivedPolicy > &, ForwardIterator,_
→ ForwardIterator, const T &, StrictWeakOrdering)
```

**Template Function `thrust::upper_bound(ForwardIterator, ForwardIterator, InputIterator, InputIterator, OutputIterator)`****Function Documentation**

```
template<class ForwardIterator, class InputIterator, class OutputIteratorOutputIterator thrust::upper_bound(ForwardIterator first, ForwardIterator last, InputIterator values_first, InputIterator values_last, OutputIterator result)
```

`upper_bound` is a vectorized version of binary search: for each iterator `v` in `[values_first, values_last)` it attempts to find the value `*v` in an ordered range `[first, last)`. Specifically, it returns the index of last position where value could be inserted without violating the ordering.

The following code snippet demonstrates how to use `upper_bound` to search for multiple values in a ordered range.

**Pre** The ranges `[first, last)` and `[result, result + (last - first))` shall not overlap.

**Parameters**

- `first`: The beginning of the ordered sequence.
- `last`: The end of the ordered sequence.
- `values_first`: The beginning of the search values sequence.
- `values_last`: The end of the search values sequence.
- `result`: The beginning of the output sequence.

**Template Parameters**

- `ForwardIterator`: is a model of `Forward Iterator`.
- `InputIterator`: is a model of `Input Iterator`. and `InputIterator`'s `value_type` is `LessThanComparable`.
- `OutputIterator`: is a model of `Output Iterator`. and `ForwardIterator`'s `difference_type` is convertible to `OutputIterator`'s `value_type`.

```
#include <thrust/binary_search.h>
#include <thrust/device_vector.h>
...
thrust::device_vector<int> input(5);

input[0] = 0;
input[1] = 2;
input[2] = 5;
input[3] = 7;
input[4] = 8;

thrust::device_vector<int> values(6);
values[0] = 0;
values[1] = 1;
values[2] = 2;
values[3] = 3;
values[4] = 8;
values[5] = 9;

thrust::device_vector<unsigned int> output(6);

thrust::upper_bound(input.begin(), input.end(),
```

(continues on next page)

(continued from previous page)

```

values.begin(), values.end(),
output.begin());

// output is now [1, 1, 2, 2, 5, 5]

```

**See** [http://www.sgi.com/tech/stl/upper\\_bound.html](http://www.sgi.com/tech/stl/upper_bound.html)

**See** `upper_bound`

**See** `equal_range`

**See** `binary_search`

**Template Function** `thrust::upper_bound(const thrust::detail::execution_policy_base<DerivedPolicy>&, ForwardIterator, ForwardIterator, InputIterator, InputIterator, OutputIterator, StrictWeakOrdering)`

## Function Documentation

**Warning:** doxygenfunction: Unable to resolve multiple matches for function “thrust::upper\_bound” with arguments (const thrust::detail::execution\_policy\_base<DerivedPolicy>&, ForwardIterator, ForwardIterator, InputIterator, InputIterator, OutputIterator, StrictWeakOrdering) in doxygen xml output for project “rocThrust” from directory: ./docBin/xml. Potential matches:

```

- template<class ForwardIterator, class InputIterator, class OutputIterator, class_
→StrictWeakOrdering>
OutputIterator thrust::upper_bound(ForwardIterator, ForwardIterator,
→InputIterator, InputIterator, OutputIterator, StrictWeakOrdering)
- template<class ForwardIterator, class InputIterator, class OutputIterator>
OutputIterator thrust::upper_bound(ForwardIterator, ForwardIterator,
→InputIterator, InputIterator, OutputIterator)
- template<class ForwardIterator, class LessThanComparable>
ForwardIterator thrust::upper_bound(ForwardIterator, ForwardIterator, const_
→LessThanComparable&)
- template<class ForwardIterator, class T, class StrictWeakOrdering>
ForwardIterator thrust::upper_bound(ForwardIterator, ForwardIterator, const T&,
→StrictWeakOrdering)
- template<typename DerivedPolicy, typename ForwardIterator, typename InputIterator,
→ typename OutputIterator, typename StrictWeakOrdering>__host__ __device__
→OutputIterator thrust::upper_bound(const thrust::detail::execution_policy_base<
→DerivedPolicy > &, ForwardIterator, ForwardIterator, InputIterator, InputIterator,
→OutputIterator, StrictWeakOrdering)
- template<typename DerivedPolicy, typename ForwardIterator, typename InputIterator,
→ typename OutputIterator>__host__ __device__ OutputIterator thrust::upper_
→bound(const thrust::detail::execution_policy_base< DerivedPolicy > &,
→ForwardIterator, ForwardIterator, InputIterator, InputIterator, OutputIterator)
- template<typename DerivedPolicy, typename ForwardIterator, typename_
→LessThanComparable>__host__ __device__ ForwardIterator thrust::upper_bound(const_
→thrust::detail::execution_policy_base< DerivedPolicy > &, ForwardIterator,
→ForwardIterator, const LessThanComparable &)
- template<typename DerivedPolicy, typename ForwardIterator, typename T, typename_
→StrictWeakOrdering>__host__ __device__ ForwardIterator thrust::upper_bound(const_
→thrust::detail::execution_policy_base< DerivedPolicy > &, ForwardIterator,
→ForwardIterator, const T &, StrictWeakOrdering)

```

**Template Function `thrust::upper_bound(ForwardIterator, ForwardIterator, InputIterator, InputIterator, OutputIterator, StrictWeakOrdering)`****Function Documentation**

```
template<class ForwardIterator, class InputIterator, class OutputIterator, class StrictWeakOrdering>
OutputIterator thrust::upper_bound(ForwardIterator first, ForwardIterator last, InputIterator values_first,
                                 InputIterator values_last, OutputIterator result,
                                 StrictWeakOrdering comp)
```

`upper_bound` is a vectorized version of binary search: for each iterator  $v$  in  $[values\_first, values\_last]$  it attempts to find the value  $*v$  in an ordered range  $[first, last]$ . Specifically, it returns the index of first position where value could be inserted without violating the ordering. This version of `upper_bound` uses function object `comp` for comparison.

The following code snippet demonstrates how to use `upper_bound` to search for multiple values in a ordered range.

**Pre** The ranges  $[first, last)$  and  $[result, result + (last - first))$  shall not overlap.

**Parameters**

- `first`: The beginning of the ordered sequence.
- `last`: The end of the ordered sequence.
- `values_first`: The beginning of the search values sequence.
- `values_last`: The end of the search values sequence.
- `result`: The beginning of the output sequence.
- `comp`: The comparison operator.

**Template Parameters**

- `ForwardIterator`: is a model of `Forward Iterator`.
- `InputIterator`: is a model of `Input Iterator`. and `InputIterator`'s `value_type` is comparable to `ForwardIterator`'s `value_type`.
- `OutputIterator`: is a model of `Output Iterator`. and `ForwardIterator`'s `difference_type` is convertible to `OutputIterator`'s `value_type`.
- `StrictWeakOrdering`: is a model of `Strict Weak Ordering`.

```
#include <thrust/binary_search.h>
#include <thrust/device_vector.h>
#include <thrust/functional.h>
...
thrust::device_vector<int> input(5);
input[0] = 0;
input[1] = 2;
input[2] = 5;
input[3] = 7;
input[4] = 8;

thrust::device_vector<int> values(6);
values[0] = 0;
values[1] = 1;
values[2] = 2;
```

(continues on next page)

(continued from previous page)

```

values[3] = 3;
values[4] = 8;
values[5] = 9;

thrust::device_vector<unsigned int> output(6);

thrust::upper_bound(input.begin(), input.end(),
                    values.begin(), values.end(),
                    output.begin(),
                    thrust::less<int>());

// output is now [1, 1, 2, 2, 5, 5]

```

**See** [http://www.sgi.com/tech/stl/upper\\_bound.html](http://www.sgi.com/tech/stl/upper_bound.html)

**See** [lower\\_bound](#)

**See** [equal\\_range](#)

**See** [binary\\_search](#)

### 1.3.4 Variables

#### Variable `thrust::device`

##### Variable Documentation

**const** `detail::device_t thrust::device`

`thrust::device` is the default parallel execution policy associated with Thrust's device backend system configured by the `THRUST_DEVICE_SYSTEM` macro.

Instead of relying on implicit algorithm dispatch through iterator system tags, users may directly target algorithm dispatch at Thrust's device system by providing `thrust::device` as an algorithm parameter.

Explicit dispatch can be useful in avoiding the introduction of data copies into containers such as `thrust::device_vector` or to avoid wrapping e.g. raw pointers allocated by the HIP API with types such as `thrust::device_ptr`.

The user must take care to guarantee that the iterators provided to an algorithm are compatible with the device backend system. For example, raw pointers allocated by `std::malloc` typically cannot be dereferenced by a GPU. For this reason, raw pointers allocated by host APIs should not be mixed with a `thrust::device` algorithm invocation when the device backend is HIP.

The type of `thrust::device` is implementation-defined.

The following code snippet demonstrates how to use `thrust::device` to explicitly dispatch an invocation of `thrust::for_each` to the device backend system:

```

#include <thrust/for_each.h>
#include <thrust/device_vector.h>
#include <thrust/execution_policy.h>
#include <cstdio>

struct printf_functor
{
    __host__ __device__

```

(continues on next page)

(continued from previous page)

```

void operator() (int x)
{
    printf("%d\n", x);
}
};

...
thrust::device_vector<int> vec(3);
vec[0] = 0; vec[1] = 1; vec[2] = 2;

thrust::for_each(thrust::device, vec.begin(), vec.end(), printf_functor());
// 0 1 2 is printed to standard output in some unspecified order

```

**See** [host\\_execution\\_policy](#)

**See** [thrust::device](#)

## Variable `thrust::host`

### Variable Documentation

**const** detail::host\_t `thrust::host`

`thrust::host` is the default parallel execution policy associated with Thrust's host backend system configured by the `THRUST_HOST_SYSTEM` macro.

Instead of relying on implicit algorithm dispatch through iterator system tags, users may directly target algorithm dispatch at Thrust's host system by providing `thrust::host` as an algorithm parameter.

Explicit dispatch can be useful in avoiding the introduction of data copies into containers such as `thrust::host_vector`.

Note that even though `thrust::host` targets the host CPU, it is a parallel execution policy. That is, the order that an algorithm invokes functors or dereferences iterators is not defined.

The type of `thrust::host` is implementation-defined.

The following code snippet demonstrates how to use `thrust::host` to explicitly dispatch an invocation of `thrust::for_each` to the host backend system:

```

#include <thrust/for_each.h>
#include <thrust/execution_policy.h>
#include <cstdio>

struct printf_functor
{
    __host__ __device__
    void operator() (int x)
    {
        printf("%d\n", x);
    }
};

...
int vec(3);
vec[0] = 0; vec[1] = 1; vec[2] = 2;

thrust::for_each(thrust::host, vec.begin(), vec.end(), printf_functor());

```

(continues on next page)

(continued from previous page)

```
// 0 1 2 is printed to standard output in some unspecified order
```

See [host\\_execution\\_policy](#)

See [thrust::device](#)

### Variable `thrust::placeholders::_1`

- Defined in `file_thrust_functional.h`

#### Variable Documentation

**const** `thrust::detail::functional::placeholder<0>::type thrust ::placeholders::_1`  
`thrust ::placeholders::_1` is the placeholder for the first function parameter.

### Variable `thrust::placeholders::_10`

- Defined in `file_thrust_functional.h`

#### Variable Documentation

**const** `thrust::detail::functional::placeholder<9>::type thrust ::placeholders::_10`  
`thrust ::placeholders::_10` is the placeholder for the tenth function parameter.

### Variable `thrust::placeholders::_2`

- Defined in `file_thrust_functional.h`

#### Variable Documentation

**const** `thrust::detail::functional::placeholder<1>::type thrust ::placeholders::_2`  
`thrust ::placeholders::_2` is the placeholder for the second function parameter.

### Variable `thrust::placeholders::_3`

- Defined in `file_thrust_functional.h`

#### Variable Documentation

**const** `thrust::detail::functional::placeholder<2>::type thrust ::placeholders::_3`  
`thrust ::placeholders::_3` is the placeholder for the third function parameter.

### Variable `thrust::placeholders::_4`

- Defined in `file_thrust_functional.h`

## Variable Documentation

**const** `thrust::detail::functional::placeholder<3>::type thrust :: placeholders :: _4`  
    `thrust :: placeholders :: _4` is the placeholder for the fourth function parameter.

## Variable `thrust::placeholders::_5`

- Defined in `file_thrust_functional.h`

## Variable Documentation

**const** `thrust::detail::functional::placeholder<4>::type thrust :: placeholders :: _5`  
    `thrust :: placeholders :: _5` is the placeholder for the fifth function parameter.

## Variable `thrust::placeholders::_6`

- Defined in `file_thrust_functional.h`

## Variable Documentation

**const** `thrust::detail::functional::placeholder<5>::type thrust :: placeholders :: _6`  
    `thrust :: placeholders :: _6` is the placeholder for the sixth function parameter.

## Variable `thrust::placeholders::_7`

- Defined in `file_thrust_functional.h`

## Variable Documentation

**const** `thrust::detail::functional::placeholder<6>::type thrust :: placeholders :: _7`  
    `thrust :: placeholders :: _7` is the placeholder for the seventh function parameter.

## Variable `thrust::placeholders::_8`

- Defined in `file_thrust_functional.h`

## Variable Documentation

**const** `thrust::detail::functional::placeholder<7>::type thrust :: placeholders :: _8`  
    `thrust :: placeholders :: _8` is the placeholder for the eighth function parameter.

## Variable `thrust::placeholders::_9`

- Defined in `file_thrust_functional.h`

## Variable Documentation

**const** thrust::detail::functional::placeholder<8>::type thrust :: placeholders :: \_9  
thrust :: placeholders :: \_9 is the placeholder for the ninth function parameter.

### 1.3.5 Defines

#### Define \_\_THRUST\_DEVICE\_SYSTEM\_EXECUTION\_POLICY\_HEADER

- Defined in file\_thrust\_execution\_policy.h

#### Define Documentation

**\_\_THRUST\_DEVICE\_SYSTEM\_EXECUTION\_POLICY\_HEADER**

#### Define \_\_THRUST\_HOST\_SYSTEM\_EXECUTION\_POLICY\_HEADER

- Defined in file\_thrust\_execution\_policy.h

#### Define Documentation

**\_\_THRUST\_HOST\_SYSTEM\_EXECUTION\_POLICY\_HEADER**

#### Define THRUST\_MAJOR\_VERSION

- Defined in file\_thrust\_version.h

#### Define Documentation

**THRUST\_MAJOR\_VERSION**

The preprocessor macro THRUST\_MAJOR\_VERSION encodes the major version number of the Thrust library.

#### Define THRUST\_MINOR\_VERSION

- Defined in file\_thrust\_version.h

#### Define Documentation

**THRUST\_MINOR\_VERSION**

The preprocessor macro THRUST\_MINOR\_VERSION encodes the minor version number of the Thrust library.

#### Define THRUST\_PATCH\_NUMBER

- Defined in file\_thrust\_version.h

## Define Documentation

### **THRUST\_PATCH\_NUMBER**

The preprocessor macro THRUST\_PATCH\_NUMBER encodes the patch number of the Thrust library.

## Define **THRUST\_STD\_COMPLEX\_DEVICE**

- Defined in file\_thrust\_complex.h

## Define Documentation

### **THRUST\_STD\_COMPLEX\_DEVICE**

## Define **THRUST\_STD\_COMPLEX\_IMAG**

- Defined in file\_thrust\_complex.h

## Define Documentation

### **THRUST\_STD\_COMPLEX\_IMAG(z)**

## Define **THRUST\_STD\_COMPLEX\_REAL**

- Defined in file\_thrust\_complex.h

## Define Documentation

### **THRUST\_STD\_COMPLEX\_REAL(z)**

## Define **THRUST\_SUBMINOR\_VERSION**

- Defined in file\_thrust\_version.h

## Define Documentation

### **THRUST\_SUBMINOR\_VERSION**

The preprocessor macro THRUST\_SUBMINOR\_VERSION encodes the sub-minor version number of the Thrust library.

## Define **THRUST\_VERSION**

- Defined in file\_thrust\_version.h

## Define Documentation

### THRUST\_VERSION

The preprocessor macro THRUST\_VERSION encodes the version number of the Thrust library.

THRUST\_VERSION % 100 is the sub-minor version. THRUST\_VERSION / 100 % 1000 is the minor version. THRUST\_VERSION / 100000 is the major version.

## 1.3.6 Typedefs

### TypeDef thrust::random::default\_random\_engine

- Defined in file\_thrust\_random.h

#### TypeDef Documentation

##### **typedef** thrust::random::default\_random\_engine

An implementation-defined “default” random number engine.

**Note** default\_random\_engine is currently an alias for minstd\_rand, and may change in a future version.

### TypeDef thrust::random::ranlux24

- Defined in file\_thrust\_random.h

#### TypeDef Documentation

##### **typedef** thrust::random::ranlux24

A random number engine with predefined parameters which implements the RANLUX level-3 random number generation algorithm.

**Note** The 10000th consecutive invocation of a default-constructed object of type ranlux24 shall produce the value 9901578 .

### TypeDef thrust::random::ranlux48

- Defined in file\_thrust\_random.h

#### TypeDef Documentation

##### **typedef** thrust::random::ranlux48

A random number engine with predefined parameters which implements the RANLUX level-4 random number generation algorithm.

**Note** The 10000th consecutive invocation of a default-constructed object of type ranlux48 shall produce the value 88229545517833 .

## Typedef thrust::random::taus88

- Defined in file\_thrust\_random.h

### Typedef Documentation

**typedef** `thrust::random::taus88`

A random number engine with predefined parameters which implements L'Ecuyer's 1996 three-component Tausworthe random number generator.

**Note** The 10000th consecutive invocation of a default-constructed object of type `taus88` shall produce the value 3535848941 .

---

**CHAPTER  
TWO**

---

**INDICES AND TABLES**

- genindex
- search



# INDEX

## Symbols

—THRUST\_DEVICE\_SYSTEM\_EXECUTION\_POLICY\_HEADER  
    (*C macro*), 369

—THRUST\_HOST\_SYSTEM\_EXECUTION\_POLICY\_HEADER  
    (*C macro*), 369

**T**

thrust::adjacent\_difference (*C++ function*),  
    74

thrust::all\_of (*C++ function*), 77

thrust::any\_of (*C++ function*), 78

thrust::binary\_function (*C++ class*), 20

thrust::binary\_function::first\_argument\_type  
    (*C++ type*), 20

thrust::binary\_function::result\_type  
    (*C++ type*), 21

thrust::binary\_function::second\_argument\_type  
    (*C++ type*), 20

thrust::binary\_negate (*C++ class*), 21

thrust::binary\_search (*C++ function*), 81, 82,  
    84, 86

thrust::binary\_traits (*C++ class*), 21

thrust::bit\_and (*C++ class*), 22

thrust::bit\_and::first\_argument\_type  
    (*C++ type*), 22

thrust::bit\_and::result\_type (*C++ type*), 22

thrust::bit\_and::second\_argument\_type  
    (*C++ type*), 22

thrust::bit\_or (*C++ class*), 23

thrust::bit\_or::first\_argument\_type  
    (*C++ type*), 23

thrust::bit\_or::result\_type (*C++ type*), 23

thrust::bit\_or::second\_argument\_type  
    (*C++ type*), 23

thrust::bit\_xor (*C++ class*), 24

thrust::bit\_xor::first\_argument\_type  
    (*C++ type*), 24

thrust::bit\_xor::result\_type (*C++ type*), 24

thrust::bit\_xor::second\_argument\_type  
    (*C++ type*), 24

thrust::complex (*C++ class*), 25

thrust::complex::value\_type (*C++ type*), 25

thrust::copy (*C++ function*), 88

thrust::copy\_if (*C++ function*), 90, 91

thrust::copy\_n (*C++ function*), 93

thrust::count (*C++ function*), 95

thrust::count\_if (*C++ function*), 96

thrust::device (*C++ member*), 365

thrust::device\_allocator (*C++ class*), 55

thrust::device\_allocator::const\_pointer  
    (*C++ type*), 56

thrust::device\_allocator::difference\_type  
    (*C++ type*), 56

thrust::device\_allocator::pointer (*C++ type*), 56

thrust::device\_allocator::rebind (*C++ class*), 29, 55

thrust::device\_allocator::size\_type  
    (*C++ type*), 56

thrust::device\_allocator::value\_type  
    (*C++ type*), 56

thrust::device\_allocator<T>::rebind::other  
    (*C++ type*), 29, 55

thrust::device\_allocator<void> (*C++ class*), 56

thrust::device\_allocator<void>::rebind  
    (*C++ class*), 29, 56

thrust::device\_allocator<void>::rebind::other  
    (*C++ type*), 30, 56

thrust::device\_delete (*C++ function*), 97

thrust::device\_execution\_policy (*C++ class*), 30

thrust::device\_free (*C++ function*), 97

thrust::device\_malloc (*C++ function*), 98

thrust::device\_malloc\_allocator (*C++ class*), 57

thrust::device\_malloc\_allocator::const\_pointer  
    (*C++ type*), 57

thrust::device\_malloc\_allocator::const\_reference  
    (*C++ type*), 57

thrust::device\_malloc\_allocator::difference\_type  
    (*C++ type*), 57

thrust::device\_malloc\_allocator::max\_size  
    (*C++ function*), 58

thrust::device\_malloc\_allocator::pointer (*C++ type*), 33  
    (C++ type), 57  
thrust::device\_malloc\_allocator::rebind  
    (*C++ class*), 31, 58  
thrust::device\_malloc\_allocator::reference  
    (*C++ type*), 57  
thrust::device\_malloc\_allocator::size\_type  
    (*C++ type*), 57  
thrust::device\_malloc\_allocator::value\_type  
    (*C++ type*), 57  
thrust::device\_malloc\_allocator<T>::rebind  
    (*C++ type*), 31, 58  
thrust::device\_new (*C++ function*), 99  
thrust::device\_new\_allocator (*C++ class*), 59  
thrust::device\_new\_allocator::const\_pointer  
    (*C++ type*), 59  
thrust::device\_new\_allocator::const\_reference  
    (*C++ type*), 59  
thrust::device\_new\_allocator::difference\_type  
    (*C++ type*), 59  
thrust::device\_new\_allocator::pointer  
    (*C++ type*), 59  
thrust::device\_new\_allocator::rebind  
    (*C++ class*), 32, 60  
thrust::device\_new\_allocator::reference  
    (*C++ type*), 59  
thrust::device\_new\_allocator::size\_type  
    (*C++ type*), 59  
thrust::device\_new\_allocator::value\_type  
    (*C++ type*), 59  
thrust::device\_new\_allocator<T>::rebind:  
    (C++ type), 32, 61  
thrust::device\_ptr (*C++ class*), 61  
thrust::device\_reference (*C++ class*), 62  
thrust::device\_reference::pointer (*C++ type*), 65  
thrust::device\_reference::value\_type  
    (*C++ type*), 65  
thrust::device\_vector (*C++ class*), 66  
thrust::device\_vector::~device\_vector  
    (*C++ function*), 67, 68  
thrust::device\_vector::device\_vector  
    (*C++ function*), 67, 68  
thrust::divides (*C++ class*), 32  
thrust::divides::first\_argument\_type  
    (*C++ type*), 33  
thrust::divides::result\_type (*C++ type*), 33  
thrust::divides::second\_argument\_type  
    (*C++ type*), 33  
thrust::equal (*C++ function*), 101, 103  
thrust::equal\_range (*C++ function*), 104, 106  
thrust::equal\_to (*C++ class*), 33  
thrust::equal\_to::first\_argument\_type  
    (C++ type), 33  
thrust::equal\_to::result\_type (*C++ type*), 33  
    (C++ type), 33  
thrust::equal\_to::second\_argument\_type  
    (C++ type), 33  
thrust::exclusive\_scan (*C++ function*), 108, 113, 115, 117, 119  
thrust::exclusive\_scan\_by\_key (*C++ function*), 113  
thrust::find (*C++ function*), 123  
thrust::find\_if (*C++ function*), 124  
thrust::find\_if\_not (*C++ function*), 125  
thrust::for\_each (*C++ function*), 127  
thrust::for\_each\_n (*C++ function*), 128  
thrust::gather (*C++ function*), 130  
thrust::gather\_if (*C++ function*), 132, 134  
thrust::generate (*C++ function*), 136  
thrust::generate\_n (*C++ function*), 137  
thrust::greater (*C++ class*), 34  
thrust::greater::first\_argument\_type  
    (*C++ type*), 34  
thrust::greater::result\_type (*C++ type*), 34  
thrust::greater::second\_argument\_type  
    (*C++ type*), 34  
thrust::greater\_equal (*C++ class*), 35  
thrust::greater\_equal::first\_argument\_type  
    (*C++ type*), 35  
thrust::greater\_equal::result\_type (*C++ type*), 35  
thrust::greater\_equal::second\_argument\_type  
    (*C++ type*), 35  
thrust::host::host (*C++ member*), 366  
thrust::host\_execution\_policy (*C++ class*), 35  
thrust::host\_vector (*C++ class*), 68  
thrust::host\_vector::~host\_vector (*C++ function*), 69  
thrust::host\_vector::host\_vector  
    (*C++ function*), 69, 70  
thrust::identity (*C++ class*), 37  
thrust::identity::argument\_type  
    (*C++ type*), 37  
thrust::identity::result\_type (*C++ type*), 37  
thrust::inclusive\_scan (*C++ function*), 140, 141  
thrust::inclusive\_scan\_by\_key (*C++ function*), 143, 145, 147  
thrust::inner\_product (*C++ function*), 149, 150  
thrust::is\_partitioned (*C++ function*), 152  
thrust::is\_sorted (*C++ function*), 153, 155  
thrust::is\_sorted\_until (*C++ function*), 156, 157  
thrust::less (*C++ class*), 37

```

thrust::less::first_argument_type (C++ type), 38
thrust::less::result_type (C++ type), 38
thrust::less::second_argument_type (C++ type), 38
thrust::less_equal (C++ class), 38
thrust::less_equal::first_argument_type (C++ type), 38
thrust::less_equal::result_type (C++ type), 38
thrust::less_equal::second_argument_type (C++ type), 38
thrust::logical_and (C++ class), 39
thrust::logical_and::first_argument_type (C++ type), 39
thrust::logical_and::result_type (C++ type), 39
thrust::logical_and::second_argument_type (C++ type), 39
thrust::logical_not (C++ class), 39
thrust::logical_not::first_argument_type (C++ type), 40
thrust::logical_not::result_type (C++ type), 40
thrust::logical_not::second_argument_type (C++ type), 40
thrust::logical_or (C++ class), 40
thrust::logical_or::first_argument_type (C++ type), 41
thrust::logical_or::result_type (C++ type), 41
thrust::logical_or::second_argument_type (C++ type), 41
thrust::lower_bound (C++ function), 160, 161, 163, 165
thrust::max_element (C++ function), 169, 170
thrust::maximum (C++ class), 41
thrust::maximum::first_argument_type (C++ type), 41
thrust::maximum::result_type (C++ type), 41
thrust::maximum::second_argument_type (C++ type), 41
thrust::merge (C++ function), 172, 173
thrust::merge_by_key (C++ function), 175, 178
thrust::min_element (C++ function), 180, 182
thrust::minimum (C++ class), 42
thrust::minimum::first_argument_type (C++ type), 42
thrust::minimum::result_type (C++ type), 42
thrust::minimum::second_argument_type (C++ type), 42
thrust::minmax_element (C++ function), 183, 184
thrust::minus (C++ class), 43
thrust::minus::first_argument_type (C++ type), 43
thrust::minus::result_type (C++ type), 43
thrust::minus::second_argument_type (C++ type), 43
thrust::mismatch (C++ function), 186, 188
thrust::modulus (C++ class), 44
thrust::modulus::first_argument_type (C++ type), 44
thrust::modulus::result_type (C++ type), 44
thrust::multiplies (C++ class), 45
thrust::multiplies::first_argument_type (C++ type), 45
thrust::multiplies::result_type (C++ type), 45
thrust::multiplies::second_argument_type (C++ type), 45
thrust::negate (C++ class), 46
thrust::negate::argument_type (C++ type), 46
thrust::negate::result_type (C++ type), 46
thrust::none_of (C++ function), 189
thrust::not_equal_to (C++ class), 47
thrust::not_equal_to::first_argument_type (C++ type), 47
thrust::not_equal_to::result_type (C++ type), 47
thrust::not_equal_to::second_argument_type (C++ type), 47
thrust::operator>> (C++ function), 204
thrust::operator<< (C++ function), 200
thrust::pair (C++ class), 47
thrust::pair::first (C++ member), 49
thrust::pair::first_type (C++ type), 48
thrust::pair::second (C++ member), 49
thrust::pair::second_type (C++ type), 48
thrust::partition (C++ function), 205, 206
thrust::partition_copy (C++ function), 208, 210
thrust::partition_point (C++ function), 212
thrust::placeholders::_1 (C++ member), 367
thrust::placeholders::_10 (C++ member), 367
thrust::placeholders::_2 (C++ member), 367
thrust::placeholders::_3 (C++ member), 367
thrust::placeholders::_4 (C++ member), 368
thrust::placeholders::_5 (C++ member), 368
thrust::placeholders::_6 (C++ member), 368
thrust::placeholders::_7 (C++ member), 368
thrust::placeholders::_8 (C++ member), 368
thrust::placeholders::_9 (C++ member), 369
thrust::plus (C++ class), 49

```

thrust::plus::first\_argument\_type (*C++ type*), 49  
thrust::plus::result\_type (*C++ type*), 50  
thrust::plus::second\_argument\_type (*C++ type*), 49  
thrust::project1st (*C++ class*), 50  
thrust::project1st::first\_argument\_type (*C++ type*), 50  
thrust::project1st::result\_type (*C++ type*), 50  
thrust::project1st::second\_argument\_type (*C++ type*), 50  
thrust::project2nd (*C++ class*), 51  
thrust::project2nd::first\_argument\_type (*C++ type*), 51  
thrust::project2nd::result\_type (*C++ type*), 51  
thrust::project2nd::second\_argument\_type (*C++ type*), 51  
thrust::random::default\_random\_engine (*C++ type*), 371  
thrust::random::ranlux24 (*C++ type*), 371  
thrust::random::ranlux48 (*C++ type*), 371  
thrust::random::taus88 (*C++ type*), 372  
thrust::reduce (*C++ function*), 216, 217, 219  
thrust::reduce\_by\_key (*C++ function*), 220, 223, 225  
thrust::remove (*C++ function*), 226  
thrust::remove\_copy (*C++ function*), 228  
thrust::remove\_copy\_if (*C++ function*), 229, 231  
thrust::remove\_if (*C++ function*), 233, 234  
thrust::replace (*C++ function*), 236  
thrust::replace\_copy (*C++ function*), 237  
thrust::replace\_copy\_if (*C++ function*), 239, 241  
thrust::replace\_if (*C++ function*), 243, 244  
thrust::reverse (*C++ function*), 247  
thrust::reverse\_copy (*C++ function*), 248  
thrust::scatter (*C++ function*), 249  
thrust::scatter\_if (*C++ function*), 251, 253  
thrust::sequence (*C++ function*), 254, 256, 257  
thrust::set\_difference (*C++ function*), 258, 260  
thrust::set\_difference\_by\_key (*C++ function*), 262, 265  
thrust::set\_intersection (*C++ function*), 268, 270  
thrust::set\_intersection\_by\_key (*C++ function*), 272, 275  
thrust::set\_symmetric\_difference (*C++ function*), 278, 280  
thrust::set\_symmetric\_difference\_by\_key (*C++ function*), 282, 286  
thrust::set\_union (*C++ function*), 290, 292  
thrust::set\_union\_by\_key (*C++ function*), 294, 297  
thrust::sort (*C++ function*), 300  
thrust::sort\_by\_key (*C++ function*), 302, 304  
thrust::stable\_partition (*C++ function*), 305, 307  
thrust::stable\_partition\_copy (*C++ function*), 309, 311  
thrust::stable\_sort (*C++ function*), 313, 314  
thrust::stable\_sort\_by\_key (*C++ function*), 316, 317  
thrust::swap\_ranges (*C++ function*), 320  
thrust::tabulate (*C++ function*), 322  
thrust::transform (*C++ function*), 325, 327  
thrust::transform\_exclusive\_scan (*C++ function*), 328  
thrust::transform\_if (*C++ function*), 330, 332, 334  
thrust::transform\_inclusive\_scan (*C++ function*), 336  
thrust::transform\_reduce (*C++ function*), 338  
thrust::tuple (*C++ class*), 70  
thrust::tuple\_element (*C++ class*), 51  
thrust::tuple\_element::type (*C++ type*), 52  
thrust::tuple\_size (*C++ class*), 52  
thrust::tuple\_size::value (*C++ member*), 52  
thrust::unary\_function (*C++ class*), 53  
thrust::unary\_function::argument\_type (*C++ type*), 53  
thrust::unary\_function::result\_type (*C++ type*), 53  
thrust::unary\_negate (*C++ class*), 53  
thrust::unary\_traits (*C++ class*), 54  
thrust::uninitialized\_copy (*C++ function*), 339  
thrust::uninitialized\_copy\_n (*C++ function*), 341  
thrust::uninitialized\_fill (*C++ function*), 342  
thrust::uninitialized\_fill\_n (*C++ function*), 344  
thrust::unique (*C++ function*), 345, 347  
thrust::unique\_by\_key (*C++ function*), 348, 349  
thrust::unique\_by\_key\_copy (*C++ function*), 351, 353  
thrust::unique\_copy (*C++ function*), 355, 356  
thrust::upper\_bound (*C++ function*), 358, 360, 362, 364  
THRUST\_MAJOR\_VERSION (*C macro*), 369  
THRUST\_MINOR\_VERSION (*C macro*), 369  
THRUST\_PATCH\_NUMBER (*C macro*), 370  
THRUST\_STD\_COMPLEX\_DEVICE (*C macro*), 370  
THRUST\_STD\_COMPLEX\_IMAG (*C macro*), 370

THRUST\_STD\_COMPLEX\_REAL (*C macro*), 370  
THRUST\_SUBMINOR\_VERSION (*C macro*), 370  
THRUST\_VERSION (*C macro*), 371